

File created: 18-Oct-93 15:27:40 {Pele:mv:envos}<LispCore>Sources>CLTL2>DEFSTRUCT-RUN-TIME.;2

previous date: 29-Aug-91 17:01:45 {Pele:mv:envos}<LispCore>Sources>CLTL2>DEFSTRUCT-RUN-TIME.;1

Read Table: XCL

Package: LISP

Format: XCCS

; Copyright (c) 1986, 1987, 1988, 1990, 1991, 1993 by Venue & Xerox Corporation. All rights reserved.

(IL:RPAQQ **IL:DEFSTRUCT-RUN-TIMECOMS**

( (IL:COMS

;; Remembering parsed structures

(IL:VARIABLES \*PARSED-DEFSTRUCTS\*)

(IL:FUNCTIONS PARSED-STRUCTURE SET-PARSED-STRUCTURE)

(IL:SETFS PARSED-STRUCTURE))

(IL:COMS

;; Declaring storage for structures

(IL:FUNCTIONS SI::%STRUCTURE-DECLARE-DATATYPE)

(IL:DECLARE\ : IL:DONTEVAL@LOAD IL:DOCOPY

;; This defines the root of the defstruct type hierarchy.

(IL:P (IL:\ASSIGNDATATYPE1 'STRUCTURE-OBJECT NIL 0))))

(IL:COMS

;; Support for self expansions etc

(IL:VARIABLES \*DEFSTRUCT-INFO-CACHE\*)

(IL:FUNCTIONS ESTABLISH-SETFS-AND-OPTIMIZERS ESTABLISH-PREDICATE)

(IL:FUNCTIONS GET-PS-FROM-ACCESSOR GET-PS-FROM-PREDICATE GET-SLOT-DESCRIPTOR-FROM-PS)

(IL:FUNCTIONS CACHE-SETF-INFO))

(IL:COMS

;; defstruct IO

(IL:VARIABLES XCL:\*PRINT-STRUCTURE\*)

(IL:FUNCTIONS PRINT-STRUCTURE-INSTANCE DEFAULT-STRUCTURE-PRINTER STRUCTURE-SLOT-NAMES)

;; For reading

(IL:FUNCTIONS IL:CREATE-STRUCTURE STRUCTURE-CONSTRUCTOR))

(IL:PROP (IL:FILETYPE IL:MAKEFILE-ENVIRONMENT)

IL:DEFSTRUCT-RUN-TIME)

(IL:DECLARE\ : IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE IL:DONTCOPY IL:COMPILEVAR (IL:ADDVARS (IL:NLAMA)

(IL:NLAML)

(IL:LAMA))))))

;; Remembering parsed structures

(DEFVAR **\*PARSED-DEFSTRUCTS\*** (IL:HASHARRAY 100)

;; All declared structures

)

(DEFMACRO **PARSED-STRUCTURE** (NAME &OPTIONAL (NO-ERROR NIL))

;; Returns the parsed-structure corresponding to name

(COND

(NO-ERROR `(IL:GETHASH ,NAME \*PARSED-DEFSTRUCTS\*))

(T `(OR (IL:GETHASH ,NAME \*PARSED-DEFSTRUCTS\*)

(ERROR "~s is not a defined structure" ,NAME))))))

(DEFUN **SET-PARSED-STRUCTURE** (NAME PS &OPTIONAL (EXTRA NIL EXTRA-P))

;; SETF method for CL::PARSED-STRUCTURE. Extra arg is because CL::PARSED-STRUCTURE takes an optional, which we ignore here, but that  
;; pushes the new value over one.

(WHEN EXTRA-P (SETQ PS EXTRA))

(IL:PUTHASH NAME PS \*PARSED-DEFSTRUCTS\*))

(DEFSETF **PARSED-STRUCTURE** SET-PARSED-STRUCTURE)

;; Declaring storage for structures

(DEFUN **SI::%STRUCTURE-DECLARE-DATATYPE** (NAME FIELD-SPECIFICATIONS FIELD-DESCRIPTORS WORD-LENGTH  
SUPERTYPE)

;;; analagous to declare-datatype, but does not prepend the supers descriptors. You must include all descs.

;;; N.B. descriptions and specs are for ALL slots, not just local-slots.

;; field-specifications is a list of the form '(pointer pointer (bits 3) (bits 5) word fixp). See p. 8.21 IRM

;; field-descriptors is the list returned from translate.datatype when given the above FIELD-SPECIFICATIONS. They are legal to pass to fetchfield.  
;; word-length is the car of the result of translate.datatype.  
;; supertype is the typename of the supertype.

```
(IF (NOT (AND (SYMBOLP NAME)
              (IL:SMALLPOSP WORD-LENGTH)))
    (ERROR "Illegal arguments: ~s ~s" NAME WORD-LENGTH))
(LET ((REFERENCE-COUNTED-POINTERS (MAPCAN #'(LAMBDA (DESCRIPTOR)
                                           (CASE (CADDR DESCRIPTOR)
                                             ((IL:POINTER IL:FULLPOINTER) (LIST (CADR DESCRIPTOR)))
                                             (FIELD-DESCRIPTORS)))
      (MULTIPLE-VALUE-BIND (TYPE-NUMBER REDECLARED?)
        (IL:\\ASSIGNDATATYPE1 NAME FIELD-DESCRIPTORS WORD-LENGTH FIELD-SPECIFICATIONS
          REFERENCE-COUNTED-POINTERS SUPERTYPE)
        ;; set the magic global to the allocated type number
        (IL:SETTOPVAL (IL:\\TYPEGLOBALVARIABLE NAME T)
                     TYPE-NUMBER)
        (VALUES FIELD-DESCRIPTORS REDECLARED?)))
      (IL:DECLARE\ : IL:DONTEVAL@LOAD IL:DOCOPY
      (IL:\\ASSIGNDATATYPE1 'STRUCTURE-OBJECT NIL 0)
      )
```

;; Support for self expansions etc

```
(DEFVAR *DEFSTRUCT-INFO-CACHE* (IL:HASHARRAY 100)
        ;; Used to cache slots and predicates
        )
```

(DEFUN **ESTABLISH-SETFS-AND-OPTIMIZERS** (PS-NAME)

;; Caches shared self expanders and accessor optimizers where appropriate

```
(LET* ((PS (PARSED-STRUCTURE PS-NAME))
       (INLINE (PS-INLINE PS)))
  (MAPC #'(LAMBDA (SLOT)
           ;; function-defining-form decides whether or not the accessors should be defun, definline, etc.
           (LET ((ACCESSOR (PSLOT-ACCESSOR SLOT)))
             (WHEN ACCESSOR
              (REMHASH ACCESSOR *DEFSTRUCT-INFO-CACHE*)
              (IF (NOT (PSLOT-READ-ONLY SLOT))
                  ;; install the self method expander that is shared for all accessors
                  (SET-SHARED-SETF-INVERSE ACCESSOR 'DEFSTRUCT-SHARED-SETF-EXPANDER))
              (COND
               ((EQ INLINE :ONLY)
                (SETF (MACRO-FUNCTION ACCESSOR)
                      'DEFSTRUCT-SHARED-ACCESSOR-OPTIMIZER))
               ((MEMBER :ACCESSOR INLINE :TEST #'EQ)
                (SETF (GET ACCESSOR 'COMPILER:OPTIMIZER-LIST)
                      (LIST 'DEFSTRUCT-SHARED-ACCESSOR-OPTIMIZER))))
              (T (REMPROP ACCESSOR 'COMPILER:OPTIMIZER-LIST))))))
  (PS-ALL-SLOTS PS))))
```

(DEFUN **ESTABLISH-PREDICATE** (PS-NAME)

;; Establishes a shared a shared optimizer for a defstruct predicate

```
(LET* ((PS (PARSED-STRUCTURE PS-NAME))
       (PREDICATE (PS-PREDICATE PS)))
  (REMHASH PREDICATE *DEFSTRUCT-INFO-CACHE*)
  (IF (EQ (PS-INLINE PS) :ONLY)
      (SETF (MACRO-FUNCTION PREDICATE)
            'DEFSTRUCT-SHARED-PREDICATE-OPTIMIZER)
      (SETF (GET PREDICATE 'COMPILER:OPTIMIZER-LIST)
            (LIST 'DEFSTRUCT-SHARED-PREDICATE-OPTIMIZER))))
```

(DEFUN **GET-PS-FROM-ACCESSOR** (ACCESSOR &OPTIONAL (NO-ERROR-P NIL))

```
(OR (CATCH 'FIND-PS
      (MAPHASH #'(LAMBDA (KEY VALUE)
                 (DOLIST (SLOT (PS-ALL-SLOTS VALUE)
                           NIL)
                   (IF (EQ ACCESSOR (PSLOT-ACCESSOR SLOT))
                       (THROW 'FIND-PS VALUE))))
      *PARSED-DEFSTRUCTS*))
  (IF (NULL NO-ERROR-P)
      (ERROR "No such slot: ~s" ACCESSOR))))
```



```

      (GO SKIP))
      (IL:\\OUTCHAR STREAM (IL:CONSTANT (CHAR-CODE #\Space)))
      (IF (AND LENGTHSOFAR (> (INCF LENGTHSOFAR)
                                *PRINT-LENGTH*))
          (PROGN (IL:\\ELIDE.PRINT.TAIL STREAM T)
                 (RETURN NIL))
          (PROGN (PRINC (CAR FIELD)
                    STREAM)
                 (IF (AND LENGTHSOFAR (> (INCF LENGTHSOFAR)
                                          *PRINT-LENGTH*))
                     (PROGN (IL:\\ELIDE.PRINT.TAIL STREAM T)
                              (RETURN NIL))
                     (PROGN (IL:\\OUTCHAR STREAM (IL:CONSTANT (CHAR-CODE #\Space)))
                              (IL:\\PRINDATUM (IL:FETCHFIELD (CAR DESCRIPTOR)
                                                         STRUC)
                                               STREAM
                                               (1+ PRINT-LEVEL)))))))
      (WRITE-STRING " " STREAM)))
  T)))

```

```

(DEFUN STRUCTURE-SLOT-NAMES (STRUCTURE-NAME &OPTIONAL (DONT-COPY NIL))
  (LET* ((PS (PARSED-STRUCTURE STRUCTURE-NAME))
         (NAMES)
         (SETQ NAMES (PS-ALL-SLOT-NAMES PS))
         (IF DONT-COPY
             NAMES
             (COPY-LIST NAMES))))
)

```

:: For reading

```

(DEFUN IL:CREATE-STRUCTURE (STRUCTURE-FORM)
  (APPLY (STRUCTURE-CONSTRUCTOR (CAR STRUCTURE-FORM))
        (XCL:WITH-COLLECTION (DO ((TAIL (CDR STRUCTURE-FORM)
                                       (CDDR TAIL))
                                ((NULL TAIL))
                                (XCL:COLLECT (IL:MAKE-KEYWORD (CAR TAIL)))
                                (XCL:COLLECT (CADR TAIL))))))
)

```

```

(DEFUN STRUCTURE-CONSTRUCTOR (STRUCTURE-NAME)
  (OR (GET STRUCTURE-NAME 'IL:STRUCTURE-CONSTRUCTOR)
      (LET* ((PS (PARSED-STRUCTURE STRUCTURE-NAME))
             (CONSTRUCTOR (PS-STANDARD-CONSTRUCTOR PS))
             (OR CONSTRUCTOR (ERROR "~S is a structure with no standard constructor." (PS-NAME PS)))))
)

```

```

(IL:PUTPROPS IL:DEFSTRUCT-RUN-TIME IL:FILETYPE COMPILE-FILE)

```

```

(IL:PUTPROPS IL:DEFSTRUCT-RUN-TIME IL:MAKEFILE-ENVIRONMENT (:READTABLE "XCL" :PACKAGE "LISP"))

```

```

(IL:DECLARE\ : IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE IL:DONTCOPY IL:COMPILERVERS
)

```

```

(IL:ADDTOVAR IL:NLAMA )

```

```

(IL:ADDTOVAR IL:NLAML )

```

```

(IL:ADDTOVAR IL:LAMA )
)

```

```

(IL:PUTPROPS IL:DEFSTRUCT-RUN-TIME IL:COPYRIGHT ("Venue & Xerox Corporation" 1986 1987 1988 1990 1991 1993))

```

---

**FUNCTION INDEX**

SI::%STRUCTURE-DECLARE-DATATYPE ..1	ESTABLISH-SETFS-AND-OPTIMIZERS ...2	SET-PARSED-STRUCTURE .....1
CACHE-SETF-INFO .....3	GET-PS-FROM-ACCESSOR .....2	STRUCTURE-CONSTRUCTOR .....4
IL:CREATE-STRUCTURE .....4	GET-PS-FROM-PREDICATE .....3	STRUCTURE-SLOT-NAMES .....4
DEFAULT-STRUCTURE-PRINTER .....3	GET-SLOT-DESCRIPTOR-FROM-PS .....3	
ESTABLISH-PREDICATE .....2	PRINT-STRUCTURE-INSTANCE .....3	

---

**VARIABLE INDEX**

*DEFSTRUCT-INFO-CACHE* .....2	*PARSED-DEFSTRUCTS* .....1	XCL:*PRINT-STRUCTURE* .....3
-------------------------------	----------------------------	------------------------------

---

**PROPERTY INDEX**

IL:DEFSTRUCT-RUN-TIME .....4
------------------------------

---

**SETF INDEX**

PARSED-STRUCTURE .....1
-------------------------

---

**MACRO INDEX**

PARSED-STRUCTURE .....1
-------------------------

---