File created: 13-Apr-2023 09:44:06 **{DSK}<home>larry>il>medley>greetfiles>MEDLEYDIR-INIT.;6**

edit by: lmm

changes to: (VARS MEDLEYDIR-INITCOMS)

previous date: 10-Apr-2023 11:58:07 {DSK}<home>larry>il>medley>greetfiles>MEDLEYDIR-INIT.;5

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

```
(RPAQQ MEDLEYDIR-INITCOMS
       ([P (LOAD? (CONCAT (OR (UNIX-GETENV "MEDLEYDIR")
                              "")
                          "/sources/MEDLEYDIR.LCOM"))
           (MEDLEY-INIT-VARS 'GREET)
           (KEYACTION 'LOCK '(LOCKTOGGLE . IGNORE]
        (FILES BACKGROUND-YIELD)
        (VARS ;; settings for new users
              (DWIMWAIT 180)
              (HELPDEPTH 4)
              (HELPTIME 1)
              (FILING.ENUMERATION.DEPTH 1)
              [LOGINDIR (DIRECTORYNAME (OR (UNIX-GETENV "LOGINDIR")
                                           (UNIX-GETENV "HOME"]
              [USERGREETFILES `((,LOGINDIR "INIT" COM)
                                (,LOGINDIR "INIT"]
              (COPYRIGHTFLG 'NEVER)
              (COPYRIGHTSRESERVED NIL)
              (AUTOBACKTRACEFLG 'ALWAYS)
              (MAXLEVEL 30000)
              (MAXLOOP 30000))
        (FNS INTERLISPMODE)
        (ALISTS (FONTDEFS))))

(LOAD? (CONCAT (OR (UNIX-GETENV "MEDLEYDIR")
                   "")
               "/sources/MEDLEYDIR.LCOM"))

(MEDLEY-INIT-VARS 'GREET)

(KEYACTION 'LOCK '(LOCKTOGGLE . IGNORE))

(FILESLOAD BACKGROUND-YIELD)

(RPAQQ DWIMWAIT 180)

(RPAQQ HELPDEPTH 4)

(RPAQQ HELPTIME 1)

(RPAQQ FILING.ENUMERATION.DEPTH 1)

(RPAQ LOGINDIR (DIRECTORYNAME (OR (UNIX-GETENV "LOGINDIR")
                                  (UNIX-GETENV "HOME"))))

(RPAQ USERGREETFILES `((,LOGINDIR "INIT" COM)
                       (,LOGINDIR "INIT")))

(RPAQQ COPYRIGHTFLG NEVER)

(RPAQQ COPYRIGHTSRESERVED NIL)

(RPAQQ AUTOBACKTRACEFLG ALWAYS)

(RPAQQ MAXLEVEL 30000)

(RPAQQ MAXLOOP 30000)

(DEFINEQ

(INTERLISPMODE
  [LAMBDA (OLD?)                                                    (* N.H.Briggs " 2-Feb-88 14:26")
    (PROCESSPROP 'EXEC 'PROFILE (XCL:COPY-PROFILE (if OLD?
                                                      then "OLD-INTERLISP-T"
                                                    else "INTERLISP")))
    (XCL:SET-DEFAULT-EXEC-TYPE (if OLD?
                                   then "OLD-INTERLISP-T"
                                 else "INTERLISP"))
    (SETQ *DEFAULT-MAKEFILE-ENVIRONMENT* (LIST :READTABLE (if OLD?
                                                              then "OLD-INTERLISP-FILE"
                                                            else "INTERLISP")
                                               :PACKAGE "INTERLISP"])
```

```
)
(ADDTOVAR FONTDEFS )
```

FUNCTION INDEX

INTERLISPMODE 1

VARIABLE INDEX

AUTOBACKTRACEFLG 1
COPYRIGHTFLG 1
COPYRIGHTSRESERVED 1
DWIMWAIT 1
FILING.ENUMERATION.DEPTH 1
FONTDEFS 2
HELPDEPTH 1
HELPTIME 1
LOGINDIR 1
MAXLEVEL 1
MAXLOOP 1
USERGREETFILES 1