

File created: 5-Dec-2023 00:16:52 {WMEDLEY}<library>sketch>SKETCH-ELEMENTS.;1

edit by: rmk

changes to: (RECORDS LOCALCIRCLE CIRCLE LOCALELLIPSE ELLIPSE KNOTELT LOCALCURVE OPENCURVE CLOSEDCURVE
LOCALCLOSEDCURVE LOCALCLOSEDWIRE LOCALWIRE WIRE CLOSEDWIRE TEXT LOCALTEXT LOCALTEXTBOX
TEXTBOX BOX LOCALBOX ARC LOCALARC)

previous date: 4-Aug-2022 09:57:43 {WMEDLEY}<library>sketch>SKETCHELEMENTS.;2

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

(RPAQQ SKETCH-ELEMENTSCOMS

```
(  
; contains the functions need to implement the sketch basic  
; element types  
(FNS INIT.SKETCH.ELEMENTS CREATE.SKETCH.ELEMENT.TYPE SKETCH.ELEMENT.TYPEP SKETCH.ELEMENT.NAMEP  
  \CURSOR.IN.MIDDLE.MENU)  
(COMS ; color and filling stuff  
(FNS SKETCHINCOLORP READ.COLOR.CHANGE)  
(INITVARS (SKETCHINCOLORFLG)  
(FILLPOLYGONFLG T)  
(FILLINGMODEFLG T))  
(INITVARS (SK.DEFAULT.BACKCOLOR)  
(SK.DEFAULT.OPERATION))  
(GLOBALVARS SKETCHINCOLORFLG SK.DEFAULT.BACKCOLOR)  
(RECORDS SKFILLING)  
;; fns included until system is fixed so that it is ok to call DSPCOLOR in a system without color loaded. Should be removed after J  
;; release.  
(FNS SK.CREATE.DEFAULT.FILLING SKFILLINGP SK.INSURE.FILLING SK.INSURE.COLOR)  
(FNS SK.TRANSLATE.MODE SK.CHANGE.FILLING.MODE READ.FILLING.MODE))  
(COMS (FNS SKETCH.CREATE.CIRCLE CIRCLE.EXPANDFN CIRCLE.DRAWFN \CIRCLE.DRAWFN1 CIRCLE.INPUTFN  
  SK.UPDATE.CIRCLE.AFTER.CHANGE SK.READ.CIRCLE.POINT SK.SHOW.CIRCLE CIRCLE.INSIDEFN  
  CIRCLE.REGIONFN CIRCLE.GLOBALREGIONFN CIRCLE.TRANSLATE CIRCLE.READCHANGEFN CIRCLE.TRANSFORMFN  
  CIRCLE.TRANSLATEPTS SK.CIRCLE.CREATE SET.CIRCLE.SCALE SK.BRUSH.READCHANGE)  
(FNS SK.INSURE.BRUSH SK.INSURE.DASHING)  
(RECORDS BRUSH)  
(DECLARE%: DONTCOPY (RECORDS LOCALCIRCLE CIRCLE))  
(UGLYVARS CIRCLEICON)  
(CURSORS CIRCLE.CENTER CIRCLE.EDGE)  
(INITVARS [SK.DEFAULT.BRUSH (CONS 'ROUND (CONS 1 (CONS 'BLACK NIL)  
; Original was (create BRUSH BRUSHSHAPE _ 'ROUND  
; BRUSHSIZE _ 1 BRUSHCOLOR 'BLACK) _  
; Changed by yabu.fx, for SUNLOADUP without DWIM.  
(SK.DEFAULT.DASHING)  
(SK.DEFAULT.TEXTURE))  
(GLOBALVARS SK.DEFAULT.BRUSH SK.DEFAULT.DASHING SK.DEFAULT.TEXTURE))  
(COMS (FNS SKETCH.CREATE.ELLIPSE ELLIPSE.EXPANDFN ELLIPSE.DRAWFN ELLIPSE.INPUTFN  
  SK.READ.ELLIPSE.MAJOR.PT SK.SHOW.ELLIPSE.MAJOR.RADIUS SK.READ.ELLIPSE.MINOR.PT  
  SK.SHOW.ELLIPSE.MINOR.RADIUS ELLIPSE.INSIDEFN ELLIPSE.CREATE SK.UPDATE.ELLIPSE.AFTER.CHANGE  
  ELLIPSE.REGIONFN ELLIPSE.GLOBALREGIONFN ELLIPSE.TRANSLATEFN ELLIPSE.TRANSFORMFN  
  ELLIPSE.TRANSLATEPTS MARK.SPOT.DISTANCEBETWEEN SK.DISTANCE.TO.SQUARE  
  COMPUTE.ELLIPSE.ORIENTATION SK.COMPUTE.ELLIPSE.MINOR.RADIUS.PT)  
(DECLARE%: DONTCOPY (RECORDS LOCALELLIPSE ELLIPSE))  
(UGLYVARS ELLIPSEICON)  
(CURSORS ELLIPSE.CENTER ELLIPSE.SEMI.MAJOR ELLIPSE.SEMI.MINOR))  
(COMS (FNS SKETCH.CREATE.OPEN.CURVE OPENCURVE.INPUTFN SK.CURVE.CREATE MAXXEXTENT MAXYEXTENT  
  KNOT.SET.SCALE.FIELD OPENCURVE.DRAWFN OPENCURVE.EXPANDFN OPENCURVE.READCHANGEFN  
  OPENCURVE.TRANSFORMFN OPENCURVE.TRANSLATEFN OPENCURVE.TRANSLATEPTSFN  
  SKETCH.CREATE.CLOSED.CURVE CLOSEDCURVE.DRAWFN CLOSEDCURVE.EXPANDFN CLOSEDCURVE.REGIONFN  
  CLOSEDCURVE.GLOBALREGIONFN READ.LIST.OF.POINTS CLOSEDCURVE.INPUTFN CLOSEDCURVE.READCHANGEFN  
  CLOSEDCURVE.TRANSFORMFN CLOSEDCURVE.TRANSLATEPTSFN INVISIBLEPARTP SHOWSKETCHPOINT  
  SHOWSKETCHXY KNOTS.REGIONFN OPENWIRE.GLOBALREGIONFN CURVE.REGIONFN OPENCURVE.GLOBALREGIONFN  
  KNOTS.TRANSLATEFN REGION.CONTAINING.PTS)  
(FNS CHANGE.ELTS.BRUSH.SIZE CHANGE.ELTS.BRUSH CHANGE.ELTS.BRUSH.SHAPE SK.CHANGE.BRUSH.SHAPE  
  SK.CHANGE.BRUSH.COLOR SK.CHANGE.BRUSH.SIZE SK.CHANGE.ANGLE SK.CHANGE.ARC.DIRECTION  
  SK.SET.DEFAULT.BRUSH.SIZE READSIZECHANGE)  
(FNS SK.CHANGE.ELEMENT.KNOTS)  
(FNS SK.INSURE.POINT.LIST SK.INSURE.POSITION)  
(DECLARE%: DONTCOPY (RECORDS KNOTELT LOCALCURVE OPENCURVE CLOSEDCURVE LOCALCLOSEDCURVE  
  LOCALCLOSEDWIRE))  
(UGLYVARS OPENCURVEICON CLOSEDCURVEICON)  
(CURSORS CURVE.KNOT))  
(COMS (FNS SKETCH.CREATE.WIRE CLOSEDWIRE.EXPANDFN KNOTS.INSIDEFN OPEN.WIRE.DRAWFN WIRE.EXPANDFN  
  SK.UPDATE.WIRE.ELT.AFTER.CHANGE OPENWIRE.READCHANGEFN OPENWIRE.TRANSFORMFN  
  OPENWIRE.TRANSLATEFN OPENWIRE.TRANSLATEPTSFN WIRE.INPUTFN SK.READ.WIRE.POINTS  
  SK.READ.POINTS.WITH.FEEDBACK OPENWIRE.FEEDBACKFN CLOSEDWIRE.FEEDBACKFN CLOSEDWIRE.REGIONFN  
  CLOSEDWIRE.GLOBALREGIONFN SK.WIRE.CREATE WIRE.ADD.POINT.TO.END READ.ARROW.CHANGE  
  CHANGE.ELTS.ARROWHEADS)  
(FNS SKETCH.CREATE.CLOSED.WIRE CLOSED.WIRE.INPUTFN CLOSED.WIRE.DRAWFN CLOSEDWIRE.READCHANGEFN  
  CLOSEDWIRE.TRANSFORMFN CLOSEDWIRE.TRANSLATEPTSFN)  
(FNS SK.EXPAND.ARROWHEADS SK.COMPUTE.ARC.ARROWHEAD.POINTS ARC.ARROWHEAD.POINTS  
  SET.ARC.ARROWHEAD.POINTS SET.OPENCURVE.ARROWHEAD.POINTS SK.COMPUTE.CURVE.ARROWHEAD.POINTS  
  SET.WIRE.ARROWHEAD.POINTS SK.COMPUTE.WIRE.ARROWHEAD.POINTS SK.EXPAND.ARROWHEAD CHANGED.ARROW
```

```

SK.CHANGE.ARROWHEAD SK.CHANGE.ARROWHEAD1 SK.CREATE.ARROWHEAD SK.ARROWHEAD.CREATE
SK.ARROWHEAD.END.TEST READ.ARROWHEAD.END ARROW.HEAD.POSITIONS ARROWHEAD.POINTS.LIST
CURVE.ARROWHEAD.POINTS LEFT.MOST.IS.BEGINP WIRE.ARROWHEAD.POINTS DRAWARROWHEADS
\SK.DRAW.TRIANGLE.ARROWHEAD \SK.ENDPT.OF.ARROW \SK.ADJUST.FOR.ARROWHEADS
SK.SET.ARROWHEAD.LENGTH SK.SET.ARROWHEAD.ANGLE SK.SET.ARROWHEAD.TYPE SK.SET.LINE.ARROWHEAD
SK.UPDATE.ARROWHEAD.FORMAT SK.SET.LINE.LENGTH.MODE)
(FNS SK.INSURE.ARROWHEADS SK.ARROWHEADP)
(DECLARE%: DONTCOPY (RECORDS LOCALWIRE WIRE CLOSEDWIRE LOCALCLOSEDWIRE))
(RECORDS ARROWHEAD)
(UGLYVARS VSHAPE.ARROWHEAD.BITMAP TRIANGLE.ARROWHEAD.BITMAP SOLIDTRIANGLE.ARROWHEAD.BITMAP
CURVEDV.ARROWHEAD.BITMAP)
(UGLYVARS WIREICON CLOSEDWIREICON)
(INITVARS (SK.ARROWHEAD.ANGLE.INCREMENT 5)
(SK.ARROWHEAD.LENGTH.INCREMENT 2))
(ADDVARS (SK.ARROWHEAD.TYPES LINE CLOSEDLINE CURVE SOLID))
(INITVARS (SK.DEFAULT.ARROW.LENGTH 8)
(SK.DEFAULT.ARROW.TYPE 'CURVE)
(SK.DEFAULT.ARROW.ANGLE 18.0))
(GLOBALVARS SK.DEFAULT.ARROW.LENGTH SK.DEFAULT.ARROW.TYPE SK.DEFAULT.ARROW.ANGLE
SK.ARROWHEAD.TYPES)
(INITVARS (SK.ARROW.END.MENU)
(SK.ARROW.EDIT.MENU)))
(COMS ; stuff to support the text element type.
(FNS SKETCH.CREATE.TEXT TEXT.CHANGEFN TEXT.READCHANGEFN \SK.READ.FONT.SIZE1
SK.TEXT.ELT.WITH.SAME.FIELDS SK.READFONTFAMILY CLOSE.PROMPT.WINDOW TEXT.DRAWFN TEXT.DRAWFN1
TEXT.INSIDEFN TEXT.EXPANDFN SK.TEXT.LINE.REGIONS TEXT.UPDATE.GLOBAL.REGIONS REL.MOVE.REGION
LTEXT.LINE.REGIONS TEXT.INPUTFN READ.TEXT TEXT.POSITION.AND.CREATE.CREATE.TEXT.ELEMENT
SK.UPDATE.TEXT.AFTER.CHANGE SK.TEXT.FROM.TEXTBOX TEXT.SET.GLOBAL.REGIONS TEXT.REGIONFN
TEXT.GLOBALREGIONFN TEXT.TRANSLATEFN TEXT.TRANSFORMFN TEXT.TRANSLATEPTSFN TEXT.UPDATEFN
SK.CHANGE.TEXT TEXT.SET.SCALES BREAK.AT.CARRIAGE.RETURNS)
(FNS ADD.KNOWN.SKETCH.FONT SK.PICK.FONT SK.CHOOSE.TEXT.FONT SK.NEXTSIZEFONT
SK.DECREASING.FONT.LIST SK.GUESS.FONTSAVAILABLE)
(INITVARS (\KNOWN.SKETCH.FONT.SIZES))
(GLOBALVARS \KNOWN.SKETCH.FONT.SIZES)
(DECLARE%: DONTCOPY (RECORDS TEXT LOCALTEXT))
(FNS SK.SET.FONT SK.SET.TEXT.FONT SK.SET.TEXT.SIZE SK.SET.TEXT.HORIZ.ALIGN SK.READFONTSIZE
SK.COLLECT.FONT.SIZES SK.SET.TEXT.VERT.ALIGN SK.SET.TEXT.LOOKS SK.SET.DEFAULT.TEXT.FACE)
(FNS CREATE.SKETCH.TERMTABLE)
(FNS SK.FONT.LIST SK.INSURE.FONT SK.INSURE.STYLE SK.INSURE.TEXT)
(VARS INDICATE.TEXT.SHADE)
[INITVARS (SK.DEFAULT.FONT)
(SK.DEFAULT.TEXT.ALIGNMENT ' (CENTER BASELINE)]
(INITVARS \FONTSONFILE)
(ADDVARS (SK.HORIZONTAL.STYLES LEFT RIGHT CENTER)
(SK.VERTICAL.STYLES TOP CENTER BASELINE BOTTOM))
(VARS (SKETCH.TERMTABLE (CREATE.SKETCH.TERMTABLE)))
(GLOBALVARS SKETCH.TERMTABLE SK.DEFAULT.TEXT.ALIGNMENT INDICATE.TEXT.SHADE \FONTSONFILE
SK.HORIZONTAL.STYLES SK.VERTICAL.STYLES))
(COMS ; stuff for supporting the TEXTBOX sketch element.
(FNS SKETCH.CREATE.TEXTBOX SK.COMPUTE.TEXTBOX.REGION.FOR.STRING SK.BREAK.INTO.LINES SK.BRUSH.SIZE
SK.TEXTBOX.CREATE SK.TEXTBOX.CREATE1 SK.UPDATE.TEXTBOX.AFTER.CHANGE
SK.TEXTBOX.POSITION.IN.BOX TEXTBOX.CHANGEFN TEXTBOX.DRAWFN SK.TEXTURE.AROUND.REGIONS
ALL.EMPTY.REGIONS TEXTBOX.EXPANDFN TEXTBOX.INPUTFN TEXTBOX.INSIDEFN TEXTBOX.REGIONFN
TEXTBOX.GLOBALREGIONFN TEXTBOX.SET.GLOBAL.REGIONS TEXTBOX.TRANSLATEFN TEXTBOX.TRANSLATEPTSFN
TEXTBOX.TRANSFORMFN TEXTBOX.UPDATEFN TEXTBOX.READCHANGEFN SK.TEXTBOX.TEXT.POSITION
SK.TEXTBOX.FROM.TEXT.ADD.EOLS)
(DECLARE%: DONTCOPY (RECORDS LOCALTEXTBOX TEXTBOX))
(COMS ; stuff to handle default alignment for text boxes
(FNS SK.SET.TEXTBOX.VERT.ALIGN SK.SET.TEXTBOX.HORIZ.ALIGN)
(VARS TEXTBOXICON)
[INITVARS (SK.DEFAULT.TEXTBOX.ALIGNMENT ' (CENTER CENTER)
(GLOBALVARS SK.DEFAULT.TEXTBOX.ALIGNMENT))])
(COMS ; functions to implement the box sketch element.
(FNS SKETCH.CREATE.BOX SK.BOX.DRAWFN BOX.DRAWFN1 KNOTS.OF.REGION SK.DRAWAREABOX SK.DRAWBOX
SK.BOX.EXPANDFN SK.BOX.GETREGIONFN BOX.SET.SCALES SK.BOX.INPUTFN SK.BOX.CREATE
SK.UPDATE.BOX.AFTER.CHANGE SK.BOX.INSIDEFN SK.BOX.REGIONFN SK.BOX.GLOBALREGIONFN
SK.BOX.READCHANGEFN SK.CHANGE.FILLING SK.CHANGE.FILLING.COLOR SK.BOX.TRANSLATEFN
SK.BOX.TRANSFORMFN SK.BOX.TRANSLATEPTSFN UNSCALE.REGION.TO.GRID INCREASEREGION
INSUREREGIONSIZE EXPANDREGION REGION.FROM.COORDINATES)
(DECLARE%: DONTCOPY (RECORDS BOX LOCALBOX))
(UGLYVARS BOXICON))
(COMS ; fns for the arc sketch element type
(FNS SKETCH.CREATE.ARC ARC.DRAWFN ARC.EXPANDFN ARC.INPUTFN SK.INVERT.CIRCLE
SK.READ.ARC.ANGLE.POINT SK.SHOW.ARC ARC.CREATE SK.UPDATE.ARC.AFTER.CHANGE ARC.MOVEFN
ARC.TRANSLATEPTS ARC.INSIDEFN ARC.REGIONFN ARC.GLOBALREGIONFN ARC.TRANSLATE ARC.TRANSFORMFN
ARC.READCHANGEFN)
(FNS SK.COMPUTE.ARC.ANGLE.PT SK.COMPUTE.ARC.ANGLE.PT.FROM.ANGLE SK.COMPUTE.ARC.PTS
SK.SET.ARC.DIRECTION SK.SET.ARC.DIRECTION.CW SK.SET.ARC.DIRECTION.CCW
SK.COMPUTE.SLOPE.OF.LINE SK.CREATE.ARC.USING SET.ARC.SCALES)
(FNS SK.INSURE.DIRECTION)
(INITVARS (SK.NUMBER.OF.POINTS.IN.ARC 8))
(GLOBALVARS SK.NUMBER.OF.POINTS.IN.ARC)
(DECLARE%: DONTCOPY (RECORDS ARC LOCALARC))
(CURSORS ARC.RADIUS.CURSOR ARC.ANGLE.CURSOR CW.ARC.ANGLE.CURSOR CW.ARC.RADIUS.CURSOR)
(UGLYVARS ARCICON))
(COMS ; property getting and setting stuff
(FNS GETSKETCHELEMENTPROP \SK.GET.ARC.ANGLEPT \GETSKETCHELEMENTPROP1 \SK.GET.BRUSH \SK.GET.FILLING

```

```

\SK.GET.ARROWHEADS \SK.GET.FONT \SK.GET.JUSTIFICATION \SK.GET.DIRECTION \SK.GET.DASHING
PUTSKETCHELEMENTPROP \SK.PUT.FILLING ADDSKETCHELEMENTPROP REMOVESKETCHELEMENTPROP
\SK.PUT.FONT \SK.PUT.JUSTIFICATION \SK.PUT.DIRECTION \SK.PUT.DASHING \SK.PUT.BRUSH
\SK.PUT.ARROWHEADS SK.COPY.ELEMENT.PROPERTY.LIST SKETCH.UPDATE SKETCH.UPDATE1
\SKELT.GET.SCALE \SKELT.PUT.SCALE \SKELT.PUT.DATA SK.REPLACE.TEXT.IN.ELEMENT \SKELT.GET.DATA
\SK.GET.1STCONTROLPT \SK.PUT.1STCONTROLPT \SK.GET.2NDCONTROLPT \SK.PUT.2NDCONTROLPT
\SK.GET.3RDCONTROLPT \SK.PUT.3RDCONTROLPT
(FNS LOWERLEFTCORNER UPPERRIGHTCORNER)))

```

:: contains the functions need to implement the sketch basic element types

(DEFINEQ

(INIT.SKETCH.ELEMENTS

[LAMBDA NIL

; Edited 23-Jul-90 15:38 by matsuda
(* sets up the initial sketch element types.)

(* put the datatype for the element on the property list of the name and use the name in the instances.)

[COND

```

((NOT (SKETCH.ELEMENT.TYEP 'CIRCLE))
 (CREATE.SKETCH.ELEMENT.TYPE 'CIRCLE CIRCLEICON "Adds a circle to the figure." (FUNCTION CIRCLE.DRAWFN)
  (FUNCTION CIRCLE.EXPANDFN)
  'OBSOLETE
  (FUNCTION SK.ELEMENTS.CHANGEFN)
  (FUNCTION CIRCLE.INPUTFN)
  (FUNCTION CIRCLE.INSIDEFN)
  (FUNCTION CIRCLE.REGIONFN)
  (FUNCTION CIRCLE.TRANSLATE)
  NIL
  (FUNCTION CIRCLE.READCHANGEFN)
  (FUNCTION CIRCLE.TRANSFORMFN)
  (FUNCTION CIRCLE.TRANSLATEPTS)
  (FUNCTION CIRCLE.GLOBALREGIONFN]

```

[COND

```

((NOT (SKETCH.ELEMENT.TYEP 'ELLIPSE))
 (CREATE.SKETCH.ELEMENT.TYPE 'ELLIPSE ELLIPSEICON "Adds an ellipse to the figure."
  (FUNCTION ELLIPSE.DRAWFN)
  (FUNCTION ELLIPSE.EXPANDFN)
  'OBSOLETE
  (FUNCTION SK.ELEMENTS.CHANGEFN)
  (FUNCTION ELLIPSE.INPUTFN)
  (FUNCTION ELLIPSE.INSIDEFN)
  (FUNCTION ELLIPSE.REGIONFN)
  (FUNCTION ELLIPSE.TRANSLATEFN)
  NIL
  (FUNCTION SK.BRUSH.READCHANGE)
  (FUNCTION ELLIPSE.TRANSFORMFN)
  (FUNCTION ELLIPSE.TRANSLATEPTS)
  (FUNCTION ELLIPSE.GLOBALREGIONFN]

```

[COND

```

((NOT (SKETCH.ELEMENT.TYEP 'ARC))
 (CREATE.SKETCH.ELEMENT.TYPE 'ARC ARCICON "Adds an arc to the figure." (FUNCTION ARC.DRAWFN)
  (FUNCTION ARC.EXPANDFN)
  'OBSOLETE
  (FUNCTION SK.ELEMENTS.CHANGEFN)
  (FUNCTION ARC.INPUTFN)
  (FUNCTION ARC.INSIDEFN)
  (FUNCTION ARC.REGIONFN)
  (FUNCTION ARC.TRANSLATE)
  NIL
  (FUNCTION ARC.READCHANGEFN)
  (FUNCTION ARC.TRANSFORMFN)
  (FUNCTION ARC.TRANSLATEPTS)
  (FUNCTION ARC.GLOBALREGIONFN]

```

[COND

```

((NOT (SKETCH.ELEMENT.TYEP 'OPENCURVE))
 (CREATE.SKETCH.ELEMENT.TYPE 'OPENCURVE OPENCURVEICON "Adds a curve by accepting points the curve goes
 through." (FUNCTION OPENCURVE.DRAWFN)
  (FUNCTION OPENCURVE.EXPANDFN)
  'OBSOLETE
  (FUNCTION SK.ELEMENTS.CHANGEFN)
  (FUNCTION OPENCURVE.INPUTFN)
  (FUNCTION KNOTS.INSIDEFN)
  (FUNCTION CURVE.REGIONFN)
  (FUNCTION OPENCURVE.TRANSLATEFN)
  NIL
  (FUNCTION OPENCURVE.READCHANGEFN)
  (FUNCTION OPENCURVE.TRANSFORMFN)
  (FUNCTION OPENCURVE.TRANSLATEPTSFN)
  (FUNCTION OPENCURVE.GLOBALREGIONFN]

```

[COND

```

((NOT (SKETCH.ELEMENT.TYEP 'CLOSEDCURVE))
 (CREATE.SKETCH.ELEMENT.TYPE 'CLOSEDCURVE CLOSEDCURVEICON "Adds a closed curve by accepting points that
 it goes through." (FUNCTION CLOSEDCURVE.DRAWFN)
  (FUNCTION CLOSEDCURVE.EXPANDFN)
  'OBSOLETE

```

```
(FUNCTION SK.ELEMENTS.CHANGEFN)
(FUNCTION CLOSEDCURVE.INPUTFN)
(FUNCTION KNOTS.INSIDEFN)
(FUNCTION CLOSEDCURVE.REGIONFN)
(FUNCTION KNOTS.TRANSLATEFN)
NIL
(FUNCTION CLOSEDCURVE.READCHANGEFN)
(FUNCTION CLOSEDCURVE.TRANSFORMFN)
(FUNCTION CLOSEDCURVE.TRANSLATEPTSFN)
(FUNCTION CLOSEDCURVE.GLOBALREGIONFN]
```

```
[COND
((NOT (SKETCH.ELEMENT.TYEP 'WIRE))
(CREATE.SKETCH.ELEMENT.TYPE 'WIRE WIREICON "Adds a series of lines by accepting points."
(FUNCTION OPEN.WIRE.DRAWFN)
(FUNCTION WIRE.EXPANDFN)
' OBSOLETE
(FUNCTION SK.ELEMENTS.CHANGEFN)
(FUNCTION WIRE.INPUTFN)
(FUNCTION KNOTS.INSIDEFN)
(FUNCTION KNOTS.REGIONFN)
(FUNCTION OPENWIRE.TRANSLATEFN)
NIL
(FUNCTION OPENCURVE.READCHANGEFN)
(FUNCTION OPENWIRE.TRANSFORMFN)
(FUNCTION OPENWIRE.TRANSLATEPTSFN)
(FUNCTION OPENWIRE.GLOBALREGIONFN]
```

```
[COND
((NOT (SKETCH.ELEMENT.TYEP 'CLOSEDWIRE))
(CREATE.SKETCH.ELEMENT.TYPE 'CLOSEDWIRE CLOSEDWIREICON "Adds a closed polygon by accepting the
corners." (FUNCTION CLOSED.WIRE.DRAWFN)
(FUNCTION CLOSEDWIRE.EXPANDFN)
' OBSOLETE
(FUNCTION SK.ELEMENTS.CHANGEFN)
(FUNCTION CLOSED.WIRE.INPUTFN)
(FUNCTION KNOTS.INSIDEFN)
(FUNCTION CLOSEDWIRE.REGIONFN)
(FUNCTION KNOTS.TRANSLATEFN)
NIL
(FUNCTION CLOSEDWIRE.READCHANGEFN)
(FUNCTION CLOSEDWIRE.TRANSFORMFN)
(FUNCTION CLOSEDWIRE.TRANSLATEPTSFN)
(FUNCTION CLOSEDWIRE.GLOBALREGIONFN]
```

```
[COND
((NOT (SKETCH.ELEMENT.TYEP 'TEXT))
(CREATE.SKETCH.ELEMENT.TYPE 'TEXT NIL "text is added by pointing to its position and typing."
(FUNCTION TEXT.DRAWFN)
(FUNCTION TEXT.EXPANDFN)
' OBSOLETE
(FUNCTION SK.ELEMENTS.CHANGEFN)
(FUNCTION TEXT.INPUTFN)
(FUNCTION TEXT.INSIDEFN)
(FUNCTION TEXT.REGIONFN)
(FUNCTION TEXT.TRANSLATEFN)
(FUNCTION TEXT.UPDATEFN)
(FUNCTION TEXT.READCHANGEFN)
(FUNCTION TEXT.TRANSFORMFN)
(FUNCTION TEXT.TRANSLATEPTSFN)
(FUNCTION TEXT.GLOBALREGIONFN]
```

```
[COND
((NOT (SKETCH.ELEMENT.TYEP 'BOX))
(CREATE.SKETCH.ELEMENT.TYPE 'BOX BOXICON "Adds a box by accepting two corners." (FUNCTION SK.BOX.DRAWFN
)
(FUNCTION SK.BOX.EXPANDFN)
' OBSOLETE
(FUNCTION SK.ELEMENTS.CHANGEFN)
(FUNCTION SK.BOX.INPUTFN)
(FUNCTION SK.BOX.INSIDEFN)
(FUNCTION SK.BOX.REGIONFN)
(FUNCTION SK.BOX.TRANSLATEFN)
NIL
(FUNCTION SK.BOX.READCHANGEFN)
(FUNCTION SK.BOX.TRANSFORMFN)
(FUNCTION SK.BOX.TRANSLATEPTSFN)
(FUNCTION SK.BOX.GLOBALREGIONFN]
```

```
[COND
((NOT (SKETCH.ELEMENT.TYEP 'TEXTBOX))
(CREATE.SKETCH.ELEMENT.TYPE 'TEXTBOX TEXTBOXICON "Adds a box into which text can be typed."
(FUNCTION TEXTBOX.DRAWFN)
(FUNCTION TEXTBOX.EXPANDFN)
' OBSOLETE
(FUNCTION SK.ELEMENTS.CHANGEFN)
(FUNCTION TEXTBOX.INPUTFN)
(FUNCTION TEXTBOX.INSIDEFN)
(FUNCTION TEXTBOX.REGIONFN)
(FUNCTION TEXTBOX.TRANSLATEFN)
(FUNCTION TEXTBOX.UPDATEFN)
(FUNCTION TEXTBOX.READCHANGEFN)
```

(FUNCTION TEXTBOX.TRANSFORMFN)
(FUNCTION TEXTBOX.TRANSLATEPTSFN)
(FUNCTION TEXTBOX.GLOBALREGIONFN))

(CREATE.SKETCH.ELEMENT.TYPE

```
[LAMBDA (SKETCHTYPE LABEL DOCSTR DRAWFN EXPANDFN OBSOLETE CHANGEFN INPUTFN INSIDEFN REGIONFN TRANSLATEFN
UPDATEFN READCHANGEFN TRANSFORMFN TRANSLATEPTSFN GLOBALREGIONFN)
(* rrb "18-Oct-85 17:18")
(* creates a new sketch element type.)

(COND
  ((AND OBSOLETE (NEQ OBSOLETE 'OBSOLETE))
    (printout T OBSOLETE " will never be called. CREATE.SKETCH.ELEMENT.TYPE"))
  (SETQ SKETCH.ELEMENT.TYPES
    (CONS (PUTPROP SKETCHTYPE 'SKETCHTYPE
      (create SKETCHTYPE
        LABEL _ LABEL
        DOCSTR _ DOCSTR
        DRAWFN _ DRAWFN
        EXPANDFN _ EXPANDFN
        CHANGEFN _ CHANGEFN
        INPUTFN _ INPUTFN
        INSIDEFN _ INSIDEFN
        REGIONFN _ REGIONFN
        TRANSLATEFN _ TRANSLATEFN
        UPDATEFN _ UPDATEFN
        READCHANGEFN _ READCHANGEFN
        TRANSFORMFN _ TRANSFORMFN
        TRANSLATEPTSFN _ TRANSLATEPTSFN
        GLOBALREGIONFN _ GLOBALREGIONFN)
        SKETCH.ELEMENT.TYPES))
      (OR (MEMB SKETCHTYPE SKETCH.ELEMENT.TYPE.NAMES)
        (SETQ SKETCH.ELEMENT.TYPE.NAMES (CONS SKETCHTYPE SKETCH.ELEMENT.TYPE.NAMES)))
      SKETCHTYPE])
```

(SKETCH.ELEMENT.TYPEP

```
[LAMBDA (SKETCHTYPE)
(* rrb "28-Dec-84 15:39")
(* is SKETCHTYPE a sketch element type?)

(AND (MEMB SKETCHTYPE SKETCH.ELEMENT.TYPE.NAMES)
  (GETPROP SKETCHTYPE 'SKETCHTYPE])
```

(SKETCH.ELEMENT.NAMEP

```
[LAMBDA (X)
(* rrb "18-MAR-83 11:53")
(* is X a sketch element type name?)

(FMEMB X SKETCH.ELEMENT.TYPE.NAMES])
```

(CURSOR.IN.MIDDLE.MENU

```
[LAMBDA (MENU)
(* rrb " 6-Nov-85 09:46")
(* brings up the menu so that the cursor is in the middle.)

(MENU MENU (create POSITION
  XCOORD _ (DIFFERENCE LASTMOUSEX (QUOTIENT (fetch (MENU IMAGEWIDTH) of MENU)
  2))
  YCOORD _ (DIFFERENCE LASTMOUSEY (QUOTIENT (fetch (MENU IMAGEHEIGHT) of MENU)
  2))

)
```

:: color and filling stuff

(DEFINEQ

(SKETCHINCOLORP

```
[LAMBDA NIL
(* rrb "12-Jul-85 10:11")
(* hook to determine if sketch should allow color.)

SKETCHINCOLORFLG])
```

(READ.COLOR.CHANGE

```
[LAMBDA (MSG ALLOWNONEFLG CURRENTCOLOR)
(* rrb "29-Oct-85 12:30")
(* reads a color from the user and returns it)

(READCOLOR1 MSG ALLOWNONEFLG CURRENTCOLOR)]
```

(RPAQ? SKETCHINCOLORFLG)

(RPAQ? FILLPOLYGONFLG T)

(RPAQ? FILLINGMODEFLG T)

(RPAQ? SK.DEFAULT.BACKCOLOR)

(RPAQ? SK.DEFAULT.OPERATION)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS SKETCHINCOLORFLG SK.DEFAULT.BACKCOLOR)
)

(DECLARE%: EVAL@COMPILE

(RECORD SKFILLING (FILLING.TEXTURE FILLING.COLOR FILLING.OPERATION))
)

:: fns included until system is fixed so that it is ok to call DSPCOLOR in a system without color loaded. Should be removed after J release.

(DEFINEQ

(SK.CREATE.DEFAULT.FILLING

[LAMBDA NIL (* rrb "21-Feb-86 11:22")
(create SKFILLING
FILLING.TEXTURE _ SK.DEFAULT.TEXTURE
FILLING.COLOR _ SK.DEFAULT.BACKCOLOR
FILLING.OPERATION _ SK.DEFAULT.OPERATION)])

(SKFILLINGP

[LAMBDA (FILLING) (* rrb "21-Feb-86 11:20")
(* determines if FILLING is a legal sketch filling.)
(COND
(AND (LISTP FILLING)
(TEXTUREP (fetch (SKFILLING FILLING.TEXTURE) of FILLING))
(NULL (CDDDR FILLING))) (* should also check if (fetch (SKFILLING FILLING.COLOR)) is
a color and that (SKFILLING FILLING.OPERATION) is an
operation.)
FILLING)])

(SK.INSURE.FILLING

[LAMBDA (FILLING SKW) (* rrb "16-Oct-85 15:47")
(* converts several possible legal filling specifications into a
sketch filling)
(COND
((SKFILLINGP FILLING))
(T (PROG [(DEFAULTFILLING (COND
[(WINDOWP SKW)
(fetch (SKETCHCONTEXT SKETCHFILLING) of (WINDOWPROP SKW 'SKETCHCONTEXT])
(T (SK.CREATE.DEFAULT.FILLING]
(RETURN (COND
(NULL FILLING)
DEFAULTFILLING)
(TEXTUREP FILLING)
(create SKFILLING using DEFAULTFILLING FILLING.TEXTURE _ FILLING))
(\POSSIBLECOLOR FILLING)
(* note that small numbers can be either a texture or a color. This algorithm will make them be a texture.)
(create SKFILLING using DEFAULTFILLING FILLING.COLOR _ FILLING))
(T (* should be a check here for a color too.)
(\ILLEGAL.ARG FILLING)])

(SK.INSURE.COLOR

[LAMBDA (COLOR) (* rrb "16-Oct-85 18:05")
(* checks the validity of a color argument.)
(COND
((NULL COLOR)
NIL)
(\POSSIBLECOLOR COLOR))
(T (\ILLEGAL.ARG COLOR])
)

(DEFINEQ

(SK.TRANSLATE.MODE

[LAMBDA (OPERATION STREAM) (* rrb "10-Mar-86 17:20")
(* picks the best operation for a filling.)
(COND
((EQ (DSOPERATION NIL STREAM)
'ERASE) (* drawing should do its best job of erasing the current image)
(SELECTQ OPERATION
(INVERT 'INVERT)
(ERASE
(* don't know what to do because we don't know what bits were removed but this at least lets the user know something
happened wrt this element.)
'PAINT)
'ERASE))
(T OPERATION)])

(SK.CHANGE.FILLING.MODE

[LAMBDA (ELTWITHFILLING HOW SKW)

(* rrb " 3-Mar-86 14:36")

(* changes the texture in the element ELTWITHFILLING.)

(PROG (GFILLEDELT MODE FILLING NEWFILLING TYPE NEWELT)
(RETURN (COND

((MEMB (SETQ TYPE (fetch (GLOBALPART GTYPE) of ELTWITHFILLING))
' (BOX TEXTBOX CLOSEDWIRE CIRCLE)) (* only works for things that have a filling, for now just boxes and
polygons)
(SETQ GFILLEDELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHFILLING))
[SETQ MODE (fetch (SKFILLING FILLING.OPERATION) of (SETQ FILLING
(SELECTQ TYPE
(BOX (fetch (BOX BOXFILLING)
of GFILLEDELT))
(TEXTBOX (fetch (TEXTBOX
TEXTBOXFILLING
)
of GFILLEDELT))
(CIRCLE (fetch (CIRCLE CIRCLEFILLING
)
of GFILLEDELT))
(CLOSEDWIRE (fetch (CLOSEDWIRE
CLOSEDWIREFILLING
)
of GFILLEDELT))
(SHOULDNT])

(COND

((NOT (EQUAL HOW MODE)) (* new filling mode)
(SETQ NEWFILLING (create SKFILLING using FILLING FILLING.OPERATION _ HOW))
(SETQ NEWELT (SELECTQ TYPE
(BOX (create BOX using GFILLEDELT BOXFILLING _ NEWFILLING))
(TEXTBOX (create TEXTBOX using GFILLEDELT TEXTBOXFILLING _ NEWFILLING)
(CLOSEDWIRE (create CLOSEDWIRE using GFILLEDELT CLOSEDWIREFILLING _
NEWFILLING))
(CIRCLE (create CIRCLE using GFILLEDELT CIRCLEFILLING _ NEWFILLING))
(SHOULDNT)))
(create SKHISTORYCHANGESPEC
NEWELT _ (create GLOBALPART
COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
of ELTWITHFILLING)
INDIVIDUALGLOBALPART _ NEWELT)
OLDELT _ ELTWITHFILLING
PROPERTY _ 'FILLING
NEWVALUE _ NEWFILLING
OLDVALUE _ FILLING])

(READ.FILLING.MODE

[LAMBDA NIL

(* rrb " 3-Mar-86 14:30")

(* reads a filling mode from the user.)

(CURSOR.IN.MIDDLE.MENU (create MENU
CENTERFLG _ T
TITLE _ "How should the filling merge with the covered figures?"
MENURROWS _ 1
ITEMS _ '((REPLACE 'REPLACE "the filling completely covers anything under
it.")
(PAINT 'PAINT "the black parts of the filling cover but the white
parts show through.")
(ERASE 'ERASE "the black parts of the filling are erased.")
(INVERT 'INVERT "the black parts of the filling are inverted."))

(DEFINEQ

(SKETCH.CREATE.CIRCLE

[LAMBDA (CENTERPT RADIUSPT BRUSH DASHING FILLING SCALE)

(* rrb "11-Dec-85 10:43")

(* creates a sketch circle element.)

(SK.CIRCLE.CREATE (SK.INSURE.POSITION CENTERPT)
(COND
[(NUMBERP RADIUSPT)
(create POSITION
XCOORD _ (PLUS (fetch (POSITION XCOORD) of CENTERPT)
RADIUSPT)
YCOORD _ (PLUS (fetch (POSITION YCOORD) of CENTERPT)
RADIUSPT))]
(T (SK.INSURE.POSITION RADIUSPT)))
(SK.INSURE.BRUSH BRUSH)
(SK.INSURE.DASHING DASHING)
(OR (NUMBERP SCALE)
1.0)
(SK.INSURE.FILLING FILLING])

(CIRCLE.EXPANDFN

[LAMBDA (GCIRCLE SCALE)

(* rrb " 7-Dec-85 20:45")

(* returns a screen elt that has a circle screen element calculated from the global part.)

(PROG (CENTER RADIUSPT BRUSH (INDGCIRCLE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCIRCLE))))

(* check to make sure there is an initial scale field. This change was introduced on Apr 27 and can be taken out the release after Jazz It can also be taken out of the other expand fns as well.)

```
[COND
  ((fetch (CIRCLE CIRCLEINITSSCALE) of INDGCIRCLE))
  (T
    (replace (GLOBALPART INDIVIDUALGLOBALPART) of GCIRCLE
      with (SETQ INDGCIRCLE (create CIRCLE using INDGCIRCLE CIRCLEINITSSCALE _ 1.0])
    (RETURN (create SCREENELT
      LOCALPART _ (create LOCALCIRCLE
        CENTERPOSITION _ (SETQ CENTER (SK.SCALE.POSITION.INTO.VIEWER
          (fetch (CIRCLE CENTERLATLON)
            of INDGCIRCLE)
          SCALE))
        RADIUSPOSITION _ (SETQ RADIUSPT (SK.SCALE.POSITION.INTO.VIEWER
          (fetch (CIRCLE RADIUSLATLON)
            of INDGCIRCLE)
          SCALE))
        RADIUS _ (DISTANCEBETWEEN CENTER RADIUSPT)
        LOCALCIRCLEBRUSH _
        (SCALE.BRUSH (COND
          ([NOT (NUMBERP (SETQ BRUSH (fetch (CIRCLE BRUSH)
            of INDGCIRCLE]
            BRUSH)
            (* new format, old format had brush width only.)
          (T [replace (CIRCLE BRUSH) of INDGCIRCLE
            with (SETQ BRUSH
              (create BRUSH
                BRUSHSIZE _ BRUSH
                BRUSHSHAPE _ 'ROUND]
              BRUSH))
            (fetch (CIRCLE CIRCLEINITSSCALE) of INDGCIRCLE)
            SCALE)
          LOCALCIRCLEFILLING _ (APPEND (fetch (CIRCLE CIRCLEFILLING)
            of INDGCIRCLE))
          LOCALCIRCLEDASHING _ (fetch (CIRCLE DASHING) of INDGCIRCLE))
          GLOBALPART _ GCIRCLE])

```

(CIRCLE.DRAWFN

[LAMBDA (CIRCLEELT WINDOW REGION)

(* rrb "20-Jun-86 17:08")

(* draws a circle from a circle element.)

```
(PROG ((GCIRCLE (fetch (SCREENELT INDIVIDUALGLOBALPART) of CIRCLEELT))
  (LCIRCLE (fetch (SCREENELT LOCALPART) of CIRCLEELT))
  CPOS DASHING FILLING)
  (SETQ CPOS (fetch (LOCALCIRCLE CENTERPOSITION) of LCIRCLE))
  (SETQ DASHING (fetch (LOCALCIRCLE LOCALCIRCLEDASHING) of LCIRCLE))
  (SETQ FILLING (fetch (LOCALCIRCLE LOCALCIRCLEFILLING) of LCIRCLE))
  (COND
    ((fetch (SKFILLING FILLING.COLOR) of FILLING)
```

(* if the circle is filled with a color call FILLCIRCLE with both the texture and the color. This allows iris to do its thing before textures and colors are merged.)

```
(DSOPERATION (PROG1 (DSOPERATION (fetch (SKFILLING FILLING.OPERATION) of FILLING)
  WINDOW)
  (FILLCIRCLE (fetch (POSITION XCOORD) of CPOS)
    (fetch (POSITION YCOORD) of CPOS)
    (fetch (LOCALCIRCLE RADIUS) of LCIRCLE)
    FILLING WINDOW))
  WINDOW))
```

((fetch (SKFILLING FILLING.TEXTURE) of FILLING) (* if the circle is filled with texture, call FILLCIRCLE.)

```
(DSOPERATION (PROG1 (DSOPERATION (fetch (SKFILLING FILLING.OPERATION) of FILLING)
  WINDOW)
  (FILLCIRCLE (fetch (POSITION XCOORD) of CPOS)
    (fetch (POSITION YCOORD) of CPOS)
    (fetch (LOCALCIRCLE RADIUS) of LCIRCLE)
    (COND
```

((EQ (DSOPERATION NIL WINDOW) 'ERASE)

(* use black in case the window moved because of texture to window alignment bug.)

```
BLACKSHADE)
  (T (fetch (SKFILLING FILLING.TEXTURE) of FILLING)))
  WINDOW))
```

```
(RETURN (\CIRCLE.DRAWFN1 CPOS (fetch (LOCALCIRCLE RADIUSPOSITION) of LCIRCLE)
  (fetch (LOCALCIRCLE RADIUS) of LCIRCLE)
  (fetch (LOCALCIRCLE LOCALCIRCLEBRUSH) of LCIRCLE)
  DASHING WINDOW])
```

(\CIRCLE.DRAWFN1


```
[LAMBDA (CENTERPT RADIUSPT RADIUS BRUSH DASHING WINDOW) ; Edited 17-Apr-90 17:24 by matsuda
; (* draws a circle for sketch from some information.
; Calls by CIRCLE.DRAWFN and ARC.DRAWFN)

(COND
  (DASHING
    (DRAWCURVE (SK.COMPUTE.ARC.PTS CENTERPT RADIUSPT (* draw it with the arc drawing code which does dashing.)
      [COND
        [(LESSP (FETCH (POSITION XCOORD) OF CENTERPT)
          (FETCH (POSITION XCOORD) OF RADIUSPT))
          (PTPLUS RADIUSPT (CONSTANT (create POSITION
            XCOORD _ 0
            YCOORD _ -1]
        [(GREATERP (FETCH (POSITION XCOORD) OF CENTERPT)
          (FETCH (POSITION XCOORD) OF RADIUSPT))
          (PTPLUS RADIUSPT (CONSTANT (create POSITION
            XCOORD _ 0
            YCOORD _ 1]
        [(LESSP (FETCH (POSITION YCOORD) OF CENTERPT)
          (FETCH (POSITION YCOORD) OF RADIUSPT))
          (PTPLUS RADIUSPT (CONSTANT (create POSITION
            XCOORD _ 1
            YCOORD _ 0]
        (T (PTPLUS RADIUSPT (CONSTANT (create POSITION
            XCOORD _ -1
            YCOORD _ 0]
          NIL)
        T BRUSH DASHING WINDOW))
      (T (DRAWCIRCLE (fetch (POSITION XCOORD) of CENTERPT)
        (fetch (POSITION YCOORD) of CENTERPT)
        RADIUS BRUSH DASHING WINDOW])
```

(CIRCLE.INPUTFN

```
[LAMBDA (WINDOW) (* rrb "20-May-86 10:49")
```

(* reads a two points from the user and returns a circle element that it represents.)

```
(PROG [CENTERPT RADIUSPT (SKETCHCONTEXT (WINDOWPROP WINDOW 'SKETCHCONTEXT)
  (STATUSPRINT WINDOW "
    " "Indicate center of circle")
  (COND
    ((NOT (SETQ CENTERPT (SK.READ.POINT.WITH.FEEDBACK WINDOW CIRCLE.CENTER NIL NIL NIL NIL
      SKETCH.USE.POSITION.PAD)))
      (CLOSEPROMPTWINDOW WINDOW)
      (RETURN NIL)))
    (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTERPT)
      NIL WINDOW)
    (STATUSPRINT WINDOW "
      " "Indicate a point of the circumference of the circle")
    (SETQ RADIUSPT (SK.READ.CIRCLE.POINT WINDOW (fetch (INPUTPT INPUT.POSITION) of CENTERPT)
      CIRCLE.EDGE)) (* erase center mark)
    (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTERPT)
      NIL WINDOW)
    (CLOSEPROMPTWINDOW WINDOW)
    (OR RADIUSPT (RETURN NIL))
    (SETQ CENTERPT (SK.MAP.INPUT.PT.TO.GLOBAL CENTERPT WINDOW))
    (SETQ RADIUSPT (SK.MAP.INPUT.PT.TO.GLOBAL RADIUSPT WINDOW))
    (RETURN (SK.CIRCLE.CREATE CENTERPT RADIUSPT (fetch (SKETCHCONTEXT SKETCHBRUSH) of SKETCHCONTEXT)
      (fetch (SKETCHCONTEXT SKETCHDASHING) of SKETCHCONTEXT)
      (SK.INPUT.SCALE WINDOW)
      (fetch (SKETCHCONTEXT SKETCHFILLING) of SKETCHCONTEXT])
```

(SK.UPDATE.CIRCLE.AFTER.CHANGE

```
[LAMBDA (GCIRELT) (* rrb " 7-Dec-85 19:50")
(* updates the dependent fields of a circle element when a field
changes.)
(replace (CIRCLE CIRCLEREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCIRELT) with NIL])
```

(SK.READ.CIRCLE.POINT

```
[LAMBDA (WINDOW CENTERPT CURSOR) (* rrb "20-May-86 10:46")
```

(* reads a point from the user prompting them with a circle that follows the cursor)

```
(SK.READ.POINT.WITH.FEEDBACK WINDOW CURSOR (AND SKETCH.VERBOSE.FEEDBACK (FUNCTION SK.SHOW.CIRCLE))
  CENTERPT
  'MIDDLE NIL SKETCH.USE.POSITION.PAD])
```

(SK.SHOW.CIRCLE

```
[LAMBDA (X Y WINDOW CENTERPT) (* rrb "15-Nov-85 14:18")
```

(* xors a circle to X Y from CENTERPT in a window. Used as the feedback function for reading the radius point for circles.)
(* Mark the point too.)

```
(SHOWSKETCHXY X Y WINDOW)
(PROG ((CENTERX (fetch (POSITION XCOORD) of CENTERPT))
```

```
(CENTERY (fetch (POSITION YCOORD) of CENTERPT))
(DRAWCIRCLE CENTERX CENTERY (SK.DISTANCE.TO CENTERX CENTERY X Y)
 1 NIL WINDOW)
```

(CIRCLE.INSIDEFN

```
[LAMBDA (GCIRCLE WREG)
  (REGIONSINTERSECTP WREG (CIRCLE.GLOBALREGIONFN GCIRCLE])
  (* rrb "20-Jan-87 14:44")
  (* determines if the global circle GCIRCLE is inside of WREG.)
```

(CIRCLE.REGIONFN

```
[LAMBDA (CIRCSCRELT)
  (PROG ((LOCALCIRCLE (fetch (SCREENELT LOCALPART) of CIRCSCRELT))
    RADIUS)
    (SETQ RADIUS (IPLUS (FIX (ADD1 (fetch (LOCALCIRCLE RADIUS) of LOCALCIRCLE)))
      (LRSH [ADD1 (MAX 1 (fetch (BRUSH BRUSHSIZE) of (fetch (LOCALCIRCLE LOCALCIRCLEBRUSH)
        of LOCALCIRCLE]
        1))))
    (RETURN (CREATEREGION (IDIFFERENCE (fetch (POSITION XCOORD) of (SETQ LOCALCIRCLE (fetch (LOCALCIRCLE
      CENTERPOSITION)
      of LOCALCIRCLE)))
      RADIUS)
      (IDIFFERENCE (fetch (POSITION YCOORD) of LOCALCIRCLE)
        RADIUS)
      (SETQ RADIUS (ITIMES RADIUS 2))
      RADIUS])
  (* rrb "3-Oct-85 17:12")
  (* returns the region occupied by a circle.)
```

(CIRCLE.GLOBALREGIONFN

```
[LAMBDA (GCIRELT)
  (OR (fetch (CIRCLE CIRCLEREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCIRELT))
    (PROG ((INDVCIRCLE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCIRELT))
      RADIUS CENTER REGION)
      (* rrb "18-Oct-85 16:32")
      (* returns the global region occupied by a global circle element.)
```

(* make the radius be too large by the amount of the brush to catch round off, i.e. it should be half the brush size.)

```
[SETQ RADIUS (PLUS (DISTANCEBETWEEN (SETQ CENTER (fetch (CIRCLE CENTERLATON) of INDVCIRCLE))
  (fetch (CIRCLE RADIUSLATON) of INDVCIRCLE))
  (fetch (BRUSH BRUSHSIZE) of (fetch (CIRCLE BRUSH) of INDVCIRCLE))
(SETQ REGION (CREATEREGION (DIFFERENCE (fetch (POSITION XCOORD) of CENTER)
  RADIUS)
  (DIFFERENCE (fetch (POSITION YCOORD) of CENTER)
    RADIUS)
  (SETQ RADIUS (TIMES RADIUS 2))
  RADIUS))
(replace (CIRCLE CIRCLEREGION) of INDVCIRCLE with REGION)
(RETURN REGION])
```

(CIRCLE.TRANSLATE

```
[LAMBDA (CIRCLESKELT DELTAPOS)
  (PROG ((GCIRCLE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of CIRCLESKELT))
    (RETURN (create GLOBALPART
      COMMONGLOBALPART _ (APPEND (fetch (GLOBALPART COMMONGLOBALPART) of CIRCLESKELT))
      INDIVIDUALGLOBALPART _ (create CIRCLE using GCIRCLE CENTERLATON _
        (PTPLUS (fetch (CIRCLE CENTERLATON)
          of GCIRCLE)
          DELTAPOS)
        RADIUSLATON _ (PTPLUS (fetch (CIRCLE
          RADIUSLATON
          of GCIRCLE)
          DELTAPOS)
          CIRCLEREGION _ NIL])
  (* rrb "18-Oct-85 11:00")
  (* returns a changed global circle element which has the circle translated by DELTAPOS.)
```

(CIRCLE.READCHANGEFN

```
[LAMBDA (SKW SCRNELTS) ; Edited 23-Jul-90 15:30 by matsuda
```

(* the users has selected SCRNELT to be changed this function reads a specification of how the circle elements should change.)

```
(PROG (ASPECT HOW)
  (SETQ HOW (SELECTQ [SETQ ASPECT (\CURSOR.IN.MIDDLE.MENU
    (create MENU
      CENTERFLG _ T
      TITLE _ "Which aspect?"
      ITEMS _ (APPEND (COND
        [(SKETCHINCOLORP)
          ('("Brush color" 'BRUSHCOLOR "changes the
            color of the outline")
```

```

("Filling color" 'FILLINGCOLOR
 "changes the color of the
 filling"]
(T NIL))
[COND
 (FILLPOLYGONFLG ' ("Filling 'FILLING
 "allows changing of
 the filling texture
 of the box."])
[COND
 (FILLINGMODEFLG ' ("Filling mode"
 'FILLINGMODE "changes how
 the filling effects the
 figures it covers."])
' ((Shape 'SHAPE "changes the shape of the
 brush")
 (Size 'SIZE "changes the size of the brush")
 (Dashing 'DASHING "changes the dashing of the
 line."])
(SIZE (READSIZECHANGE "Change size how?" T))
(FILLING (READ.FILLING.CHANGE))
(FILLINGMODE (READ.FILLING.MODE))
(DASHING (READ.DASHING.CHANGE))
(SHAPE (READBRUSHSHAPE))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change outline color how?" NIL
 (fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
 (fetch (SCREENELT GLOBALPART)
 of (CAR SCRNELTS))
 'BRUSH)])
(FILLINGCOLOR [READ.COLOR.CHANGE "Change filling color how?" T
 (fetch (SKFILLING FILLING.COLOR) of (GETSKETCHELEMENTPROP
 (fetch (SCREENELT GLOBALPART)
 of (CAR SCRNELTS))
 'FILLING])
NIL))
(RETURN (AND HOW (LIST ASPECT HOW]))

```

(CIRCLE.TRANSFORMFN

```

[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR) (* rrb "18-Oct-85 11:04")

```

(* returns a copy of the global element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to tranformfn.)

```

(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
 (RETURN (create GLOBALPART using GELT INDIVIDUALGLOBALPART _ (create CIRCLE
 using INDVPART CENTERLATLON _
 (SK.TRANSFORM.POINT
 (fetch (CIRCLE CENTERLATLON)
 of INDVPART)
 TRANSFORMFN TRANSFORMDATA)
 RADIUSLATLON _
 (SK.TRANSFORM.POINT
 (fetch (CIRCLE RADIUSLATLON)
 of INDVPART)
 TRANSFORMFN TRANSFORMDATA)
 BRUSH _ (SK.TRANSFORM.BRUSH
 (fetch (CIRCLE BRUSH)
 of INDVPART)
 SCALEFACTOR)
 CIRCLEREGION _ NIL]))

```

(CIRCLE.TRANSLATEPTS

```

[LAMBDA (CIRCLESPEC SELPTS GLOBALDELTA WINDOW) (* rrb "9-Aug-85 09:55")
 (* returns a changed global circle element which has the part
 SELPOS moved to NEWPOS.)

```

```

(PROG ((LCIRCLE (fetch (SCREENELT LOCALPART) of CIRCLESPEC))
 (GCIRCLE (fetch (SCREENELT INDIVIDUALGLOBALPART) of CIRCLESPEC)))
 (RETURN (SK.CIRCLE.CREATE (COND
 ((MEMBER (fetch (LOCALCIRCLE CENTERPOSITION) of LCIRCLE)
 SELPTS) (* move the center)
 (PTPLUS (fetch (CIRCLE CENTERLATLON) of GCIRCLE)
 GLOBALDELTA))
 (T (fetch (CIRCLE CENTERLATLON) of GCIRCLE))))
 (COND
 ((MEMBER (fetch (LOCALCIRCLE RADIUSPOSITION) of LCIRCLE)
 SELPTS) (* move the radius point.)
 (PTPLUS (fetch (CIRCLE RADIUSLATLON) of GCIRCLE)
 GLOBALDELTA))
 (T (fetch (CIRCLE RADIUSLATLON) of GCIRCLE))))
 (fetch (CIRCLE BRUSH) of GCIRCLE)
 (fetch (CIRCLE DASHING) of GCIRCLE)
 (fetch (CIRCLE CIRCLEINITSCALE) of GCIRCLE)
 (fetch (CIRCLE CIRCLEFILLING) of GCIRCLE]))

```

(SK.CIRCLE.CREATE

[LAMBDA (CENTERPT RADIUSPT BRUSH DASHING INITSCALE FILLING)

(* rrb "18-Oct-85 11:01")
(* creates a sketch element)
(* region is a cache that will be filled if needed.)

(SET.CIRCLE.SCALE (create GLOBALPART
INDIVIDUALGLOBALPART _
(create CIRCLE
CENTERLATLON _ CENTERPT
RADIUSLATLON _ RADIUSPT
BRUSH _ BRUSH
DASHING _ DASHING
CIRCLEINITSCALE _ INITSCALE
CIRCLEFILLING _ FILLING
CIRCLEREGION _ NIL])

(SET.CIRCLE.SCALE

[LAMBDA (GCIRCELT)

(* rrb " 7-Feb-85 12:22")

(* sets the scale fields in a circle. Sets scale so that it goes from radius 1 to 3000.0)

(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCIRCELT))
RAD)
(SETQ RAD (DISTANCEBETWEEN (fetch (CIRCLE CENTERLATLON) of INDVPART)
(fetch (CIRCLE RADIUSLATLON) of INDVPART)))
(replace (GLOBALPART COMMONGLOBALPART) of GCIRCELT with (create COMMONGLOBALPART
MAXSCALE _ RAD
MINSCALE _ (QUOTIENT RAD 3000.0)))

(RETURN GCIRCELT])

(SK.BRUSH.READCHANGE

[LAMBDA (SKW SCRNELTS)

(* rrb " 6-Nov-85 09:49")
(* changefn for curves)

(PROG (ASPECT HOW)
(SETQ HOW (SELECTQ [SETQ ASPECT (\CURSOR.IN.MIDDLE.MENU (create MENU
CENTERFLG _ T
TITLE _ "select aspect of brush to
change"
ITEMS _
(APPEND
(COND
[(SKETCHINCOLORP)
'(("Color" 'BRUSHCOLOR "changes
the color of the brush")
(T NIL))
'((Shape 'SHAPE "changes the shape of
the brush")
(Size 'SIZE "changes the size of the
brush")
(Dashing 'DASHING "changes the
dashing of the line.")]

(SIZE (READSIZECHANGE "Change size how?"))
(SHAPE (READBRUSHSHAPE))
(DASHING (READ.DASHING.CHANGE))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change brush color how?" NIL
(fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
(fetch (SCREENELT GLOBALPART)
of (CAR SCRNELTS))
'BRUSH])

NIL))
(RETURN (AND HOW (LIST ASPECT HOW])

(DEFINEQ

(SK.INSURE.BRUSH

[LAMBDA (BRUSH)

(* rrb "16-Oct-85 15:37")
(* coerces BRUSH into a brush. Errors if it won't go.)

(COND
((BRUSHP BRUSH))
(NUMBERP BRUSH)
(create BRUSH
BRUSHSIZE _ BRUSH))
(NULL BRUSH)
SK.DEFAULT.BRUSH)
(T (\ILLEGAL.ARG BRUSH])

(SK.INSURE.DASHING

[LAMBDA (DASHING)

(* rrb "16-Oct-85 17:04")
(* checks the validity of a dashing argument.
NIL is ok and means no dashing.)

(AND DASHING (OR (DASHINGP DASHING)
(\ILLEGAL.ARG DASHING])

```

)
(DECLARE%: EVAL@COMPILE
(RECORD BRUSH (BRUSHSHAPE BRUSHSIZE BRUSHCOLOR)
  BRUSHSHAPE _ 'ROUND BRUSHSIZE _ 1)
)
(DECLARE%: DONTCOPY
(DECLARE%: EVAL@COMPILE
(RECORD LOCALCIRCLE ((CENTERPOSITION RADIUSPOSITION)
  LOCALHOTREGION RADIUS LOCALCIRCLEBRUSH LOCALCIRCLEFILLING LOCALCIRCLEDASHING))
(TYPERECORD CIRCLE (CENTERLATLON RADIUSLATLON BRUSH DASHING CIRCLEINITSSCALE CIRCLEFILLING CIRCLEREGION))
)
)
(READVARS-FROM-STRINGS ' (CIRCLEICON)
  "({ (READBITMAP) (20 12
    %"AOH@@@@"
    %"COL@@@@"
    %"G@N@@@@"
    %"F@F@@@@"
    %"N@G@@@@"
    %"L@C@@@@"
    %"L@C@@@@"
    %"N@G@@@@"
    %"F@F@@@@"
    %"G@N@@@@"
    %"COL@@@@"
    %"AOH@@@@"}) )
  ")


```

```

(RPAQ CIRCLE.CENTER (CURSORCREATE ' 
  'NIL 7 7))

```

```

(RPAQ CIRCLE.EDGE (CURSORCREATE ' 
  'NIL 15 7))

```

```

(RPAQ? SK.DEFAULT.BRUSH (CONS 'ROUND (CONS 1 (CONS 'BLACK NIL))))

```

```

(RPAQ? SK.DEFAULT.DASHING )

```

```

(RPAQ? SK.DEFAULT.TEXTURE )

```

```

(DECLARE%: DOEVAL@COMPILE DONTCOPY

```

```

(GLOBALVARS SK.DEFAULT.BRUSH SK.DEFAULT.DASHING SK.DEFAULT.TEXTURE)
)

```

```

(DEFINEQ

```

(SKETCH.CREATE.ELLIPSE

```

[LAMBDA (CENTERPT ORIENTATIONPT OTHERRADIUSPT BRUSH DASHING WILLBEFILLING SCALE)
  (* rrb "16-Oct-85 17:05")
  (* creates a sketch ellipse element.)

```

```

  (ELLIPSE.CREATE (SK.INSURE.POSITION CENTERPT)
    (SK.INSURE.POSITION ORIENTATIONPT)
    (SK.INSURE.POSITION OTHERRADIUSPT)
    (SK.INSURE.BRUSH BRUSH)
    (SK.INSURE.DASHING DASHING)
    (OR (NUMBERP SCALE)
      1.0))

```

(ELLIPSE.EXPANDFN

```

[LAMBDA (GELLIPSE SCALE)
  (* rrb " 7-Dec-85 20:40")

```

(* returns a screen elt that has a ellipse screen element calculated from the global part.)

```

(PROG (CENTER MINRAD MAJRAD BRUSH (INDGELLIPSE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELLIPSE)))
[COND
  ((fetch (ELLIPSE ELLIPSEINITSSCALE) of INDGELLIPSE))
  (T
    (* old format didn't have an initial scale, create one and default it
      to 1.0)
    (replace (GLOBALPART INDIVIDUALGLOBALPART) of GELLIPSE
      with (SETQ INDGELLIPSE (create ELLIPSE using INDGELLIPSE ELLIPSEINITSSCALE _ 1.0 ELLIPSEREGION _
        NIL]
  (RETURN (create SCREENELT
    LOCALPART _ (create LOCALELLIPSE
      ELLIPSECENTER _ (SETQ CENTER (SK.SCALE.POSITION.INTO.VIEWER
        (fetch (ELLIPSE ELLIPSECENTERLATLON)
          of INDGELLIPSE)

```

```

                                SCALE))
MINORRADIUSPOSITION _ (SETQ MINRAD (SK.SCALE.POSITION.INTO.VIEWER
                                (fetch (ELLIPSE SEMIMINORLATION)
                                of INDGELLIPSE)
                                SCALE))
MAJORRADIUSPOSITION _ (SETQ MAJRAD (SK.SCALE.POSITION.INTO.VIEWER
                                (fetch (ELLIPSE SEMIMAJORLATION)
                                of INDGELLIPSE)
                                SCALE))
SEMIMINORRADIUS _ (DISTANCEBETWEEN CENTER MINRAD)
SEMIMAJORRADIUS _ (DISTANCEBETWEEN CENTER MAJRAD)
LOCALELLIPSEBRUSH _
(SCALE.BRUSH (COND
              ([NOT (NUMBERP (SETQ BRUSH (fetch (ELLIPSE BRUSH)
              of INDGELLIPSE]
              (* new format, old format had brush width only.)
              BRUSH)
              (T [replace (ELLIPSE BRUSH) of INDGELLIPSE
              with (SETQ BRUSH
              (create BRUSH
              BRUSHSIZE _ BRUSH
              BRUSHSHAPE _ 'ROUND]
              BRUSH))
              (fetch (ELLIPSE ELLIPSEINITSIZE) of INDGELLIPSE)
              SCALE)
              LOCALELLIPSE DASHING _ (fetch (ELLIPSE DASHING) of INDGELLIPSE))
GLOBALPART _ GELLIPSE])

```

(ELLIPSE.DRAWFN

```

[LAMBDA (ELLIPSELT WINDOW REGION)
                                (* rrb " 7-Dec-85 20:40")
                                (* draws a ellipse from a circle element.)
(PROG ((GELLIPSE (fetch (SCREENELT INDIVIDUALGLOBALPART) of ELLIPSELT))
      (LELLIPSE (fetch (SCREENELT LOCALPART) of ELLIPSELT))
      CPOS DASHING ORIENTATION)
      (SETQ CPOS (fetch (LOCALELLIPSE ELLIPSECENTER) of LELLIPSE))
      (SETQ DASHING (fetch (LOCALELLIPSE LOCALELLIPSE DASHING) of LELLIPSE))
      (SETQ ORIENTATION (fetch (ELLIPSE ORIENTATION) of GELLIPSE))
      (RETURN (COND
              (DASHING
              (* draw it with the curve drawing code which does dashing.)
              (PROG ((SINOR (SIN ORIENTATION))
                    (COSOR (COS ORIENTATION))
                    (CENTERX (fetch (POSITION XCOORD) of CPOS))
                    (CENTERY (fetch (POSITION YCOORD) of CPOS))
                    (SEMIMINORRADIUS (fetch (LOCALELLIPSE SEMIMINORRADIUS) of LELLIPSE))
                    (SEMIMAJORRADIUS (fetch (LOCALELLIPSE SEMIMAJORRADIUS) of LELLIPSE)))
                    (DRAWCURVE [LIST (CREATEPOSITION (PLUS CENTERX (FTIMES COSOR SEMIMAJORRADIUS))
                    (PLUS CENTERY (FTIMES SINOR SEMIMAJORRADIUS)))
                    (CREATEPOSITION (DIFFERENCE CENTERX (FTIMES SINOR
                    SEMIMINORRADIUS))
                    (PLUS CENTERY (FTIMES COSOR SEMIMINORRADIUS)))
                    (CREATEPOSITION (DIFFERENCE CENTERX (FTIMES COSOR
                    SEMIMAJORRADIUS))
                    (DIFFERENCE CENTERY (FTIMES SINOR SEMIMAJORRADIUS)))
                    (CREATEPOSITION (PLUS CENTERX (FTIMES SINOR SEMIMINORRADIUS))
                    (DIFFERENCE CENTERY (FTIMES COSOR SEMIMINORRADIUS))
                    T
                    (fetch (LOCALELLIPSE LOCALELLIPSEBRUSH) of LELLIPSE)
                    DASHING WINDOW)))
              (T (DRAWELLIPSE (fetch (POSITION XCOORD) of CPOS)
              (fetch (POSITION YCOORD) of CPOS)
              (fetch (LOCALELLIPSE SEMIMINORRADIUS) of LELLIPSE)
              (fetch (LOCALELLIPSE SEMIMAJORRADIUS) of LELLIPSE)
              ORIENTATION
              (fetch (LOCALELLIPSE LOCALELLIPSEBRUSH) of LELLIPSE)
              DASHING WINDOW]))

```

(ELLIPSE.INPUTFN

```

[LAMBDA (WINDOW)
                                (* rrb "21-May-86 16:13")
                                (* reads three points from the user and returns the ellipse figure element that it represents.)
(PROG (CENTER MAJRAD MINRAD)
      (STATUSPRINT WINDOW "
      " "Indicate center of ellipse")
      (COND
        ((SETQ CENTER (SK.READ.POINT.WITH.FEEDBACK WINDOW ELLIPSE.CENTER NIL NIL NIL NIL
        SKETCH.USE.POSITION.PAD))
        (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTER)
        NIL WINDOW))
        (T (CLOSEPROMPTWINDOW WINDOW)
        (RETURN NIL)))
      (STATUSPRINT WINDOW "
      " "Indicate semi-major axis")
      (COND
        ((SETQ MAJRAD (SK.READ.ELLIPSE.MAJOR.PT WINDOW (fetch (INPUTPT INPUT.POSITION) of CENTER)))

```

```

(MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of MAJRAD)
  NIL WINDOW)
(T
  (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTER)
    NIL WINDOW)
  (CLOSEPROMPTWINDOW WINDOW)
  (RETURN NIL))
(STATUSPRINT WINDOW "
  " "Indicate semi-minor axis")
(SETQ MINRAD (SK.READ.ELLIPSE.MINOR.PT WINDOW (fetch (INPUTPT INPUT.POSITION) of CENTER)
  (fetch (INPUTPT INPUT.POSITION) of MAJRAD)))
(CLOSEPROMPTWINDOW WINDOW)
(MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of MAJRAD)
  NIL WINDOW)
(MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTER)
  NIL WINDOW)
(OR MINRAD (RETURN NIL))
(RETURN (ELLIPSE.CREATE (SK.MAP.INPUT.PT.TO.GLOBAL CENTER WINDOW)
  (SK.MAP.INPUT.PT.TO.GLOBAL MINRAD WINDOW)
  (SK.MAP.INPUT.PT.TO.GLOBAL MAJRAD WINDOW)
  (fetch (SKETCHCONTEXT SKETCHBRUSH) of (WINDOWPROP WINDOW 'SKETCHCONTEXT))
  (fetch (SKETCHCONTEXT SKETCHDASHING) of (WINDOWPROP WINDOW 'SKETCHCONTEXT))
  (SK.INPUT.SCALE WINDOW]))

```

(SK.READ.ELLIPSE.MAJOR.PT

[LAMBDA (SKW CENTERPT) (* rrb "20-May-86 10:47")

(* reads a position from the user that will be the major radius point of an ellipse.)

```

(SK.READ.POINT.WITH.FEEDBACK WINDOW ELLIPSE.SEMI.MAJOR (AND SKETCH.VERBOSE.FEEDBACK (FUNCTION
  SK.SHOW.ELLIPSE.MAJOR.RADIUS
  )))
CENTERPT
'MIDDLE NIL SKETCH.USE.POSITION.PAD])

```

(SK.SHOW.ELLIPSE.MAJOR.RADIUS

[LAMBDA (X Y WINDOW CENTERPT) (* rrb "14-Nov-85 16:46")

(* xors a line from X Y to a point the opposite side of CENTERPT in a window.
Used as the feedback function for reading the major radius point for ellipses.)
(* Mark the point too.)

```

(SHOWSKETCHXY X Y WINDOW)
(DRAWLINE X Y (PLUS X (TIMES 2 (DIFFERENCE (fetch (POSITION XCOORD) of CENTERPT)
  X)))
  (PLUS Y (TIMES 2 (DIFFERENCE (fetch (POSITION YCOORD) of CENTERPT)
  Y)))
  1
  'INVERT WINDOW])

```

(SK.READ.ELLIPSE.MINOR.PT

[LAMBDA (SKW CENTERPT MAJORPT) (* rrb "20-May-86 10:47")

(* reads a position from the user that will be the major radius point of an ellipse.)

```

(SK.READ.POINT.WITH.FEEDBACK WINDOW ELLIPSE.SEMI.MINOR (AND SKETCH.VERBOSE.FEEDBACK (FUNCTION
  SK.SHOW.ELLIPSE.MINOR.RADIUS
  )))
(LIST CENTERPT (DISTANCEBETWEEN CENTERPT MAJORPT)
  (COMPUTE.ELLIPSE.ORIENTATION CENTERPT MAJORPT))
'MIDDLE NIL SKETCH.USE.POSITION.PAD])

```

(SK.SHOW.ELLIPSE.MINOR.RADIUS

[LAMBDA (X Y WINDOW ELLIPSEARGS) (* rrb "15-Nov-85 14:17")

(* xors a line from X Y to a point the opposite side of CENTERPT in a window.
Used as the feedback function for reading the major radius point for ellipses.)
(* Mark the point too.)

```

(SHOWSKETCHXY X Y WINDOW)
(PROG ((CENTERX (CAR ELLIPSEARGS))
  CENTERX)
  (SETQ CENTERX (fetch (POSITION YCOORD) of CENTERX))
  (SETQ CENTERX (fetch (POSITION XCOORD) of CENTERX))
  (DRAWELLIPSE CENTERX CENTERX (SK.DISTANCE.TO CENTERX CENTERX X Y)
    (CADR ELLIPSEARGS)
    (CADDR ELLIPSEARGS)
    1 NIL WINDOW])

```

(ELLIPSE.INSIDFN

[LAMBDA (GELLIPSE WREG) (* rrb "20-Jan-87 14:45")

(* determines if the global ellipse GELLIPSE is inside of WREG.)

```

(REGIONSINTERSECTP WREG (ELLIPSE.GLOBALREGIONFN GELLIPSE])

```

(ELLIPSE.CREATE

```
[LAMBDA (CENTERPT MINPT MAJPT BRUSH DASHING INITSCALE) (* rrb "19-Jul-85 14:26")
(* creates a global ellipse element.)

(PROG ((MAXRAD (MAX (DISTANCEBETWEEN CENTERPT MINPT)
(DISTANCEBETWEEN CENTERPT MAJPT)))
ORIENTATION)
(RETURN (create GLOBALPART
COMMONGLOBALPART _ (create COMMONGLOBALPART
MAXSCALE _ MAXRAD
MINSCALE _ (QUOTIENT MAXRAD 3000.0))
INDIVIDUALGLOBALPART _ (create ELLIPSE
ORIENTATION _ (SETQ ORIENTATION (
COMPUTE.ELLIPSE.ORIENTATION
CENTERPT MAJPT))
BRUSH _ BRUSH
DASHING _ DASHING
ELLIPSECENTERLATLON _ CENTERPT
SEMIMINORLATLON _ (SK.COMPUTE.ELLIPSE.MINOR.RADIUS.PT
CENTERPT MAJPT MINPT ORIENTATION)
SEMIMAJORLATLON _ MAJPT
ELLIPSEINITSCALE _ INITSCALE])
```

(SK.UPDATE.ELLIPSE.AFTER.CHANGE

```
[LAMBDA (GELLIPSEELT) (* rrb " 7-Dec-85 19:54")
(* updates the dependent fields of an ellipse element when a
field changes.)

(replace (ELLIPSE ELLIPSEREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELLIPSEELT) with NIL])
```

(ELLIPSE.REGIONFN

```
[LAMBDA (ELLIPSCRELT) (* rrb " 3-Oct-85 17:10")
(* returns the region occupied by an ellipse.)

(PROG ((LOCALELLIPSE (fetch (SCREENELT LOCALPART) of ELLIPSCRELT))
MAJORRADPT CENTERX CENTERY BRUSHADJ HALFWD HALFHGT RADRATIO DELTAX DELTAY)
(SETQ MAJORRADPT (fetch (LOCALELLIPSE MAJORRADIUSPOSITION) of LOCALELLIPSE))
(SETQ CENTERX (fetch (LOCALELLIPSE ELLIPSECENTER) of LOCALELLIPSE))
[SETQ RADRATIO (ABS (FQUOTIENT (fetch (LOCALELLIPSE SEMIMINORRADIUS) of LOCALELLIPSE)
(fetch (LOCALELLIPSE SEMIMAJORRADIUS) of LOCALELLIPSE)
1))
[SETQ DELTAX (ABS (IDIFFERENCE (SETQ CENTERX (fetch (POSITION XCOORD) of CENTERX))
(fetch (POSITION XCOORD) of MAJORRADPT)
1))
[SETQ DELTAY (ABS (IDIFFERENCE (SETQ CENTERX (fetch (POSITION YCOORD) of CENTERX))
(fetch (POSITION YCOORD) of MAJORRADPT)
1))
(SETQ BRUSHADJ (LRSH (ADD1 (fetch (BRUSH BRUSHSIZE) of (fetch (LOCALELLIPSE LOCALELLIPSEBRUSH)
of LOCALELLIPSE)))
1))
(SETQ HALFWD (FIXR (PLUS DELTAX (FTIMES RADRATIO DELTAY)
BRUSHADJ)))
(SETQ HALFHGT (FIXR (PLUS DELTAY (FTIMES RADRATIO DELTAX)
BRUSHADJ)))

(* use the rectangle that contains the rectangle made by the extreme points of the ellipse.
This gets more than is called for when the orientation isn't 0 or 90.0)

(RETURN (CREATEREGION (IDIFFERENCE CENTERX HALFWD)
(IDIFFERENCE CENTERX HALFHGT)
(ITIMES HALFWD 2)
(ITIMES HALFHGT 2]))
```

(ELLIPSE.GLOBALREGIONFN

```
[LAMBDA (GELELT) (* rrb "20-Nov-85 16:09")
(* returns the global region occupied by a global ellipse element.)

(OR (fetch (ELLIPSE ELLIPSEREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELELT))
(PROG ((INDVELLIPSE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELELT))
CENTERPT HALFBOXSIZE MAXRAD REGION)
(SETQ CENTERPT (fetch (ELLIPSE ELLIPSECENTERLATLON) of INDVELLIPSE))
[SETQ MAXRAD (MAX (DISTANCEBETWEEN CENTERPT (fetch (ELLIPSE SEMIMAJORLATLON) of INDVELLIPSE))
(DISTANCEBETWEEN CENTERPT (fetch (ELLIPSE SEMIMINORLATLON) of INDVELLIPSE))
[SETQ HALFBOXSIZE (PLUS MAXRAD (fetch (BRUSH BRUSHSIZE) of (fetch (ELLIPSE BRUSH) of INDVELLIPSE))

(* use a square about the center as wide as the largest radius. This gets too much but is easy to calculate.)

(SETQ REGION (CREATEREGION (DIFFERENCE (fetch (POSITION XCOORD) of CENTERPT)
HALFBOXSIZE)
(DIFFERENCE (fetch (POSITION YCOORD) of CENTERPT)
HALFBOXSIZE)
(ITIMES HALFBOXSIZE 2)
(ITIMES HALFBOXSIZE 2)))
(replace (ELLIPSE ELLIPSEREGION) of INDVELLIPSE with REGION)
(RETURN REGION])
```

(ELLIPSE.TRANSLATEFN

```
[LAMBDA (SKELT DELTAPOS) (* rrb "18-Oct-85 17:08")
(* returns a global ellipse element which has been translated by
DELTAPOS.)
```



```
(PROG ((GLOBALEL (fetch (GLOBALPART INDIVIDUALGLOBALPART) of SKELT)))
  (RETURN (create GLOBALPART
    COMMONGLOBALPART _ (APPEND (fetch (GLOBALPART COMMONGLOBALPART) of SKELT))
    INDIVIDUALGLOBALPART _ (create ELLIPSE using GLOBALEL ORIENTATION _ (fetch (ELLIPSE
      ORIENTATION
    )
      of GLOBALEL)
    ELLIPSECENTERLATLON _
    (PTPLUS (fetch (ELLIPSE ELLIPSECENTERLATLON)
      of GLOBALEL)
    DELTAPOS)
    SEMIMINORLATLON _ (PTPLUS
      (fetch (ELLIPSE
        SEMIMINORLATLON
      )
      of GLOBALEL)
    DELTAPOS)
    SEMIMAJORLATLON _ (PTPLUS
      (fetch (ELLIPSE
        SEMIMAJORLATLON
      )
      of GLOBALEL)
    DELTAPOS)
    ELLIPSEREGION _ NIL]))
```

(ELLIPSE.TRANSFORMFN

```
[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR) (* rrb "26-Apr-85 16:21")
```

(* returns a copy of the global ellipse element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to transformfn.)

```
(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (RETURN (ELLIPSE.CREATE (SK.TRANSFORM.POINT (fetch (ELLIPSE ELLIPSECENTERLATLON) of INDVPART)
    TRANSFORMFN TRANSFORMDATA)
    (SK.TRANSFORM.POINT (fetch (ELLIPSE SEMIMINORLATLON) of INDVPART)
    TRANSFORMFN TRANSFORMDATA)
    (SK.TRANSFORM.POINT (fetch (ELLIPSE SEMIMAJORLATLON) of INDVPART)
    TRANSFORMFN TRANSFORMDATA)
    (SK.TRANSFORM.BRUSH (fetch (ELLIPSE BRUSH) of INDVPART)
    SCALEFACTOR)
    (fetch (ELLIPSE DASHING) of INDVPART)
    (fetch (ELLIPSE ELLIPSEINITSSCALE) of INDVPART]))
```

(ELLIPSE.TRANSLATEPTS

```
[LAMBDA (ELLIPSESPEC SELPTS GLOBALDELTA WINDOW) (* rrb " 5-May-85 16:41")
```

(* returns a new global ellipse element which has the points on SELPTS moved by a global distance.)

```
(PROG ((LELLIPSE (fetch (SCREENELT LOCALPART) of ELLIPSESPEC))
  (GELLIPSE (fetch (SCREENELT INDIVIDUALGLOBALPART) of ELLIPSESPEC)))
  (RETURN (ELLIPSE.CREATE (COND
    ((MEMBER (fetch (LOCALELLIPSE ELLIPSECENTER) of LELLIPSE)
      SELPTS) (* move the center)
    (PTPLUS (fetch (ELLIPSE ELLIPSECENTERLATLON) of GELLIPSE)
      GLOBALDELTA))
    (T (fetch (ELLIPSE ELLIPSECENTERLATLON) of GELLIPSE))))
  (COND
    ((MEMBER (fetch (LOCALELLIPSE MINORRADIUSPOSITION) of LELLIPSE)
      SELPTS) (* move the radius point.)
    (PTPLUS (fetch (ELLIPSE SEMIMINORLATLON) of GELLIPSE)
      GLOBALDELTA))
    (T (fetch (ELLIPSE SEMIMINORLATLON) of GELLIPSE))))
  (COND
    ((MEMBER (fetch (LOCALELLIPSE MAJORRADIUSPOSITION) of LELLIPSE)
      SELPTS) (* move the radius point.)
    (PTPLUS (fetch (ELLIPSE SEMIMAJORLATLON) of GELLIPSE)
      GLOBALDELTA))
    (T (fetch (ELLIPSE SEMIMAJORLATLON) of GELLIPSE))))
  (fetch (ELLIPSE BRUSH) of GELLIPSE)
  (fetch (ELLIPSE DASHING) of GELLIPSE)
  (fetch (ELLIPSE ELLIPSEINITSSCALE) of GELLIPSE]))
```

(MARK.SPOT

```
[LAMBDA (X/POSITION Y WINDOW) (* rrb "14-JAN-83 15:40")
```

```
(PROG [X WIDTH HEIGHT (COLORDS (WINDOWPROP WINDOW 'INCOLOR])
  (COND
    ((POSITIONP X/POSITION)
      (SETQ X (fetch (POSITION XCOORD) of X/POSITION))
      (SETQ Y (fetch (POSITION YCOORD) of X/POSITION)))
    (T (SETQ X X/POSITION)))
  (SETQ WIDTH (BITMAPWIDTH SPOTMARKER))
  (SETQ HEIGHT (BITMAPHEIGHT SPOTMARKER))
  (BITBLT (COND
    [COLORDS (COND
```

```

      ((AND (BITMAPP COLORSPOTMARKER)
            (EQ (BITSPERPIXEL COLORSPOTMARKER)
                (COLORNUMBERBITSPPERPIXEL)))
        COLORSPOTMARKER)
      (T (SETQ COLORSPOTMARKER (COLORIZEBITMAP SPOTMARKER 0 (MAXIMUMCOLOR)
                                                (COLORNUMBERBITSPPERPIXEL]
          (T SPOTMARKER))
      0 0 (OR COLORDS WINDOW)
      (IDIFFERENCE X (IQUOTIENT WIDTH 2))
      (IDIFFERENCE Y (IQUOTIENT HEIGHT 2))
      WIDTH HEIGHT 'INPUT 'INVERT])

```

(DISTANCEBETWEEN

```

[LAMBDA (P1 P2)
  (SQRT (PLUS (SQUARE (DIFFERENCE (fetch (POSITION XCOORD) of P1)
                                     (fetch (POSITION XCOORD) of P2)))
              (SQUARE (DIFFERENCE (fetch (POSITION YCOORD) of P1)
                                     (fetch (POSITION YCOORD) of P2)))
  (* rrb "5-JAN-83 12:17")
  (* returns the distance between two points)

```

(SK.DISTANCE.TO

```

[LAMBDA (X1 Y1 X2 Y2)
  (SQRT (PLUS (SQUARE (DIFFERENCE X1 X2))
              (SQUARE (DIFFERENCE Y1 Y2)))
  (* rrb "15-Nov-85 14:17")
  (* returns the distance between two points)

```

(SQUARE

```

[LAMBDA (X)
  (TIMES X X)]

```

(COMPUTE.ELLIPSE.ORIENTATION

```

[LAMBDA (CENTERPT MAJRADPT)
  (* computes the orientation of an ellipse from its center point and its major radius point.)
  (PROG [(DELTAX (IDIFFERENCE (fetch (POSITION XCOORD) of MAJRADPT)
                               (fetch (POSITION XCOORD) of CENTERPT))
        (RETURN (COND
                  ((ZEROP DELTAX)
                   90.0)
                  (T (ARCTAN2 (IDIFFERENCE (fetch (POSITION YCOORD) of MAJRADPT)
                                           (fetch (POSITION YCOORD) of CENTERPT))
                              DELTAX)])
  (* rrb "19-Oct-85 12:44")

```

(SK.COMPUTE.ELLIPSE.MINOR.RADIUS.PT

```

[LAMBDA (CENTER MAJORRADPT MINORPT ORIENTATION)
  (* computes the point that is on the minor radius of an ellipse about CENTER with major radius and axis determined by MAJORRADPT and minor radius determines by MINORPT.)
  (PROG ((SINOR (SIN ORIENTATION))
        (COSOR (COS ORIENTATION))
        (SEMIMINORRADIUS (DISTANCEBETWEEN CENTER MINORPT))
        (SEMIMAJORRADIUS (DISTANCEBETWEEN CENTER MAJORRADPT)))
        (RETURN (CREATEPOSITION (DIFFERENCE (fetch (POSITION XCOORD) of CENTER)
                                           (FTIMES SINOR SEMIMINORRADIUS))
                                (PLUS (fetch (POSITION YCOORD) of CENTER)
                                       (FTIMES COSOR SEMIMINORRADIUS)]))
  (* rrb "19-Jul-85 14:23")

```

```

)
(DECLARE%: DONTCOPY
(DECLARE%: EVAL@COMPILE
(RECORD LOCALELLIPSE ((ELLIPSECENTER MINORRADIUSPOSITION MAJORRADIUSPOSITION)
                     LOCALHOTREGION SEMIMINORRADIUS SEMIMAJORRADIUS LOCALELLIPSEBRUSH LOCALELLIPSEDASHING
                     LOCALELLIPSEFILLING))
(TYPERECORD ELLIPSE (ELLIPSECENTERLATLON SEMIMINORLATLON SEMIMAJORLATLON ORIENTATION BRUSH DASHING
                    ELLIPSEINITSCALE ELLIPSEFILLING ELLIPSEREGION))
)
(READVARS-FROM-STRINGS '(ELLIPSEICON)
  "{(READBITMAP) (20 12
  "%COL@@@@"
  "%AOOH@@@"
  "%CN@GL@@@"
  "%G@@@N@@@"
  "%N@@@G@@@"
  "%L@@@C@@@"

```

```

% "L@@@C@@@%"
% "N@@@G@@@%"
% "G@@@N@@@%"
% "CN@GL@@@%"
% "A@@@H@@@%"
% "@COL@@@%" })
")


```

```

(RPAQ ELLIPSE.CENTER (CURSORCREATE ' 
'NIL 7 7))

```

```

(RPAQ ELLIPSE.SEMI.MAJOR (CURSORCREATE ' 
'NIL 15 7))

```

```

(RPAQ ELLIPSE.SEMI.MINOR (CURSORCREATE ' 
'NIL 7 15))

```

(DEFINEQ

(SKETCH.CREATE.OPEN.CURVE

```

[LAMBDA (POINTS BRUSH DASHING ARROWHEADS SCALE)
(SK.CURVE.CREATE (SK.INSURE.POINT.LIST POINTS)
NIL
(SK.INSURE.BRUSH BRUSH)
(SK.INSURE.DASHING DASHING)
(OR (NUMBERP SCALE)
1.0)
(SK.INSURE.ARROWHEADS ARROWHEADS])

```

(* rrb "16-Oct-85 17:14")
(* creates a sketch open curve element.)

(OPENCURVE.INPUTFN

```

[LAMBDA (W)
(PROG ((SKCONTEXT (WINDOWPROP W 'SKETCHCONTEXT))
KNOTS)
(RETURN (SK.CURVE.CREATE (SETQ KNOTS (for PT in (READ.LIST.OF.POINTS W T) collect (
NIL
(fetch (SKETCHCONTEXT SKETCHBRUSH) of SKCONTEXT)
(fetch (SKETCHCONTEXT SKETCHDASHING) of SKCONTEXT)
(SK.INPUT.SCALE W)
(SK.ARROWHEAD.CREATE W KNOTS]))

```

(* rrb "19-Mar-86 17:40")
(* reads a spline {series of points} from the user.)
SK.MAP.INPUT.PT.TO.GLOBAL
PT W)))

(SK.CURVE.CREATE

```

[LAMBDA (GKNOTS CLOSED BRUSH DASHING INITSCALE ARROWHEADS)
(AND GKNOTS
(KNOT.SET.SCALE.FIELD (create GLOBALPART
INDIVIDUALGLOBALPART _
(COND
(CLOSED (create CLOSEDCURVE
LATLONKNOTS _ GKNOTS
BRUSH _ BRUSH
DASHING _ DASHING
CLOSEDCURVEINITSCALE _ INITSCALE))
(T (SET.OPENCURVE.ARROWHEAD.POINTS (create
OPENCURVE
LATLONKNOTS _ GKNOTS
BRUSH _ BRUSH
DASHING _ DASHING
OPENCURVEINITSCALE _
INITSCALE
CURVEARROWHEADS _
ARROWHEADS])

```

(* rrb "19-Mar-86 17:40")
(* creates a sketch element representing a curve.)

(MAXXEXTENT

```

[LAMBDA (PTS)
(COND
((NULL PTS)
0)
(T (PROG ((XMIN (fetch (POSITION XCOORD) of (CAR PTS)))
XMAX)
(SETQ XMAX XMIN)
[for PT in (CDR PTS) do (COND
((GREATERP (SETQ PT (fetch (POSITION XCOORD) of PT))
XMAX)
(SETQ XMAX PT)))
(COND
((GREATERP XMIN PT)

```

(* rrb "1-APR-83 17:24")
(* returns the maximum width between any two points on pts)

```
(SETQ XMIN PT)
(RETURN (DIFFERENCE XMAX XMIN])
```

(MAXYEXTENT

[LAMBDA (PTS)

(* rrb " 1-APR-83 17:24")
(* returns the maximum height between any two points on pts)

```
(COND
  ((NULL PTS)
   0)
  (T (PROG ((YMIN (fetch (POSITION YCOORD) of (CAR PTS)))
            YMAX)
         (SETQ YMAX YMIN)
         [for PT in (CDR PTS) do (COND
                                ((GREATERP (SETQ PT (fetch (POSITION YCOORD) of PT))
                                             YMAX)
                                 (SETQ YMAX PT))
                                (COND
                                 ((GREATERP YMIN PT)
                                  (SETQ YMIN PT)
                                  (RETURN (DIFFERENCE YMAX YMIN]))
                                 (RETURN (DIFFERENCE YMAX YMIN]))
```

(KNOT.SET.SCALE.FIELD

[LAMBDA (GKNOTELE)

(* rrb "31-Jan-85 18:22")
(* updates the scale field after a change in the knots of a knotted

```
element.)
(PROG [(PTS (fetch (KNOTELE LATLONKNOTS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GKNOTELE))
      (replace (GLOBALPART MINSCALE) of GKNOTELE with 0.0) (* show it as long as it is two points wide or high.)
      (replace (GLOBALPART MAXSCALE) of GKNOTELE with (FQUOTIENT (MAX 8 (MAXXEXTENT PTS)
                                                                    (MAXYEXTENT PTS))
                                                                    2.0))
      (RETURN GKNOTELE)])
```

(OPENCURVE.DRAWFN

[LAMBDA (CURVEELE WINDOW REGION)

(* rrb " 6-May-86 17:42")
(* draws a curve figure element.)

```
(PROG ((G CURVE (fetch (SCREENELE INDIVIDUALGLOBALPART) of CURVEELE))
      (LCURVE (fetch (SCREENELE LOCALPART) of CURVEELE))
      BRUSH LOCALPTS LOCALARROWPTS GARROWSPECS)
      (AND REGION (NOT (REGIONSINTERSECTP REGION (SK.ITEM.REGION CURVEELE))))
      (RETURN))
      (SETQ GARROWSPECS (fetch (OPENCURVE CURVEARROWHEADS) of G CURVEELE))
      (SETQ LOCALARROWPTS (fetch (LOCALCURVE ARROWHEADPTS) of LCURVEELE))
      (SETQ LOCALPTS (\SK.ADJUST.FOR.ARROWHEADS (fetch (LOCALCURVE KNOTS) of LCURVEELE)
                                                LOCALARROWPTS GARROWSPECS WINDOW))
      (DRAWCURVE LOCALPTS NIL (SETQ BRUSH (fetch (LOCALCURVE LOCALCURVEBRUSH) of LCURVEELE)
                                                (fetch (LOCALCURVE LOCALCURVEDASHING) of LCURVEELE)
                                                WINDOW))
      (DRAWARROWHEADS GARROWSPECS LOCALARROWPTS WINDOW BRUSH)])
```

(OPENCURVE.EXPANDFN

[LAMBDA (GELT SCALE)

(* rrb " 2-May-86 10:50")

(* returns a local record which has the LATLONKNOTS field of the global element GELT translated into window coordinats.
Used for open curves)

```
(PROG ((INDGELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
      LOCALKNOTS TMP)
      [COND
        ((fetch (OPENCURVE OPENCURVEINITSCALE) of INDGELT))
        (T
         (replace (GLOBALPART INDIVIDUALGLOBALPART) of GELT
                  with (SETQ INDGELT (create OPENCURVE using INDGELT OPENCURVEINITSCALE _ 1.0 OPENCURVEREGION _
                                             NIL))
                  (* old format didn't have an initial scale, default it to 1.0)
                  (* old form didn't have global points, update it)
                  (SET.OPENCURVE.ARROWHEAD.POINTS INDGELT)))
         (SETQ LOCALKNOTS (for LATLONPT in (fetch (OPENCURVE LATLONKNOTS) of INDGELT)
          collect (SK.SCALE.POSITION.INTO.VIEWER LATLONPT SCALE)))
         (RETURN (create SCREENELE
                        LOCALPART _ (create LOCALCURVE
                                           KNOTS _ LOCALKNOTS
                                           ARROWHEADPTS _ (SK.EXPAND.ARROWHEADS (fetch (OPENCURVE
                                                                 OPENCURVEARROWHEADPOINTS)
                                                                 of INDGELT))
                                           SCALE)
                        LOCALCURVEBRUSH _
                        (SCALE.BRUSH (COND
                                     ([NOT (NUMBERP (SETQ TMP (fetch (OPENCURVE BRUSH)
                                                                       of INDGELT))
                                     (* new format, old format had brush width only.)
```

```

TMP)
(T [replace (OPENCURVE BRUSH) of INDGELT
with (SETQ TMP
(create BRUSH
BRUSHSIZE _ TMP
BRUSHSHAPE _ 'ROUND]
TMP))
(fetch (OPENCURVE OPENCURVEINITSCALE) of INDGELT)
SCALE)
LOCALCURVEDASHING _ (fetch (OPENCURVE DASHING) of INDGELT))
GLOBALPART _ GELT]]

```

(OPENCURVE.READCHANGEFN

[LAMBDA (SKW SCRNELTS)

(* rrb "17-Dec-85 16:22")
(* changefn for curves)

```

(PROG (ASPECT HOW)
(SETQ HOW (SELECTQ [SETQ ASPECT (\CURSOR.IN.MIDDLE.MENU (create MENU
CENTERFLG _ T
TITLE _ "Which aspect?"
ITEMS _
(APPEND
(COND
((SKETCHINCOLORP)
'((Color 'BRUSHCOLOR "Changes the
color of the curve.")
(T NIL))
'((Arrowheads 'ARROW "allows changing
of arrow head
characteristics.")
(Shape 'SHAPE "changes the shape of
the brush")
(Size 'SIZE "changes the size of the
brush")
(Dashing 'DASHING "changes the
dashing of the line.")
("Add point" 'ADDPPOINT "adds a point
to the curve."])
(SIZE (READSIZECHANGE "Change size how?"))
(SHAPE (READBRUSHSHAPE))
(ARROW (READ.ARROW.CHANGE SCRNELTS))
(DASHING (READ.DASHING.CHANGE))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change curve color how?" NIL
(fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
(fetch (SCREENELT GLOBALPART)
of (CAR SCRNELTS))
'BRUSH])
(ADDPPOINT (READ.POINT.TO.ADD (CAR SCRNELTS)
SKW))
NIL))
(RETURN (AND HOW (LIST ASPECT HOW))

```

(OPENCURVE.TRANSFORMFN

[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR)

(* rrb "19-Mar-86 17:40")

(* returns a copy of the global OPENCURVE element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to tranformfn.)

```

(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
(RETURN (KNOT.SET.SCALE.FIELD (create GLOBALPART using GELT INDIVIDUALGLOBALPART
(SET.OPENCURVE.ARROWHEAD.POINTS
(create OPENCURVE
using INDVPART LATLONKNOTS _
(SK.TRANSFORM.POINT.LIST
(fetch (OPENCURVE LATLONKNOTS)
of INDVPART)
TRANSFORMFN TRANSFORMDATA)
BRUSH _ (SK.TRANSFORM.BRUSH
(fetch (OPENCURVE BRUSH)
of INDVPART)
SCALEFACTOR)
CURVEARROWHEADS _
(SK.TRANSFORM.ARROWHEADS
(fetch (OPENCURVE CURVEARROWHEADS)
of INDVPART)
SCALEFACTOR)
OPENCURVEREGION _ NIL]))

```

(OPENCURVE.TRANSLATEFN

[LAMBDA (OCELT DELTAPOS)

(* rrb "20-Mar-86 15:09")

(* translates an opencurve element)

```

(PROG ((NEWOCELT (KNOTS.TRANSLATEFN OCELT DELTAPOS)))
(SET.OPENCURVE.ARROWHEAD.POINTS (fetch (GLOBALPART INDIVIDUALGLOBALPART) of NEWOCELT))
(RETURN NEWOCELT])

```

(OPENCURVE.TRANSLATEPTSFN

[LAMBDA (KNOTE LT SELPTS GDELTA WINDOW)

(* rrb " 5-May-85 17:49")

(* returns a curve element which has the knots that are members of SELPTS translated by the global amount GDELTA.)

```
(PROG ((GKNOTE LT (fetch (SCREENELT INDIVIDUALGLOBALPART) of KNOTE LT)))
  (RETURN (SK.CURVE.CREATE (for PT in (fetch (LOCALCURVE KNOTS) of (fetch (SCREENELT LOCALPART)
    of KNOTE LT)))
    as LATLONPT in (fetch LATLONKNOTS of GKNOTE LT)
    collect (COND
      ((MEMBER PT SELPTS)
        (PTPLUS LATLONPT GDELTA))
      (T LATLONPT)))
    NIL
    (fetch (OPENCURVE BRUSH) of GKNOTE LT)
    (fetch (OPENCURVE DASHING) of GKNOTE LT)
    (fetch (OPENCURVE OPENCURVEINITSCALE) of GKNOTE LT)
    (fetch (OPENCURVE CURVEARROWHEADS) of GKNOTE LT]))
```

(SKETCH.CREATE.CLOSED.CURVE

[LAMBDA (POINTS BRUSH DASHING WILLBEFILLING SCALE)

(* rrb "16-Oct-85 17:15")

(* creates a sketch closed curve element.)

```
(SK.CURVE.CREATE (SK.INSURE.POINT.LIST POINTS)
  T
  (SK.INSURE.BRUSH BRUSH)
  (SK.INSURE.DASHING DASHING)
  (OR (NUMBERP SCALE)
    1.0])
```

(CLOSEDCURVE.DRAWFN

[LAMBDA (CURVEELT WINDOW REGION)

(* rrb " 7-Dec-85 20:45")

(* draws a curve figure element.)

(* make sure this curve might be in the REGION of interest.)

```
(PROG ((LCURVE (fetch (SCREENELT LOCALPART) of CURVEELT)))
  (AND REGION (NOT (REGIONSINTERSECTP REGION (SK.ITEM.REGION CURVEELT))))
  (RETURN))
  (DRAWCURVE (fetch (LOCALCLOSEDCURVE LOCALCLOSEDCURVEKNOTS) of LCURVE)
    T
    (fetch (LOCALCLOSEDCURVE LOCALCLOSEDCURVEBRUSH) of LCURVE)
    (fetch (LOCALCLOSEDCURVE LOCALCLOSEDCURVEDASHING) of LCURVE)
    WINDOW])
```

(CLOSEDCURVE.EXPANDFN

[LAMBDA (GELT SCALE)

(* rrb " 7-Dec-85 20:45")

(* returns a local record which has the LATLONKNOTS field of the global element GELT translated into window coordinats. Used for curves and wires.)

```
(PROG ((INDVKNOTE LT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
  BRSH)
  [COND
    ((fetch (CLOSEDCURVE CLOSEDCURVEINITSCALE) of INDVKNOTE LT))
    (T
      (replace (GLOBALPART INDIVIDUALGLOBALPART) of GELT
        with (SETQ INDVKNOTE LT (create CLOSEDCURVE using INDVKNOTE LT CLOSEDCURVEINITSCALE _ 1.0
          CLOSEDCURVEREGION _ NIL]
          (* old format didn't have an initial scale, default it to 1.0)
        (RETURN (create SCREENELT
          LOCALPART _ (create LOCALCLOSEDCURVE
            LOCALCLOSEDCURVEKNOTS _ (for LATLONPT
              in (fetch LATLONKNOTS of INDVKNOTE LT)
              collect (SK.SCALE.POSITION.INTO.VIEWER
                LATLONPT SCALE))
            LOCALCLOSEDCURVEBRUSH _
            (SCALE.BRUSH (COND
              ([NOT (NUMBERP (SETQ BRSH (fetch (CLOSEDCURVE BRUSH)
                of INDVKNOTE LT])
                (* new format, old format had brush width only.)
                BRSH)
              (T [replace (CLOSEDCURVE BRUSH) of INDVKNOTE LT
                with (SETQ BRSH
                  (create BRUSH
                    BRUSHSIZE _ BRSH
                    BRUSHSHAPE _ 'ROUND]
                    BRSH))
                (fetch (CLOSEDCURVE CLOSEDCURVEINITSCALE) of INDVKNOTE LT)
                SCALE)
            LOCALCLOSEDCURVEFILLING _ (APPEND (fetch (CLOSEDCURVE
              CLOSEDCURVEFILLING)
              of INDVKNOTE LT))
            LOCALCLOSEDCURVEDASHING _ (fetch (CLOSEDCURVE DASHING) of INDVKNOTE LT)
          )
        GLOBALPART _ GELT])
```

(CLOSEDCURVE.REGIONFN

[LAMBDA (KNOTSCRELT)

(* rrb "2-Dec-85 20:40")

(* returns the region occupied by a list of knots which represent

a curve.)

(* uses the heuristic that the region containing the curve is not more than 20% larger than the knots.
This was determined empirically on several curves.)

(INCREASEREGION (EXPANDREGION (REGION.CONTAINING.PTS (fetch (SCREENELT HOTSPOTS) of KNOTSCRELT))

(IQUOTIENT [ADD1 (SK.BRUSH.SIZE (fetch (LOCALCLOSEDCURVE LOCALCLOSEDCURVEBRUSH)
of (fetch (SCREENELT LOCALPART) of KNOTSCRELT))

2])

(CLOSEDCURVE.GLOBALREGIONFN

[LAMBDA (GCLOSEDCURVEELT)

(* rrb "18-Oct-85 16:37")

(* returns the global region occupied by a global closed curve
element.)

(OR (fetch (CLOSEDCURVE CLOSEDCURVEREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCLOSEDCURVEELT))
(PROG ((INDVCLOSEDCURVE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCLOSEDCURVEELT))
REGION)

(* uses the heuristic that the region containing the curve is not more than 40% larger than the knots.
This was determined empirically on several curves.)

[SETQ REGION (INCREASEREGION (EXPANDREGION (REGION.CONTAINING.PTS (fetch (CLOSEDCURVE
LATLONKNOTS)
of INDVCLOSEDCURVE))

(SK.BRUSH.SIZE (fetch (CLOSEDCURVE BRUSH) of INDVCLOSEDCURVE]
(replace (CLOSEDCURVE CLOSEDCURVEREGION) of INDVCLOSEDCURVE with REGION)
(RETURN REGION)]

(READ.LIST.OF.POINTS

[LAMBDA (W ALLOWDUPS?)

(* rrb "10-Jun-86 15:43")

(* reads a spline {series of points} from the user.)

(PROG (PT PTS ERRSTAT)
(STATUSPRINT W "

" "Enter the points the curve goes through using the left button.
Click outside the window to stop.")

LP (COND

((AND [SETQ ERRSTAT (ERSETQ (SETQ PT (SK.READ.POINT.WITH.FEEDBACK W POINTREADINGCURSOR NIL NIL NIL
NIL (AND SKETCH.USE.POSITION.PAD 'MULTIPLE]

(* add the point to the list and mark it.)

PT)

[COND

([OR ALLOWDUPS? (NOT (EQUAL (fetch (INPUTPT INPUT.POSITION) of (CAR (LAST PTS)))
(fetch (INPUTPT INPUT.POSITION) of PT]

(SHOWSKETCHPOINT (fetch (INPUTPT INPUT.POSITION) of PT)

W PTS)

(SETQ PTS (NCONC1 PTS PT]

(GO LP)))

(* erase point markers.)

(for PTTAIL on PTS do (SHOWSKETCHPOINT (fetch (INPUTPT INPUT.POSITION) of (CAR PTTAIL))

W
(CDR PTTAIL)))

(CLOSEPROMPTWINDOW W)

(CLRSPROMPT)

(COND

(ERRSTAT

(* no error.)

(RETURN PTS))

(T

(* had an error, pass it on)

(ERROR!))

(CLOSEDCURVE.INPUTFN

[LAMBDA (W)

(* rrb "4-Sep-85 15:49")

(* reads a spline {series of points} from the user.)

(SK.CURVE.CREATE (for PT in (READ.LIST.OF.POINTS W T) collect (SK.MAP.INPUT.PT.TO.GLOBAL PT W))

T

(fetch (SKETCHCONTEXT SKETCHBRUSH) of (WINDOWPROP W 'SKETCHCONTEXT))

(fetch (SKETCHCONTEXT SKETCHDASHING) of (WINDOWPROP W 'SKETCHCONTEXT))

(SK.INPUT.SCALE W])

(CLOSEDCURVE.READCHANGEFN

[LAMBDA (SKW SCRNELTS)

(* rrb "20-Nov-85 11:09")

(* changefn for curves)

(PROG (ASPECT HOW)

(SETQ HOW (SELECTQ [SETQ ASPECT (\CURSOR.IN.MIDDLE.MENU (create MENU

CENTERFLG _ T

TITLE _ "select aspect of brush to
change"

ITEMS _

(APPEND

(COND

[(SKETCHINCOLORP)

```

'(("Color" 'BRUSHCOLOR "changes
the color of the brush"]
(T NIL))
'((Shape 'SHAPE "changes the shape of
the brush")
(Size 'SIZE "changes the size of the
brush")
(Dashing 'DASHING "changes the
dashing of the line.")
("Add point" 'ADDPPOINT "adds a point
to the curve."])

(SIZE (READSIZECHANGE "Change size how?"))
(SHAPE (READBRUSHSHAPE))
(DASHING (READ.DASHING.CHANGE))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change brush color how?" NIL
(fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
(fetch (SCREENELT GLOBALPART)
of (CAR SCRNELTS)
'BRUSH])

(ADDPPOINT (READ.POINT.TO.ADD (CAR SCRNELTS)
SKW))

NIL))
(RETURN (AND HOW (LIST ASPECT HOW]))

```

(CLOSEDCURVE.TRANSFORMFN

[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR) (* rrb "18-Oct-85 16:52")

(* returns a copy of the global CLOSEDCURVE element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to transformfn.)

```

(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
GELT INDIVIDUALGLOBALPART _
(create CLOSEDCURVE
using INDVPART LATLONKNOTS _
(SK.TRANSFORM.POINT.LIST
(fetch (CLOSEDCURVE LATLONKNOTS)
of INDVPART)
TRANSFORMFN TRANSFORMDATA)
BRUSH _ (SK.TRANSFORM.BRUSH
(fetch (CLOSEDCURVE BRUSH)
of INDVPART)
SCALEFACTOR)
CLOSEDCURVEREGION _ NIL])

```

(CLOSEDCURVE.TRANSLATEPTSFN

[LAMBDA (KNOTELT SELPTS GDELTA WINDOW) (* rrb " 5-May-85 18:35")

(* returns a closed curve element which has the knots that are members of SELPTS translated by the global amount GDELTA.)

```

(PROG ((GKNOTELT (fetch (SCREENELT INDIVIDUALGLOBALPART) of KNOTELT)))
(RETURN (SK.CURVE.CREATE (for PT in (fetch (LOCALCURVE KNOTS) of (fetch (SCREENELT LOCALPART)
of KNOTELT)))
as LATLONPT in (fetch LATLONKNOTS of GKNOTELT)
collect (COND
((MEMBER PT SELPTS)
(PTPLUS LATLONPT GDELTA))
(T LATLONPT)))
T
(fetch (CLOSEDCURVE BRUSH) of GKNOTELT)
(fetch (CLOSEDCURVE DASHING) of GKNOTELT)
(fetch (CLOSEDCURVE CLOSEDCURVEINITSCALE) of GKNOTELT)
NIL])

```

(INVISIBLEPARTP

[LAMBDA (WINDOW POINT) (* rrb "30-NOV-82 17:25") (* determines if POINT is in the visible part of a window.)

```

(INSIDE? (DSPCLIPPINGREGION NIL WINDOW)
(fetch (POSITION XCOORD) of POINT)
(fetch (POSITION YCOORD) of POINT])

```

(SHOWSKETCHPOINT

[LAMBDA (NEWPT W PTS) (* rrb "12-May-85 18:50")

(* puts down the marker for a new point unless it is already a member of points.)

```

(OR (MEMBER NEWPT PTS)
(MARKPOINT NEWPT W SPOTMARKER))

```

(SHOWSKETCHXY

[LAMBDA (X Y WINDOW) (* rrb " 2-Oct-85 09:58") (* puts down a marker for a point at position X,Y)


```
(BITBLT SPOTMARKER NIL NIL WINDOW (IDIFFERENCE X (LRSH (fetch (BITMAP BITMAPWIDTH) of SPOTMARKER)
1))
(IDIFFERENCE Y (LRSH (fetch (BITMAP BITMAPHEIGHT) of SPOTMARKER)
1))
NIL NIL 'INPUT 'INVERT])
```

(KNOTS.REGIONFN

```
[LAMBDA (KNOTSCRELT) (* rrb "29-May-85 21:17")
(* returns the region occupied by a list of knots)
```

(* increase by half the brush size plus 2 This has the nice property of insuring that the region always has both height and width.)

```
(INCREASEREGION (REGION.CONTAINING.PTS (fetch (SCREENELT HOTSPOTS) of KNOTSCRELT))
(IPLUS 3 (QUOTIENT (fetch (BRUSH BRUSHSIZE) of (fetch (LOCALWIRE LOCALOPENWIREBRUSH)
of (fetch (SCREENELT LOCALPART) of KNOTSCRELT)))
2))
```

(OPENWIRE.GLOBALREGIONFN

```
[LAMBDA (GOPENWIREELT) (* rrb "23-Oct-85 11:30")
(* returns the global region occupied by a global open curve
element.)
```

```
(OR (fetch (WIRE OPENWIREREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GOPENWIREELT))
(PROG ((INDVOPENWIRE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GOPENWIREELT))
REGION)
[SETQ REGION (INCREASEREGION (REGION.CONTAINING.PTS (fetch (WIRE LATLONKNOTS) of INDVOPENWIRE))
(SK.BRUSH.SIZE (fetch (WIRE BRUSH) of INDVOPENWIRE))
(replace (WIRE OPENWIREREGION) of INDVOPENWIRE with REGION)
(RETURN REGION])
```

(CURVE.REGIONFN

```
[LAMBDA (OPENCURVESCRELT) (* rrb "18-Oct-85 16:36")
(* returns the region occupied by a list of knots which represent
a curve.)
```

(* uses the heuristic that the region containing the curve is not more than 40% larger than the knots. This was determined empirically on several curves.)

```
(INCREASEREGION (EXPANDREGION (REGION.CONTAINING.PTS (fetch (SCREENELT HOTSPOTS) of OPENCURVESCRELT))
1.4)
(IQUOTIENT [ADD1 (SK.BRUSH.SIZE (fetch (LOCALCURVE LOCALCURVEBRUSH) of (fetch (SCREENELT LOCALPART)
of OPENCURVESCRELT))
2))
```

(OPENCURVE.GLOBALREGIONFN

```
[LAMBDA (GOPENCURVEELT) (* rrb "18-Oct-85 16:36")
(* returns the global region occupied by a global open curve
element.)
```

```
(OR (fetch (OPENCURVE OPENCURVEREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GOPENCURVEELT))
(PROG ((INDVOPENCURVE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GOPENCURVEELT))
REGION)
```

(* uses the heuristic that the region containing the curve is not more than 40% larger than the knots. This was determined empirically on several curves.)

```
[SETQ REGION (INCREASEREGION (EXPANDREGION (REGION.CONTAINING.PTS (fetch (OPENCURVE LATLONKNOTS)
of INDVOPENCURVE))
1.4)
(SK.BRUSH.SIZE (fetch (OPENCURVE BRUSH) of INDVOPENCURVE))
(replace (OPENCURVE OPENCURVEREGION) of INDVOPENCURVE with REGION)
(RETURN REGION])
```

(KNOTS.TRANSLATEFN

```
[LAMBDA (SKELT DELTAPOS) (* rrb " 4-Apr-86 11:31")
```

(* replaces the knots field of the global part of a screen element with knots that have been translated DELTAPOS.)

```
(PROG [(GKNOTELT (APPEND (fetch (GLOBALPART INDIVIDUALGLOBALPART) of SKELT)
(replace (KNOTELT LATLONKNOTS) of GKNOTELT with (for PT in (fetch (KNOTELT LATLONKNOTS) of GKNOTELT)
collect (PTPLUS PT DELTAPOS)))
(* clear the region cache.)
(replace (KNOTELT KNOTREGION) of GKNOTELT with NIL)
(RETURN (create GLOBALPART
COMMONGLOBALPART _ (APPEND (fetch (GLOBALPART COMMONGLOBALPART) of SKELT))
INDIVIDUALGLOBALPART _ GKNOTELT])
```

(REGION.CONTAINING.PTS

```
[LAMBDA (PTLST) (* rrb " 7-Sep-84 11:26")
(* returns the region that contains all of the points on PTLST.)
```

```
(AND PTLST (PROG ((XMIN (fetch (POSITION XCOORD) of (CAR PTLST)))
(XMAX (fetch (POSITION XCOORD) of (CAR PTLST)))
```

```

(YMIN (fetch (POSITION YCOORD) of (CAR PTLST)))
(YMAX (fetch (POSITION YCOORD) of (CAR PTLST)))
TMP)
[for PT in (CDR PTLST) do (COND
  ((GREATERP (SETQ TMP (fetch (POSITION XCOORD) of PT))
    XMAX)
    (SETQ XMAX TMP))
  ((GREATERP XMIN TMP)
    (SETQ XMIN TMP)))
  (COND
  ((GREATERP (SETQ TMP (fetch (POSITION YCOORD) of PT))
    YMAX)
    (SETQ YMAX TMP))
  ((GREATERP YMIN TMP)
    (SETQ YMIN TMP)
  (RETURN (CREATEREGION XMIN YMIN (DIFFERENCE XMAX XMIN)
    (DIFFERENCE YMAX YMIN]))

```

)

(DEFINEQ

(CHANGE.ELTS.BRUSH.SIZE

[LAMBDA (HOWTOCHANGE ELTSWITHBRUSH SKW)

(* rrb "10-Jan-85 14:00")

(* function that prompts for how the line thickness should change and changes it for all elements in ELTSWITHBRUSH that have a brush size or thickness.)

(* knows about the various types of sketch elements types and shouldn't.)

(AND HOWTOCHANGE (for LINEDEL in ELTSWITHBRUSH collect (SK.CHANGE.BRUSH.SIZE LINEDEL HOWTOCHANGE SKW))

(CHANGE.ELTS.BRUSH

[LAMBDA (CURVELTS SKW HOW)

(* rrb " 4-Jan-85 14:55")

(* changefn for curves Actually makes the change.)

```

(SELECTQ (CAR HOW)
  (SIZE (CHANGE.ELTS.BRUSH.SIZE (CADR HOW)
    CURVELTS SKW))
  (SHAPE (CHANGE.ELTS.BRUSH.SHAPE (CADR HOW)
    CURVELTS SKW))
  NIL])

```

(CHANGE.ELTS.BRUSH.SHAPE

[LAMBDA (NEWSHAPE CURVELTS SKW)

(* rrb "10-Jan-85 16:49")

(* changes the brush shape of a list of curve elements. Knows about the various sketch element types and shouldn't need to.)

(AND NEWSHAPE (for CURVELT in CURVELTS collect (SK.CHANGE.BRUSH.SHAPE CURVELT NEWSHAPE SKW))

(SK.CHANGE.BRUSH.SHAPE

[LAMBDA (ELTWITHBRUSH HOW SKW)

(* rrb "10-Mar-86 16:07")

(* changes the brush shape in the element ELTWITHBRUSH.)

```

(PROG (G CURVELT BRUSH TYPE NEWELT NEWBRUSH)
  (RETURN (COND
    ((MEMB (SETQ TYPE (fetch (GLOBALPART GTYPE) of ELTWITHBRUSH))
      ' (CLOSEDCURVE OPENCURVE ELLIPSE CIRCLE ARC CLOSEDWIRE WIRE))
      (* only works for things of curve type.)
    (SETQ G CURVELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHBRUSH))
    (SETQ BRUSH (SELECTQ TYPE
      (CIRCLE (fetch (CIRCLE BRUSH) of G CURVELT))
      (ARC (fetch (ARC ARCBRUSH) of G CURVELT))
      (ELLIPSE (fetch (ELLIPSE BRUSH) of G CURVELT))
      (WIRE (fetch (WIRE BRUSH) of G CURVELT))
      (CLOSEDWIRE (fetch (CLOSEDWIRE BRUSH) of G CURVELT))
      (fetch (OPENCURVE BRUSH) of G CURVELT)))
    (COND
      ((NEQ HOW (fetch (BRUSH BRUSHSHAPE) of BRUSH))
        (* new brush shape)
      (SETQ NEWBRUSH (create BRUSH using BRUSH BRUSHSHAPE _ HOW))
      (SETQ NEWELT (SELECTQ TYPE
        (CLOSEDCURVE (create CLOSEDCURVE using G CURVELT BRUSH _ NEWBRUSH))
        (OPENCURVE (create OPENCURVE using G CURVELT BRUSH _ NEWBRUSH))
        (CIRCLE (create CIRCLE using G CURVELT BRUSH _ NEWBRUSH))
        (ARC (create ARC using G CURVELT ARCBRUSH _ NEWBRUSH))
        (ELLIPSE (create ELLIPSE using G CURVELT BRUSH _ NEWBRUSH))
        (WIRE (create WIRE using G CURVELT BRUSH _ NEWBRUSH))
        (CLOSEDWIRE (create CLOSEDWIRE using G CURVELT BRUSH _ NEWBRUSH))
        (SHOULDNT)))
      (create SKHISTORYCHANGESPEC
        OLDEL _ ELTWITHBRUSH
        NEWELT _ (create GLOBALPART
          COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
            of ELTWITHBRUSH)
          INDIVIDUALGLOBALPART _ NEWELT)

```

PROPERTY _ 'BRUSH
NEWVALUE _ NEWBRUSH
OLDVALUE _ BRUSH])

(SK.CHANGE.BRUSH.COLOR

[LAMBDA (ELTWITHTHLINE COLOR SKW)

(* rrb " 8-Jan-86 17:25")
(* changes the brush color of ELTWITHTHLINE if it has a brush)
(* knows about the various types of sketch elements types and shouldn't.)

(PROG ((GLINELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHTHLINE))
TYPE BRUSH NEWBRUSH NEWELT)
(COND

[(MEMB (SETQ TYPE (fetch (GLOBALPART GTYPE) of ELTWITHTHLINE))

'(WIRE BOX CLOSEDWIRE CLOSEDCURVE OPENCURVE CIRCLE ELLIPSE TEXTBOX ARC))

(* only works for things of wire type.)
(* the brush is stored in the different place for all element types.)

(SETQ BRUSH (SELECTQ TYPE

(CIRCLE (fetch (CIRCLE BRUSH) of GLINELT))
(ELLIPSE (fetch (ELLIPSE BRUSH) of GLINELT))
(TEXTBOX (fetch (TEXTBOX TEXTBOXBRUSH) of GLINELT))
(CLOSEDCURVE (fetch (CLOSEDCURVE BRUSH) of GLINELT))
(BOX (fetch (BOX BRUSH) of GLINELT))
(ARC (fetch (ARC ARCBRUSH) of GLINELT))
(fetch (OPENCURVE BRUSH) of GLINELT))

(COND

((NOT (EQUAL COLOR (fetch (BRUSH BRUSHCOLOR) of BRUSH)))
(SETQ NEWBRUSH (create BRUSH using BRUSH BRUSHCOLOR _ COLOR))
(SETQ NEWELT (SELECTQ TYPE

(WIRE (create WIRE using GLINELT BRUSH _ NEWBRUSH))
(BOX (create BOX using GLINELT BRUSH _ NEWBRUSH))
(ARC (create ARC using GLINELT ARCBRUSH _ NEWBRUSH))
(TEXTBOX (create TEXTBOX using GLINELT TEXTBOXBRUSH _ NEWBRUSH TEXTCOLOR _
COLOR))
(CLOSEDWIRE (create CLOSEDWIRE using GLINELT BRUSH _ NEWBRUSH))
(CLOSEDCURVE (create CLOSEDCURVE using GLINELT BRUSH _ NEWBRUSH))
(OPENCURVE (create OPENCURVE using GLINELT BRUSH _ NEWBRUSH))
(CIRCLE (create CIRCLE using GLINELT BRUSH _ NEWBRUSH))
(ELLIPSE (create ELLIPSE using GLINELT BRUSH _ NEWBRUSH))
(SHOULDNT)))

(RETURN (create SKHISTORYCHANGESPEC

NEWELT _ (create GLOBALPART
COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
of ELTWITHTHLINE)
INDIVIDUALGLOBALPART _ NEWELT)
OLDELT _ ELTWITHTHLINE
PROPERTY _ 'BRUSH
NEWVALUE _ NEWBRUSH
OLDVALUE _ BRUSH])

((EQ TYPE 'TEXT)

(* change the color of text too.)

(COND

((NOT (EQUAL COLOR (fetch (TEXT TEXTCOLOR) of GLINELT)))

(RETURN (create SKHISTORYCHANGESPEC

NEWELT _ (create GLOBALPART
COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
of ELTWITHTHLINE)
INDIVIDUALGLOBALPART _ (create TEXT using GLINELT TEXTCOLOR _
COLOR))

OLDELT _ ELTWITHTHLINE
PROPERTY _ 'TEXTCOLOR
NEWVALUE _ COLOR
OLDVALUE _ (fetch (TEXT TEXTCOLOR) of GLINELT])

(SK.CHANGE.BRUSH.SIZE

[LAMBDA (ELTWITHTHLINE HOW SKW)

(* rrb "10-Jan-86 13:57")

(* changes the line size of ELTWITHTHLINE if it has a brush size or thickness and returns a change event.)

(* knows about the various types of sketch elements types and shouldn't.)

(PROG (SIZE GLINELT TYPE BRUSH NEWBRUSH NEWELT)

(COND

((MEMB (SETQ TYPE (fetch (GLOBALPART GTYPE) of ELTWITHTHLINE))

'(WIRE BOX CLOSEDWIRE CLOSEDCURVE OPENCURVE CIRCLE ELLIPSE TEXTBOX ARC))

(SETQ GLINELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHTHLINE))

(SETQ BRUSH (SELECTQ TYPE

(CIRCLE (fetch (CIRCLE BRUSH) of GLINELT))
(ELLIPSE (fetch (ELLIPSE BRUSH) of GLINELT))
(TEXTBOX (fetch (TEXTBOX TEXTBOXBRUSH) of GLINELT))
(CLOSEDCURVE (fetch (CLOSEDCURVE BRUSH) of GLINELT))
(BOX (fetch (BOX BRUSH) of GLINELT))
(ARC (fetch (ARC ARCBRUSH) of GLINELT))
(fetch (OPENCURVE BRUSH) of GLINELT))

(* the change to the brush size must take into account the current scale and the scale at which the brush was entered.)

(COND

```

((GEQ [SETQ SIZE (COND
  ((NUMBERP HOW)
   HOW)
  (T (SELECTQ HOW
      (SMALLER (FQUOTIENT (fetch (BRUSH BRUSHSIZE) of BRUSH)
                          2.0))
      (FTIMES (fetch (BRUSH BRUSHSIZE) of BRUSH)
              2.0]
      0) (* don't let the brush size go negative.)
(SETQ NEWBRUSH (create BRUSH using BRUSH BRUSHSIZE _ SIZE))
(SETQ NEWELT (SELECTQ TYPE
  (WIRE (create WIRE using GLINELT BRUSH _ NEWBRUSH OPENWIREREGION _ NIL))
  (BOX (create BOX using GLINELT BRUSH _ NEWBRUSH))
  (ARC (create ARC using GLINELT ARCBRUSH _ NEWBRUSH ARCREGION _ NIL))
  (TEXTBOX

```

(* since this may change the location of characters in the box, clear the selection. Probably should happen somewhere else.)

```

(SKED.CLEAR.SELECTION SKW)
(create TEXTBOX using GLINELT TEXTBOXBRUSH _ NEWBRUSH))
(CLOSEDWIRE (create CLOSEDWIRE using GLINELT BRUSH _ NEWBRUSH CLOSEDWIREREGION
_ NIL))
(CLOSEDCURVE (create CLOSEDCURVE using GLINELT BRUSH _ NEWBRUSH
CLOSEDCURVEREGION _ NIL))
(OPENCURVE (create OPENCURVE using GLINELT BRUSH _ NEWBRUSH OPENCURVEREGION _
NIL))
(CIRCLE (create CIRCLE using GLINELT BRUSH _ NEWBRUSH CIRCULEREGION _ NIL))
(ELLIPSE (create ELLIPSE using GLINELT BRUSH _ NEWBRUSH ELLIPSEREGION _ NIL))
(SHOULDNT))
(RETURN (create SKHISTORYCHANGESPEC
NEWELT _ (create GLOBALPART
COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
of ELTWITHLINE)
INDIVIDUALGLOBALPART _ NEWELT)
OLDDELT _ ELTWITHLINE
PROPERTY _ 'BRUSH
NEWVALUE _ NEWBRUSH
OLDVALUE _ BRUSH])

```

(SK.CHANGE.ANGLE

[LAMBDA (ELTWITHARC HOW SKW) (* rrb "20-Jun-86 17:18") (* changes the arc size of ELTWITHARC if it is an arc element)

```

(PROG (GARCLT ARMANGLE RADIUS CENTERPT RADIUSPT CENTERX NEWANGLEPT CENTERY)
(COND
  ((EQ (fetch (GLOBALPART GTYPE) of ELTWITHARC)
'ARC) (* only works for things of arc type.)
  (SETQ GARCLT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHARC))
  (SETQ CENTERPT (fetch (ARC ARCCENTERPT) of GARCLT))
  (SETQ CENTERX (fetch (POSITION XCOORD) of CENTERPT))
  (SETQ CENTERY (fetch (POSITION YCOORD) of CENTERPT))
  (SETQ RADIUSPT (fetch (ARC ARCRADIUSPT) of GARCLT))
  [SETQ ARMANGLE (COND
    ((fetch (ARC ARCDIRECTION) of GARCLT)
     (* clockwise direction)
     (DIFFERENCE (SK.COMPUTE.SLOPE.OF.LINE CENTERPT RADIUSPT)
                 HOW))
    (T (* positive direction)
     (PLUS (SK.COMPUTE.SLOPE.OF.LINE CENTERPT RADIUSPT)
           HOW])
  (SETQ RADIUS (DISTANCEBETWEEN CENTERPT RADIUSPT))
  (* calculate a position on the circle the right number of degrees
  out.)
  [SETQ NEWANGLEPT (COND
    ((OR (GEQ ARMANGLE 360.0)
         (LEQ ARMANGLE -360.0)) (* mark greater than 360 by T)
    T)
  (T (create POSITION
      XCOORD _ [FIXR (PLUS CENTERX (TIMES RADIUS (COS ARMANGLE)
      YCOORD _ [FIXR (PLUS CENTERY (TIMES RADIUS (SIN ARMANGLE)
(RETURN (create SKHISTORYCHANGESPEC
NEWELT _ (create GLOBALPART
COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART) of ELTWITHARC
)
INDIVIDUALGLOBALPART _
(SET.ARC.ARROWHEAD.POINTS (create ARC
using GARCLT ARCANGLEPT _ NEWANGLEPT
ARCREGION _ NIL)))
OLDDELT _ ELTWITHARC
PROPERTY _ '3RDCONTROLPT
NEWVALUE _ NEWANGLEPT
OLDVALUE _ (fetch (ARC ARCRADIUSPT) of GARCLT])

```

(SK.CHANGE.ARC.DIRECTION

[LAMBDA (ELTWITHARC HOW SKW) (* rrb "19-Mar-86 17:16")

(* changes the direction around the circle that the arc element goes.)

```
(PROG (GARCLT NOWDIRECTION)
  (COND
    ((EQ (fetch (GLOBALPART GTYPE) of ELTWITHARC)
      'ARC)
      (* only works for things of arc type.)
      (SETQ GARCLT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHARC))
      (SETQ NOWDIRECTION (fetch (ARC ARCDIRECTION) of GARCLT))
      (COND
        ((OR (AND (EQ HOW 'CLOCKWISE)
          (NULL NOWDIRECTION))
          (AND (EQ HOW 'COUNTERCLOCKWISE)
            NOWDIRECTION))
          (* spec calls for one direction and it is currently going the other.)
          (RETURN (create SKHISTORYCHANGESPEC
            NEWELT _ (create GLOBALPART
              COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
                of ELTWITHARC)
              INDIVIDUALGLOBALPART _ (SET.ARC.ARROWHEAD.POINTS
                (create ARC using GARCLT ARCDIRECTION _
                  (NOT NOWDIRECTION)
                  ARCREGION _ NIL)))
            OLDELT _ ELTWITHARC
            PROPERTY _ 'DIRECTION
            NEWVALUE _ HOW
            OLDVALUE _ (COND
              (NOWDIRECTION 'CLOCKWISE)
              (T 'COUNTERCLOCKWISE]))
  )
```

(SK.SET.DEFAULT.BRUSH.SIZE

```
[LAMBDA (NEWBRUSHSIZE SKW)
  (* rrb "12-Jan-85 10:13")
  (* sets the default brush size to NEWBRUSHSIZE)
  (AND (NUMBERP NEWBRUSHSIZE)
    (replace (SKETCHCONTEXT SKETCHBRUSH) of (WINDOWPROP SKW 'SKETCHCONTEXT)
      with (create BRUSH using (fetch (SKETCHCONTEXT SKETCHBRUSH) of (WINDOWPROP SKW 'SKETCHCONTEXT))
        BRUSHSIZE _ NEWBRUSHSIZE]))
)
```

(READSIZECHANGE

```
[LAMBDA (MENUTITLE ALLOWZEROF LG)
  (* rrb "14-May-86 19:26")
  (* interacts to get whether a line size should be increased or decreased.)
  (PROG [(NEWVALUE (\CURSOR.IN.MIDDLE.MENU (create MENU
    TITLE _ MENUTITLE
    ITEMS _ ' ("smaller line" 'SMALLER "decreases the line
      thickness by 1."
      ("LARGER LINE" 'LARGER "increases the line
      thickness by 1."
      ("Set line size" 'SETSIZE "sets the line thickness
      to an entered value."))
    CENTERFLG _ T]
    (RETURN (COND
      ((EQ NEWVALUE 'SETSIZE)
        (SETQ NEWVALUE (RNUMBER "Enter the new line thickness." NIL NIL NIL T T T)))
      (COND
        ((AND (NULL ALLOWZEROF LG)
          (EQ NEWVALUE 0))
          NIL)
          ((GREATERP 0 NEWVALUE)
            (MINUS NEWVALUE))
          (T NEWVALUE)))
      (* don't allow negative values)
      (T NEWVALUE]))
  )
)
```

(DEFINEQ

(SK.CHANGE.ELEMENT.KNOTS

```
[LAMBDA (ELTWITHKNOTS NEWKNOTS)
  (* rrb "19-Mar-86 17:50")
  (* changes the knots in the element ELTWITHKNOTS)
  (PROG ((G CURVELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHKNOTS))
    NEWELT)
    (SETQ NEWELT (SELECTQ (fetch (INDIVIDUALGLOBALPART GTYPE) of G CURVELT)
      (CLOSEDCURVE (create CLOSEDCURVE using G CURVELT LATLONKNOTS _ NEWKNOTS))
      (OPENCURVE (SET.OPENCURVE.ARROWHEAD.POINTS (create OPENCURVE
        using G CURVELT LATLONKNOTS _
        NEWKNOTS)))
      (WIRE (SET.WIRE.ARROWHEAD.POINTS (create WIRE using G CURVELT LATLONKNOTS _ NEWKNOTS))
        (CLOSEDWIRE (create CLOSEDWIRE using G CURVELT LATLONKNOTS _ NEWKNOTS))
        (RETURN)))
    (RETURN (KNOT.SET.SCALE.FIELD (create GLOBALPART
      COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
        of ELTWITHKNOTS)
      INDIVIDUALGLOBALPART _ NEWELT))
  )
)
```

(DEFINEQ

(SK.INSURE.POINT.LIST

[LAMBDA (POINTLST)

(* rrb "16-Oct-85 17:01")
(* makes sure POINTLST is a list of positions.)

(COND
((LISTP POINTLST)
(AND (EVERY POINTLST (FUNCTION SK.INSURE.POSITION)
POINTLST))
(T (\ILLEGAL.ARG POINTLST]))

(SK.INSURE.POSITION

[LAMBDA (POSITION)
(OR (POSITIONP POSITION)
(\ILLEGAL.ARG POSITION])

(* rrb "16-Oct-85 17:02")

)

(DECLARE%: DONTCOPY

(DECLARE%: EVAL@COMPILE

(TYPE RECORD KNOTELT (LATLONKNOTS BRUSH DASHING NIL NIL KNOTREGION))

(RECORD LOCALCURVE (KNOTS LOCALHOTREGION ARROWHEADPTS LOCALCURVEBRUSH LOCALCURVEDASHING))

(TYPE RECORD OPENCURVE (LATLONKNOTS BRUSH DASHING CURVEARROWHEADS OPENCURVEINITSCALE OPENCURVEREGION
OPENCURVEARROWHEADPOINTS))


(TYPE RECORD CLOSEDCURVE (LATLONKNOTS BRUSH DASHING CLOSEDCURVEINITSCALE CLOSEDCURVEFILLING CLOSEDCURVEREGION))

(RECORD LOCALCLOSEDCURVE (LOCALCLOSEDCURVEKNOTS LOCALCLOSEDCURVEHOTREGION LOCALCLOSEDCURVEBRUSH
LOCALCLOSEDCURVEFILLING LOCALCLOSEDCURVEDASHING))

(RECORD LOCALCLOSEDWIRE (KNOTS LOCALHOTREGION LOCALCLOSEDWIREBRUSH LOCALCLOSEDWIREFILLING))
)

(READVARS-FROM-STRINGS ' (OPENCURVEICON CLOSEDCURVEICON)

"({ (READBITMAP) (20 12
% " @ @ @ @ @ @ @ @ % "
% " @ L @ @ @ @ @ @ % "
% " @ L @ @ F @ @ @ % "
% " A L @ @ O @ @ @ % "
% " A H @ @ G @ @ @ % "
% " C H @ @ C @ @ @ % "
% " C H @ @ C @ @ @ % "
% " C H @ @ G @ @ @ % "
% " A N @ @ N @ @ @ % "
% " @ O C L N @ @ @ % "
% " @ C O O L @ @ @ % "
% " @ @ N C H @ @ @ % ") { (READBITMAP) (20 12
% " @ @ C @ @ @ @ @ % "
% " A L G O @ @ @ @ % "
% " C N L O L @ @ @ % "
% " G C L A N @ @ @ % "
% " F A A H F @ @ @ % "
% " L @ C L C @ @ @ % "
% " N @ C F C @ @ @ % "
% " F @ F G @ @ @ % "
% " C @ F G F @ @ @ % "
% " C L F C L @ @ @ % "
% " A O N E H @ @ @ % "
% " @ G L @ @ @ @ @ % ") })
")

(RPAQ CURVE.KNOT (CURSORCREATE ' 
'NIL 0 8))

(DEFINEQ

(SKETCH.CREATE.WIRE

[LAMBDA (POINTS BRUSH DASHING ARROWHEADS SCALE)

(* rrb "16-Oct-85 17:05")
(* creates a sketch wire element.)

(SK.WIRE.CREATE (SK.INSURE.POINT.LIST POINTS)
(SK.INSURE.BRUSH BRUSH)
(SK.INSURE.DASHING DASHING)
NIL
(OR (NUMBERP SCALE)
1.0)
(SK.INSURE.ARROWHEADS ARROWHEADS)
NIL])

(CLOSEDWIRE.EXPANDFN

[LAMBDA (GELT SCALE)

(* rrb " 2-Dec-85 20:42")

(* returns a local record which has the LATLONKNOTS field of the global element GELT translated into window coordinats. Used for closed wires.)

```
(PROG ((INDVKNOTE1T (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
BRSH)
[COND
((fetch (CLOSEDWIRE CLOSEDWIREINITSSCALE) of INDVKNOTE1T))
(T
(replace (GLOBALPART INDIVIDUALGLOBALPART) of GELT
with (SETQ INDVKNOTE1T (create CLOSEDWIRE using INDVKNOTE1T CLOSEDWIREINITSSCALE _ 1.0
CLOSEDWIREREGION _ NIL]
(RETURN (create SCREENELT
LOCALPART _ (create LOCALCLOSEDWIRE
KNOTS _ (for LATLONPT in (fetch LATLONKNOTS of INDVKNOTE1T)
collect (SK.SCALE.POSITION.INTO.VIEWER LATLONPT SCALE))
LOCALCLOSEDWIREBRUSH _
(SCALE.BRUSH (COND
([NOT (NUMBERP (SETQ BRSH (fetch (CLOSEDWIRE BRUSH)
of INDVKNOTE1T))
(* new format, old format had brush width only.)
BRSH)
(T [replace (CLOSEDWIRE BRUSH) of INDVKNOTE1T
with (SETQ BRSH
(create BRUSH
BRUSHSIZE _ BRSH
BRUSHSHAPE _ 'ROUND]
BRSH)
(fetch (CLOSEDWIRE CLOSEDWIREINITSSCALE) of INDVKNOTE1T)
SCALE)
LOCALCLOSEDWIREFILLING _ (APPEND (fetch (CLOSEDWIRE CLOSEDWIREFILLING
of INDVKNOTE1T)))
GLOBALPART _ GELT]))
```

(KNOTS.INSIDFN

[LAMBDA (KNOTE1T WREG)

(* rrb "21-Jan-87 09:37")

(* determines if the global curve GCURVE is inside of WREG.)

(* this should be broken down between wires and curves but isn't here so it can be loaded as a patch.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of KNOTE1T)
(WIRE (REGIONSINTERSECTP WREG (OPENWIRE.GLOBALREGIONFN KNOTE1T)))
(CLOSEDWIRE (REGIONSINTERSECTP WREG (CLOSEDWIRE.GLOBALREGIONFN KNOTE1T)))
(CLOSEDCURVE (REGIONSINTERSECTP WREG (CLOSEDCURVE.GLOBALREGIONFN KNOTE1T)))
(REGIONSINTERSECTP WREG (OPENCURVE.GLOBALREGIONFN KNOTE1T)))
```

(OPEN.WIRE.DRAWFN

[LAMBDA (OPENWIREELT WIN REG OPERATION)

(* rrb " 7-Dec-85 20:11")

(* draws an open wire element.)

```
(WB.DRAWLINE OPENWIREELT WIN REG OPERATION NIL (fetch (LOCALWIRE LOCALWIREDASHING) of (fetch (SCREENELT
LOCALPART)
of OPENWIREELT))
(fetch (LOCALWIRE LOCALOPENWIREBRUSH) of (fetch (SCREENELT LOCALPART) of OPENWIREELT))
```

(WIRE.EXPANDFN

[LAMBDA (GELT SCALE)

(* rrb " 2-May-86 10:50")

(* returns a local record which has the LATLONKNOTS field of the global element GELT translated into window coordinats. Used for wires.)

```
(PROG ((INDGELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
LOCALKNOTS TMP)
[COND
((fetch (WIRE OPENWIREINITSSCALE) of INDGELT))
(T
(replace (GLOBALPART INDIVIDUALGLOBALPART) of GELT
with (SETQ INDGELT (create WIRE using INDGELT OPENWIREINITSSCALE _ 1.0 OPENWIREREGION _ NIL]
(COND
((AND (fetch (WIRE WIREARROWHEADS) of INDGELT)
(NOT (fetch (WIRE OPENWIREARROWHEADPOINTS) of INDGELT)))
(* old form didn't have global points, update it)
(SET.WIRE.ARROWHEAD.POINTS INDGELT)))
(SETQ LOCALKNOTS (for LATLONPT in (fetch (WIRE LATLONKNOTS) of INDGELT) collect (
SK.SCALE.POSITION.INTO.VIEWER
LATLONPT SCALE)))
(RETURN (create SCREENELT
LOCALPART _ (create LOCALWIRE
KNOTS _ LOCALKNOTS
ARROWHEADPTS _ (SK.EXPAND.ARROWHEADS (fetch (WIRE
OPENWIREARROWHEADPOINTS
)
```

```

of INDGELT)
SCALE)
LOCALOPENWIREBRUSH _
(SCALE.BRUSH (COND
  ([NOT (NUMBERP (SETQ TMP (fetch (WIRE BRUSH)
of INDGELT])
(* new format, old format had brush width only.)
TMP)
(T [replace (WIRE BRUSH) of INDGELT
with (SETQ TMP
(create BRUSH
BRUSHSIZE _ TMP
BRUSHSHAPE _ 'ROUND]
TMP))
(fetch (WIRE OPENWIREINITSIZE) of INDGELT)
SCALE)
LOCALWIREDASHING _ (fetch (WIRE OPENWIREDASHING) of INDGELT))
GLOBALPART _ GELT])

```

(SK.UPDATE.WIRE.ELT.AFTER.CHANGE

```

[LAMBDA (GWIRELT)
(* rrb "11-Dec-85 11:27")
(* updates the dependent fields of a wire element after one of
the fields changes.)
(* clear the region cache)
(replace (OPENCURVE OPENCURVEREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GWIRELT) with NIL)
(KNOT.SET.SCALE.FIELD GWIRELT])

```

(OPENWIRE.READCHANGEFN

```

[LAMBDA (SKW WIREELTS)
(* rrb "17-Dec-85 16:22")
(* ** change function for line elements.)
(PROG (ASPECT HOW)
(SETQ HOW (SELECTQ [SETQ ASPECT (\CURSOR.IN.MIDDLE.MENU (create MENU
CENTERFLG _ T
TITLE _ "Which aspect?"
ITEMS _
(APPEND
(COND
[(SKETCHINCOLORP)
'(("Brush color" 'BRUSHCOLOR
"changes the color of the
outline"]
(T NIL))
'((Arrowheads 'ARROW "allows changing
of arrow head
characteristics.")
(Size 'SIZE "changes the size of the
brush")
(Dashing 'DASHING "changes the
dashing of the line.")
(SIZE (READSIZECHANGE "Change size how?"))
(ARROW (READ.ARROW.CHANGE WIREELTS))
(DASHING (READ.DASHING.CHANGE))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change line color how?" NIL
(fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
(fetch (SCREENELT GLOBALPART)
of (CAR WIREELTS))
'BRUSH])
NIL))
(RETURN (AND HOW (LIST ASPECT HOW]))

```

(OPENWIRE.TRANSFORMFN

```

[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR)
(* rrb "19-Mar-86 17:51")
(* returns a copy of the global WIRE element that has had each of its control points transformed by transformfn.
TRANSFORMDATA is arbitrary data that is passed to tranformfn.)
(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
(RETURN (KNOT.SET.SCALE.FIELD (create GLOBALPART using GELT INDIVIDUALGLOBALPART _
(SET.WIRE.ARROWHEAD.POINTS
(create WIRE using
INDVPART LATLONKNOTS _
(SK.TRANSFORM.POINT.LIST
(fetch (WIRE LATLONKNOTS)
of INDVPART)
TRANSFORMFN TRANSFORMDATA)
BRUSH _
(SK.TRANSFORM.BRUSH
(fetch (WIRE BRUSH)
of INDVPART)
SCALEFACTOR)
WIREARROWHEADS _
(SK.TRANSFORM.ARROWHEADS
(fetch (WIRE WIREARROWHEADS)

```


of INDVPART)
SCALEFACTOR)
OPENWIREREGION _ NIL])

(OPENWIRE.TRANSLATEFN

[LAMBDA (WIREELT DELTAPOS)

(* rrb "20-Mar-86 15:08")
(* translates an open wire element)

(PROG ((NEWWIREELT (KNOTS.TRANSLATEFN WIREELT DELTAPOS))
(SET.WIRE.ARROWHEAD.POINTS (fetch (GLOBALPART INDIVIDUALGLOBALPART) of NEWWIREELT))
(RETURN NEWWIREELT]))

(OPENWIRE.TRANSLATEPTSFN

[LAMBDA (KNOTEPT SELPTS GDELTA WINDOW)

(* rrb "26-Sep-85 17:45")

(* returns an open wire element which has the knots that are members of SELPTS translated by the global amount GDELTA.)

(PROG ((GKNOTEPT (fetch (SCREENELT INDIVIDUALGLOBALPART) of KNOTEPT))
(RETURN (SK.WIRE.CREATE (for PT in (fetch (LOCALWIRE KNOTS) of (fetch (SCREENELT LOCALPART) of KNOTEPT))
as LATLONPT in (fetch (WIRE LATLONKNOTS) of GKNOTEPT)
collect (COND
(MEMBER PT SELPTS)
(PTPLUS LATLONPT GDELTA))
(T LATLONPT))
(fetch (WIRE BRUSH) of GKNOTEPT)
(fetch (WIRE OPENWIREDASHING) of GKNOTEPT)
NIL
(fetch (WIRE OPENWIREINITSCALE) of GKNOTEPT)
(fetch (WIRE WIREARROWHEADS) of GKNOTEPT))

(WIRE.INPUTFN

[LAMBDA (W GPTLIST CLOSEDFLG BRUSH DEFSCALE DASHING FILLING) (* rrb "15-Nov-85 11:39")

(* creates a wire {a series of straight lines through a list of points} from a list of points passed in or a list that is read from the user via mouse.)

(PROG ((SKCONTEXT (WINDOWPROP W 'SKETCHCONTEXT))
KNOTS)
(RETURN (SK.WIRE.CREATE [SETQ KNOTS (OR GPTLIST (for PT in (SK.READ.WIRE.POINTS W CLOSEDFLG)
collect (SK.MAP.INPUT.PT.TO.GLOBAL PT W]
(COND
(NUMBERP BRUSH)

(* called with a number from the sketch stream drawline operation.
Make it a round brush.)

(create BRUSH
BRUSHSIZE _ BRUSH
BRUSHSHAPE _ 'ROUND))
(T (fetch (SKETCHCONTEXT SKETCHBRUSH) of SKCONTEXT))
(OR (DASHINGP DASHING)
(fetch (SKETCHCONTEXT SKETCHDASHING) of SKCONTEXT))
CLOSEDFLG
(OR (NUMBERP DEFSCALE)
(SK.INPUT.SCALE W))
(SK.ARROWHEAD.CREATE W KNOTS)
FILLING])

(SK.READ.WIRE.POINTS

[LAMBDA (SKW CLOSEDFLG)

(* rrb "12-May-86 18:31")
(* reads a list of points for a wire.)

(SK.READ.POINTS.WITH.FEEDBACK SKW NIL (AND SKETCH.VERBOSE.FEEDBACK (COND
(CLOSEDFLG (FUNCTION
CLOSEDWIRE.FEEDBACKFN))
(T (FUNCTION OPENWIRE.FEEDBACKFN]))

(SK.READ.POINTS.WITH.FEEDBACK

[LAMBDA (W ALLOWDUPS? FEEDBACKFN)

(* rrb "10-Jun-86 15:44")
(* reads a {series of points} from the user.)

(PROG (PT PTS ERRSTAT)
(STATUSPRINT W "
" "Enter the points the curve goes through using the left button.
Click outside the window to stop.")
LP (COND
((AND [SETQ ERRSTAT (ERSETQ (SETQ PT (SK.READ.POINT.WITH.FEEDBACK W POINTREADINGCURSOR FEEDBACKFN
PTS 'MIDDLE NIL (AND SKETCH.USE.POSITION.PAD
'MULTIPLE])
PT) (* add the point to the list and mark it.)
[COND
([OR ALLOWDUPS? (NOT (EQUAL (fetch (INPUTPT INPUT.POSITION) of (CAR (LAST PTS)))
(fetch (INPUTPT INPUT.POSITION) of PT))
(SHOWSKETCHPOINT (fetch (INPUTPT INPUT.POSITION) of PT)

W PTS)

(* draw the line so it will remain displayed while the user adds other points. This will not close it.)

```
(AND PTS (DRAWBETWEEN (fetch (INPUTPT INPUT.POSITION) of (CAR (LAST PTS)))
  (fetch (INPUTPT INPUT.POSITION) of PT)
  1
  'INVERT W))
  (SETQ PTS (NCONC1 PTS PT]
  (GO LP)))
(for PTTAIL on PTS do (SHOWSKETCHPOINT (fetch (INPUTPT INPUT.POSITION) of (CAR PTTAIL))
  W
  (CDR PTTAIL)) (* erase line)
  (AND (CDR PTTAIL)
  (DRAWBETWEEN (fetch (INPUTPT INPUT.POSITION) of (CAR PTTAIL))
  (fetch (INPUTPT INPUT.POSITION) of (CADR PTTAIL))
  1
  'INVERT W)))
(CLRPROMPT)
(CLOSEPROMPTWINDOW W)
(COND
  (ERRSTAT (* no error.)
  (RETURN PTS))
  (T (* had an error, pass it on)
  (ERROR!]))
```

(OPENWIRE.FEEDBACKFN

[LAMBDA (X Y WINDOW PREVPTS)

(* rrb "15-Nov-85 11:32")
(* provides the rubberbanding feedback for the user inputting a point for an open wire.)

```
(SHOWSKETCHXY X Y WINDOW)
(AND PREVPTS (PROG (LASTPT)
  (RETURN (DRAWLINE [fetch (POSITION XCOORD) of (SETQ LASTPT (fetch (INPUTPT INPUT.POSITION)
  of (CAR (LAST PREVPTS))
  (fetch (POSITION YCOORD) of LASTPT)
  X Y 1 'INVERT WINDOW]))
```

(CLOSEDWIRE.FEEDBACKFN

[LAMBDA (X Y WINDOW PREVPTS)

(* rrb "15-Nov-85 11:31")
(* provides the rubberbanding feedback for the user inputting a point for an open wire.)
(* draw from the first pt to the new pt)

```
(SHOWSKETCHXY X Y WINDOW)
(PROG (ENDPT)
  (AND PREVPTS (DRAWLINE [fetch (POSITION XCOORD) of (SETQ ENDPT (fetch (INPUTPT INPUT.POSITION)
  of (CAR PREVPTS))
  (fetch (POSITION YCOORD) of ENDPT)
  X Y 1 'INVERT WINDOW)) (* draw from the last pt to the new pt)
  (AND (CDR PREVPTS)
  (DRAWLINE [fetch (POSITION XCOORD) of (SETQ ENDPT (fetch (INPUTPT INPUT.POSITION)
  of (CAR (LAST PREVPTS))
  (fetch (POSITION YCOORD) of ENDPT)
  X Y 1 'INVERT WINDOW]))
```

(CLOSEDWIRE.REGIONFN

[LAMBDA (KNOTSCRELT)

(* rrb " 2-Jun-85 17:15")
(* returns the region occupied by a closed wire)

(* increase by half the brush size plus 2 This has the nice property of insuring that the region always has both height and width.)

```
(INCREASEREGION (REGION.CONTAINING.PTS (fetch (SCREENELT HOTSPOTS) of KNOTSCRELT))
  (IPLUS 3 (QUOTIENT (fetch (BRUSH BRUSHSIZE) of (fetch (LOCALCLOSEDWIRE LOCALCLOSEDWIREBRUSH)
  of (fetch (SCREENELT LOCALPART) of KNOTSCRELT)))
  2))
```

(CLOSEDWIRE.GLOBALREGIONFN

[LAMBDA (GCLOSEDWIREELT)

(* rrb "23-Oct-85 11:30")
(* returns the global region occupied by a global closed curve element.)

```
(OR (fetch (CLOSEDWIRE CLOSEDWIREREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCLOSEDWIREELT))
  (PROG ((INDVCLOSEDWIRE (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GCLOSEDWIREELT))
  REGION)
  [SETQ REGION (INCREASEREGION (REGION.CONTAINING.PTS (fetch (CLOSEDWIRE LATLONKNOTS) of
  INDVCLOSEDWIRE
  ))
  (SK.BRUSH.SIZE (fetch (CLOSEDWIRE BRUSH) of INDVCLOSEDWIRE)
  (replace (CLOSEDWIRE CLOSEDWIREREGION) of INDVCLOSEDWIRE with REGION)
  (RETURN REGION]))
```

(SK.WIRE.CREATE

[LAMBDA (KNOTS BRUSH DASHING CLOSED SCALE ARROWHEADS FILLING) (* rrb "19-Mar-86 17:51")

(* creates a wire sketch element.)

```
(AND KNOTS
  (KNOT.SET.SCALE.FIELD (create GLOBALPART
    INDIVIDUALGLOBALPART _
    (COND
      (CLOSED (create CLOSEDWIRE
        LATLONKNOTS _ KNOTS
        BRUSH _ BRUSH
        CLOSEDWIREDASHING _ DASHING
        CLOSEDWIREINITSSCALE _ SCALE
        CLOSEDWIREFILLING _ FILLING))
      (T (SET.WIRE.ARROWHEAD.POINTS (create WIRE
        LATLONKNOTS _ KNOTS
        BRUSH _ BRUSH
        WIREARROWHEADS _ ARROWHEADS
        OPENWIREDASHING _ DASHING
        OPENWIREINITSSCALE _ SCALE]))
```

(WIRE.ADD.POINT.TO.END

```
[LAMBDA (WIREELT PT SKW)
  (PROG ((NEWPOS (SK.MAP.INPUT.PT.TO.GLOBAL PT SKW))
    KNOTS GWIREELT)
    (SETQ GWIREELT (fetch (SCREENELT GLOBALPART) of WIREELT))
    (SETQ KNOTS (fetch LATLONKNOTS of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GWIREELT)))
    (RETURN (COND
      ((EQUAL NEWPOS (CAR (LAST KNOTS)))
        WIREELT)
      (T
        (SK.UPDATE.ELEMENT GWIREELT (WIRE.INPUTFN SKW (APPEND KNOTS (CONS NEWPOS))
          NIL)
          SKW]))
    (* rrb "11-Jul-85 11:26")
    (* adds a point onto the end of a wire element.)
    (* don't add duplicate points)
    (* add point at the end.)
```

(READ.ARROW.CHANGE

```
[LAMBDA (SCRELTS SKW)
  (DECLARE (GLOBALVARS SK.ARROW.EDIT.MENU)
    (* rrb "17-Dec-85 17:09")
    (* gets a description of how to change the arrow heads of a wire or curve.)
    (OR (type? MENU SK.ARROW.EDIT.MENU)
      (SETQ SK.ARROW.EDIT.MENU (create MENU
        TITLE _ "specify change"
        ITEMS _ (APPEND '((Add% Arrow 'ADD "Adds an arrow head."
          ("Remove Arrow" 'DELETE "Removes the arrow head."
            ("Same as First" 'SAME "Makes all of the arrowheads be
              the same as the first one selected."
            (Wider 'WIDER "Makes the angle of the head wider."
            (Narrower 'NARROWER "Makes the angle of the head
              smaller."
            (Larger 'LARGER "Makes the arrow head larger."
            (Smaller 'SMALLER "Makes the arrow head smaller."))
          (LIST (LIST VSHAPE.ARROWHEAD.BITMAP ''OPEN "Makes the
            head be the side lines only."
            (LIST CURVEDV.ARROWHEAD.BITMAP ''OPENCURVE
            "Makes the arrowhead have curved side
            lines."
            (LIST TRIANGLE.ARROWHEAD.BITMAP ''CLOSED "Makes the
            head be two sides and a base."
            (LIST SOLIDTRIANGLE.ARROWHEAD.BITMAP
            ''SOLID "makes a solid triangular
            arrowhead.")))
          CENTERFLG _ T)))
    (PROG (HOW)
      (RETURN (LIST (OR (READ.ARROWHEAD.END)
        (RETURN))
        (COND
          ((EQ (SETQ HOW (\CURSOR.IN.MIDDLE.MENU SK.ARROW.EDIT.MENU))
            'SAME)
            (* if the user chooses SAME, determine the characteristics.)
            (OR (bind NOWARROWS INDGELT for ELT in SCRELTS
              do (SETQ INDGELT (fetch (SCREENELT INDIVIDUALGLOBALPART) of ELT))
                [COND
                  ((SETQ NOWARROWS (SELECTQ (fetch (INDIVIDUALGLOBALPART GTYPE)
                    of INDGELT)
                    (OPENCURVE (fetch (OPENCURVE CURVEARROWHEADS)
                    of INDGELT))
                    (ARC (fetch (ARC ARROWHEADS) of INDGELT))
                    (WIRE (fetch (WIRE WIREARROWHEADS) of INDGELT))
                    NIL))
                  (COND
                    [(CAR NOWARROWS)
                      (RETURN (CONS 'SAME (CAR NOWARROWS))]
                    ((CADR NOWARROWS)
                      (RETURN (CONS 'SAME (CADR NOWARROWS))]
                    finally (STATUSPRINT SKW "None of the selected elements have arrowheads."))
                    (RETURN))
```

(HOW)
(T (RETURN])

(CHANGE.ELTS.ARROWHEADS

[LAMBDA (CHANGESPEC ELTSWITHARROWS SKW) (* rrb "10-Jan-85 16:58")

(* * function that changes the arrow characteristics for all elements in ELTSWITHARROWS that can have arrows.)

(AND CHANGESPEC (for ARROWELT in ELTSWITHARROWS collect (SK.CHANGE.ARROWHEADS ARROWELT CHANGESPEC SKW])

)

(DEFINEQ

(SKETCH.CREATE.CLOSED.WIRE

[LAMBDA (POINTS BRUSH DASHING FILLING SCALE) (* rrb "16-Oct-85 17:12")
(* creates a sketch closed wire element.)

(SK.WIRE.CREATE (SK.INSURE.POINT.LIST POINTS)

(SK.INSURE.BRUSH BRUSH)
(SK.INSURE.DASHING DASHING)

T
(OR (NUMBERP SCALE)
1.0)

NIL
(SK.INSURE.FILLING FILLING])

(CLOSED.WIRE.INPUTFN

[LAMBDA (W PTLIST) (* rrb "13-Dec-84 10:10")

(* creates a closed wire {a series of straight lines through a list of points} from a list of points passed in or a list that is read from the user via mouse.)

(WIRE.INPUTFN W PTLIST T])

(CLOSED.WIRE.DRAWFN

[LAMBDA (CLOSEDWIREELT WIN REG OPERATION) ; Edited 3-Mar-87 10:09 by rrb
(* draws a closed wire element.)

(PROG ((GINDVELT (fetch (SCREENELT INDIVIDUALGLOBALPART) of CLOSEDWIREELT))

(LOCALPART (fetch (SCREENELT LOCALPART) of CLOSEDWIREELT))

VARX)

(SETQ VARX (fetch (LOCALCLOSEDWIRE LOCALCLOSEDWIREFILLING) of LOCALPART))

[COND

((OR (fetch (SKFILLING FILLING.TEXTURE) of VARX)

(fetch (SKFILLING FILLING.COLOR) of VARX)) (* if there isn't any filling, don't fill.)

(FILLPOLYGON (fetch (LOCALCLOSEDWIRE KNOTS) of LOCALPART)

[COND

(SKETCHINCOLORFLG VARX)

((fetch (SKFILLING FILLING.TEXTURE) of VARX))

(T (* simulate color)

(TEXTUREOFCOLOR (fetch (SKFILLING FILLING.COLOR) of VARX])

WIN

(COND

((EQ (DSOPERATION NIL WIN)

'ERASE)

(* if the stream is erasing, erase.)

'ERASE)

(T (* otherwise use the element's mode.)

(OR (EQ (fetch (SKFILLING FILLING.OPERATION) of VARX)
(fetch (BRUSH BRUSHSIZE) of (SETQ VARX (fetch (LOCALCLOSEDWIRE LOCALCLOSEDWIREBRUSH)
of LOCALPART))))

0)

(WB.DRAWLINE CLOSEDWIREELT WIN REG OPERATION T (fetch (CLOSEDWIRE CLOSEDWIREDASHING) of GINDVELT)
VARX])

(CLOSEDWIRE.READCHANGEFN

[LAMBDA (SKW SCRNELTS) (* rrb " 5-Mar-86 13:35")

(* the users has selected SCRNELT to be changed this function reads a specification of how the closed wire elements should change.)

(PROG (ASPECT HOW)

(SETQ HOW (SELECTQ [SETQ ASPECT (\CURSOR.IN.MIDDLE.MENU

(create MENU

CENTERFLG _ T

TITLE _ "Which aspect?"

ITEMS _ (APPEND (COND

[(SKETCHINCOLORP)

'(("Brush color" 'BRUSHCOLOR "changes the
color of the outline")

("Filling color" 'FILLINGCOLOR

"changes the color of the
filling"]

(T NIL))

[COND

```

(FILLPOLYGONFLG ' ((Filling 'FILLING
                    "allows changing of
                    the filling texture
                    of the box.")]
[COND
  (FILLINGMODEFLG ' ("Filling mode"
                    'FILLINGMODE "changes how
                    the filling effects the
                    figures it covers.")]
' ((Shape 'SHAPE "changes the shape of the
   brush")
   (Size 'SIZE "changes the size of the brush")
   (Dashing 'DASHING "changes the dashing of the
   line.")
   ("Add point" 'ADDPPOINT "adds a point to the
   curve.")]
(SIZE (READSIZECHANGE "Change size how?" T))
(FILLING (READ.FILLING.CHANGE))
(FILLINGMODE (READ.FILLING.MODE))
(DASHING (READ.DASHING.CHANGE))
(SHAPE (READBRUSHSHAPE))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change outline color how?" NIL
             (fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
             (fetch (SCREENELT GLOBALPART)
             of (CAR SCRNELTS))
             'BRUSH])
(ADDPPOINT (READ.POINT.TO.ADD (CAR SCRNELTS)
              SKW))
(FILLINGCOLOR [READ.COLOR.CHANGE "Change filling color how?" T
              (fetch (SKFILLING FILLING.COLOR) of (GETSKETCHELEMENTPROP
              (fetch (SCREENELT GLOBALPART)
              of (CAR SCRNELTS))
              'FILLING])
NIL))
(RETURN (AND HOW (LIST ASPECT HOW])

```

(CLOSEDWIRE.TRANSFORMFN

[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR) (* rrb "18-Oct-85 16:46")

(* returns a copy of the global CLOSEDWIRE element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to transformfn.)

```

(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (RETURN (KNOT.SET.SCALE.FIELD (create GLOBALPART using
  (create CLOSEDWIRE
    using INDVPART LATLONKNOTS _
    (SK.TRANSFORM.POINT.LIST
      (fetch (CLOSEDWIRE LATLONKNOTS)
        of INDVPART)
      TRANSFORMFN TRANSFORMDATA)
    BRUSH _ (SK.TRANSFORM.BRUSH
      (fetch (CLOSEDWIRE BRUSH)
        of INDVPART)
      SCALEFACTOR)
    CLOSEDWIREREGION _ NIL])

```

(CLOSEDWIRE.TRANSLATEPTSFN

[LAMBDA (KNOTELT SELPTS GDELTA WINDOW) (* rrb "27-Sep-85 18:58")

(* returns a closed wire element which has the knots that are members of SELPTS translated by the global amount GDELTA.)

```

(PROG ((GKNOTELT (fetch (SCREENELT INDIVIDUALGLOBALPART) of KNOTELT)))
  (RETURN (SK.WIRE.CREATE (for PT in (fetch (LOCALCLOSEDWIRE KNOTS) of (fetch (SCREENELT LOCALPART)
  of KNOTELT)))
    as LATLONPT in (fetch (CLOSEDWIRE LATLONKNOTS) of GKNOTELT)
    collect (COND
      ((MEMBER PT SELPTS)
        (PTPLUS LATLONPT GDELTA))
      (T LATLONPT)))
    (fetch (CLOSEDWIRE BRUSH) of GKNOTELT)
    (fetch (CLOSEDWIRE CLOSEDWIREDASHING) of GKNOTELT)
    T
    (fetch (CLOSEDWIRE CLOSEDWIREINITSSCALE) of GKNOTELT)
    NIL
    (fetch (CLOSEDWIRE CLOSEDWIREFILLING) of GKNOTELT]))

```

)

(DEFINEQ

(SK.EXPAND.ARROWHEADS

[LAMBDA (GARROWHEADPOINTS SCALE) (* rrb " 2-May-86 10:50")

(* returns a list of local arrowhead points from the list of global arrowhead points.)

(for ARROWHEAD in GARROWHEADPOINTS collect (SK.EXPAND.ARROWHEAD ARROWHEAD SCALE])

(SK.COMPUTE.ARC.ARROWHEAD.POINTS

[LAMBDA (ARROWSPEC CENTERPT RADPT ARCANGLEPT DIRECTION) (* rrb "19-Mar-86 17:09")

(* returns a list of global arrowhead points from the specs and points that define an arc.)

```
(PROG (SPEC)
  (OR ARROWSPEC (RETURN NIL))
  (RETURN (LIST (AND (SETQ SPEC (CAR ARROWSPEC))
    (ARC.ARROWHEAD.POINTS CENTERPT RADPT DIRECTION (fetch (ARROWHEAD ARROWANGLE)
      of SPEC)
      (fetch (ARROWHEAD ARROWLENGTH) of SPEC)
      (fetch (ARROWHEAD ARROWTYPE) of SPEC)))
    (AND (SETQ SPEC (CADR ARROWSPEC))
      (ARC.ARROWHEAD.POINTS CENTERPT ARCANGLEPT (NOT DIRECTION)
        (fetch (ARROWHEAD ARROWANGLE) of SPEC)
        (fetch (ARROWHEAD ARROWLENGTH) of SPEC)
        (fetch (ARROWHEAD ARROWTYPE) of SPEC)))))
```

(ARC.ARROWHEAD.POINTS

[LAMBDA (CENTERPT ENDPT CLOCKWISEFLG HEAD.ANGLE HEAD.LENGTH HEAD.TYPE) (* rrb "20-Mar-86 09:12")

(* returns a list of arrowhead points for an arc. If CLOCKWISEFLG is T, it is to go on the clockwise direction.)

```
(ARROWHEAD.POINTS.LIST ENDPT HEAD.ANGLE HEAD.LENGTH (TIMES (COND
  (CLOCKWISEFLG -1)
  (T 1))
  (DIFFERENCE (fetch (POSITION YCOORD) of ENDPT)
    (fetch (POSITION YCOORD) of CENTERPT)))
  (TIMES (COND
    (CLOCKWISEFLG 1)
    (T -1))
    (DIFFERENCE (fetch (POSITION XCOORD) of ENDPT)
      (fetch (POSITION XCOORD) of CENTERPT)))
  HEAD.TYPE))
```

(SET.ARC.ARROWHEAD.POINTS

[LAMBDA (INDVDARCEL) (* rrb "20-Jun-86 13:56")

(* * updates the global arrowhead points field of an element.)

```
(PROG ((ARROWSPECS (fetch (ARC ARCARROWHEADS) of INDVDARCEL)))
  [COND
    (ARROWSPECS (SK.INSURE.HAS.LENGTH INDVDARCEL (SK.RECORD.LENGTH 'ARC)
      'ARC)
      (replace (ARC ARCARROWHEADPOINTS) of INDVDARCEL with (SK.COMPUTE.ARC.ARROWHEAD.POINTS
        ARROWSPECS
        (fetch (ARC ARCCENTERPT) of INDVDARCEL)
        (fetch (ARC ARCRADIUSPT) of INDVDARCEL)
        (SK.GET.ARC.ANGLEPT INDVDARCEL)
        (fetch (ARC ARCDIRECTION) of INDVDARCEL))
      (RETURN INDVDARCEL]))
```

(SET.OPENCURVE.ARROWHEAD.POINTS

[LAMBDA (INDVOPENCURVEELT) (* rrb "20-Mar-86 14:30")

(* * updates the global arrowhead points field of an element.)

```
(PROG ((ARROWSPECS (fetch (OPENCURVE CURVEARROWHEADS) of INDVOPENCURVEELT)))
  [COND
    (ARROWSPECS (SK.INSURE.HAS.LENGTH INDVOPENCURVEELT (SK.RECORD.LENGTH 'OPENCURVE)
      'OPENCURVE)
      (replace (OPENCURVE OPENCURVEARROWHEADPOINTS) of INDVOPENCURVEELT
        with (SK.COMPUTE.CURVE.ARROWHEAD.POINTS ARROWSPECS (fetch (OPENCURVE LATLONKNOTS)
          of INDVOPENCURVEELT))
      (RETURN INDVOPENCURVEELT]))
```

(SK.COMPUTE.CURVE.ARROWHEAD.POINTS

[LAMBDA (ARROWSPEC KNOTS) (* rrb "19-Mar-86 17:32")

(* returns a list of global arrowhead points from the specs and points that define an curve.)

```
(PROG (SPEC)
  (OR ARROWSPEC (RETURN NIL))
  (RETURN (LIST (AND (SETQ SPEC (CAR ARROWSPEC))
    (CURVE.ARROWHEAD.POINTS KNOTS T (fetch (ARROWHEAD ARROWANGLE) of SPEC)
      (fetch (ARROWHEAD ARROWLENGTH) of SPEC)
      (fetch (ARROWHEAD ARROWTYPE) of SPEC)))
    (AND (SETQ SPEC (CADR ARROWSPEC))
      (CURVE.ARROWHEAD.POINTS KNOTS NIL (fetch (ARROWHEAD ARROWANGLE) of SPEC)))))
```

(fetch (ARROWHEAD ARROWLENGTH) of SPEC)
 (fetch (ARROWHEAD ARROWTYPE) of SPEC)]

(SET.WIRE.ARROWHEAD.POINTS

[LAMBDA (INDVWIREELT)

(* rrb "20-Mar-86 14:31")

(* updates the global arrowhead points field of an element.)

(PROG ((ARROWSPECS (fetch (WIRE WIREARROWHEADS) of INDVWIREELT)))
 [COND

(ARROWSPECS (SK.INSURE.HAS.LENGTH INDVWIREELT (SK.RECORD.LENGTH 'WIRE)
 'WIRE)

(replace (WIRE OPENWIREARROWHEADPOINTS) of INDVWIREELT with (

SK.COMPUTE.WIRE.ARROWHEAD.POINTS
 ARROWSPECS
 (fetch (WIRE LATLONKNOTS)
 of INDVWIREELT])

(RETURN INDVWIREELT])

(SK.COMPUTE.WIRE.ARROWHEAD.POINTS

[LAMBDA (ARROWSPEC KNOTS)

(* rrb "19-Mar-86 17:46")

(* returns a list of global arrowhead points from the specs and points that define an curve.)

(PROG (SPEC)

(OR ARROWSPEC (RETURN NIL))

(* format keeps arrow specs as (FIRST LAST T)%.)

(RETURN (LIST (AND (SETQ SPEC (CAR ARROWSPEC))

(**WIRE.ARROWHEAD.POINTS** KNOTS T (fetch (ARROWHEAD ARROWANGLE) of SPEC)

(fetch (ARROWHEAD ARROWLENGTH) of SPEC)

(fetch (ARROWHEAD ARROWTYPE) of SPEC)))

(AND (SETQ SPEC (CADR ARROWSPEC))

(**WIRE.ARROWHEAD.POINTS** KNOTS NIL (fetch (ARROWHEAD ARROWANGLE) of SPEC)

(fetch (ARROWHEAD ARROWLENGTH) of SPEC)

(fetch (ARROWHEAD ARROWTYPE) of SPEC]))

(SK.EXPAND.ARROWHEAD

[LAMBDA (ARROWHEAD SCALE)

(* rrb "11-Jul-86 15:54")

(* expands an arrowhead to a given scale. The format of Arrowhead points is
 (HEADPT ONESIDEENDPT OTHERSIDEENDPT) or (HEADPT
 (SIDE1PT1 SIDE1PT2) (SIDE2PT1 SIDE2PT2)))

(AND ARROWHEAD (CONS (SK.SCALE.POSITION.INTO.VIEWER (CAR ARROWHEAD)
 SCALE)

(COND

((POSITIONP (CADR ARROWHEAD))

(for PT in (CDR ARROWHEAD) collect (SK.SCALE.POSITION.INTO.VIEWER PT SCALE)))

(T (* form is (HEADPT (SIDE1PT1 SIDE1PT2)
 (SIDE2PT1 SIDE2PT2)))

(for PTLST in (CDR ARROWHEAD) collect (for PT in PTLST collect (SK.SCALE.POSITION.INTO.VIEWER
 PT SCALE]))

(CHANGED.ARROW

[LAMBDA (ARROW HOWTOCHANGE SCALE DEFARROW)

(* rrb "17-Dec-85 17:04")

(* returns an arrow that has been changed according to the spec HOWTOCHANGE.)

(COND

((EQ HOWTOCHANGE 'ADD)

(* if there already is one, leave it alone.)

(OR ARROW (**SK.CREATE.ARROWHEAD** DEFARROW SCALE)))

((OR (EQ HOWTOCHANGE 'DELETE)

(NULL ARROW))

NIL)

((EQ (CAR HOWTOCHANGE)

(* make it the same as the one given.)

'SAME)

(APPEND (CDR HOWTOCHANGE)))

(T (SELECTQ HOWTOCHANGE

(WIDER (**create** ARROWHEAD **using** ARROW ARROWANGLE _ (PLUS SK.ARROWHEAD.ANGLE.INCREMENT

(fetch (ARROWHEAD ARROWANGLE) of ARROW)))

(NARROWER (**create** ARROWHEAD **using** ARROW ARROWANGLE _ (DIFFERENCE (fetch (ARROWHEAD ARROWANGLE)

of ARROW)

SK.ARROWHEAD.ANGLE.INCREMENT)))

(LARGER (**create** ARROWHEAD **using** ARROW ARROWLENGTH _ (PLUS (TIMES SK.ARROWHEAD.LENGTH.INCREMENT

SCALE)

(fetch (ARROWHEAD ARROWLENGTH)

of ARROW)))

(SMALLER (**create** ARROWHEAD **using** ARROW ARROWLENGTH _ (MAX (DIFFERENCE (fetch (ARROWHEAD ARROWLENGTH)

of ARROW)

(TIMES

SK.ARROWHEAD.LENGTH.INCREMENT

SCALE))

SCALE)))

```

(OPEN (create ARROWHEAD using ARROW ARROWTYPE _ 'LINE))
(CLOSED (create ARROWHEAD using ARROW ARROWTYPE _ 'CLOSEDLINE))
(SOLID (create ARROWHEAD using ARROW ARROWTYPE _ 'SOLID))
(OPENCURVE (create ARROWHEAD using ARROW ARROWTYPE _ 'CURVE))
ARROW])

```

(SK.CHANGE.ARROWHEAD

```

[LAMBDA (ARROWELT HOW SKW) (* rrb " 1-May-86 16:27")

```

(* changes the arrow heads of an element and returns the new element if any actually occurred.)

```

(SK.CHANGE.ARROWHEAD1 ARROWELT (CAR HOW)
(CADR HOW)
(SK.INPUT.SCALE SKW)
(fetch (SKETCHCONTEXT SKETCHARROWHEAD) of (WINDOWPROP SKW 'SKETCHCONTEXT])

```

(SK.CHANGE.ARROWHEAD1

```

[LAMBDA (GARROWELT WHICHEND HOWTOCHANGE SCALE DEFAULTARROWHEAD) (* rrb "20-Jun-86 13:57")

```

```

(PROG (INDGARROWELT NEWARROWS NOWARROWS CHANGEDFLG TYPE KNOTS)
(RETURN (COND
  ((MEMB (SETQ TYPE (fetch (GLOBALPART GTYPE) of GARROWELT))
    ' (WIRE OPENCURVE ARC)) (* only works for things of wire type.)
  (SETQ INDGARROWELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GARROWELT))
  [SETQ NOWARROWS (OR (SELECTQ TYPE
    (OPENCURVE (fetch (OPENCURVE CURVEARROWHEADS) of INDGARROWELT))
    (ARC (fetch (ARC ARCARROWHEADS) of INDGARROWELT))
    (fetch (WIRE WIREARROWHEADS) of INDGARROWELT))
    ' (NIL NIL T)]
  (SETQ KNOTS (SELECTQ TYPE
    (ARC (* calculate the knots for the left most test)
      (LIST (fetch (ARC ARCRADIUSPT) of INDGARROWELT)
        (\SK.GET.ARC.ANGLEPT INDGARROWELT)))
    (fetch LATLONKNOTS of INDGARROWELT)))
    (* the brush is stored in the same place for all element types.)
  (SETQ NEWARROWS (bind NEWARROW for ARROW in NOWARROWS as END
    in '(FIRST LAST) collect (SETQ NEWARROW (COND
      ((SK.ARROWHEAD.END.TEST
        WHICHEND END KNOTS)
        (* change the spec)
        (CHANGED.ARROW ARROW
          HOWTOCHANGE SCALE
          DEFAULTARROWHEAD))
        (T ARROW)))
    (COND
      ((NOT (EQUAL NEWARROW ARROW))
        (* keep track of whether or not any arrow was changed.)
        (SETQ CHANGEDFLG T)))
    NEWARROW))
  (AND CHANGEDFLG (create SKHISTORYCHANGESPEC
    NEWELT _
    (create GLOBALPART
      COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
        of GARROWELT)
      INDIVIDUALGLOBALPART _
      (SELECTQ TYPE
        (WIRE (SET.WIRE.ARROWHEAD.POINTS (create WIRE
          using INDGARROWELT
          WIREARROWHEADS
          _ NEWARROWS))
        (ARC (SET.ARC.ARROWHEAD.POINTS (create ARC
          using INDGARROWELT
          ARCARROWHEADS _
          NEWARROWS))
        (OPENCURVE (SET.OPENCURVE.ARROWHEAD.POINTS
          (create OPENCURVE using INDGARROWELT
          CURVEARROWHEADS _
          NEWARROWS))
        (SHOULDNT)))
    OLDELТ _ GARROWELT
    PROPERTY _ ' ARROWHEADS
    NEWVALUE _ NEWARROWS
    OLDVALUE _ NOWARROWS])

```

(SK.CREATE.ARROWHEAD

```

[LAMBDA (DEFAULTARROWHEAD SCALE) (* rrb " 5-May-85 17:39")
(* creates a new arrowhead which is the default
DEFAULTARROWHEAD scaled to SCALE.)
(create ARROWHEAD using DEFAULTARROWHEAD ARROWLENGTH _ (TIMES (fetch (ARROWHEAD ARROWLENGTH) of
DEFAULTARROWHEAD
SCALE]))

```



```
(COND
  (BEGFLG (MINUS (CDR SLOPE)))
  (T (CDR SLOPE)))
HEAD.TYPE])
```

(LEFT.MOST.IS.BEGINP

```
[LAMBDA (KNOTLST) (* rrb "30-Nov-84 16:55")
```

(* returns T if the beginning of the curve thru KNOTLST is to the left of its end.)

```
(COND
  ((NULL (CDR (LISTP KNOTLST)))
   (ERROR KNOTLST "should have at least two elements.))
  (T (PROG ((FIRST (CAR KNOTLST))
            (LAST (CAR (LAST KNOTLST)))
            FIRSTX LASTX)
          (RETURN (OR (GREATERP (SETQ LASTX (fetch (POSITION XCOORD) of LAST))
                               (SETQ FIRSTX (fetch (POSITION XCOORD) of FIRST)))
                    (AND (EQ LASTX FIRSTX)
                         (GREATERP (fetch (POSITION YCOORD) of FIRST)
                                    (fetch (POSITION YCOORD) of LAST))))))
```

(WIRE.ARROWHEAD.POINTS

```
[LAMBDA (KNOTS FIRSTFLG HEAD.ANGLE HEAD.LENGTH HEAD.TYPE) (* rrb "19-Mar-86 17:46")
```

(* returns a list of arrowhead points for a wire. If FIRSTFLG is T, it is to go on the first end.)

```
(PROG (HEADPT TAILPT)
  (COND
    (FIRSTFLG (SETQ HEADPT (CAR KNOTS))
              (SETQ TAILPT (CADR KNOTS)))
    ((CDR KNOTS)
     (for KNOTTAIL on KNOTS when (NULL (CDDR KNOTTAIL)) do (SETQ TAILPT (CAR KNOTTAIL))
                                           (SETQ HEADPT (CADR KNOTTAIL))
                                           (RETURN)))
     (* only one point, don't put on an arrowhead.)
    (T (RETURN)))
  (RETURN (ARROWHEAD.POINTS.LIST HEADPT HEAD.ANGLE HEAD.LENGTH (COND
    (TAILPT (DIFFERENCE (fetch (POSITION XCOORD) of HEADPT)
                        (fetch (POSITION XCOORD) of TAILPT)))
    (T 1))
    (COND
      (TAILPT (DIFFERENCE (fetch (POSITION YCOORD) of HEADPT)
                          (fetch (POSITION YCOORD) of TAILPT)))
      (T 0))
    HEAD.TYPE]))
```

(DRAWARROWHEADS

```
[LAMBDA (ARROWSPECS ARROWPTS WINDOW SIZE OPERATION) (* rrb " 6-May-86 18:19")
```

(* draws the arrowhead from the specs in ARROWSPECS and the points in ARROWPTS)

(* PTS may be NIL in the case where an arrowhead was added to a closed knot element that only has one point.)

```
(bind ARROWTYPE for SPEC in ARROWSPECS as PTS in ARROWPTS when (AND SPEC PTS)
  do (SELECTQ (SETQ ARROWTYPE (fetch (ARROWHEAD ARROWTYPE) of SPEC))
    (CURVE (* curve type. ARROWPTS format is
            (headPt (side1pt1 side1pt2) (side2pt1 side2pt2)))
          (DRAWCURVE (CONS (CAR PTS)
                          (CADR PTS))
                     NIL SIZE NIL WINDOW)
          (DRAWCURVE (CONS (CAR PTS)
                          (CADDR PTS))
                     NIL SIZE NIL WINDOW))
    (SOLID (* solid triangle)
          (COND
            ((IMAGESTREAMTYPEP WINDOW 'PRESS) (* PRESS doesn't implement filled areas.)
             (\SK.DRAW.TRIANGLE.ARROWHEAD PTS SIZE WINDOW T))
            (T (COND
                 ((OR (WINDOWP WINDOW)
                     (IMAGESTREAMTYPEP WINDOW 'DISPLAY))
                  (* DISPLAY code doesn't fill out the entire area.)
                  (\SK.DRAW.TRIANGLE.ARROWHEAD PTS SIZE WINDOW T)))
                (FILLPOLYGON PTS BLACKSHADE WINDOW))))
    (LINE (* straight line form of arrow.)
          (\SK.DRAW.TRIANGLE.ARROWHEAD PTS SIZE WINDOW NIL))
    (CLOSEDLINE (* triangle form of arrow.)
                 (\SK.DRAW.TRIANGLE.ARROWHEAD PTS SIZE WINDOW T))
    NIL]))
```

(\SK.DRAW.TRIANGLE.ARROWHEAD

[LAMBDA (ARROWHEADPTS BRUSH STREAM CLOSED?)

(* rrb " 6-May-86 18:15")
(* draws a triangle form arrowhead.)
(* could be replaced with a drawpolygon call if this were implemented in everybody.)

(COND
 ((OR [NOT (OR (WINDOWP STREAM)
 (IMAGESTREAMTYPEP STREAM 'DISPLAY)]
 (EQ (**SK.BRUSH.SIZE** BRUSH)
 1))

(* call draw line instead because draw curve is off by 1 and makes arrowheads look bad.)

(DRAWBETWEEN (CAR ARROWHEADPTS)
 (CADR ARROWHEADPTS)
 (**SK.BRUSH.SIZE** BRUSH)
 NIL STREAM)
(DRAWBETWEEN (CAR ARROWHEADPTS)
 (CADDR ARROWHEADPTS)
 (**SK.BRUSH.SIZE** BRUSH)
 NIL STREAM)
(AND CLOSED? (DRAWBETWEEN (CADR ARROWHEADPTS)
 (CADDR ARROWHEADPTS)
 (**SK.BRUSH.SIZE** BRUSH)
 NIL STREAM)))

(* use curve drawing because the end pts of the lines look better)

(T
 (DRAWCURVE (LIST (CAR ARROWHEADPTS)
 (CADR ARROWHEADPTS))
 NIL BRUSH NIL STREAM)
 (DRAWCURVE (LIST (CAR ARROWHEADPTS)
 (CADDR ARROWHEADPTS))
 NIL BRUSH NIL STREAM)
 (AND CLOSED? (DRAWCURVE (LIST (CADR ARROWHEADPTS)
 (CADDR ARROWHEADPTS))
 NIL BRUSH NIL STREAM])

(\SK.ENDPT.OF.ARROW

[LAMBDA (LOCALARROWHEADPTS)

(* rrb " 2-May-86 10:58")

(* returns the point inside an arrowhead that the last point of the line should hit.)

(PROG ((LASTPT (CADDR LOCALARROWHEADPTS))
 (RETURN (**create** POSITION
 XCOORD _ (QUOTIENT (PLUS (**fetch** (POSITION XCOORD) **of** (CAR LOCALARROWHEADPTS))
 (TIMES (QUOTIENT (PLUS (**fetch** (POSITION XCOORD)
 of (CADR LOCALARROWHEADPTS))
 (**fetch** (POSITION XCOORD) **of** LASTPT))
 2)
 3))
 4)
 YCOORD _ (QUOTIENT (PLUS (**fetch** (POSITION YCOORD) **of** (CAR LOCALARROWHEADPTS))
 (TIMES (QUOTIENT (PLUS (**fetch** (POSITION YCOORD)
 of (CADR LOCALARROWHEADPTS))
 (**fetch** (POSITION YCOORD) **of** LASTPT))
 2)
 3))
 4])

(\SK.ADJUST.FOR.ARROWHEADS

[LAMBDA (LOCALKNOTS LOCALARROWPTSLSST GARROWHEADSPECS STREAM)

(* rrb " 6-May-86 17:43")

(* returns a list of the knots that LOCALKNOTS should really be drawn through.
This is different when the arrowhead is solid because wide lines will make the arrow look funny if they are run out all the way to the end.)

(COND
 ((IMAGESTREAMTYPEP STREAM 'PRESS) (* PRESS doesn't implement filled areas.)
 LOCALKNOTS)
 (T (PROG (LASTFIXED X)
 (SETQ LASTFIXED (COND
 ((AND (CADR LOCALARROWPTSLSST)
 (EQ (**fetch** (ARROWHEAD ARROWTYPE) **of** (CADR GARROWHEADSPECS))
 'SOLID))
 (RPLACA (LAST (SETQ X (APPEND LOCALKNOTS)))
 (**SK.ENDPT.OF.ARROW** (CADR LOCALARROWPTSLSST)))
 X)
 (T LOCALKNOTS)))
 (RETURN (COND
 ((AND (CAR LOCALARROWPTSLSST)
 (EQ (**fetch** (ARROWHEAD ARROWTYPE) **of** (CAR GARROWHEADSPECS))
 'SOLID))
 (CONS (**SK.ENDPT.OF.ARROW** (CAR LOCALARROWPTSLSST))
 (CDR LASTFIXED)))
 (T LASTFIXED]
(PROG (LASTFIXED X)

```
(SETQ LASTFIXED (COND
  ((AND (CADR LOCALARROWPTSLST)
    (EQ (fetch (ARROWHEAD ARROWTYPE) of (CADR GARROWHEADSPECS))
      'SOLID))
    (RPLACA (LAST (SETQ X (APPEND LOCALKNOTS)))
      (\SK.ENDPT.OF.ARROW (CADR LOCALARROWPTSLST)))
    X)
  (T LOCALKNOTS)))
(RETURN (COND
  ((AND (CAR LOCALARROWPTSLST)
    (EQ (fetch (ARROWHEAD ARROWTYPE) of (CAR GARROWHEADSPECS))
      'SOLID))
    (CONS (\SK.ENDPT.OF.ARROW (CAR LOCALARROWPTSLST))
      (CDR LASTFIXED)))
  (T LASTFIXED]))
```

(SK.SET.ARROWHEAD.LENGTH

```
[LAMBDA (W)
  (* rrb "14-May-86 19:27")
  (* sets the size of the default arrowhead.)
  (PROG [NEWSIZE (NOWARROWHEAD (fetch (SKETCHCONTEXT SKETCHARROWHEAD) of (WINDOWPROP W 'SKETCHCONTEXT)
    (SETQ NEWSIZE (RNUMBER (CONCAT "New arrowhead size in screen pts. Current arrowhead size is "
      (MKSTRING (fetch (ARROWHEAD ARROWLENGTH) of NOWARROWHEAD)))
      NIL NIL NIL T T T))
  (RETURN (COND
    ((OR (NULL NEWSIZE)
      (IGEQ 0 NEWSIZE))
      NIL)
    (T (replace (SKETCHCONTEXT SKETCHARROWHEAD) of (WINDOWPROP W 'SKETCHCONTEXT)
      with (create ARROWHEAD using NOWARROWHEAD ARROWLENGTH _ NEWSIZE]))
```

(SK.SET.ARROWHEAD.ANGLE

```
[LAMBDA (W)
  (* rrb "14-May-86 19:27")
  (* sets the angle of the default arrowhead.)
  (PROG [NEWSIZE (NOWARROWHEAD (fetch (SKETCHCONTEXT SKETCHARROWHEAD) of (WINDOWPROP W 'SKETCHCONTEXT)
    (SETQ NEWSIZE (RNUMBER (CONCAT "New head angle in degrees. Current arrowhead angle is "
      (MKSTRING (fetch (ARROWHEAD ARROWANGLE) of NOWARROWHEAD)))
      NIL NIL NIL T T T))
  (RETURN (COND
    ((OR (NULL NEWSIZE)
      (IGEQ 0 NEWSIZE))
      NIL)
    (T (replace (SKETCHCONTEXT SKETCHARROWHEAD) of (WINDOWPROP W 'SKETCHCONTEXT)
      with (create ARROWHEAD using NOWARROWHEAD ARROWANGLE _ NEWSIZE]))
```

(SK.SET.ARROWHEAD.TYPE

```
[LAMBDA (W VALUE)
  (* rrb "19-Mar-86 10:25")
  (* Sets the type of the default arrowhead)
  (PROG ([NEWSHAPE (COND
    ((MEMB VALUE ' (LINE CURVE CLOSEDLINE SOLID))
      VALUE)
    (T (\CURSOR.IN.MIDDLE.MENU (create MENU
      TITLE _ "Choose style"
      ITEMS _ (LIST (LIST VSHAPE.ARROWHEAD.BITMAP
        ''LINE "arrowhead consists of two
        line segments.")
        (LIST CURVEDV.ARROWHEAD.BITMAP
        ''CURVE "arrowhead has curved side
        lines.")
        (LIST TRIANGLE.ARROWHEAD.BITMAP
        ''CLOSEDLINE "arrowhead consists
        of a triangle.")
        (LIST SOLIDTRIANGLE.ARROWHEAD.BITMAP
        ''SOLID "makes a solid triangular
        arrowhead."))
      ITEMHEIGHT _ (PLUS 2 (BITMAPHEIGHT
        VSHAPE.ARROWHEAD.BITMAP))
      CENTERFLG _ T]
      SKETCHCONTEXT)
    (RETURN (AND NEWSHAPE (replace (SKETCHCONTEXT SKETCHARROWHEAD) of (SETQ SKETCHCONTEXT
      (WINDOWPROP W 'SKETCHCONTEXT))
      with (create ARROWHEAD using (fetch (SKETCHCONTEXT SKETCHARROWHEAD) of
        SKETCHCONTEXT
        )
        ARROWTYPE _ NEWSHAPE]))
```

(SK.SET.LINE.ARROWHEAD

```
[LAMBDA (W NEWVALUE)
  (* rrb " 6-Nov-85 09:50")
  (* sets whether or not the default line has an arrowhead.)
  (PROG [(ARROWHEADEND (COND
    ((MEMB NEWVALUE ' (FIRST LAST BOTH NEITHER LEFT RIGHT))
      NEWVALUE)
    (T (\CURSOR.IN.MIDDLE.MENU (create MENU
      TITLE _ "Which end?"
```

```

ITEMS _ '( (First 'FIRST "An arrowhead will be at
           the first point of any new lines
           or curves.")
          (Last 'LAST "An arrowhead will be at the
           last point of any new lines or
           curves.")
          (Both 'BOTH "Arrowheads will be both
           ends of any new lines or curves.")
          (Neither 'NEITHER "New lines will not
           have any arrowheads.")
          (|Left      | 'LEFT "An arrowhead will be
           at the leftmost end of any new
           lines or curves.")
          (|      Right| 'RIGHT "An arrowhead will
           be at the rightmost end of any
           new lines or curves.")

```

```

          CENTERFLG _ T]
(RETURN (AND ARROWHEADEND (replace (SKETCHCONTEXT SKETCHUSEARROWHEAD) of (WINDOWPROP W 'SKETCHCONTEXT)
with ARROWHEADEND]))

```

(SK.UPDATE.ARROWHEAD.FORMAT

[LAMBDA (GELT)

(* rrb "25-Apr-85 10:28")

(* makes sure that the element GELT is in new format.)

(* the fields of this are first arrowhead, last arrowhead and new format indicator.
The old format had left arrowhead and right arrowhead.)

```

(PROG ((INDGARROWELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
      NOWARROWS)
      (SELECTQ (fetch (INDIVIDUALGLOBALPART GTYPE) of INDGARROWELT)
              (OPENCURVE [AND (SETQ NOWARROWS (fetch (OPENCURVE CURVEARROWHEADS) of INDGARROWELT))
                              (NULL (CDDR NOWARROWS))
                              (replace (OPENCURVE CURVEARROWHEADS) of INDGARROWELT
                                      with (COND
                                           ((LEFT.MOST.IS.BEGINP (fetch LATLONKNOTS of INDGARROWELT))
                                            (LIST (CAR NOWARROWS)
                                                (CADR NOWARROWS)
                                                T))
                                           (T (LIST (CADR NOWARROWS)
                                                  (CAR NOWARROWS)
                                                  T))
                                           (WIRE [AND (SETQ NOWARROWS (fetch (WIRE WIREARROWHEADS) of INDGARROWELT))
                                                    (NULL (CDDR NOWARROWS))
                                                    (replace (WIRE WIREARROWHEADS) of INDGARROWELT with (COND
                                                                 ((LEFT.MOST.IS.BEGINP (fetch
                                                                                                     LATLONKNOTS
                                                                                                     of
                                                                                                     INDGARROWELT
                                                                                                     ))
                                                                 (LIST (CAR NOWARROWS)
                                                                 (CADR NOWARROWS)
                                                                 T))
                                                                 (T (LIST (CADR NOWARROWS)
                                                                 (CAR NOWARROWS)
                                                                 T))
                                                                 NIL)
                                                                 (RETURN GELT]))

```

(SK.SET.LINE.LENGTH.MODE

[LAMBDA (W VAL?)

(* rrb " 6-Nov-85 09:51")

(* sets whether the lines drawn with the middle button connect e.g the next segment begins where the last one left off or whether it takes two clicks to get a single segment line.)

```

(PROG [(LINEMODE (COND
                ((MEMBER VAL? '(YES NO))
                 VAL?)
                (T (\CURSOR.IN.MIDDLE.MENU (create MENU
                                             TITLE _ "Connect middle button lines?"
                                             ITEMS _ '((Yes 'YES "The lines drawn with the middle
                                             button will pick up where the last one
                                             left off.")
                                             (No 'NO "Sets the default so that two middle
                                             clicks make a line."))
                                             CENTERFLG _ T]
                (RETURN (AND LINEMODE (replace (SKETCHCONTEXT SKETCHLINEMODE) of (WINDOWPROP W 'SKETCHCONTEXT)
with (EQ LINEMODE 'NO))

```

(DEFINEQ

(SK.INSURE.ARROWHEADS

[LAMBDA (ARROWHEADSPECS)

; Edited 8-Jan-87 19:46 by rrb

(* makes sure ARROWHEADSPECS is a legal list of two arrowhead specifications.)


```

% " @ H @ @ B @ @ @ % "
% " @ H @ @ L @ @ @ % "
% " @ H @ C @ @ @ @ % "
% " @ H @ L @ @ @ @ % "
% " @ H C @ @ @ @ @ % "
% " @ H L @ @ @ @ @ % "
% " @ K @ @ @ @ @ @ % "
% " @ L @ @ @ @ @ @ % " } { (READBITMAP) (24 18
% " @ @ @ @ @ @ @ @ % "
% " @ L @ @ @ @ @ @ % "
% " @ O @ @ @ @ @ @ % "
% " @ O L @ @ @ @ @ % "
% " @ O O @ @ @ @ @ % "
% " @ O O L @ @ @ @ % "
% " @ O O O @ @ @ @ % "
% " @ O O O L @ @ @ % "
% " @ O O O N @ @ @ @ % "
% " O O O O O @ @ @ @ % "
% " @ O O O N @ @ @ @ % "
% " @ O O O L @ @ @ @ % "
% " @ O O O @ @ @ @ @ % "
% " @ O L @ @ @ @ @ % "
% " @ O @ @ @ @ @ @ % "
% " @ L @ @ @ @ @ @ % " } { (READBITMAP) (24 18
% " @ @ @ @ @ @ @ @ % "
% " @ A @ @ @ @ @ @ % "
% " @ H @ @ @ @ @ @ % "
% " @ D @ @ @ @ @ @ % "
% " @ C @ @ @ @ @ @ % "
% " @ @ N @ @ @ @ @ % "
% " @ @ @ A L @ @ @ @ % "
% " @ @ @ C H @ @ @ @ % "
% " O O O O O @ @ @ @ % "
% " @ @ @ C H @ @ @ @ % "
% " @ @ @ A L @ @ @ @ % "
% " @ @ @ N @ @ @ @ @ % "
% " @ C @ @ @ @ @ @ % "
% " @ D @ @ @ @ @ @ % "
% " @ H @ @ @ @ @ @ % "
% " @ A @ @ @ @ @ @ % "
% " @ @ @ @ @ @ @ @ % " } )
" )

```

```

(READVARS-FROM-STRINGS ' (WIREICON CLOSEDWIREICON)
" { (READBITMAP) (20 12
% " D @ @ @ @ @ @ @ % "
% " L @ @ @ @ @ @ @ % "
% " A H @ @ @ @ @ @ % "
% " C @ G O L @ @ @ @ % "
% " F @ O O L @ @ @ @ % "
% " L @ L @ L @ @ @ @ % "
% " L A H @ L @ @ @ @ % "
% " F A H A H @ @ @ @ % "
% " C C @ C @ @ @ @ @ % "
% " A K @ C @ @ @ @ @ % "
% " @ N @ F @ @ @ @ @ % "
% " @ F @ L @ @ @ @ @ % " } { (READBITMAP) (20 12
% " @ G @ G N @ @ @ @ @ % "
% " @ O H O N @ @ @ @ @ % "
% " A M M L N @ @ @ @ @ % "
% " C H O I L @ @ @ @ @ % "
% " G @ G C H @ @ @ @ @ % "
% " N @ @ G @ @ @ @ @ % "
% " G @ @ N @ @ @ @ @ % "
% " C H @ G H @ @ @ @ @ % "
% " A L @ @ A N @ @ @ @ @ % "
% " @ O @ @ F @ @ @ @ @ % "
% " @ G O O N @ @ @ @ @ % "
% " @ C O O N @ @ @ @ @ % " } )
" )

```

```

(RPAQ? SK.ARROWHEAD.ANGLE.INCREMENT 5)
(RPAQ? SK.ARROWHEAD.LENGTH.INCREMENT 2)
(ADDTOVAR SK.ARROWHEAD.TYPES LINE CLOSEDLINE CURVE SOLID)
(RPAQ? SK.DEFAULT.ARROW.LENGTH 8)
(RPAQ? SK.DEFAULT.ARROW.TYPE 'CURVE)
(RPAQ? SK.DEFAULT.ARROW.ANGLE 18.0)
(DECLARE%: DOEVAL@COMPILE DONTCOPY

```


(GLOBALVARS SK.DEFAULT.ARROW.LENGTH SK.DEFAULT.ARROW.TYPE SK.DEFAULT.ARROW.ANGLE SK.ARROWHEAD.TYPES)
)

(RPAQ? SK.ARROW.END.MENU)

(RPAQ? SK.ARROW.EDIT.MENU)

:: stuff to support the text element type.

(DEFINEQ

(SKETCH.CREATE.TEXT

[LAMBDA (STRING POSITION FONT JUSTIFICATION COLOR SCALE) (* rrb " 4-Dec-85 20:51")
(* creates a text element.)

(CREATE.TEXT.ELEMENT (SK.INSURE.TEXT STRING)
(SK.INSURE.POSITION POSITION)
(OR (NUMBERP SCALE)
1.0)
(SK.INSURE.STYLE JUSTIFICATION SK.DEFAULT.TEXT.ALIGNMENT)
(SK.INSURE.FONT FONT)
(SK.INSURE.COLOR COLOR])

(TEXT.CHANGEFN

[LAMBDA (SCRNELTS SKW HOW) (* rrb "10-Jan-85 16:58")
(* the users has selected SCRNELT to be changed)
(for ELTWITHTEXT inside SCRNELTS collect (SK.CHANGE.TEXT ELTWITHTEXT HOW SKW])

(TEXT.READCHANGEFN

[LAMBDA (SKW SCRNELTS INTEXTBOXFLG) (* rrb " 3-Oct-86 15:26")

(* the users has selected SCRNELT to be changed this function reads a specification of how the text elements should change.)

(PROG ((COMMAND (\CURSOR.IN.MIDDLE.MENU (create MENU
TITLE _ "Change text how?"
ITEMS _ [APPEND (COND
[(SKETCHINCOLORP)
'(("Color" 'BRUSHCOLOR "changes the color
of the text")
(T NIL))
[COND
(SCREENELEMENTP SCRNELTS)
NIL
(T '("look same" 'SAME "makes the font
characteristics the same as
those of the first selected
piece of text.")
[COND
(AND (NULL INTEXTBOXFLG)
(SKETCH.ELEMENT.TYEP 'TEXTBOX))
'("box the text" 'BOX "makes the selected
text into boxed text.")
[COND
(DATATYPEP 'LOOKEDSTRING)
'(("Fancy format" 'LOOKEDSTRING
"changes to a form that can have
complete character formatting.")
'(("different font" 'NEWFONT "prompts for a
new font family.")
("smaller font" 'SMALLER "Make the text
smaller")
("LARGER FONT" 'LARGER "Make the text font
larger.")
("set font size" 'SETSIZE "makes all fonts a
prompted for size")
("set family & size" 'FAMILY&SIZE "allows
changing both the family and the
size")
("BOLD" 'BOLD "makes the text bold.")
("unbold" 'UNBOLD "removes the bold look of
text.")
("italic" 'ITALIC "makes the text italic.")
("unitalic" 'UNITALIC "removes the italic
look of text.")
("center justify" 'CENTER "centers the text
about its location")
("left justify " 'LEFT "left justifies
the text to its location")
(" right justify" 'RIGHT "right justifies
the text to its location.")
("top justify" 'TOP "makes the location be
the top of the text.")
("bottom justify" 'BOTTOM "makes the
location be the bottom of the text.")

("middle justify" 'MIDDLE "makes the control point specify the mid-height of the text.")
("baseline justify" 'BASELINE "makes the control popint specify the baseline of the text.")

```
CENTERFLG _ T))
FIRSTTEXTTEL VAL)
(OR COMMAND (RETURN))
(SKED.CLEAR.SELECTION SKW)
[SETQ VAL (SELECTQ COMMAND
  (SETSIZE (* read the new font size once)
    (\SK.READ.FONT.SIZE1 SCRNELTS SKW))
  (FAMILY&SIZE (* gets both a font size and a family)
    (AND (SETQ VAL (\SK.READFONTFAMILY SKW "New font family?")
      (\SK.READ.FONT.SIZE1 SCRNELTS SKW VAL)))
  (SAME (* set the text characteristics from the first selection.)
    (AND (SETQ FIRSTTEXTTEL (for SCRNELT inside SCRNELTS
      when (MEMB (fetch (SCREENELT GTYPE) of SCRNELT)
        '(TEXTBOX TEXT))
      do (RETURN SCRNELT)))
      (fetch (SCREENELT GLOBALPART) of FIRSTTEXTTEL)))
  (NEWFONT (* get a new font family)
    (\SK.READFONTFAMILY SKW "New font family?"))
  (BRUSHCOLOR [READ.COLOR.CHANGE "Change text color how?" NIL
    (fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
      (fetch (SCREENELT GLOBALPART)
        of (CAR SCRNELTS))
      'BRUSH])
  (RETURN (LIST 'TEXT COMMAND])
(RETURN (AND VAL (LIST COMMAND VAL])
```

(\SK.READ.FONT.SIZE1

[LAMBDA (SELECTEDELTS SKETCHW NEWFAMILY) (* rrb "14-Jul-86 13:43")

(* reads a font size from the user. If NEWFONT is NIL, use the one of the first selected element.)

```
(PROG (FIRSTTEXTTEL NEWSIZE NOWFONT NEWFONT)
  (OR (SETQ FIRSTTEXTTEL (for SCRNELT inside SELECTEDELTS when (MEMB (fetch (SCREENELT GTYPE) of SCRNELT)
    '(TEXTBOX TEXT))
    do (RETURN SCRNELT)))
  (RETURN))
  (SETQ FIRSTTEXTTEL (fetch (SCREENELT INDIVIDUALGLOBALPART) of FIRSTTEXTTEL))
  (SETQ NOWFONT (fetch (TEXT FONT) of FIRSTTEXTTEL))
  (STATUSPRINT SKETCHW "Size of " (COND
    ((SCREENELEMENTP SELECTEDELTS)
      "text")
    (T "first selected text")))
  " is "
  (FONTPROP NOWFONT 'SIZE))
  (SETQ NEWSIZE (\SK.READFONTSIZE NIL [OR NEWFAMILY (SETQ NEWFAMILY (FONTPROP NOWFONT 'FAMILY)
    SKETCHW))
  (RETURN (COND
    ((NULL NEWSIZE)
      (CLOSE.PROMPT.WINDOW SKETCHW)
      NIL)
    ((NULL (SETQ NEWFONT (FONTCREATE NEWFAMILY NEWSIZE (FONTPROP NOWFONT 'FACE)
      NIL NIL T)))
      (STATUSPRINT SKETCHW NEWFAMILY NEWSIZE " not found.")
      NIL)
    (T (CLOSE.PROMPT.WINDOW SKETCHW)
      (SK.FONTNAMELIST NEWFONT]))
```

(SK.TEXT.ELT.WITH.SAME.FIELDS

[LAMBDA (NEWONE ORGONE) (* rrb "18-Jul-85 14:16")

(* returns an element of the type of ORGONE whose text fields are the same as NEWONE.)

```
(SELECTQ (fetch (INDIVIDUALGLOBALPART GTYPE) of ORGONE)
  (TEXT (create TEXT
    LOCATIONLATLON _ (fetch (TEXT LOCATIONLATLON) of ORGONE)
    LISTOFCHARACTERS _ (fetch (TEXT LISTOFCHARACTERS) of ORGONE)
    INITIALSCALE _ (fetch (TEXT INITIALSCALE) of NEWONE)
    TEXTSTYLE _ (fetch (TEXT TEXTSTYLE) of NEWONE)
    FONT _ (fetch (TEXT FONT) of NEWONE)
    LISTOFREGIONS _ (fetch (TEXT LISTOFREGIONS) of NEWONE)
    TEXTCOLOR _ (fetch (TEXT TEXTCOLOR) of NEWONE)))
  (TEXTBOX (create TEXTBOX
    TEXTBOXREGION _ (fetch (TEXTBOX TEXTBOXREGION) of ORGONE)
    LISTOFCHARACTERS _ (fetch (TEXT LISTOFCHARACTERS) of ORGONE)
    INITIALSCALE _ (fetch (TEXT INITIALSCALE) of NEWONE)
    TEXTSTYLE _ (fetch (TEXT TEXTSTYLE) of NEWONE)
    FONT _ (fetch (TEXT FONT) of NEWONE)
    LISTOFREGIONS _ (fetch (TEXT LISTOFREGIONS) of NEWONE)
    TEXTCOLOR _ (fetch (TEXT TEXTCOLOR) of NEWONE)
```

```
TEXTBOXBRUSH _ (fetch (TEXTBOX TEXTBOXBRUSH) of ORGONE)))
NIL])
```

(SK.READFONTFAMILY

```
[LAMBDA (SKW TITLE)
(* rrb "21-Nov-85 11:28"
(* reads a font family name.)
(PROG ([KNOWNFAMILIES (UNION (for X in \FONTSONFILE collect (CAR X))
(for X in \FONTSINCORE collect (CAR X))
FAMILY)
(COND
((AND KNOWNFAMILIES (NEQ (SETQ FAMILY (\CURSOR.IN.MIDDLE.MENU
(create MENU
ITEMS _ (APPEND '("other" 'OTHER "prompts for a
family not on the menu."))
KNOWNFAMILIES)
TITLE _ (OR TITLE "Choose font")
CENTERFLG _ T)))
'OTHER))
(RETURN FAMILY))
(T
(* grab the tty.)
(TTY.PROCESS (THIS.PROCESS))
(RETURN (CAR (ERSETQ (MKATOM (U-CASE (PROMPTFORWARD "New family: " NIL NIL (GETPROMPTWINDOW
SKW))
```

(CLOSE.PROMPT.WINDOW

```
[LAMBDA (WINDOW)
(* rrb "28-Oct-84 14:14"
(* gets rid of the prompt window.)
(PROG (PRMPTWIN)
(RETURN (COND
((SETQ PRMPTWIN (GETPROMPTWINDOW WINDOW NIL NIL T))
(DETACHWINDOW PRMPTWIN)
(CLOSEW PRMPTWIN])
```

(TEXT.DRAWFN

```
[LAMBDA (TEXTELT WINDOW)
(* rrb " 9-Aug-85 09:38"
(* shows a text element)
(TEXT.DRAWFN1 (fetch (LOCALTEXT LOCALLISTOFCHARACTERS) of (fetch (SCREENELT LOCALPART) of TEXTELT))
(fetch (LOCALTEXT LINEREGIONS) of (fetch (SCREENELT LOCALPART) of TEXTELT))
(fetch (LOCALTEXT LOCALFONT) of (fetch (SCREENELT LOCALPART) of TEXTELT))
(fetch (TEXT TEXTCOLOR) of (fetch (SCREENELT INDIVIDUALGLOBALPART) of TEXTELT))
WINDOW])
```

(TEXT.DRAWFN1

```
[LAMBDA (STRS REGIONS FONT COLOR SKWINDOW OPERATION)
; Edited 3-Oct-89 13:48 by rmk:
; Edited 3-Oct-89 13:47 by rmk:
(* rrb " 3-Mar-86 21:37")
;; draws the image of a list of string in their local regions on a sketch window. It is broken out as a subfunction so that it can be called by the
;; update function also.
(COND
((AND COLOR (SKETCHINCOLORP))
(DSPCOLOR COLOR SKWINDOW)))
(PROG (DESCENT OLDFONT)
(COND
(NULL FONT) ; text is too small or too large to be at this scale.
(RETURN)
(FONTP FONT) ; font was found.
(SETQ OLDFONT (DSPFONT FONT SKWINDOW)) ; Install font, then refetch it from window/stream, in case there
; was device coercion, so descent will be right.
(SETQ DESCENT (FONTPROP (DSPFONT NIL SKWINDOW)
'DESCENT))
(DSPOPERATION (PROG1 (DSPOPERATION OPERATION SKWINDOW)
(RESETFORM (SETTERMTABLE SKETCH.TERMTABLE)
(for REGION in REGIONS as CHARS in STRS
do (MOVETO (fetch (REGION LEFT) of REGION)
(PLUS (fetch (REGION BOTTOM) of REGION)
DESCENT)
SKWINDOW)
(PRIN3 CHARS SKWINDOW) )))
SKWINDOW) ; return to original font so that messages come out ok.
(DSPFONT OLDFONT SKWINDOW))
(T ; if no font, just gray in regions
```

;;; This code was left by RRB on the theory that hardcopy can't support bitblt, which I think is wrong--RMK. (COND ((EQ (IMAGESTREAMTYPE
;;; SKWINDOW) 'DISPLAY) (for REGION in REGIONS do (BITBLT NIL NIL NIL SKWINDOW (fetch LEFT of REGION) (fetch BOTTOM of REGION)
;;; (fetch WIDTH of REGION) (IQUOTIENT (ADD1 (fetch HEIGHT of REGION)) 2) 'TEXTURE OPERATION INDICATE.TEXT SHADE))) (T ; hardcopy
;;; can't support bitblt, draw a line instead. (bind MIDHGHT for REGION in REGIONS do (DRAWLINE (fetch LEFT of REGION) (SETQ MIDHGHT (PLUS
;;; (fetch BOTTOM of REGION) (IQUOTIENT (ADD1 (fetch HEIGHT of REGION)) 2))) (fetch RIGHT of REGION) MIDHGHT (fetch HEIGHT of REGION)
;;; OPERATION SKWINDOW))))

```
(for REGION in REGIONS do (BITBLT NIL NIL NIL SKWINDOW (fetch LEFT of REGION)
(fetch BOTTOM of REGION)
(fetch WIDTH of REGION)
```

(IQUOTIENT (ADD1 (fetch HEIGHT of REGION)
2)
'TEXTURE OPERATION INDICATE.TEXT.SHADE])

(TEXT.INSIDFN

[LAMBDA (GTEXT WREG) (* rrb "5-AUG-83 16:54")
(* determines if the global text element is inside of WREG.)
(for GREG in (fetch (TEXT LISTOFREGIONS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXT))
when (REGIONSINTERSECTP GREG WREG) do (RETURN T])

(TEXT.EXPANDFN

[LAMBDA (GTEXTPART SCALE STREAM) (* rrb "19-Mar-86 15:59")
(* creates a local text screen element from a global text
element.)
(PROG ((GTEXT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTPART))
TEXTPOS LOCALFONT STYLE LINEREGIONS)
[COND
((NLISTP (SETQ STYLE (fetch (TEXT TEXTSTYLE) of GTEXT)))
(* old format had horizontal positioning only, now has vertical
too. Fill in old default.)
(replace (TEXT TEXTSTYLE) of GTEXT with (SETQ STYLE ' (CENTER CENTER)
(SETQ LOCALFONT (SK.CHOOSE.TEXT.FONT GTEXT SCALE STREAM))
[SETQ LINEREGIONS (SK.TEXT.LINE.REGIONS (fetch (TEXT LISTOFCHARACTERS) of GTEXT)
(SETQ TEXTPOS (SK.SCALE.POSITION.INTO.VIEWER (fetch (TEXT LOCATIONLATLON)
of GTEXT)
SCALE))
(fetch (TEXT LISTOFREGIONS) of GTEXT)
LOCALFONT STYLE SCALE (COND
((STREAMP STREAM))
(T (WINDOWPROP STREAM 'DSP]
(RETURN (create SCREENELT
LOCALPART _ (create LOCALTEXT
DISPLAYPOSITION _ TEXTPOS
LINEREGIONS _ LINEREGIONS
LOCALFONT _ LOCALFONT
LOCALLISTOFCHARACTERS _ (APPEND (fetch (TEXT LISTOFCHARACTERS)
of GTEXT))
GLOBALPART _ GTEXTPART])

(SK.TEXT.LINE.REGIONS

[LAMBDA (LISTOFTEXT TEXTPOS GREGIONS LOCALFONT STYLE SCALE IMAGESTREAM) (* rrb "19-Mar-86 15:44")

(* calculates the list of regions that each line of text in LISTOFTEXT will occupy.
Used by both TEXT.EXPANDFN and TEXTBOX.EXPANDFN. Captures those things which are common to the two
elements.)

(COND
[(FONTP LOCALFONT)
(LTEXT.LINE.REGIONS LISTOFTEXT TEXTPOS (COND
((IMAGESTREAMTYPEPEP IMAGESTREAM 'HARDCOPY)

(* actually make the font be the font of the stream so that the stream can be passed to STRINGWIDTH to get hardcopy
characteristics.)

(DSPFONT LOCALFONT IMAGESTREAM)
IMAGESTREAM)
(T LOCALFONT))

STYLE
(FIXR (TIMES (QUOTIENT (fetch (REGION HEIGHT) of (CAR GREGIONS))
SCALE)
(LENGTH LISTOFTEXT])
(T (for GREG in GREGIONS collect (CREATEREGION (FIXR (QUOTIENT (fetch (REGION LEFT) of GREG)
SCALE))
(FIXR (QUOTIENT (fetch (REGION BOTTOM) of GREG)
SCALE))
(FIXR (QUOTIENT (fetch (REGION WIDTH) of GREG)
SCALE))
1])

(TEXT.UPDATE.GLOBAL.REGIONS

[LAMBDA (GTEXTTELT NEWGPOS OLDGPOS) (* rrb "12-Sep-84 11:36")
(* updates the list of regions occupied by the text in the global
coordinate space.)
(* this is used to determine the extent of a text element in a
region.)
(PROG ((XDIFF (DIFFERENCE (fetch (POSITION XCOORD) of NEWGPOS)
(fetch (POSITION XCOORD) of OLDGPOS)))
(YDIFF (DIFFERENCE (fetch (POSITION YCOORD) of NEWGPOS)
(fetch (POSITION YCOORD) of OLDGPOS)))
(INDTEXTGELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTTELT)))
(replace (TEXT LISTOFREGIONS) of INDTEXTGELT with (for GREG in (fetch (TEXT LISTOFREGIONS) of INDTEXTGELT)
collect (REL.MOVE.REGION GREG XDIFF YDIFF)))

(RETURN GTEXTLT])

(REL.MOVE.REGION

[LAMBDA (REGION DELTAX DELTAY) (* rrb "15-AUG-83 17:30")
(* moves a region by an amount DELTAX DELTAY)
(CREATEREGION (PLUS DELTAX (fetch (REGION LEFT) of REGION))
(PLUS DELTAY (fetch (REGION BOTTOM) of REGION))
(fetch (REGION WIDTH) of REGION)
(fetch (REGION HEIGHT) of REGION])

(LTEXT.LINE.REGIONS

[LAMBDA (LINES LPOSITION STREAMORFONT STYLE TOTALHEIGHT) (* rrb " 4-Dec-85 11:51")
(* returns the regions occupied by the lines of text LINES to format them in STYLE in font FONT at position LPOSITION.)
(AND STREAMORFONT (PROG ((FONT (FONTCREATE STREAMORFONT))
(TEXTXPOS (fetch (POSITION XCOORD) of LPOSITION))
(TEXTYPOS (fetch (POSITION YCOORD) of LPOSITION))
HEIGHT HEIGHTOFLOCALTEXT LINEWIDTH)
[SETQ HEIGHT (COND
((STREAMP STREAMORFONT)
(* use the line feed height because in hardcopy streams this is
more correct.)
(MINUS (DSPLINEFEED NIL STREAMORFONT)))
(T (FONTPROP FONT 'HEIGHT)
(SETQ HEIGHTOFLOCALTEXT (TIMES HEIGHT (LENGTH LINES)))
(RETURN (for CHARS in LINES as Y
from [PLUS TEXTYPOS (SELECTQ (CADR STYLE)
(BASELINE

(* vertically center the baseline. The baseline alignment should probably be independent of the top -
bottom alignment eventually.)

(DIFFERENCE (DIFFERENCE (QUOTIENT
HEIGHTOFLOCALTEXT
2.0)
HEIGHT)
(MINUS (FONTPROP FONT
'DESCENT]))
(CENTER (DIFFERENCE (QUOTIENT HEIGHTOFLOCALTEXT
2.0)
HEIGHT))
(TOP (DIFFERENCE 1 HEIGHT))
(BOTTOM (DIFFERENCE HEIGHTOFLOCALTEXT HEIGHT))
(ERROR "illegal vertical text style" (CADR STYLE])
by (IMINUS HEIGHT)
collect [SETQ LINEWIDTH (DIFFERENCE (STRINGWIDTH CHARS STREAMORFONT)
(COND
((EQ (NTHCHARCODE CHARS -1)
(CHARCODE CR))
(CHARWIDTH (CHARCODE CR)
STREAMORFONT))
(T 0])
(CREATEREGION (SELECTQ (CAR STYLE)
(CENTER (DIFFERENCE TEXTXPOS (QUOTIENT LINEWIDTH
2.0)))
(LEFT TEXTXPOS)
(DIFFERENCE TEXTXPOS LINEWIDTH))
Y LINEWIDTH HEIGHT])

(TEXT.INPUTFN

[LAMBDA (WINDOW) (* rrb "12-Dec-84 11:44")
(* reads text and a place to put it from the user and returns a TEXTLT that represents it.
Can return NIL if the user positions it outside of the window.)

(TEXT.POSITION.AND.CREATE (READ.TEXT "Text to be added: ")
(fetch (SKETCHCONTEXT SKETCHFONT) of (WINDOWPROP WINDOW 'SKETCHCONTEXT))
WINDOW "locate the text"])

(READ.TEXT

[LAMBDA (PRMPT) (* rrb " 9-AUG-83 12:42")
(PROG ([CLOSEWFLG (COND
((EQ (TTYDISPLAYSTREAM)
\DEFAULTTTYDISPLAYSTREAM)
T)
((AND (WFROMDS (TTYDISPLAYSTREAM))
(NOT (OPENWP (TTYDISPLAYSTREAM))
LST)
(AND PRMPT (PRIN1 PRMPT T))
(SETQ LST (CONS (READ T)
(READLINE)))
(AND CLOSEWFLG (CLOSEW (TTYDISPLAYSTREAM)))

```
(RETURN (APPLY (FUNCTION CONCAT)
              (CONS (CAR LST)
                    (for WORD in (CDR LST) join (LIST '% WORD]))))
```

(TEXT.POSITION.AND.CREATE

```
[LAMBDA (TEXT FONT WINDOW PROMPTMSG) (* rrb "16-Oct-85 18:29")
```

(* gets a position for a piece of text from the user and returns a text element that represents it.
The text location is the center position of the text.)

(* later this should change the cursor to the image being placed.)

```
(PROG [P1 LOCATION DISPLAYPOSITION (SCALE (SK.INPUT.SCALE WINDOW))
      NEW.BITMAP DSP (WIDTH (STRINGWIDTH TEXT FONT))
      (HGHT (FONTHEIGHT FONT))
      (TEXTALIGNMENT (fetch (SKETCHCONTEXT SKETCHTEXTALIGNMENT) of (WINDOWPROP WINDOW 'SKETCHCONTEXT])
      (SETQ NEW.BITMAP (BITMAPCREATE WIDTH HGHT))
      (SETQ DSP (DSPCREATE NEW.BITMAP))
      (DSPFONT FONT DSP)
      (MOVETO 0 (FONTDESCENT FONT)
              DSP)
      (PRIN3 TEXT DSP)
      [SETQ P1 (GET.BITMAP.POSITION WINDOW NEW.BITMAP 'PAINT PROMPTMSG
              (IMINUS (SELECTQ (CAR TEXTALIGNMENT)
                            (CENTER (LRSH (ADD1 WIDTH)
                                         1))
                            (LEFT 0)
                            (SUB1 WIDTH)))
              (IMINUS (SELECTQ (CADR TEXTALIGNMENT)
                            (BASELINE (FONTPROP FONT 'DESCENT))
                            (CENTER (LRSH (ADD1 HGHT)
                                         1))
                            (TOP (SUB1 HGHT))
              0] (* scale range goes from 20 to 1.0 Use FONT as an initial.)
      (RETURN (AND P1 (CREATE.TEXT.ELEMENT (CONS TEXT)
                                          (SK.MAP.INPUT.PT.TO.GLOBAL P1 WINDOW)
                                          SCALE TEXTALIGNMENT FONT (fetch (BRUSH BRUSHCOLOR)
                                          of (fetch (SKETCHCONTEXT SKETCHBRUSH)
                                          of (WINDOWPROP WINDOW 'SKETCHCONTEXT]))))
```

(CREATE.TEXT.ELEMENT

```
[LAMBDA (STRLST GPOSITION SCALE JUSTIFICATION FONT COLOR) (* rrb " 4-Dec-85 20:50")
(* creates a text element for a sketch)
```

```
(SK.UPDATE.TEXT.AFTER.CHANGE (create GLOBALPART
INDIVIDUALGLOBALPART _
(create TEXT
LOCATIONLATLON _ GPOSITION
LISTOFCHARACTERS _ STRLST
INITIALSCALE _ SCALE
TEXTSTYLE _ JUSTIFICATION
FONT _ FONT
TEXTCOLOR _ COLOR])
```

(SK.UPDATE.TEXT.AFTER.CHANGE

```
[LAMBDA (GTEXTELT) (* rrb " 4-Dec-85 20:50")
```

(* updates the dependent fields in a text element that has had its text field changed.)

```
(TEXT.SET.GLOBAL.REGIONS (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTELT))
(TEXT.SET.SCALES GTEXTELT)
GTEXTELT])
```

(SK.TEXT.FROM.TEXTBOX

```
[LAMBDA (TEXTBOXELT SKW) (* rrb "30-Sep-86 18:34")
(* returns change event spec with a textbox that replaces
GTEXTBOXELT.)
```

```
(PROG ((INDTEXTBOXELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of TEXTBOXELT))
      TEXTSTYLE REGION NEWTEXTELT)
      (SETQ TEXTSTYLE (fetch (TEXTBOX TEXTSTYLE) of INDTEXTBOXELT))
      (SETQ REGION (APPLY (FUNCTION SK.UNIONREGIONS)
                          (fetch (TEXTBOX LISTOFREGIONS) of INDTEXTBOXELT)))
      (SETQ NEWTEXTELT (CREATE.TEXT.ELEMENT (ADD.EOLS (fetch (TEXTBOX LISTOFCHARACTERS) of INDTEXTBOXELT)
                                                POSITION
                                                XCOORD _
                                                (SELECTQ (CAR TEXTSTYLE)
                                                          (LEFT (fetch (REGION LEFT) of REGION))
                                                          (RIGHT (fetch (REGION RIGHT) of REGION))
                                                          (PLUS (fetch (REGION LEFT) of REGION)
                                                                (QUOTIENT (fetch (REGION WIDTH)
                                                                of REGION)
                                                                2)))
                                                YCOORD _
                                                (SELECTQ (CADR TEXTSTYLE)
                                                          (TOP (fetch (REGION TOP) of REGION))
                                                          (BOTTOM (fetch (REGION BOTTOM) of REGION))
```

(PLUS (fetch (REGION BOTTOM) of REGION)
(QUOTIENT (fetch (REGION HEIGHT)
of REGION)
2])

(fetch (TEXTBOX INITIALSCALE) of INDTEXTBOXELT)
(COND ((EQ (CADR TEXTSTYLE)
'CENTER)

(* make center into baseline because it looks better and because it is converted the other direction.)

(LIST (CAR TEXTSTYLE)
'BASELINE))
(T TEXTSTYLE))
(fetch (TEXTBOX FONT) of INDTEXTBOXELT)
(fetch (TEXTBOX TEXTCOLOR) of INDTEXTBOXELT))
(RETURN (create SKHISTORYCHANGESPEC
NEWELT _ NEWTEXTELT
OLDELTA _ TEXTBOXELT
PROPERTY _ 'HASBOX
NEWVALUE _ NEWTEXTELT
OLDVALUE _ TEXTBOXELT])

(TEXT.SET.GLOBAL.REGIONS

[LAMBDA (GTEXTTEL)

(* rrb "29-Jan-85 14:50")
(* updates the list of regions occupied by the text in the global
coordinate space.)
(* this is used to determine the extent of a text element in a
region.)

(PROG ((SCALE (fetch (TEXT INITIALSCALE) of GTEXTTEL))
(replace (TEXT LISTOFREGIONS) of GTEXTTEL with (for LREG
in [LTEXT.LINE.REGIONS
(fetch (TEXT LISTOFCHARACTERS) of GTEXTTEL)
(SK.SCALE.POSITION.INTO.VIEWER (fetch (TEXT
LOCATIONLATLON
)
of GTEXTTEL)
SCALE)
(fetch (TEXT FONT) of GTEXTTEL)
(fetch (TEXT TEXTSTYLE) of GTEXTTEL)
(IITIMES (FONTHEIGHT (fetch (TEXT FONT) of GTEXTTEL))
(LENGTH (fetch (TEXT LISTOFCHARACTERS)
of GTEXTTEL)
collect (UNSCALE.REGION LREG SCALE))))
(RETURN GTEXTTEL])

(TEXT.REGIONFN

[LAMBDA (SCRTEXTTEL)

(* rrb "2-Oct-84 16:36")
(* determines the local region covered by TEXTTEL.)

(PROG [REG (LINEREGIONS (fetch (LOCALTEXT LINEREGIONS) of (fetch (SCREENELT LOCALPART) of SCRTEXTTEL)
(RETURN (COND
((NULL LINEREGIONS)
NIL)
(T (SETQ REG (CAR LINEREGIONS))
(for LINEREG in (CDR LINEREGIONS) do (SETQ REG (UNIONREGIONS REG LINEREG)))
REG])

(TEXT.GLOBALREGIONFN

[LAMBDA (GTEXTTEL)

(* rrb "18-Oct-85 16:43")
(* returns the global region occupied by a global text element.)

(PROG [REG (LINEREGIONS (fetch (TEXT LISTOFREGIONS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTTEL)
(RETURN (COND
((NULL LINEREGIONS)
NIL)
(T (SETQ REG (CAR LINEREGIONS))
(for LINEREG in (CDR LINEREGIONS) do (SETQ REG (UNIONREGIONS REG LINEREG)))
REG])

(TEXT.TRANSLATEFN

[LAMBDA (GTEXT DELTAPOS WINDOW)

(* rrb "28-Apr-85 18:45")
(* moves a text figure element to a new position.)

(PROG ((INDTEXTTEL (COPY (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXT)))
NEWGPOS NEWTEXTTEL)
(TEXT.UPDATE.GLOBAL.REGIONS (SETQ NEWTEXTTEL (create GLOBALPART
COMMONGLOBALPART _ (APPEND (fetch (GLOBALPART
COMMONGLOBALPART
)
of GTEXT))
INDIVIDUALGLOBALPART _ INDTEXTTEL))
(SETQ NEWGPOS (PIPLUS DELTAPOS (fetch (TEXT LOCATIONLATLON) of INDTEXTTEL)))
(fetch (TEXT LOCATIONLATLON) of INDTEXTTEL))

(replace (TEXT LOCATIONLATLON) of INDTEXTELT with NEWGPOS)
(RETURN NEWTEXTELT])

(TEXT.TRANSFORMFN

[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR) (* rrb "16-Oct-85 18:30")

(* returns a copy of the global TEXT element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to transformfn. SCALEFACTOR is the amount the transformation scales by and is used to reset the size of the text.)

(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
(RETURN (CREATE.TEXT.ELEMENT (fetch (TEXT LISTOFCHARACTERS) of INDVPART)
(SK.TRANSFORM.POINT (fetch (TEXT LOCATIONLATLON) of INDVPART)
TRANSFORMFN TRANSFORMDATA)
(TIMES (fetch (TEXT INITIALSCALE) of INDVPART)
SCALEFACTOR)
(fetch (TEXT TEXTSTYLE) of INDVPART)
(fetch (TEXT FONT) of INDVPART)
(fetch (TEXT TEXTCOLOR) of INDVPART]))

(TEXT.TRANSLATEPTSFN

[LAMBDA (TEXTELT SELPTS GDELTA WINDOW) (* rrb " 5-May-85 18:05")
(* returns a text element that has its position translated.)

(* shouldn't ever happen because a text element only has one control pt and its translatefn should get used.)

(fetch (SCREENELT GLOBALPART) of TEXTELT])

(TEXT.UPDATEFN

[LAMBDA (OLDLOCALELT NEWGELT SKETCHW) (* rrb "11-Jul-86 15:51")

(* update function for text. Tries to repaint only the lines of text that have changed.)

(PROG ((NEWTEXTELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of NEWGELT))
(OLDTEXTELT (fetch (SCREENELT INDIVIDUALGLOBALPART) of OLDLOCALELT))
LOCALTEXT NEWSCREENELT)
(COND
((AND (EQUAL (fetch (TEXT FONT) of NEWTEXTELT)
(fetch (TEXT FONT) of OLDTEXTELT))
(EQUAL (fetch (TEXT TEXTSTYLE) of NEWTEXTELT)
(fetch (TEXT TEXTSTYLE) of OLDTEXTELT))
(EQUAL (fetch (TEXT LOCATIONLATLON) of NEWTEXTELT)
(fetch (TEXT LOCATIONLATLON) of OLDTEXTELT))
(EQUAL (fetch (TEXT INITIALSCALE) of NEWTEXTELT)
(fetch (TEXT INITIALSCALE) of OLDTEXTELT))
(EQUAL (LENGTH (fetch (TEXT LISTOFCHARACTERS) of NEWTEXTELT))
(LENGTH (fetch (TEXT LISTOFCHARACTERS) of OLDTEXTELT))
(EQUAL (fetch (TEXT TEXTCOLOR) of NEWTEXTELT)
(fetch (TEXT TEXTCOLOR) of OLDTEXTELT)))
(* if font, style or number of lines has changed, erase and redraw.)
(SETQ LOCALTEXT (fetch (SCREENELT LOCALPART) of OLDLOCALELT))
(SETQ NEWSCREENELT (SK.ADD.ITEM NEWGELT SKETCHW)) (* update the screen display)
[PROG ((NEWSTRS (fetch (LOCALTEXT LOCALLISTOFCHARACTERS) of (fetch (SCREENELT LOCALPART)
of NEWSCREENELT)))
(OLDSTRS (fetch (LOCALTEXT LOCALLISTOFCHARACTERS) of LOCALTEXT))
(NEWLOCALREGIONS (fetch (LOCALTEXT LINEREGIONS) of (fetch (SCREENELT LOCALPART) of
NEWSCREENELT
)))
(OLDLOCALREGIONS (fetch (LOCALTEXT LINEREGIONS) of LOCALTEXT)))
(COND
((NEQ (LENGTH NEWSTRS)
(LENGTH OLDSTRS))

(* creating the new element caused the line filling routines to change the number of lines so the partial redrawing algorithms don't work and we have to redraw the whole element. Do this by erasing the old one then drawing the new one.)

(SK.ERASE.ELT OLDLOCALELT SKETCHW)
(SK.DRAWFIGURE NEWSCREENELT SKETCHW NIL (VIEWER.SCALE SKETCHW))
(RETURN NEWSCREENELT))
LP (COND
((OR NEWSTRS OLDSTRS) (* continue until both new and old are exhausted.)
[COND
([NOT (AND (EQUAL (CAR NEWSTRS)
(CAR OLDSTRS))
(EQUAL (CAR NEWLOCALREGIONS)
(CAR OLDLOCALREGIONS))
(* this line is the different, redraw it.)
(AND OLDLOCALREGIONS (DSPFILL (CAR OLDLOCALREGIONS)
BLACKSHADE
'ERASE SKETCHW))
(AND NEWSTRS (TEXT.DRAWFN1 (LIST (CAR NEWSTRS))
(LIST (CAR NEWLOCALREGIONS))
(fetch (LOCALTEXT LOCALFONT) of LOCALTEXT))


```

(fetch (TEXT TEXTCOLOR) of OLDTEXT)
SKETCHW]
(SETQ NEWSTRS (CDR NEWSTRS))
(SETQ OLDSTRS (CDR OLDSTRS))
(SETQ NEWLOCALREGIONS (CDR NEWLOCALREGIONS))
(SETQ OLDLOCALREGIONS (CDR OLDLOCALREGIONS))
(GO LP]
(RETURN NEWSCREENELT])

```

(SK.CHANGE.TEXT

; Edited 7-Apr-87 13:41 by rrb

```

[LAMBDA (ELTWITHTEXT HOW SKW)
  (PROG ((COMMAND (CADR HOW))
        (PROPERTY 'FONT)
        NEWVALUE GINDTEXT TELT NEWGTEXT OLDVALUE OLDFACE GTYPE)
    (OR HOW (RETURN)) (* take down the caret before any change.)
    (SKED.CLEAR.SELECTION SKW)
    (COND
      ((MEMB (SETQ GTYPE (fetch (GLOBALPART GTYPE) of ELTWITHTEXT))
            '(TEXTBOX TEXT))
        (SETQ GINDTEXT TELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHTEXT))

```

(* set the old value to the old font. In the case where the thing that changes is the justification, this will get re-set)

```

(SETQ OLDVALUE (fetch (TEXT FONT) of GINDTEXT TELT))
(SETQ NEWGTEXT (SELECTQ (CAR HOW)
  (TEXT (SELECTQ COMMAND
    ((SMALLER LARGER) (* change the font)
    [COND
      [[SETQ NEWVALUE (SK.NEXTSIZEFONT COMMAND
        (LIST (FONTPROP OLDVALUE 'FAMILY)
              (FONTPROP OLDVALUE 'SIZE)
              (* if there is an appropriate size font, use it.)
        [SETQ NEWVALUE (LIST (FONTPROP NEWVALUE 'FAMILY)
                          (FONTPROP NEWVALUE 'SIZE)
                          (FONTPROP OLDVALUE 'FACE)
        (COND
          ((EQ GTYPE 'TEXT)
            (create TEXT using GINDTEXT TELT FONT _ NEWVALUE))
          (T (create TEXTBOX using GINDTEXT TELT FONT _ NEWVALUE)
            (* otherwise just scale the area some.)
          (SETQ NEWVALUE (FTIMES (SETQ OLDVALUE (fetch (TEXT
            INITIALSCALE
            )
            of GINDTEXT TELT))
            (SELECTQ COMMAND
              (LARGER 1.4)
              0.7142858)))
          (SETQ PROPERTY 'SCALE)
          (COND
            ((EQ GTYPE 'TEXT)
              (create TEXT using GINDTEXT TELT INITIALSCALE _ NEWVALUE)
              )
            (T (create TEXTBOX using GINDTEXT TELT INITIALSCALE _
              NEWVALUE]))
          ((CENTER LEFT RIGHT)
            (* change the horizontal justification)
            [SETQ NEWVALUE (LIST COMMAND (CADR (SETQ OLDVALUE
              (fetch (TEXT TEXTSTYLE)
              of GINDTEXT TELT])
            (SETQ PROPERTY 'JUSTIFICATION)
            (COND
              ((EQ GTYPE 'TEXT)
                (create TEXT using GINDTEXT TELT TEXTSTYLE _ NEWVALUE))
              (T (create TEXTBOX using GINDTEXT TELT TEXTSTYLE _ NEWVALUE))))
            ((TOP BOTTOM MIDDLE BASELINE)
              (* change the vertical justification)
              [SETQ NEWVALUE (LIST (CAR (SETQ OLDVALUE (fetch (TEXT TEXTSTYLE)
                of GINDTEXT TELT))))
              (COND
                ((EQ COMMAND 'MIDDLE)
                  'CENTER)
                (T COMMAND])
              (SETQ PROPERTY 'JUSTIFICATION)
              (COND
                ((EQ GTYPE 'TEXT)
                  (create TEXT using GINDTEXT TELT TEXTSTYLE _ NEWVALUE))
                (T (create TEXTBOX using GINDTEXT TELT TEXTSTYLE _ NEWVALUE))))
            ((BOLD UNBOLD ITALIC UNITALIC)
              (* change the face)
              (SETQ OLDFACE (FONTPROP OLDVALUE 'FACE))
              [SETQ NEWVALUE (LIST (FONTPROP OLDVALUE 'FAMILY)
                (FONTPROP OLDVALUE 'SIZE)
                (LIST (SELECTQ COMMAND
                  (BOLD 'BOLD)
                  (UNBOLD 'MEDIUM)
                  (CAR OLDFACE))

```

```

(SELECTQ COMMAND
  (ITALIC 'ITALIC)
  (UNITALIC 'REGULAR)
  (CADR OLDFACE))
(CADDR OLDFACE]
(COND
  ((EQ GTYPE 'TEXT)
   (create TEXT using GINDTEXTELT FONT _ NEWVALUE))
  (T (create TEXTBOX using GINDTEXTELT FONT _ NEWVALUE))))
(BOX [COND
  ((EQ GTYPE 'TEXT)
   (RETURN (SK.TEXTBOX.FROM.TEXT ELTWITHTEXT SKW))
   (* if it is a text element, BOX it)
  (UNBOX [COND
  ((EQ GTYPE 'TEXTBOX)
   (RETURN (SK.TEXT.FROM.TEXTBOX ELTWITHTEXT SKW))
  (LOOKEDSTRING [COND
  ((EQ GTYPE 'TEXT)
   (RETURN (SK.LOOKEDSTRING.FROM.TEXT ELTWITHTEXT SKW
   ]))
  (SHOULDNT)))
(SETSIZE (SETQ NEWVALUE COMMAND)
(COND
  [(EQ (FONTPROP NEWVALUE 'FAMILY)
   (FONTPROP OLDVALUE 'FAMILY))

```

(* if the families are the same, change them, otherwise don't as it isn't known whether or not this family has the right size.)

```

(COND
  [(EQ GTYPE 'TEXT)
   (create TEXT using GINDTEXTELT FONT _
   (LIST (FONTPROP OLDVALUE 'FAMILY)
   (FONTPROP NEWVALUE 'SIZE)
   (FONTPROP OLDVALUE 'FACE]
   (T (create TEXTBOX using GINDTEXTELT FONT _
   (LIST (FONTPROP OLDVALUE 'FAMILY)
   (FONTPROP NEWVALUE 'SIZE)
   (FONTPROP OLDVALUE 'FACE]
   (T (RETURN))))))
  (* set the font family)
(NEWFONT [SETQ NEWVALUE (LIST COMMAND (FONTPROP OLDVALUE 'SIZE)
(FONTPROP OLDVALUE 'FACE]
(COND
  ((NULL (FONTCREATE NEWVALUE NIL NIL NIL NIL T))
   (STATUSPRINT SKW " Couldn't find " (CAR NEWVALUE)
   " in size "
   (CADR NEWVALUE))
   (RETURN)))
  (EQ GTYPE 'TEXT)
  (create TEXT using GINDTEXTELT FONT _ NEWVALUE))
  (T (create TEXTBOX using GINDTEXTELT FONT _ NEWVALUE))))
  (* set the font family and size)
(FAMILY&SIZE [SETQ NEWVALUE (LIST (CAR COMMAND)
(CADR COMMAND)
(FONTPROP (fetch (TEXT FONT) of GINDTEXTELT)
'FACE]
(COND
  ((EQ GTYPE 'TEXT)
   (create TEXT using GINDTEXTELT FONT _ NEWVALUE))
  (T (create TEXTBOX using GINDTEXTELT FONT _ NEWVALUE))))
  (* set all of the font characteristics from the first selected one.)
(SAME

```

(* set the variables to cause the right things to go into the change spec event.)

```

(SETQ OLDVALUE ELTWITHTEXT)
(SETQ PROPERTY 'LOOKSAME)
(SETQ NEWVALUE (SK.TEXT.ELT.WITH.SAME.FIELDS (fetch (GLOBALPART
INDIVIDUALGLOBALPART
)
of COMMAND)
GINDTEXTELT)))
(SHOULDNT))
[SETQ NEWGTEXT (COND
  [(EQ GTYPE 'TEXT)
   (* adjust the scales at which this appears because font or scale
   may have changed.)
   (TEXT.SET.SCALES (create GLOBALPART
COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
of ELTWITHTEXT)
INDIVIDUALGLOBALPART _ (TEXT.SET.GLOBAL.REGIONS
NEWGTEXT]
  (T

```

(* scaling for text boxes depends on the box size which can't change in this function.)

```
(create GLOBALPART
```

```

COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART) of ELTWITHTEXT)
INDIVIDUALGLOBALPART _ (TEXTBOX.SET.GLOBAL.REGIONS NEWGTEXT]
(RETURN (create SKHISTORYCHANGESPEC
NEWELT _ NEWGTEXT
OLDELT _ ELTWITHTEXT
PROPERTY _ PROPERTY
NEWVALUE _ NEWVALUE
OLDVALUE _ OLDVALUE])

```

(TEXT.SET.SCALES

[LAMBDA (GTEXT)ELT]

(* rrb "12-May-85 16:29")

(* sets the min and max scale properties of a global text element.
Called after something about the text changes.)

```

(PROG [(COMMONPART (fetch (GLOBALPART COMMONGLOBALPART) of GTEXT)ELT)
(ORIGSCALE (fetch (TEXT INITIALSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXT)ELT)
(replace (COMMONGLOBALPART MINSCALE) of COMMONPART with (QUOTIENT ORIGSCALE 20.0))
(replace (COMMONGLOBALPART MAXSCALE) of COMMONPART with (FTIMES (FONTHEIGHT (fetch (TEXT FONT)
of (fetch (GLOBALPART
INDIVIDUALGLOBALPART
)
of GTEXT)ELT)))
ORIGSCALE))
(RETURN GTEXT)ELT])

```

(BREAK.AT.CARRIAGE.RETURNS

[LAMBDA (STRING)

(* rrb "16-Oct-85 18:24")

(* returns a list of strings breaking string at carriage returns.)

```

(PROG (STRLST (STR (OR (STRINGP STRING)
(MKSTRING STRING)))
(PREV 0)
(WHERE 0))
LP (COND
((SETQ WHERE (STRPOS "
" STR (ADD1 WHERE)))
[SETQ STRLST (NCONC1 STRLST (COND
((EQ WHERE (ADD1 PREV))
"")
(T (SUBSTRING STR (ADD1 PREV)
(SUB1 WHERE)
(SETQ PREV WHERE)
(GO LP)))
(RETURN (NCONC1 STRLST (OR (SUBSTRING STR (ADD1 PREV)
-1)
""])]
)
)

```

(DEFINEQ

(ADD.KNOWN.SKETCH.FONT

[LAMBDA (FAMILY WID DEVICE FONT)

; Edited 10-May-93 16:49 by rmk:
; Edited 21-Feb-89 15:06 by snow

```

;; add to the globally cached font list
(DECLARE (GLOBALVARS \KNOWN.SKETCH.FONT.SIZES))
[LET ((CACHE (ASSOC FAMILY \KNOWN.SKETCH.FONT.SIZES))
(CACHED))
(COND
[ (NULL CACHE)
(if \KNOWN.SKETCH.FONT.SIZES
then [NCONC1 \KNOWN.SKETCH.FONT.SIZES (LIST FAMILY (LIST DEVICE (CONS WID FONT)
else (SETQ \KNOWN.SKETCH.FONT.SIZES (LIST (LIST FAMILY (LIST DEVICE (CONS WID FONT)
(T (COND
((SETQ CACHED (ASSOC DEVICE CACHE))
(NCONC1 CACHED (CONS WID FONT)))
(T (NCONC1 CACHE (CONS DEVICE (CONS WID FONT)
FONT])
)
)

```

(SK.PICK.FONT

[LAMBDA (WID STRING DEVICE DISPLAYFONT)

; Edited 10-May-93 17:11 by rmk:
; Edited 22-Feb-89 07:53 by snow

```

;; returns the font in FAMILY that text should be printed in to have the text STRING fit into a region WID points wide
(DECLARE (GLOBALVARS \KNOWN.SKETCH.FONT.SIZES))
[LET [STARTFONT FONTWIDTH SCALE CACHEDFONT SIZE (FAMILY (FONTPROP DISPLAYFONT 'FAMILY)
(IF [SETQ CACHEDFONT (ASSOC WID (ASSOC DEVICE (ASSOC FAMILY \KNOWN.SKETCH.FONT.SIZES))
THEN (CDR CACHEDFONT)
ELSE (SETQ STARTFONT (FONTCOPY DISPLAYFONT 'DEVICE DEVICE))
NIL
(SETQ SCALE (FONTPROP STARTFONT 'SCALE))
(SETQ SIZE (FONTPROP STARTFONT 'SIZE))
[SETQ FONTWIDTH (COND

```

```

(SCALE ;; IF THERE IS A SCALE, YOU MUST SCALE THE WIDTH.
  (FIXR (QUOTIENT (STRINGWIDTH STRING STARTFONT)
                SCALE)))
(T (STRINGWIDTH STRING STARTFONT])
[SETQ CACHEDFONT
  (IF (IGREATERP FONTWIDTH WID)
    THEN ;; Font width was too big, try smaller fonts in decreasing size.
      [FOR FONT IN [CDR (FIND F ON [SORT (FONTSAVAILABLE FAMILY '* 'MRR 0 DEVICE T)
                                       (FUNCTION (LAMBDA (F1 F2)
                                                 (IGREATERP (CADR F1)
                                                             (CADR F2))
                                       SUCHTHAT (EQ SIZE (CADR F])
        WHEN (ILESSP [SETQ FONTWIDTH (COND
                      (SCALE ;; IF THERE IS A SCALE, YOU MUST SCALE THE
                      ;; WIDTH.
                      (FIXR (QUOTIENT (STRINGWIDTH STRING FONT)
                                      SCALE)))
                      (T (STRINGWIDTH STRING FONT])
                    WID)
        DO (RETURN (ADD.KNOWN.SKETCH.FONT FAMILY WID DEVICE FONT))
        FINALLY (RETURN (ADD.KNOWN.SKETCH.FONT FAMILY WID DEVICE
          (IF (GREATERP FONTWIDTH (TIMES 1.5 WID))
            THEN 'SHADE
            ELSEIF (OR FONT STARTFONT])
        ELSEIF (IEQP FONTWIDTH WID)
        THEN (ADD.KNOWN.SKETCH.FONT FAMILY WID DEVICE STARTFONT)
        ELSE ;; FONT width was too small, try bigger fonts.
          (FOR FONT PREVFONT IN [CDR (FIND F ON [SORT (FONTSAVAILABLE FAMILY '* 'MRR 0 DEVICE T)
                                                    (FUNCTION (LAMBDA (F1 F2)
                                                              (ILESSP (CADR F1)
                                                                      (CADR F2))
                                                    SUCHTHAT (EQ SIZE (CADR F])
            DO (IF (IGREATERP (COND
                      (SCALE ;; IF THERE IS A SCALE, YOU MUST SCALE THE WIDTH.
                      (FIXR (QUOTIENT (STRINGWIDTH STRING FONT)
                                      SCALE)))
                      (T (STRINGWIDTH STRING FONT)))
                    WID)
              THEN (RETURN (ADD.KNOWN.SKETCH.FONT FAMILY WID DEVICE PREVFONT))
              (SETQ PREVFONT FONT)
            FINALLY (RETURN (ADD.KNOWN.SKETCH.FONT FAMILY WID DEVICE (OR FONT PREVFONT
                                                                      STARTFONT])
          (IF (FONTP CACHEDFONT)
            THEN ; Could be SHADE
              (FONTCOPY CACHEDFONT 'FACE (FONTPROP DISPLAYGFONT 'FACE))
            ELSE CACHEDFONT])

```

(SK.CHOOSE.TEXT.FONT

[LAMBDA (GTEXT SCALE VIEWER)

; Edited 10-May-93 16:18 by rmk:

; Edited 1-Nov-91 16:56 by jds

;; returns the font that text in the individual global part of a text or textbox element GTEXT should be displayed in when shown in VIEWER.

```

(PROG ([VIEWERFONTCACHE (OR (AND (WINDOWP VIEWER)
                                (WINDOWPROP VIEWER 'PICKFONTCACHE))
                            (AND (STREAMP VIEWER)
                                (STREAMPROP VIEWER 'PICKFONTCACHE])
      (GFONT (fetch (TEXT FONT) of GTEXT))
      LOCALFONT)
[COND
  ((SETQ LOCALFONT (SASSOC GFONT VIEWERFONTCACHE)) ; look in the viewer's font cache.
   (RETURN (CDR LOCALFONT])
  (RETURN (PROG ((CANONICALTESTSTR "AWIaiw")
                (CANONICALWIDTH DEVICE DISPLAYGFONT)
                [SETQ DEVICE (COND
                            ((STREAMP VIEWER)
                             (fetch (IMAGEOPS IMFONTCREATE) of (fetch (STREAM IMAGEOPS) of VIEWER)))
                            (T 'DISPLAY])
    [COND
      ((EQUAL (TIMES SCALE (DSPSCALE NIL VIEWER))
              (fetch (TEXT INITIALSCALE) of GTEXT))
        ;; special case scales being the same so there is not a large delay when first character is typed and to avoid font
        ;; look up problems when hardcopying at scale 1
        (SETQ LOCALFONT (FONTCREATE GFONT NIL NIL NIL DEVICE)))
      (T ;; use a canonical string to determine the font size so that all strings of a given font at a given scale look the
        ;; same. If font is determined by the width of the particular string, two different string will appear in different
        ;; fonts. In particular, the string may change fonts as the user is typing into it.
        ;; don't use the face information when determining string width because in some cases HELVETICA 10, the
        ;; bold is smaller than the regular.
        (SETQ DISPLAYGFONT (FONTCREATE GFONT NIL NIL NIL 'DISPLAY))

```

```

[SETQ CANONICALWIDTH (FIXR (QUOTIENT (TIMES [STRINGWIDTH
                                         CANONICALTESTSTR
                                         (LIST (FONTPROP DISPLAYFONT
                                                'FAMILY)
                                                (FONTPROP DISPLAYFONT
                                                'SIZE)
                                         (fetch (TEXT INITIALSCALE) of GTEXT))
                                         (TIMES SCALE (DSPSCALE NIL VIEWER]
                                         ; calculate the local font.
[COND
  ((WINDOWP VIEWER)
   (WINDOWPROP VIEWER 'PICKFONTCACHE (CONS (CONS GFONT LOCALFONT)
                                             VIEWERFONTCACHE)))
  ((STREAMP VIEWER)
   (STREAMPROP VIEWER 'PICKFONTCACHE (CONS (CONS GFONT LOCALFONT)
                                             VIEWERFONTCACHE)))
(RETURN LOCALFONT)]

```

(SK.NEXTSIZEFONT

```

[LAMBDA (WHICHDIR NOWFONT)
  (PROG [(NOWSIZE (FONTPROP NOWFONT 'HEIGHT))
         (DECREASEFONTLST (SK.DECREASING.FONT.LIST (CAR NOWFONT)
                                                    'DISPLAY)]
        (RETURN (COND
                  [(EQ WHICHDIR 'LARGER)
                   (COND
                    ((IGEQ NOWSIZE (FONTPROP (CAR DECREASEFONTLST)
                                             'HEIGHT))
                     (* nothing larger)
                    (NIL)
                    (T (for FONTTAIL on DECREASEFONTLST when [AND (CDR FONTTAIL)
                                                                    (IGEQ NOWSIZE (FONTPROP (CADR FONTTAIL)
                                                                    'HEIGHT)]
                        do (RETURN (SK.FONTNAMELIST (CAR FONTTAIL)]
                    (T (for FONT in DECREASEFONTLST when (LESSP (FONTPROP FONT 'HEIGHT)
                                                                    NOWSIZE)
                        do (RETURN (SK.FONTNAMELIST FONT)]

```

(* rrb "14-Jul-86 13:43")
(* returns the next sized font either SMALLER or LARGER that on of size FONT.)

(SK.DECREASING.FONT.LIST

```

[LAMBDA (FAMILY DEVICETYPE)
  ;; returns a list of fonts of family FAMILY which work on device DEVICETYPE
  [COND
   ((NULL FAMILY)
    (SETQ FAMILY 'MODERN)]
  ;; convert to families that exist on the known devices.

```

; Edited 12-Oct-92 12:39 by sybalsky:mv:envos

;;; NOTE: this is a very bad way to convert the family. It HARDCODES in the conversions for PRESS and INTERPRESS and does nothing for new device types. I have added the conversion for POSTSCRIPT that does things a little cleaner, but it should really look at a property of the device (fontconversions or some such animal.) --was 2/19/89

```

(LET ((CONVERSION))
  [COND
   [(EQ DEVICETYPE 'PRESS)
    (COND
     ((EQ FAMILY 'MODERN)
      (SETQ FAMILY 'HELVETICA))
     ((EQ FAMILY 'CLASSIC)
      (SETQ FAMILY 'TIMESROMAN))
     ((EQ FAMILY 'TERMINAL)
      (SETQ FAMILY 'GACHA)]
   [(EQ DEVICETYPE 'INTERPRESS)
    (COND
     ((EQ FAMILY 'HELVETICA)
      (SETQ FAMILY 'MODERN))
     ((EQ FAMILY 'TIMESROMAN)
      (SETQ FAMILY 'CLASSIC))
     ((EQ FAMILY 'GACHA)
      (SETQ FAMILY 'TERMINAL)]
   ((EQ DEVICETYPE 'POSTSCRIPT)
    (if (SETQ CONVERSION (ASSOC FAMILY POSTSCRIPT.FONT.ALIST))
        then ;; convert the family here for postscript as well as the other well known devices.
        (SETQ FAMILY (CDR CONVERSION)]
  (for FONT in (SK.GUESS.FONTSAVAILABLE FAMILY DEVICETYPE) collect (FONTCOPY FONT 'DEVICE DEVICETYPE)]

```

(SK.GUESS.FONTSAVAILABLE

```

[LAMBDA (FAMILY HDCPYTYPE)
  (PROG (FILEFONTS CACHE DISPLAYFONTSIZES)
        (SETQ HDCPYTYPE (COND
                          ((NULL HDCPYTYPE)

```

(* rrb " 9-Oct-85 16:10")
(* returns a list of all fonts of a FAMILY in decreasing order.)

```

(PRINTERTYPE))
(NLISTP HDCPYTYPE)
HDCPYTYPE)
(T HDCPYTYPE))) (* cache the file fonts.)
[COND
  [[SETQ FILEFONTS (ASSOC HDCPYTYPE (CDR (ASSOC FAMILY \FONTSONFILE)
                                         (* note if a cache has been calculated.
                                         Use it even if it is NIL)

(* \FONTSONFILE seems to group things such as CLASSICTHIN under CLASSIC so make sure to remove anything that
has the wrong family.)

  (SETQ FILEFONTS (SUBSET (CDR FILEFONTS)
                        (FUNCTION (LAMBDA (X)
                                  (EQ (CAR X)
                                       FAMILY])
  (T (RESETFORM (CURSOR WAITINGCURSOR)
               (SETQ FILEFONTS (FONTSAVAILABLE FAMILY '* ' (MEDIUM REGULAR REGULAR)
                                               NIL HDCPYTYPE T))

(* Since there is no way to determine the real sizes for PRESS fonts with size of 0 {meaning the widths scale}, guess that
they are available in 10)

[COND
  [(EQ HDCPYTYPE 'PRESS) (* make sure to look for anything that has a display font.)
  (SETQ DISPLAYFONTSIZES (for FONT in (FONTSAVAILABLE FAMILY '* ' (MEDIUM REGULAR REGULAR
                                     )
                                     NIL
                                     'DISPLAY)
                          collect (CADR FONT)))
  (SETQ FILEFONTS
    (for FONT in FILEFONTS
      join (COND
        [(EQ (CADR FONT)
             0)
          (for SIZE
            in (UNION DISPLAYFONTSIZES
                    '(36 30 24 18 14 12 10 8 6))
            when (FONTCREATE (CAR FONT)
                            SIZE NIL NIL 'DISPLAY T)
            collect (CONS (CAR FONT)
                        (CONS SIZE (CDDR FONT)
                              (T (CONS FONT)
                                 (* patch around the bug in FONTSAVAILABLE.
                                 Remove after J release.)
                                 (SETQ FILEFONTS (SUBSET FILEFONTS (FUNCTION (LAMBDA (FONT)
                                                                              (EQUAL (CADR FONT)
                                                                                   '(MEDIUM REGULAR REGULAR)
                                                                              (* remove duplicates and sort)
[SETQ FILEFONTS (SORT (INTERSECTION FILEFONTS FILEFONTS)
                    (FUNCTION (LAMBDA (A B)
                              (GREATERP (CADR A)
                                          (CADR B)
[COND
  ((NULL (SETQ CACHE (ASSOC FAMILY \FONTSONFILE)))
   (SETQ \FONTSONFILE (CONS (LIST FAMILY (CONS HDCPYTYPE FILEFONTS)
                              \FONTSONFILE)))
   (T (NCONC1 CACHE (CONS HDCPYTYPE FILEFONTS)
                   (* reget the fonts in core since they may have changed since
                   last time.)
  (RETURN (SORT (UNION (FONTSAVAILABLE FAMILY '* NIL NIL HDCPYTYPE)
                    FILEFONTS)
            (FUNCTION (LAMBDA (A B)
                      (COND
                        ((EQ (CADR A)
                             (CADR B))
                          (* in case both TIMESROMAN and TIMESROMAND for
                          example make it in.)
                        (ALPHORDER (CADR A)
                                  (CADR B)))
                        (T (GREATERP (CADR A)
                                    (CADR B)
)
(RPAQ? \KNOWN.SKETCH.FONTSIZES )
(DECLARE%: DOEVAL@COMPILE DONTCOPY
(GLOBALVARS \KNOWN.SKETCH.FONTSIZES)
)
(DECLARE%: DONTCOPY
(DECLARE%: EVAL@COMPILE
(TYPERECORD TEXT (LOCATIONLATLON LISTOFCHARACTERS INITIALSCALE TEXTSTYLE FONT LISTOFREGIONS TEXTCOLOR))

```

```
(RECORD LOCALTEXT ((DISPLAYPOSITION)
  LOCALHOTREGION LINEREGIONS LOCALFONT LOCALLISTOFCHARACTERS))
)
```

(DEFINEQ

(SK.SET.FONT

[LAMBDA (W NEWFONT) (* rrb " 2-Oct-85 14:55")

(* sets the entire default font. Used when a sketch stream is created.
or any of the defaults are changed. NEWFONT is a list of (FAMILY SIZE FACE))

```
(COND
  (NEWFONT (COND
    ((FONTCREATE NEWFONT NIL NIL NIL NIL T)
```

(* clear the cache of looked up fonts. This provides the user a way of clearing the cache that shouldn't happen too much and
is documented.)

```
(AND (FASSOC (CAR NEWFONT)
  \FONTSONFILE)
  (SETQ \FONTSONFILE (for BUCKET in \FONTSONFILE when (NEQ (CAR BUCKET)
    (CAR NEWFONT))
    collect BUCKET)))
  (replace (SKETCHCONTEXT SKETCHFONT) of (WINDOWPROP W 'SKETCHCONTEXT) with NEWFONT))
(T (STATUSPRINT W (CAR NEWFONT)
  " "
  (CADR NEWFONT)
  " "
  (SELECTQ (CAR (CADDR NEWFONT))
    (BOLD 'BOLD)
    " ")
  (SELECTQ (CADR (CADDR NEWFONT))
    (ITALIC 'ITALIC)
    " ")
  " not found"])
```

(SK.SET.TEXT.FONT

[LAMBDA (W) (* rrb " 4-Oct-85 16:21")
(* sets the size of the default arrowhead.)

```
(PROG [NEWFONT NOWFONT (SKCONTEXT (WINDOWPROP W 'SKETCHCONTEXT)
  (SETQ NEWFONT (SK.READFONTFAMILY W (PACK* "now: " (CAR (SETQ NOWFONT (fetch (SKETCHCONTEXT SKETCHFONT)
    of SKCONTEXT))))
    " "
    (CADR NOWFONT)
    ". New?"))))
(COND
  (NEWFONT (SK.SET.FONT W (LIST NEWFONT (CADR NOWFONT)
    (CADDR NOWFONT]))
```

(SK.SET.TEXT.SIZE

[LAMBDA (W) (* rrb " 2-Oct-85 14:36")
(* sets the size of the default font.)

```
(PROG (NEWSIZE (SKCONTEXT (WINDOWPROP W 'SKETCHCONTEXT)
  NOWFONT)
  (SETQ NOWFONT (fetch (SKETCHCONTEXT SKETCHFONT) of SKCONTEXT))
  (SETQ NEWSIZE (SK.READFONTSIZE NIL (FONTPROP NOWFONT 'FAMILY)
    W))
  (COND
    (NEWSIZE (SK.SET.FONT W (LIST (CAR NOWFONT)
      NEWSIZE
      (CADDR NOWFONT]))
```

(SK.SET.TEXT.HORIZ.ALIGN

[LAMBDA (SKW NEWALIGN) (* rrb " 6-Nov-85 09:51")

(* * reads a new value for the horizontal justification)

```
(PROG ([NEWJUST (COND
  ((MEMB NEWALIGN '(CENTER LEFT RIGHT))
    NEWALIGN)
  (T (\CURSOR.IN.MIDDLE.MENU (create MENU
    ITEMS _ ' (" Center " 'CENTER "New text will be
      centered around its position")
      ("Left " 'LEFT "the left edge of the text
        will be at its position.")
      (" Right" 'RIGHT "the right edge of the
        text will be at its position.")
    SKCONTEXT)
  (RETURN (AND NEWJUST (replace (SKETCHCONTEXT SKETCHTEXTALIGNMENT) of (SETQ SKCONTEXT (WINDOWPROP
    SKW
    'SKETCHCONTEXT))
    with (CONS NEWJUST (CDR (fetch (SKETCHCONTEXT SKETCHTEXTALIGNMENT) of SKCONTEXT))
```

)

(SK.READFONTSIZE

```
[LAMBDA (TITLE FONTFAMILY SKW) (* rrb " 6-Nov-85 09:51")

(* * gets a legal known font size from the user.)

(* this should have MENUROWS _ 1 when title height bug in menu package gets fixed.)

(PROG ((FONTSIZES (SK.COLLECT.FONT.SIZES FONTFAMILY))
NEWSIZE)
(COND
((NULL FONTSIZES)
(GO MORE)))
(SETQ NEWSIZE (\CURSOR.IN.MIDDLE.MENU (create MENU
TITLE _ (COND
(TITLE)
(FONTFAMILY (CONCAT "new " FONTFAMILY "
size?"))
(T "New font size?"))
ITEMS _ (CONS '(More 'MORE "will look on font directories
to find more sizes.")
FONTSIZES)
CENTERFLG _ T)))

(COND
((NEQ NEWSIZE 'MORE)
(RETURN NEWSIZE)))
MORE

(* do longer search of files)
(SETQ NEWSIZE (SK.COLLECT.FONT.SIZES FONTFAMILY T))
(COND
((NULL NEWSIZE) (* could not find any fonts of that family)
(RETURN NIL))
((EQUAL NEWSIZE FONTSIZES) (* not new ones found)
(STATUSPRINT SKW "
No more font sizes found.)))
(RETURN (MENU (create MENU
TITLE _ (OR TITLE "New font size?")
ITEMS _ NEWSIZE
CENTERFLG _ T]))
```

(SK.COLLECT.FONT.SIZES

```
[LAMBDA (FAMILY FILESTOOF LG) (* rrb " 2-Oct-85 10:43")

(* collects all of the sizes that are known. If FAMILY is given, gets just those sizes.)

(PROG (INCORESIZES FILESIZES)
[COND
[FAMILY (for TYPEBUCKET in (CDR (FASSOC FAMILY \FONTSONFILE))
do (for FFONT in (CDR TYPEBUCKET) do (OR (MEMB (CADR FFONT)
INCORESIZES)
(SETQ INCORESIZES (CONS (CADR FFONT)
INCORESIZES]
(T (* look at all fonts)
(for FAMILYBUCKET in \FONTSONFILE
do (for TYPEBUCKET in (CDR FAMILYBUCKET)
do (for FFONT in (CDR TYPEBUCKET) do (OR (MEMB (CADR FFONT)
INCORESIZES)
(SETQ INCORESIZES (CONS (CADR FFONT)
INCORESIZES]
(RETURN (SORT (UNION INCORESIZES (COND
[FILESTOOF LG (* wants those on files too, Flip the cursor to note wait.)
(RESETFORM (CURSOR WAITINGCURSOR)
(bind SIZES for FONT
in (FONTSAVAILABLE (OR FAMILY '*))
'* NIL NIL 'DISPLAY T)
do (OR (MEMB (FONTPROP FONT 'SIZE)
SIZES)
(SETQ SIZES (CONS (FONTPROP FONT 'SIZE)
SIZES)))
finally (RETURN SIZES]
(T (bind SIZES for FONT in (FONTSAVAILABLE (OR FAMILY '*))
'* NIL NIL 'DISPLAY FILESTOOF LG)
do (OR (MEMB (FONTPROP FONT 'SIZE)
SIZES)
(SETQ SIZES (CONS (FONTPROP FONT 'SIZE)
SIZES)))
finally (RETURN SIZES]))
```

(SK.SET.TEXT.VERT.ALIGN

```
[LAMBDA (SKW NEWALIGN) (* rrb " 6-Nov-85 09:52")
```

(* * reads a new value for the vertical justification)


```
(PROG ([NEWJUST (COND
  ((MEMB NEWALIGN '(TOP CENTER BASELINE BOTTOM))
   NEWALIGN)
  (T (\CURSOR.IN.MIDDLE.MENU (create MENU
    TITLE _ "New vertical alignment?"
    ITEMS _ ' ("Top" 'TOP "the top of new text's vertical
              extent will be at its position")
              ("Center" 'CENTER "New text's vertical extent
              will be centered around its position")
              ("Baseline" 'BASELINE "The baseline of new
              text will be at its position.")
              ("Bottom" 'BOTTOM "the bottom of new text's
              vertical extent will be at its
              position"))
    CENTERFLG _ T]
  SKCONTEXT)
  (RETURN (AND NEWJUST (replace (SKETCHCONTEXT SKETCHTEXTALIGNMENT) of (SETQ SKCONTEXT (WINDOWPROP
    SKW
    'SKETCHCONTEXT))
    with (LIST (CAR (fetch (SKETCHCONTEXT SKETCHTEXTALIGNMENT) of SKCONTEXT))
              NEWJUST]))
```

(SK.SET.TEXT.LOOKS

```
[LAMBDA (W) (* rrb " 6-Nov-85 09:52")
```

(* reads a new value for the looks of default text)

```
(SK.SET.DEFAULT.TEXT.FACE (\CURSOR.IN.MIDDLE.MENU (create MENU
  ITEMS _ ' ((regular '(MEDIUM REGULAR REGULAR)
                    "new text will be neither bold nor
                    italic.")
             (bold '(BOLD REGULAR REGULAR)
                    "new text will be bold.")
             (italic '(MEDIUM ITALIC REGULAR)
                    "new text will be italic.")
             (bold/italic '(BOLD ITALIC REGULAR)
                    "new text will be bold and
                    italic."))
  TITLE _ "New default look"
  CENTERFLG _ T)
  W])
```

(SK.SET.DEFAULT.TEXT.FACE

```
[LAMBDA (NEWDEFAULTFACE SKW) (* rrb " 4-Oct-85 16:24")
(* changes the default text face to NEWDEFAULTFACE.)
```

```
(PROG [(NOWFONT (fetch (SKETCHCONTEXT SKETCHFONT) of (WINDOWPROP SKW 'SKETCHCONTEXT)
  (RETURN (AND NEWDEFAULTFACE (SK.SET.FONT SKW (LIST (CAR NOWFONT)
    (CADR NOWFONT)
    NEWDEFAULTFACE]))
```

)

(DEFINEQ

(CREATE.SKETCH.TERMTABLE

```
[LAMBDA NIL (* rrb " 2-Oct-85 10:40")
(* returns a terminal table that has most characters printing as
REAL)
(* it is used by TEXT.DRAWFN1 to print strings in sketch.)
```

```
(PROG ((TTBL (COPYTERMTABLE NIL)))
  (for I from 128 to 255 do (AND (EQ (ECHOCHAR I NIL TTBL)
    'INDICATE)
    (ECHOCHAR I 'REAL TTBL)))
  (RETURN TTBL])
```

)

(DEFINEQ

(SK.FONT.LIST

```
[LAMBDA (FONTDESCRIPTOR) (* rrb " 2-Oct-85 14:41")
(* returns the font family, and size of a font descriptor)
```

```
(LIST (FONTPROP FONTDESCRIPTOR 'FAMILY)
  (FONTPROP FONTDESCRIPTOR 'SIZE)
  (FONTPROP FONTDESCRIPTOR 'FACE])
```

(SK.INSURE.FONT

```
[LAMBDA (FONT) (* rrb "16-Oct-85 17:46")
(* checks the validity of a font argument for a sketch element.)
```

```
(COND
  [(NULL FONT)
   (SK.FONT.LIST (OR (AND SK.DEFAULT.FONT (FONTCREATE SK.DEFAULT.FONT))
    (DEFAULTFONT 'DISPLAY]
  ((FONTP FONT)
```

```
(SK.FONT.LIST FONT)
((FONTCREATE FONT)
 (SK.FONT.LIST (FONTCREATE FONT)))
(T (\ILLEGAL.ARG FONT])
```

(SK.INSURE.STYLE

```
[LAMBDA (STYLE DEFAULT)
```

(* rrb "16-Oct-85 17:51")
 (* checks the validity of a STYLE argument for a sketch element)

```
(COND
 ((NULL STYLE)
  DEFAULT)
 ((AND (LISTP STYLE)
  (MEMB (CAR STYLE)
  SK.HORIZONTAL.STYLES)
  (MEMB (CAR (LISTP (CDR STYLE)))
  SK.VERTICAL.STYLES)
  (NULL (CDDR STYLE)))
  STYLE)
 (T (\ILLEGAL.ARG STYLE])
```

(SK.INSURE.TEXT

```
[LAMBDA (TEXTTHING)
```

(* rrb " 4-Nov-85 18:53")
 (* puts something in the form necessary for a text list of characters.)

```
(COND
 ((NLISTP TEXTTHING)
  (BREAK.AT.CARRIAGE.RETURNS TEXTTHING))
 (T (for X in TEXTTHING join (BREAK.AT.CARRIAGE.RETURNS X])
```

```
)
(RPAQQ INDICATE.TEXT.SHADE 23130)
(RPAQ? SK.DEFAULT.FONT )
(RPAQ? SK.DEFAULT.TEXT.ALIGNMENT ' (CENTER BASELINE))
(RPAQ? \FONTSONFILE NIL)
(ADDTOVAR SK.HORIZONTAL.STYLES LEFT RIGHT CENTER)
(ADDTOVAR SK.VERTICAL.STYLES TOP CENTER BASELINE BOTTOM)
(RPAQ SKETCH.TERMTABLE (CREATE.SKETCH.TERMTABLE))
(DECLARE%: DOEVAL@COMPILE DONTCOPY
(GLOBALVARS SKETCH.TERMTABLE SK.DEFAULT.TEXT.ALIGNMENT INDICATE.TEXT.SHADE \FONTSONFILE SK.HORIZONTAL.STYLES
SK.VERTICAL.STYLES)
)
```

:: stuff for supporting the TEXTBOX sketch element.

```
(DEFINEQ
```

(SKETCH.CREATE.TEXTBOX

```
[LAMBDA (STRING REGION FONT JUSTIFICATION BOXBRUSH BOXDASHING FILLING TEXTCOLOR SCALE)
```

(* rrb " 6-Aug-86 17:06")
 (* creates a sketch box element.)

```
(PROG ((XBRUSH (SK.INSURE.BRUSH BOXBRUSH))
 [XTEXT (COND
 ((NLISTP STRING)
  (BREAK.AT.CARRIAGE.RETURNS STRING))
 (T (for X in STRING join (BREAK.AT.CARRIAGE.RETURNS X])
 (XFONT (SK.INSURE.FONT FONT))
 (XJUSTIFICATION (SK.INSURE.STYLE JUSTIFICATION SK.DEFAULT.TEXTBOX.ALIGNMENT))
 XREGION)
```

(* calculate the region the textbox is to have. This is complicated in the case where REGION is a position because all of the other parameters must be know to calculate the region.)

```
[SETQ XREGION (COND
 ((REGIONP REGION))
 ((POSITIONP REGION)
  (SK.COMPUTE.TEXTBOX.REGION.FOR.STRING REGION XTEXT XFONT XBRUSH XJUSTIFICATION))
 (T (\ILLEGAL.ARG REGION)
  1.0)
 (RETURN (SK.TEXTBOX.CREATE1 XREGION XBRUSH XTEXT (OR (NUMBERP SCALE)
  XJUSTIFICATION XFONT (SK.INSURE.DASHING BOXDASHING)
  (SK.INSURE.FILLING FILLING)
  (SK.INSURE.COLOR TEXTCOLOR])
```

(SK.COMPUTE.TEXTBOX.REGION.FOR.STRING

```
[LAMBDA (POSITION STRLST FONT BRUSH JUSTIFICATION)
```

(* rrb "30-Jul-86 14:30")

```

(* returns the region of the box around STRLST whose control
point is POSITION.)
(PROG ((TEXTWIDTH (bind NOWWIDTH (WIDTH _ 0) for STR in STRLST do (COND
((GREATERP (SETQ NOWWIDTH
(STRINGWIDTH STR FONT))
WIDTH)
(SETQ WIDTH NOWWIDTH)))
finally (RETURN WIDTH)))
(TEXTHEIGHT (TIMES (LENGTH STRLST)
(FONTHEIGHT FONT)))
(MARGIN (SK.BRUSH.SIZE BRUSH))) (* leave two extra points for the width because it looks better.)
(SETQ TEXTWIDTH (PLUS MARGIN MARGIN TEXTWIDTH 2))
(SETQ TEXTHEIGHT (PLUS MARGIN MARGIN TEXTHEIGHT))
(RETURN (CREATEREGION (DIFFERENCE (fetch (POSITION XCOORD) of POSITION)
(SELECTQ (CAR JUSTIFICATION)
(LEFT 0)
(RIGHT TEXTWIDTH)
(CENTER (QUOTIENT TEXTWIDTH 2.0))
(SHOULDNT)))
(DIFFERENCE (fetch (POSITION YCOORD) of POSITION)
(SELECTQ (CADR JUSTIFICATION)
(BASELINE (PLUS (QUOTIENT (DIFFERENCE TEXTHEIGHT (FONTHEIGHT FONT))
2.0)
(FONTPROP FONT 'DESCENT)))
(TOP TEXTHEIGHT)
(BOTTOM 0)
(CENTER (QUOTIENT TEXTHEIGHT 2.0))
(SHOULDNT)))
TEXTWIDTH TEXTHEIGHT]))

```

(SK.BREAK.INTO.LINES

[LAMBDA (STRLST FONT WIDTH)

(* rrb "14-Jun-85 18:04")

(* returns a list of lines {as strings} of the text stored on STRLST broken so that as many words as possible fit on a line WIDTH wide.)

```

(COND
[(OR (FONTP FONT)
(WINDOWP FONT))
(PROG ((SPACEWIDTH (CHARWIDTH (CHARCODE % )
FONT))
(REMAINING WIDTH)
THISLINE NEWLST PREVCHARCR)
(for STR in STRLST
do (PROG ((BEGPTR 1)
(CHPTR 1)
(CHARSWID 0)
(LIMITPTR (ADD1 (NCHARS STR)))
CHCODE ENDPTR)
CHLP
(COND
((EQ CHPTR LIMITPTR) (* ran out of characters.)
(COND
((EQ LIMITPTR 1) (* empty line, ignore it.)
(RETURN))
[(ILEQ CHARSWID REMAINING) (* this whole thing fits.)
(SETQ THISLINE (CONS [COND
((EQ BEGPTR 1)
(* save substring call.)
STR)
(T (* put substring in.)
(SUBSTRING STR BEGPTR (SUB1 CHPTR)
(COND
(THISLINE
(* put a space in)
(CONS " " THISLINE]
(ENDPTR
(* found a word or words that will fit, put them on this line and finish this line.)
(SETQ NEWLST (CONS [CONS (COND
((EQ ENDPTR 0)
(* line began with a space and only it fit)
" ")
(T (SUBSTRING STR BEGPTR ENDPTR))]
(COND
(THISLINE
(* put a space in)
(CONS " " THISLINE]
NEWLST))
(SETQ THISLINE (CONS (OR (SUBSTRING STR (PLUS ENDPTR 2)
(SUB1 CHPTR))
""))))
(SETQ REMAINING WIDTH))
(T (* the remainder of this string goes on the next line.)
(AND THISLINE (SETQ NEWLST (CONS THISLINE NEWLST)))

```

```
[SETQ THISLINE (CONS (COND
    ((EQ BEGPTR 1)
     (* save substring call.)
     STR)
    (T (* put substring in.)
     (SUBSTRING STR BEGPTR (SUB1 CHPTR)
      (SETQ REMAINING WIDTH)))
     (* decrement space remaining.)
    (SETQ REMAINING (IDIFFERENCE REMAINING (IPLUS CHARSWID SPACEWIDTH)))
    (RETURN)
     (* put the part of this line that didn't fit on the next line.))
)
(EQ (CHARCODE %)
 (SETQ CHCODE (NTHCHARCODE STR CHPTR)))
(* got to a space)
[COND
 ((ILEQ CHARSWID REMAINING)
  (* mark the end of something that we know fits.)
  (* decrement space remaining.)
  (SETQ REMAINING (DIFFERENCE REMAINING CHARSWID)))
 (ENDPTR
```

(* found a word or words that will fit, put them on this line and finish this line.)

```
(SETQ NEWLST (CONS [CONS (OR (SUBSTRING STR BEGPTR ENDPTR)
    " ")
    (COND
     (THISLINE
      (* put a space in)
      (CONS " " THISLINE]
    NEWLST))
(* reset the pointers to note this beginning.)
(SETQ THISLINE NIL)
```

(* ENDPTR is always just before a space, put the beginning at the character following the space.)

```
(SETQ BEGPTR (PLUS ENDPTR 2))
(SETQ REMAINING (DIFFERENCE WIDTH CHARSWID)))
(T
 (COND
  (THISLINE (SETQ NEWLST (CONS THISLINE NEWLST))
   (SETQ THISLINE NIL)))
  (SETQ REMAINING (DIFFERENCE WIDTH CHARSWID])
  (SETQ ENDPTR (SUB1 CHPTR))
  (SETQ CHARSWID 0))
(EQ CHCODE (CHARCODE EOL)) (* CR, end a line.)
[COND
 ((GREATERP CHARSWID REMAINING) (* the last word before the CR doesn't fit on this line.)
  (COND
   (ENDPTR
    (* put some of it on the previous line)
    (SETQ NEWLST (CONS [CONS (OR (SUBSTRING STR BEGPTR ENDPTR)
      " ")
      (COND
       (THISLINE
        (* put a space in)
        (CONS " " THISLINE]
      NEWLST))
    (SETQ THISLINE NIL)
    (SETQ BEGPTR (PLUS ENDPTR 2)))
  (T
   (COND
    (THISLINE (SETQ NEWLST (CONS THISLINE NEWLST))
     (SETQ THISLINE NIL]
  [SETQ THISLINE (CONS (COND
    ((AND (EQ (ADD1 CHPTR)
      LIMITPTR)
      (EQ BEGPTR 1))
     (* last character of str, save substring call.
     for efficiency)
     STR)
    (T (* put substring in.)
     (SUBSTRING STR BEGPTR CHPTR)))
    (COND
     (THISLINE (* put a space in)
      (CONS " " THISLINE]
    (SETQ NEWLST (CONS THISLINE NEWLST))
    (SETQ THISLINE NIL)
    (SETQ CHARSWID 0)
    (SETQ REMAINING WIDTH)
    (COND
     ((EQ (ADD1 CHPTR)
      LIMITPTR)
      (SETQ PREVCHARCR T)
      (RETURN))
     (T (SETQ BEGPTR (ADD1 CHPTR))
      (SETQ ENDPTR)))
    (SETQ CHPTR (ADD1 CHPTR))
    (GO CHLP)))
  (SETQ CHARSWID (PLUS CHARSWID (CHARWIDTH CHCODE FONT)))
  (SETQ CHPTR (ADD1 CHPTR))
```

```

      (SETQ PREVCHARCR NIL)
      (GO CHLP))
  (RETURN (for LINE in [REVERSE (COND
    (THISLINE (CONS THISLINE NEWLST))
    (NEWLST (COND
      (PREVCHARCR

```

(* if end of last line was a CR, put an empty line in so cursor shows there.)

```

      (CONS "" NEWLST))
      (T NEWLST)))
      (T (LIST "" ]
  collect (APPLY (FUNCTION CONCAT)
    (REVERSE LINE)
  (T
    STRLST])
  (* if there isn't any font, it is probably SHADE.
  Just leave the strings alone)

```

(SK.BRUSH.SIZE

[LAMBDA (SKBRUSH)

(* rrb "30-Dec-84 13:38")

(* returns the size of a brush. This is used in places where the brush can be either an instance of the record BRUSH or a thickness.)

```

(COND
  ((NUMBERP SKBRUSH))
  (T (fetch (BRUSH BRUSHSIZE) of SKBRUSH]))

```

(SK.TEXTBOX.CREATE

[LAMBDA (SKETCHREGION BRUSH SCALE WINDOW)

(* rrb "16-Oct-85 17:59")

(* * creates a sketch element from a region)

```

(PROG [(CONTEXT (WINDOWPROP WINDOW 'SKETCHCONTEXT)
  (RETURN (SK.TEXTBOX.CREATE1 SKETCHREGION BRUSH (LIST "" ]
  SCALE
  (fetch (SKETCHCONTEXT SKETCHTEXTBOXALIGNMENT) of CONTEXT)
  (fetch (SKETCHCONTEXT SKETCHFONT) of CONTEXT)
  (fetch (SKETCHCONTEXT SKETCHDASHING) of CONTEXT)
  (fetch (SKETCHCONTEXT SKETCHFILLING) of CONTEXT)
  (fetch (BRUSH BRUSHCOLOR) of (fetch (SKETCHCONTEXT SKETCHBRUSH) of CONTEXT)])

```

(SK.TEXTBOX.CREATE1

[LAMBDA (SKETCHREGION BRUSH LSTOFSTRS INITSCALE STYLE INITFONT DASHING FILLING TEXTCOLOR)

(* rrb " 4-Dec-85 20:45")

```

(SK.UPDATE.TEXTBOX.AFTER.CHANGE (create GLOBALPART
  INDIVIDUALGLOBALPART _
  (create TEXTBOX
    TEXTBOXREGION _ SKETCHREGION
    LISTOFCHARACTERS _ LSTOFSTRS
    INITIALSCALE _ INITSCALE
    TEXTSTYLE _ STYLE
    FONT _ INITFONT
    TEXTCOLOR _ TEXTCOLOR
    TEXTBOXBRUSH _ BRUSH
    TEXTBOXDASHING _ DASHING
    TEXTBOXFILLING _ FILLING])

```

(SK.UPDATE.TEXTBOX.AFTER.CHANGE

[LAMBDA (GTEXTBOXELT)

(* rrb " 4-Dec-85 21:51")

(* updates the dependent fields in a textbox element that has had its text field changed.)

```

(PROG ((INDELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTBOXELT)))
  (TEXTBOX.SET.GLOBAL.REGIONS INDELT)
  (BOX.SET.SCALES (fetch (TEXTBOX TEXTBOXREGION) of INDELT)
    GTEXTBOXELT)
  (RETURN GTEXTBOXELT])

```

(SK.TEXTBOX.POSITION.IN.BOX

[LAMBDA (REGION STYLE FONT BRUSHWIDTH)

(* rrb "31-Jul-86 15:43")

(* returns the position that the text should be put at to have it look right within box REGION, style STYLE in font FONT)

```

(create POSITION
  XCOORD _ (SELECTQ (CAR STYLE)
    (LEFT (PLUS (fetch (REGION LEFT) of REGION)
      BRUSHWIDTH))
    (RIGHT (DIFFERENCE (fetch (REGION RIGHT) of REGION)
      BRUSHWIDTH))
    (CENTER (PLUS (fetch (REGION LEFT) of REGION)
      (QUOTIENT (fetch (REGION WIDTH) of REGION)

```

```

                2.0)))
        (SHOULDNT))
        YCOORD _ (SELECTQ (CADR STYLE)
                    (TOP (DIFFERENCE (fetch (REGION TOP) of REGION)
                                     BRUSHWIDTH))
                    (BOTTOM (PLUS (fetch (REGION BOTTOM) of REGION)
                                   BRUSHWIDTH))
                    (CENTER (PLUS (fetch (REGION BOTTOM) of REGION)
                                   (QUOTIENT (fetch (REGION HEIGHT) of REGION)
                                             2.0)))
                    (BASELINE [PLUS (fetch (REGION BOTTOM) of REGION)
                                   (PLUS (QUOTIENT (DIFFERENCE (fetch (REGION HEIGHT) of REGION)
                                                       (FONTPROP FONT 'HEIGHT))
                                             2.0)
                                   (FONTPROP FONT 'DESCENT])
                    (SHOULDNT]))
    
```

(TEXTBOX.CHANGEFN

```

[LAMBDA (SCRNELTS SKW HOW)
    (* rrb " 6-Jan-85 19:03"
    (* the users has selected SCRNELT to be changed)

    (SELECTQ (CAR HOW)
      (TEXT (TEXT.CHANGEFN SCRNELTS SKW HOW))
      (SIZE (CHANGE.ELTS.BRUSH.SIZE (CADR HOW)
                                       SCRNELTS SKW))
      NIL])
    
```

(TEXTBOX.DRAWFN

```

[LAMBDA (TEXTBOXELT WINDOW WINREG OPERATION)
    (* rrb " 3-Mar-86 21:38"
    (* draws a text box element.)

    (PROG ((LOCALPART (fetch (SCREENELT LOCALPART) of TEXTBOXELT))
           FILLING BRUSH ELTOPERATION)
      (OR (NULL WINREG)
          (REGIONSINTERSECTP WINREG (fetch (LOCALTEXTBOX LOCALTEXTBOXREGION) of LOCALPART))
          (RETURN))
      (SETQ BRUSH (fetch (LOCALTEXTBOX LOCALTEXTBOXBRUSH) of LOCALPART))
      (SETQ FILLING (fetch (LOCALTEXTBOX LOCALTEXTBOXFILLING) of LOCALPART))
      (SETQ ELTOPERATION (fetch (SKFILLING FILLING.OPERATION) of FILLING))
      (* just put texture where there won't be any text.)
      (SK.TEXTURE.AROUND.REGIONS (fetch (LOCALTEXTBOX LOCALTEXTBOXREGION) of LOCALPART)
        (fetch (LOCALTEXTBOX LINEREGIONS) of LOCALPART)
        (fetch (SKFILLING FILLING.TEXTURE) of FILLING)
        WINDOW
        (fetch (SKFILLING FILLING.COLOR) of FILLING)
        ELTOPERATION
        (fetch (BRUSH BRUSHSIZE) of BRUSH))
      (BOX.DRAWFN1 (fetch (LOCALTEXTBOX LOCALTEXTBOXREGION) of LOCALPART)
        (fetch (BRUSH BRUSHSIZE) of BRUSH)
        WINDOW WINREG ELTOPERATION (fetch (LOCALTEXTBOX LOCALTEXTBOXDASHING) of LOCALPART)
        NIL
        (fetch (BRUSH BRUSHCOLOR) of BRUSH))
      (TEXT.DRAWFN1 (fetch (LOCALTEXTBOX LOCALLISTOFCHARACTERS) of LOCALPART)
        (fetch (LOCALTEXTBOX LINEREGIONS) of LOCALPART)
        (fetch (LOCALTEXTBOX LOCALFONT) of LOCALPART)
        (fetch (BRUSH BRUSHCOLOR) of BRUSH)
        WINDOW ELTOPERATION])
    
```

(SK.TEXTURE.AROUND.REGIONS

```

[LAMBDA (BOXREGION INREGIONS TEXTURE STREAM COLOR OPERATION BRUSHSIZE)
    ; Edited 29-Sep-92 23:18 by jds

    ;; puts texture inside of a box but not in a collection of interior regions. Assumes INREGIONS are in order from top to bottom and abut in the Y
    ;; direction.
    ;; JDS 9/29/92 -- CHANGED TO AVOID DOING THIS WHEN TEXTURE IS NIL, THE MOST COMMON CASE IN TEXTBOXES. This speeds up
    ;; PostScript printing something fierce.

    (AND TEXTURE (PROG (BOXLEFT BOXRIGHT BOXTOP BOXBOTTOM X Y (MARGIN (TIMES 2 (DSPSCALE NIL STREAM)))
                      (USEOP (SK.TRANSLATE.MODE OPERATION STREAM)))
      [SETQ BOXLEFT (PLUS (fetch (REGION LEFT) of BOXREGION)
                        (ADD1 (IQUOTIENT BRUSHSIZE 2)
                        (ADD1 (IQUOTIENT BRUSHSIZE 2)
                        [SETQ BOXBOTTOM (PLUS (fetch (REGION BOTTOM) of BOXREGION)
                        (ADD1 (IQUOTIENT BRUSHSIZE 2)
                        (SETQ BOXTOP (DIFFERENCE (fetch (REGION TOP) of BOXREGION)
                        (IQUOTIENT (ADD1 BRUSHSIZE)
                        2)))
                        (SETQ BOXRIGHT (DIFFERENCE (fetch (REGION RIGHT) of BOXREGION)
                        (IQUOTIENT (ADD1 BRUSHSIZE)
                        2)))
      (COND
        ((OR (NULL INREGIONS)
            (ALL.EMPTY.REGIONS INREGIONS))
          (DSPFILL (CREATEREGION BOXLEFT BOXBOTTOM (ADD1 (DIFFERENCE BOXRIGHT BOXLEFT))
                    (ADD1 (DIFFERENCE BOXTOP BOXBOTTOM)))
                    TEXTURE USEOP STREAM)
          (RETURN)))
        (COND
    
```

```

([GREATERP BOXTOP (SETQ X (fetch (REGION TOP) of (CAR INREGIONS)
; fill area above the first region
(BLTSHADE TEXTURE STREAM BOXLEFT (ADD1 X)
(ADD1 (DIFFERENCE BOXRIGHT BOXLEFT))
(DIFFERENCE BOXTOP X)
USEOP NIL COLOR)))
[for LEAVEREGION in INREGIONS
do (COND
((ZEROP (fetch (REGION WIDTH) of LEAVEREGION))
; this line doesn't have any characters, just fill all the way across.
(BLTSHADE TEXTURE STREAM BOXLEFT (fetch (REGION BOTTOM) of LEAVEREGION)
(ADD1 (DIFFERENCE BOXRIGHT BOXLEFT))
(fetch (REGION HEIGHT) of LEAVEREGION)
USEOP NIL COLOR))
(T
; look for the part before and after the characters on this line.
(COND
((GREATERP (SETQ X (DIFFERENCE (fetch (REGION LEFT) of LEAVEREGION)
MARGIN))
BOXLEFT)
; fill area to the left of this region
(BLTSHADE TEXTURE STREAM BOXLEFT (fetch (REGION BOTTOM) of LEAVEREGION)
(DIFFERENCE X BOXLEFT)
(fetch (REGION HEIGHT) of LEAVEREGION)
USEOP NIL COLOR))
(COND
((GREATERP BOXRIGHT (SETQ X (PLUS (fetch (REGION RIGHT) of LEAVEREGION)
MARGIN)))
; fill area to the right of this region
(BLTSHADE TEXTURE STREAM (ADD1 X)
(fetch (REGION BOTTOM) of LEAVEREGION)
(DIFFERENCE BOXRIGHT X)
(fetch (REGION HEIGHT) of LEAVEREGION)
USEOP NIL COLOR)
(COND
((GREATERP [SETQ X (fetch (REGION BOTTOM) of (CAR (LAST INREGIONS)
BOXBOTTOM)
; fill area below the last region
(BLTSHADE TEXTURE STREAM BOXLEFT BOXBOTTOM (ADD1 (DIFFERENCE BOXRIGHT BOXLEFT))
(DIFFERENCE X BOXBOTTOM)
USEOP NIL COLOR])

```

(ALL.EMPTY.REGIONS

```

[LAMBDA (REGIONLST)
(* rrb "3-Mar-86 20:42")
(* returns T if REGIONLST contains nothing but empty regions.)
(for REG in REGIONLST always (OR (ZEROP (fetch (REGION WIDTH) of REG))
(ZEROP (fetch (REGION HEIGHT) of REG))

```

(TEXTBOX.EXPANDFN

```

[LAMBDA (GTEXTBOXELT SCALE STREAM)
(* rrb "30-Jul-86 15:23")
(* creates a local textbox screen element from a global text box
element)
(PROG ((GTEXTBOX (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTBOXELT))
(CANONICALTESTSTR "AWIaiw")
LREG TEXTPOS LOCALFONT STYLE IMAGESTREAM LINEREGIONS BRUSHWIDTH NEWLISTOFSTRS LOCALBRUSH)
(* calculate the local brush)
(SETQ LOCALBRUSH (SCALE.BRUSH (COND
([NOT (NUMBERP (SETQ LOCALBRUSH (fetch (TEXTBOX TEXTBOXBRUSH)
of GTEXTBOX)
(* new format, old format had brush width only.)
LOCALBRUSH)
(T [replace (TEXTBOX TEXTBOXBRUSH) of GTEXTBOX
with (SETQ LOCALBRUSH (create BRUSH
BRUSHSIZE _ LOCALBRUSH
BRUSHSHAPE _ 'ROUND)
LOCALBRUSH))
(fetch (TEXTBOX INITIALSCALE) of GTEXTBOX)
SCALE))
[COND
((TEXTUREP (fetch (TEXTBOX TEXTBOXFILLING) of GTEXTBOX))
(* old format, update to new one which has a list of
(texture color))
(replace (TEXTBOX TEXTBOXFILLING) of GTEXTBOX with (create SKFILLING
FILLING.TEXTURE _ (fetch (TEXTBOX
TEXTBOXFILLING
)
of GTEXTBOX)
FILLING.COLOR _ NIL]
(* calculate the local region for the text box.)
(SETQ BRUSHWIDTH (ADD1 (QUOTIENT (fetch (BRUSH BRUSHSIZE) of LOCALBRUSH)
2)))
(SETQ LREG (SK.SCALE.REGION (fetch (TEXTBOX TEXTBOXREGION) of GTEXTBOX)
SCALE))
(* calculate the local font.)
(SETQ LOCALFONT (SK.CHOOSE.TEXT.FONT GTEXTBOX SCALE STREAM))
(* recalculate the line breaks for the particular stream given. This is necessary because the difference between display and
hardcopy must be taken into account.)

```

```
[SETQ IMAGESTREAM (COND
  ((STREAMP STREAM))
  (T (WINDOWPROP STREAM 'DSP)]
[SETQ NEWLISTOFSTRS (COND
  [(FONTP LOCALFONT)
   (SK.BREAK.INTO.LINES (fetch (TEXTBOX LISTOFCHARACTERS) of GTEXTBOX)
   (COND
     ((IMAGESTREAMTYPEP IMAGESTREAM 'HARDCOPY)
      IMAGESTREAM)
     (T LOCALFONT))
   (COND
     [(IMAGESTREAMTYPEP IMAGESTREAM 'HARDCOPY)
      (* do the split on the basis of the hardcopy font)
      (FIXR (TIMES (IDIFFERENCE (fetch (REGION WIDTH) of LREG)
      (ITIMES BRUSHWIDTH 2))
      (PROGN
```

(* the scale should be a parameter of the hardcopy font, maybe font widths scale. but for now assume widths are in micras.)

```
      MICASPERPT]
      (T (IDIFFERENCE (fetch (REGION WIDTH) of LREG)
      (ITIMES BRUSHWIDTH 2]
      (* if not local font, leave line breaks alone.)
      (fetch (TEXTBOX LISTOFCHARACTERS) of GTEXTBOX]
(SETQ STYLE (fetch (TEXTBOX TEXTSTYLE) of GTEXTBOX))
(SETQ LINEREGIONS (SK.TEXT.LINE.REGIONS (OR NEWLISTOFSTRS '(""))
(SK.TEXTBOX.POSITION.IN.BOX LREG STYLE (OR LOCALFONT (fetch (TEXTBOX FONT)
of GTEXTBOX))
BRUSHWIDTH)
(fetch (TEXTBOX LISTOFREGIONS) of GTEXTBOX)
LOCALFONT STYLE SCALE IMAGESTREAM))
(RETURN (create SCREENELT
  LOCALPART _
  (create LOCALTEXTBOX
    TEXTBOXLL _ (create POSITION
      XCOORD _ (fetch (REGION LEFT) of LREG)
      YCOORD _ (fetch (REGION BOTTOM) of LREG))
    TEXTBOXUR _ (create POSITION
      XCOORD _ (fetch (REGION PRIGHT) of LREG)
      YCOORD _ (fetch (REGION PTOP) of LREG))
    LINEREGIONS _ LINEREGIONS
    LOCALFONT _ LOCALFONT
    LOCALTEXTBOXREGION _ LREG
    LOCALLISTOFCHARACTERS _ NEWLISTOFSTRS
    LOCALTEXTBOXBRUSH _ LOCALBRUSH
    LOCALTEXTBOXFILLING _ (APPEND (fetch (TEXTBOX TEXTBOXFILLING) of GTEXTBOX))
    LOCALTEXTBOXDASHING _ (fetch (TEXTBOX TEXTBOXDASHING) of GTEXTBOX))
    GLOBALPART _ GTEXTBOXELT])
```

(TEXTBOX.INPUTFN

```
[LAMBDA (W LREGION) (* rrb "11-Jul-86 15:48")
```

(* creates a box element for a sketch window. Prompts the user for one if none is given.)

```
(PROG (LOCALREG)
  (COND
    ((REGIONP LREGION)
     (SETQ LOCALREG LREGION))
    [(NULL LREGION)
     (COND
       [[SETQ LOCALREG (CAR (ERSETQ (GETWREGION W (FUNCTION SK.BOX.GETREGIONFN)
       W] (* WINDOWPROP will get exterior of window which should
       really be reduced to the interior.)
       (* make sure the last selected point wasn't outside.)
       (COND
         ((OR (NOT (SUBREGIONP (DSPCLIPPINGREGION NIL W)
         LOCALREG))
          (AND (EQ (fetch (REGION WIDTH) of LOCALREG)
          0)
          (EQ (fetch (REGION HEIGHT) of LOCALREG)
          0)))]
         (RETURN)]
       (T (RETURN)
       (T (\ILLEGAL.ARG LREGION)))
       (RETURN (SK.TEXTBOX.CREATE (UNSCALE.REGION.TO.GRID LOCALREG (VIEWER.SCALE W))
       (fetch (SKETCHCONTEXT SKETCHBRUSH) of (WINDOWPROP W 'SKETCHCONTEXT))
       (SK.INPUT.SCALE W)
       W])
```

(TEXTBOX.INSIDFN

```
[LAMBDA (GTEXTBOX WREG) (* rrb "30-Dec-84 17:23")
(* determines if the global TEXTBOX GTEXTBOX is inside of
WREG.)
(REGIONSINTERSECTP (fetch (TEXTBOX TEXTBOXREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTBOX))
```


WREG))

(TEXTBOX.REGIONFN

[LAMBDA (TEXTBOXSCRELT)

(* rrb "3-May-85 16:47")
(* returns the region occupied by a box.)

(* is increased by the brush size This has the nice property of insuring that the region always has both height and width.)

(INCREASEREGION (fetch (LOCALTEXTBOX LOCALTEXTBOXREGION) of (fetch (SCREENELT LOCALPART) of TEXTBOXSCRELT))
(SK.BRUSH.SIZE (fetch (TEXTBOX TEXTBOXBRUSH) of (fetch (SCREENELT INDIVIDUALGLOBALPART) of TEXTBOXSCRELT
]))

(TEXTBOX.GLOBALREGIONFN

[LAMBDA (GTEXTBOXELT)

(* rrb "18-Oct-85 17:11")
(* returns the global region occupied by a global textbox
element.)

(fetch (TEXTBOX TEXTBOXREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTBOXELT))

(TEXTBOX.SET.GLOBAL.REGIONS

[LAMBDA (GTEXTBOXELT)

(* rrb "30-Jul-86 14:48")

(* updates the list of characters and list of regions occupied by the textbox in the global coordinate space.)
(* this is used to determine the extent of a text element in a
region.)

(PROG [(SCALE (fetch (TEXTBOX INITIALSCALE) of GTEXTBOXELT))
(FONT (fetch (TEXTBOX FONT) of GTEXTBOXELT))
(LISTOFSTRS (fetch (TEXTBOX LISTOFCHARACTERS) of GTEXTBOXELT))
(TEXTSTYLE (fetch (TEXTBOX TEXTSTYLE) of GTEXTBOXELT))
(REGION (fetch (TEXTBOX TEXTBOXREGION) of GTEXTBOXELT))
(BRUSHWIDTH (SK.BRUSH.SIZE (fetch (TEXTBOX TEXTBOXBRUSH) of GTEXTBOXELT))
(replace (TEXTBOX LISTOFREGIONS) of GTEXTBOXELT with (for LREG
in (LTEXT.LINE.REGIONS LISTOFSTRS
(SK.TEXTBOX.POSITION.IN.BOX REGION
TEXTSTYLE FONT BRUSHWIDTH)
FONT TEXTSTYLE (ITIMES (FONTHEIGHT
FONT)
(LENGTH
LISTOFSTRS
)))
collect LREG))
(RETURN GTEXTBOXELT)])

(TEXTBOX.TRANSLATEFN

[LAMBDA (SKELT DELTAPOS)

(* rrb "28-Apr-85 18:46")

(* returns a textbox element which has been translated by DELTAPOS)

(PROG ((GTEXTBOXELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of SKELT))
OLDREG NEWREG)
(SETQ NEWREG (REL.MOVE.REGION (SETQ OLDREG (fetch (TEXTBOX TEXTBOXREGION) of GTEXTBOXELT))
(fetch (POSITION XCOORD) of DELTAPOS)
(fetch (POSITION YCOORD) of DELTAPOS)))
(RETURN (TEXT.UPDATE.GLOBAL.REGIONS (create GLOBALPART
COMMONGLOBALPART _ (APPEND (fetch (GLOBALPART
COMMONGLOBALPART)
of SKELT))
INDIVIDUALGLOBALPART _
(create TEXTBOX using GTEXTBOXELT TEXTBOXREGION _ NEWREG))
(create POSITION
XCOORD _ (fetch (REGION LEFT) of NEWREG)
YCOORD _ (fetch (REGION BOTTOM) of NEWREG))
(create POSITION
XCOORD _ (fetch (REGION LEFT) of OLDREG)
YCOORD _ (fetch (REGION BOTTOM) of OLDREG)]))

(TEXTBOX.TRANSLATEPTSFN

[LAMBDA (TEXTBOXELT SELPTS GDELTA WINDOW)

(* rrb "16-Oct-85 17:59")

(* returns a closed wire element which has the knots that are members of SELPTS translated by the global amount
GDELTA.)

(PROG ((GTEXTBOXELT (fetch (SCREENELT INDIVIDUALGLOBALPART) of TEXTBOXELT))
OLDGLOBALREGION LLX LLY URX URY)
(SETQ OLDGLOBALREGION (fetch (TEXTBOX TEXTBOXREGION) of GTEXTBOXELT))
[COND
[(MEMBER (fetch (LOCALTEXTBOX TEXTBOXLL) of (fetch (SCREENELT LOCALPART) of TEXTBOXELT))
SELPTS)
(* lower left point is moving.)
(SETQ LLX (PLUS (fetch (REGION LEFT) of OLDGLOBALREGION)
(fetch (POSITION XCOORD) of GDELTA)))
(SETQ LLY (PLUS (fetch (REGION BOTTOM) of OLDGLOBALREGION)
(fetch (POSITION YCOORD) of GDELTA))
(T (SETQ LLX (fetch (REGION LEFT) of OLDGLOBALREGION))


```

                                filling"]
                                (T NIL))
                                ' ("The text" 'TEXT "allows changing the
                                  properties of the text.")
                                ("Box thickness" 'SIZE "changes the size of
                                  the brush")
                                (Dashing 'DASHING "changes the dashing of
                                  the box.")
                                ("Unbox the text" '(TEXT UNBOX)
                                  "takes the text out of any selected
                                  text boxes.")
                                (Filling 'FILLING "allows changing of the
                                  filling texture of the box.")
                                (COND
                                 (FILLINGMODEFLG
                                  ' ("Filling mode" 'FILLINGMODE "changes
                                    how the filling effects the
                                    figures it covers."])
                                 CENTERFLG _ T)))
HOW)
(RETURN (SELECTQ COMMAND
        (TEXT (TEXT.READCHANGEFN SKW SCRNELTS T))
        (COND
         ((LISTP COMMAND)
          COMMAND)
         ((SETQ HOW (SELECTQ COMMAND
                        (FILLING (READ.FILLING.CHANGE))
                        (FILLINGMODE (READ.FILLING.MODE))
                        (SIZE (READSIZECHANGE "Change size how?" T))
                        (DASHING (READ.DASHING.CHANGE))
                        (BRUSHCOLOR [READ.COLOR.CHANGE "Change outline color how?" NIL
                                     (fetch (BRUSH BRUSHCOLOR)
                                             of (GETSKETCHELEMENTPROP (fetch (SCREENELT
                                                                                   GLOBALPART)
                                                                                   of (CAR SCRNELTS))
                                             'BRUSH])
                                     (FILLINGCOLOR [READ.COLOR.CHANGE "Change filling color how?" T
                                                                 (fetch (SKFILLING FILLING.COLOR)
                                                                 of (GETSKETCHELEMENTPROP (fetch (SCREENELT
                                                                                   GLOBALPART)
                                                                                   of (CAR SCRNELTS)
                                                                                   )
                                                                 'FILLING]))
                                     COMMAND))
          (LIST COMMAND HOW]))

```

(SK.TEXTBOX.TEXT.POSITION

```

[LAMBDA (GTEXTBOXELT)
  (create POSITION
           XCOORD _ (fetch (REGION LEFT) of (SETQ GTEXTBOXELT (fetch (TEXTBOX TEXTBOXREGION) of GTEXTBOXELT)))
           YCOORD _ (fetch (REGION TOP) of GTEXTBOXELT))
(* returns the position of the text in a text box element.)

```

(SK.TEXTBOX.FROM.TEXT

```

[LAMBDA (TEXTILT SKW)
  (PROG ((INDTEXTILT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of TEXTILT))
         BRUSH STYLE CONTEXT NEWTEXTBOXELT)
        (SETQ BRUSH (fetch (SKETCHCONTEXT SKETCHBRUSH) of (SETQ CONTEXT (WINDOWPROP SKW 'SKETCHCONTEXT)
                                                                    (fetch (TEXT LISTOFREGIONS)
                                                                    of INDTEXTILT)))
         (SETQ NEWTEXTBOXELT (SK.TEXTBOX.CREATE1 (INCREASEREGION (APPLY (FUNCTION SK.UNIONREGIONS)
                                                                    (fetch (TEXT LISTOFREGIONS)
                                                                    of INDTEXTILT))
                                                                    (IQUOTIENT (ADD1 (SK.BRUSH.SIZE (fetch (BRUSH BRUSHSIZE)
                                                                    of BRUSH)))
                                                                    2))
         BRUSH
         (fetch (TEXT LISTOFCHARACTERS) of INDTEXTILT)
         (fetch (TEXT INITIALSCALE) of INDTEXTILT)
         (COND
          ((EQ (CADR (SETQ STYLE (fetch (TEXT TEXTSTYLE) of INDTEXTILT)))
              'BASELINE)
           (* change from baseline to center because this usually looks
           better.))
          (LIST (CAR STYLE)
                'CENTER))
         (T STYLE))
         (fetch (TEXT FONT) of INDTEXTILT)
         (fetch (SKETCHCONTEXT SKETCHDASHING) of CONTEXT)
         (fetch (SKETCHCONTEXT SKETCHFILLING) of CONTEXT)
         (fetch (BRUSH BRUSHCOLOR) of BRUSH)))
(RETURN (create SKHISTORYCHANGESPEC
               NEWELT _ NEWTEXTBOXELT
               OLDEL _ TEXTILT
               PROPERTY _ 'HASBOX
               NEWVALUE _ NEWTEXTBOXELT
               OLDVALUE _ TEXTILT])

```

(ADD.EOLS

[LAMBDA (STRLST)

(* rrb "22-Jul-86 15:23")

(* adds an eol to every string in STRLST that doesn't end in one.)

(for STRTAIL on STRLST collect (COND

((EQ (CHARCODE EOL)
(NTHCHARCODE (CAR STRTAIL)
-1))
(CAR STRTAIL))
(CDR STRTAIL)
(CONCAT (CAR STRTAIL)
"
"))
(T (CAR STRTAIL]))

(* don't put a cr after the last line.)

(DECLARE%: DONTCOPY

(DECLARE%: EVAL@COMPILE

(RECORD LOCALTEXTBOX ((TEXTBOXLL TEXTBOXUR)
LOCALHOTREGION LINEREGIONS LOCALFONT LOCALLISTOFCHARACTERS LOCALTEXTBOXREGION
LOCALTEXTBOXBRUSH LOCALTEXTBOXFILLING LOCALTEXTBOXDASHING))

(TYPERECORD TEXTBOX (TEXTBOXREGION LISTOFCHARACTERS INITIALSCALE TEXTSTYLE FONT LISTOFREGIONS TEXTCOLOR
TEXTBOXBRUSH TEXTBOXDASHING TEXTBOXFILLING))

:: stuff to handle default alignment for text boxes

(DEFINEQ

(SK.SET.TEXTBOX.VERT.ALIGN

[LAMBDA (SKW)

(* rrb " 6-Nov-85 09:52")

(* * reads a new value for the vertical justification default for text boxes)

(PROG ((NEWJUST (\CURSOR.IN.MIDDLE.MENU (create MENU
TITLE _ "New vertical alignment?"
ITEMS _ ' ("Top" 'TOP "the top of new text's vertical extent
will be at its position")
("Center" 'CENTER "New text's vertical extent will
be centered around its position")
("Baseline" 'BASELINE "The baseline of new text
will be at its position.")
("Bottom" 'BOTTOM "the bottom of new text's
vertical extent will be at its position"))
CENTERFLG _ T)))
SKCONTEXT)
(RETURN (AND NEWJUST (replace (SKETCHCONTEXT SKETCHTEXTBOXALIGNMENT) of (SETQ SKCONTEXT
(WINDOWPROP SKW 'SKETCHCONTEXT)
)
with (LIST (CAR (fetch (SKETCHCONTEXT SKETCHTEXTBOXALIGNMENT) of SKCONTEXT))
NEWJUST]))

(SK.SET.TEXTBOX.HORIZ.ALIGN

[LAMBDA (SKW NEWALIGN)

(* rrb " 6-Nov-85 09:52")

(* * reads a new value for the horizontal justification default for text boxes)

(PROG ((NEWJUST (OR NEWALIGN (\CURSOR.IN.MIDDLE.MENU (create MENU
ITEMS _ ' (" Center " 'CENTER "New text will be
centered around its position")
("Left " 'LEFT "the left edge of
the text will be at its
position.")
(" Right" 'RIGHT "the right edge of
the text will be at its
position."])
SKCONTEXT)
(RETURN (AND NEWJUST (replace (SKETCHCONTEXT SKETCHTEXTBOXALIGNMENT) of (SETQ SKCONTEXT
(WINDOWPROP SKW 'SKETCHCONTEXT)
)
with (CONS NEWJUST (CDR (fetch (SKETCHCONTEXT SKETCHTEXTBOXALIGNMENT)
of SKCONTEXT]))

(RPAQQ TEXTBOXICON )

(RPAQQ? SK.DEFAULT.TEXTBOX.ALIGNMENT ' (CENTER CENTER))

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS SK.DEFAULT.TEXTBOX.ALIGNMENT)
)

:: functions to implement the box sketch element.

(DEFINEQ

(SKETCH.CREATE.BOX

[LAMBDA (REGION BRUSH DASHING FILLING SCALE) (* rrb "16-Oct-85 17:31")
 (* creates a sketch box element.)
 (SK.BOX.CREATE (OR (REGIONP REGION)
 (\ILLEGAL.ARG REGION))
 (SK.INSURE.BRUSH BRUSH)
 (SK.INSURE.DASHING DASHING)
 (OR (NUMBERP SCALE)
 1.0)
 (SK.INSURE.FILLING FILLING])

(SK.BOX.DRAWFN

[LAMBDA (BOXELT WIN WINREG) (* rrb "21-Feb-86 11:36")
 (* draws a box from its sketch element.)
 (PROG ((LOCALBOXELT (fetch (SCREENELT LOCALPART) of BOXELT))
 FILLING BRUSH)
 (SETQ FILLING (fetch (LOCALBOX LOCALBOXFILLING) of LOCALBOXELT))
 (RETURN (BOX.DRAWFN1 (fetch (LOCALBOX LOCALREGION) of LOCALBOXELT)
 (fetch (BRUSH BRUSHSIZE) of (SETQ BRUSH (fetch (LOCALBOX LOCALBOXBRUSH) of LOCALBOXELT)))
 WIN WINREG (fetch (SKFILLING FILLING.OPERATION) of FILLING)
 (fetch (LOCALBOX LOCALBOXDASHING) of LOCALBOXELT)
 (fetch (SKFILLING FILLING.TEXTURE) of FILLING)
 (fetch (BRUSH BRUSHCOLOR) of BRUSH)
 (fetch (SKFILLING FILLING.COLOR) of FILLING])

(BOX.DRAWFN1

[LAMBDA (REG SIZE WIN WINREG OPERATION DASHING TEXTURE OUTLINECOLOR FILLINGCOLOR) (* rrb "5-Mar-86 14:27")
 (* draws a box. Used by both box and text box elements.)
 (COND
 ((OR (NULL WINREG)
 (REGIONSINTERSECTP WINREG REG))
 (COND
 ((AND SKETCHINCOLORFLG (OR FILLINGCOLOR TEXTURE)) (* call the filling routine that does color.)
 (FILLPOLYGON (KNOTS.OF.REGION REG SIZE)
 (create SKFILLING
 FILLING.TEXTURE _ TEXTURE
 FILLING.COLOR _ FILLINGCOLOR)
 WIN))
 (TEXTURE (DSPFILL REG (COND
 ((EQ (DSPOPERATION NIL WIN)
 'ERASE) (* use black in case the window moved because of texture to
 window alignment bug.)
 BLACKSHADE)
 (T TEXTURE))
 (SK.TRANSLATE.MODE OPERATION WIN)
 WIN))
 (FILLINGCOLOR (* if no texture, use the color.)
 (DSPFILL REG (TEXTUREOFCOLOR FILLINGCOLOR)
 OPERATION WIN)))

(* code to fix white space bug in Interpress. It works but Masters are larger and the one I tried wouldn't print.
(SELECTQ (IMAGESTREAMTYPE WIN) ((NIL DISPLAY PRESS)
 (* special case DISPLAY for speed and PRESS because rounded corners don't work for large brushes.)
(SK.DRAWAREABOX (fetch (REGION LEFT) of REG) (fetch (REGION BOTTOM) of REG)
(fetch (REGION WIDTH) of REG) (fetch (REGION HEIGHT) of REG) SIZE OPERATION WIN DASHING OUTLINECOLOR))
(PROG ((LFT (fetch (REGION LEFT) of REG)) (BTM (fetch (REGION BOTTOM) of REG))
(TOP (fetch (REGION TOP) of REG)) (RGHT (fetch (REGION RIGHT) of REG))))
(DRAWCURVE (LIST (CREATEPOSITION LFT BTM) (CREATEPOSITION LFT TOP)
(CREATEPOSITION RIGHT TOP) (CREATEPOSITION RIGHT BTM)) T
(create BRUSH BRUSHSHAPE _ (QUOTE ROUND) BRUSHSIZE _ SIZE BRUSHCOLOR _ OUTLINECOLOR) DASHING
 WIN)))

(SK.DRAWAREABOX (fetch (REGION LEFT) of REG)
 (fetch (REGION BOTTOM) of REG)
 (fetch (REGION WIDTH) of REG)
 (fetch (REGION HEIGHT) of REG)
 SIZE
 (SK.TRANSLATE.MODE OPERATION WIN)
 WIN DASHING OUTLINECOLOR])

(KNOTS.OF.REGION

[LAMBDA (REGION BORDER) (* rrb "18-Jul-85 09:49")
 (* returns the knots of the interior rectangle of a region.)

```
(PROG (LFT BTM TP RIGHT (HLFBORDER (FQUOTIENT BORDER 2.0)))
  (SETQ LFT (PLUS (fetch (REGION LEFT) of REGION)
    HLFBORDER))
  (SETQ BTM (PLUS (fetch (REGION BOTTOM) of REGION)
    HLFBORDER))
  (SETQ TP (DIFFERENCE (fetch (REGION TOP) of REGION)
    HLFBORDER))
  (SETQ RIGHT (DIFFERENCE (fetch (REGION RIGHT) of REGION)
    HLFBORDER))
  (RETURN (LIST (create POSITION
    XCOORD _ LFT
    YCOORD _ BTM)
    (create POSITION
    XCOORD _ LFT
    YCOORD _ TP)
    (create POSITION
    XCOORD _ RIGHT
    YCOORD _ TP)
    (create POSITION
    XCOORD _ RIGHT
    YCOORD _ BTM]))
```

(SK.DRAWAREABOX

```
[LAMBDA (LEFT BOTTOM WIDTH HEIGHT BORDER OP W DASHING COLOR) (* rrb "16-Sep-86 16:12")
```

(* draws lines along the region. Copied from the function DRAWAREABOX in GRAPHER and changed to be the same as drawing lines between the corner points.)

```
(COND
  [[OR DASHING (AND COLOR (NEQ COLOR 'BLACK]
    (* start a line at each corner so that the corners will have black on them.)
```

```
(COND
  ((OR (IMAGESTREAMTYPEP W 'PRESS)
    (IMAGESTREAMTYPEP W 'INTERPRESS)) (* both these use BUTT, overlap the lines)
```

```
(PROG (BIG/HALF SM/HALF TOP RIGHT)
  (SETQ BIG/HALF (LRSH (ADD1 BORDER)
    1))
  (SETQ SM/HALF (DIFFERENCE BORDER BIG/HALF))
  (SETQ TOP (PLUS BOTTOM HEIGHT))
  (SETQ RIGHT (PLUS LEFT WIDTH)) (* draw left edge)
  (DRAWLINE LEFT (DIFFERENCE BOTTOM SM/HALF)
    LEFT
    (PLUS TOP BIG/HALF)
    BORDER OP W COLOR DASHING) (* draw top.)
  (DRAWLINE (IDIFFERENCE LEFT SM/HALF)
    TOP
    (IPLUS RIGHT BIG/HALF)
    TOP BORDER OP W COLOR DASHING) (* draw right edge)
  (DRAWLINE RIGHT (PLUS TOP BIG/HALF)
    RIGHT
    (DIFFERENCE BOTTOM SM/HALF)
    BORDER OP W COLOR DASHING) (* draw bottom)
  (DRAWLINE (IPLUS RIGHT BIG/HALF)
    BOTTOM
    (IDIFFERENCE LEFT SM/HALF)
    BOTTOM BORDER OP W COLOR DASHING)))
```

```
(T (PROG (TOP RIGHT HALFBORDER)
  (SETQ TOP (PLUS BOTTOM HEIGHT))
  (SETQ RIGHT (PLUS LEFT WIDTH)) (* draw left edge)
  (DRAWLINE LEFT BOTTOM LEFT TOP BORDER OP W COLOR DASHING)
    (* draw top)
  (DRAWLINE LEFT TOP RIGHT TOP BORDER OP W COLOR DASHING)
    (* draw right edge)
  (DRAWLINE RIGHT TOP RIGHT BOTTOM BORDER OP W COLOR DASHING)
    (* draw bottom)
  (DRAWLINE RIGHT BOTTOM LEFT BOTTOM BORDER OP W COLOR DASHING)
    (* overlap the ends of the lines.))
```

```
((IMAGESTREAMTYPEP W 'PRESS)
  (PROG (BIG/HALF SM/HALF TOP HORIZLEFT HORIZRIGHT RIGHT)
    (SETQ BIG/HALF (LRSH (ADD1 BORDER)
      1))
    (SETQ SM/HALF (DIFFERENCE BORDER BIG/HALF))
    (SETQ TOP (PLUS BOTTOM HEIGHT))
    (SETQ RIGHT (PLUS LEFT WIDTH)) (* draw left edge)
    (DRAWLINE LEFT (DIFFERENCE BOTTOM SM/HALF)
      LEFT
      (PLUS TOP BIG/HALF)
      BORDER OP W COLOR DASHING) (* draw top.)
    (DRAWLINE (SETQ HORIZLEFT (IPLUS LEFT BIG/HALF))
      TOP
      (SETQ HORIZRIGHT (SUB1 (IDIFFERENCE RIGHT SM/HALF)))
      TOP BORDER OP W COLOR DASHING) (* draw right edge)
    (DRAWLINE RIGHT (DIFFERENCE BOTTOM SM/HALF)
      RIGHT
      (PLUS TOP BIG/HALF))
```

```

      BORDER OP W COLOR DASHING) (* draw bottom)
      (DRAWLINE HORIZLEFT BOTTOM HORIZRIGHT BOTTOM BORDER OP W COLOR DASHING)))
      ((IMAGESTREAMTYPEP W 'INTERPRESS)

```

(* kludge for interpress in koto because BLTSHADE rounds down so brushes of 1 don't show, Drawline is always BUTT and DRAWPOLYGON isn't implemented.)

```

      (PROG (BIG/HALF SM/HALF TOP HORIZLEFT HORIZRIGHT RIGHT)
      (SETQ BIG/HALF (LRSH (ADD1 BORDER
      1)))
      (SETQ SM/HALF (DIFFERENCE BORDER BIG/HALF))
      (SETQ TOP (PLUS BOTTOM HEIGHT))
      (SETQ RIGHT (PLUS LEFT WIDTH)) (* draw left edge)
      (DRAWLINE LEFT (DIFFERENCE BOTTOM SM/HALF)
      LEFT
      (PLUS TOP BIG/HALF)
      BORDER OP W COLOR DASHING)

```

(* draw top. 9 is to fix an error on the 8044 which may be from rounding to its pixel size.)

```

      (DRAWLINE (SETQ HORIZLEFT (DIFFERENCE (IPLUS LEFT BIG/HALF
      9)))
      TOP
      (SETQ HORIZRIGHT (SUB1 (IDIFFERENCE RIGHT SM/HALF)))
      TOP BORDER OP W COLOR DASHING) (* draw right edge)
      (DRAWLINE RIGHT (DIFFERENCE BOTTOM SM/HALF)
      RIGHT
      (PLUS TOP BIG/HALF)
      BORDER OP W COLOR DASHING) (* draw bottom)
      (DRAWLINE HORIZLEFT BOTTOM HORIZRIGHT BOTTOM BORDER OP W COLOR DASHING)))
      (* do other cases with bitblt)
      (T
      (PROG (BIG/HALF SM/HALF HORIZLEFT BOXBOTTOM SIDEWIDTH SIDEHEIGHT)
      (SETQ BIG/HALF (LRSH BORDER 1))
      (SETQ SM/HALF (SUB1 (DIFFERENCE BORDER BIG/HALF)))
      (* draw left edge)
      (BLTSHADE BLACKSHADE W (DIFFERENCE LEFT SM/HALF)
      (SETQ BOXBOTTOM (DIFFERENCE BOTTOM SM/HALF))
      BORDER
      (SETQ SIDEHEIGHT (PLUS HEIGHT BORDER))
      OP) (* draw right edge)
      (BLTSHADE BLACKSHADE W (DIFFERENCE (PLUS LEFT WIDTH)
      SM/HALF)
      BOXBOTTOM BORDER SIDEHEIGHT OP) (* draw top)
      (BLTSHADE BLACKSHADE W (SETQ HORIZLEFT (ADD1 (PLUS LEFT BIG/HALF)))
      (DIFFERENCE (PLUS BOTTOM HEIGHT)
      SM/HALF)
      (SETQ SIDEWIDTH (DIFFERENCE WIDTH BORDER))
      BORDER OP)
      (BLTSHADE BLACKSHADE W HORIZLEFT BOXBOTTOM SIDEWIDTH BORDER OP])

```

(SK.DRAWBOX

```

      [LAMBDA (BOXLEFT BOXBOTTOM BOXWIDTH BOXHEIGHT BORDER OP W TEXTURE)
      (* rrb "14-Jul-86 13:51")
      (* draws lines inside the region.)
      (OR TEXTURE (SETQ TEXTURE BLACKSHADE))
      (BITBLT NIL NIL NIL W BOXLEFT BOXBOTTOM BORDER BOXHEIGHT 'TEXTURE OP TEXTURE)
      (* draw left edge)
      (* draw top)
      (BITBLT NIL NIL NIL W (PLUS BOXLEFT BORDER)
      (DIFFERENCE (PLUS BOXBOTTOM BOXHEIGHT)
      BORDER)
      (DIFFERENCE BOXWIDTH (PLUS BORDER BORDER))
      BORDER
      'TEXTURE OP TEXTURE) (* draw bottom)
      (BITBLT NIL NIL NIL W (PLUS BOXLEFT BORDER)
      BOXBOTTOM
      (DIFFERENCE BOXWIDTH (PLUS BORDER BORDER))
      BORDER
      'TEXTURE OP TEXTURE) (* draw right edge)
      (BITBLT NIL NIL NIL W (DIFFERENCE (PLUS BOXLEFT BOXWIDTH)
      BORDER)
      BOXBOTTOM BORDER BOXHEIGHT 'TEXTURE OP TEXTURE])

```

(SK.BOX.EXPANDFN

```

      [LAMBDA (GBOX SCALE)
      (* rrb "11-Jul-86 15:56")
      (* returns a local record which has the region field of the global element GELT translated into window coordinats.)
      (* for now only allow to move the left-bottom or right-top corner.)
      (PROG ((INDGELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GBOX))
      LREG)
      [COND
      ((fetch (BOX BOXINITSSCALE) of INDGELT))
      (T
      (replace (GLOBALPART INDIVIDUALGLOBALPART) of GBOX with (SETQ INDGELT
      (create BOX using INDGELT BOXINITSSCALE _
      1.0])

```

```

(COND
  ((TEXTUREP (fetch (BOX BOXFILLING) of INDGELT)) (* old format, update to new one which has a list of
                                                    (texture color))
    (replace (BOX BOXFILLING) of INDGELT with (create SKFILLING
                                                    FILLING.TEXTURE _ (fetch (BOX BOXFILLING)
                                                    of INDGELT)
                                                    FILLING.COLOR _ NIL]
  (SETQ LREG (SK.SCALE.REGION (fetch (BOX GLOBALREGION) of INDGELT)
              SCALE))
  (RETURN (create SCREENELT
                 LOCALPART _ (create LOCALBOX
                                     BOXLL _ (create POSITION
                                                  XCOORD _ (fetch (REGION LEFT) of LREG)
                                                  YCOORD _ (fetch (REGION BOTTOM) of LREG))
                                     BOXUR _ (create POSITION
                                                  XCOORD _ (fetch (REGION PRIGHT) of LREG)
                                                  YCOORD _ (fetch (REGION PTOP) of LREG))
                                     LOCALREGION _ LREG
                                     LOCALBOXBRUSH _
                                     (SCALE.BRUSH (COND
                                                  ([NOT (NUMBERP (SETQ LREG (fetch (BOX BRUSH)
                                                  of INDGELT))
                                                  (* new format, old format had brush width only.)
                                                  LREG)
                                                  (T [replace (BOX BRUSH) of INDGELT
                                                         with (SETQ LREG
                                                             (create BRUSH
                                                                     BRUSHSIZE _ LREG
                                                                     BRUSHSHAPE _ 'ROUND]
                                                             LREG))
                                                         (fetch (BOX BOXINITSSCALE) of INDGELT)
                                                         SCALE)
                                                  LOCALBOXFILLING _ (APPEND (fetch (BOX BOXFILLING) of INDGELT))
                                                  LOCALBOXDASHING _ (fetch (BOX BOXDASHING) of INDGELT))
                 GLOBALPART _ GBOX])

```

(SK.BOX.GETREGIONFN

[LAMBDA (FIXPT MOVINGPT W) (* rrb "12-May-86 18:38")

(* getregion fn that generates an error if a point is clicked outside of window. Also puts things on the window grid.)

```

(SKETCHW.UPDATE.LOCATORS W)
(COND
  [MOVINGPT

```

(* this test the fixed pt every time which is unnecessary but does allow us to catch button down.)

```

  (PROG [(REG (WINDOWPROP W 'REGION)
             (RETURN (COND
                     ((INSIDEP REG FIXPT)
                      (COND
                       ((INSIDEP REG MOVINGPT)
                        (MAP.SCREEN.POSITION.ONTO.GRID MOVINGPT W (LASTMOUSESTATE MIDDLE))))
                     (T (* if the cursor is outside, return the fixed point so the feedback
                        box disappears.)
                       FIXPT)))
          (T (ERROR!])
             (T (MAP.SCREEN.POSITION.ONTO.GRID FIXPT W (LASTMOUSESTATE RIGHT]))

```

(BOX.SET.SCALES

[LAMBDA (GREG GBOXELT) (* rrb " 7-Feb-85 12:30") (* updates the scale field after a change in the region of a box element.)

(* removed the part of the scale that was limiting it to defaults. If it has to go back in, please leave a note as to why.)

```

  (PROG (WIDTH HEIGHT)
    (replace (GLOBALPART MINSCALE) of GBOXELT with (FQUOTIENT (MIN (SETQ WIDTH (fetch (REGION WIDTH)
                                                    of GREG))
                                                                (SETQ HEIGHT (fetch (REGION HEIGHT)
                                                                of GREG)))
                                                    1000.0))
    (replace (GLOBALPART MAXSCALE) of GBOXELT with (FQUOTIENT (MAX WIDTH HEIGHT)
                                                                2.0))
  (RETURN GBOXELT])

```

(SK.BOX.INPUTFN

[LAMBDA (W LREGION) (* rrb "11-Jul-86 15:48")

(* creates a box element for a sketch window. Prompts the user for one if none is given.)

```

  (PROG (LOCALREG SKCONTEXT)
    (COND

```



```

"changes the color of the
filling"]
(T NIL)
[COND
(FILLINGMODEFLG ' ("Filling mode"
'FILLINGMODE "changes how
the filling effects the
figures it covers."]
' ((Filling 'FILLING "allows changing of the
filling texture of the box.")
("Outline size" 'SIZE "changes the size of
the brush")
("Outline dashing" 'DASHING "changes the
dashing of the line.")
(SIZE (READSIZECHANGE "Change size how?" T))
(FILLING (READ.FILLING.CHANGE))
(FILLINGMODE (READ.FILLING.MODE))
(DASHING (READ.DASHING.CHANGE))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change outline color how?" NIL
(fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
(fetch (SCREENELT GLOBALPART)
of (CAR SCRNELTS)
'BRUSH])
(FILLINGCOLOR [READ.COLOR.CHANGE "Change filling color how?" T
(fetch (SKFILLING FILLING.COLOR) of (GETSKETCHELEMENTPROP
(fetch (SCREENELT GLOBALPART)
of (CAR SCRNELTS)
'FILLING])
NIL))
(RETURN (AND HOW (LIST ASPECT HOW]))

```

(SK.CHANGE.FILLING

```

[LAMBDA (ELTWITHFILLING HOW SKW) (* rrb "9-Jan-86 16:57")
(* changes the texture in the element ELTWITHFILLING.)
(PROG (GFILLEDELT TEXTURE OLDFILLING NEWFILLING TYPE NEWELT)
(AND (EQ HOW 'NONE)
(SETQ HOW NIL))
(RETURN (COND
((MEMB (SETQ TYPE (fetch (GLOBALPART GTYPE) of ELTWITHFILLING))
' (BOX TEXTBOX CLOSEDWIRE CIRCLE)) (* only works for things that have a filling, for now just boxes and
polygons)
(SETQ GFILLEDELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHFILLING))
[SETQ TEXTURE (fetch (SKFILLING FILLING.TEXTURE) of (SETQ OLDFILLING
(SELECTQ TYPE
(BOX (fetch (BOX BOXFILLING)
of GFILLEDELT))
(TEXTBOX (fetch (TEXTBOX
TEXTBOXFILLING
)
of GFILLEDELT))
(CLOSEDWIRE (fetch (CLOSEDWIRE
CLOSEDWIREFILLING
)
of GFILLEDELT))
(CIRCLE (fetch (CIRCLE
CIRCLEFILLING
)
of GFILLEDELT))
(SHOULDNT])
(COND
((NOT (EQUAL HOW TEXTURE)) (* new filling)
(SETQ NEWFILLING (create SKFILLING using OLDFILLING FILLING.TEXTURE _ HOW))
(SETQ NEWELT (SELECTQ TYPE
(BOX (create BOX using GFILLEDELT BOXFILLING _ NEWFILLING))
(TEXTBOX (create TEXTBOX using GFILLEDELT TEXTBOXFILLING _ NEWFILLING))
(CLOSEDWIRE (create CLOSEDWIRE using GFILLEDELT CLOSEDWIREFILLING _
NEWFILLING))
(CIRCLE (create CIRCLE using GFILLEDELT CIRCLEFILLING _ NEWFILLING))
(SHOULDNT)))
(create SKHISTORYCHANGESPEC
NEWELT _ (create GLOBALPART
COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
of ELTWITHFILLING)
INDIVIDUALGLOBALPART _ NEWELT)
OLDELT _ ELTWITHFILLING
PROPERTY _ 'FILLING
NEWVALUE _ NEWFILLING
OLDVALUE _ OLDFILLING])
)

```

(SK.CHANGE.FILLING.COLOR

```

[LAMBDA (ELTWITHFILLING HOW SKW) (* rrb "9-Jan-86 19:42")
(* changes the texture in the element ELTWITHFILLING.)
(PROG (GFILLEDELT COLOR FILLING NEWFILLING TYPE NEWELT)

```

```

(AND (EQ HOW 'NONE)
      (SETQ HOW NIL))
(RETURN (COND
  ((MEMB (SETQ TYPE (fetch (GLOBALPART GTYPE) of ELTWITHFILLING))
    '(BOX TEXTBOX CLOSEDWIRE CIRCLE)) (* only works for things that have a filling, for now just boxes and
    polygons)
    (SETQ GFILLEDELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of ELTWITHFILLING))
    [SETQ COLOR (fetch (SKFILLING FILLING.COLOR) of (SETQ FILLING
      (SELECTQ TYPE
        (BOX (fetch (BOX BOXFILLING)
          of GFILLEDELT))
        (TEXTBOX (fetch (TEXTBOX TEXTBOXFILLING)
          of GFILLEDELT))
        (CIRCLE (fetch (CIRCLE CIRCLEFILLING)
          of GFILLEDELT))
        (CLOSEDWIRE (fetch (CLOSEDWIRE
          CLOSEDWIREFILLING)
          of GFILLEDELT))
        (SHOULDNT]
      )
    (COND
      ((NOT (EQUAL HOW COLOR)) (* new filling)
        (SETQ NEWFILLING (create SKFILLING using FILLING FILLING.COLOR _ HOW))
        (SETQ NEWELT (SELECTQ TYPE
          (BOX (create BOX using GFILLEDELT BOXFILLING _ NEWFILLING))
          (TEXTBOX (create TEXTBOX using GFILLEDELT TEXTBOXFILLING _ NEWFILLING))
          (CLOSEDWIRE (create CLOSEDWIRE using GFILLEDELT CLOSEDWIREFILLING _
            NEWFILLING))
          (CIRCLE (create CIRCLE using GFILLEDELT CIRCLEFILLING _ NEWFILLING))
          (SHOULDNT)))
        (create SKHISTORYCHANGESPEC
          NEWELT _ (create GLOBALPART
            COMMONGLOBALPART _ (fetch (GLOBALPART COMMONGLOBALPART)
              of ELTWITHFILLING)
            INDIVIDUALGLOBALPART _ NEWELT)
          OLDELT _ ELTWITHFILLING
          PROPERTY _ 'FILLING
          NEWVALUE _ NEWFILLING
          OLDVALUE _ FILLING])
      )
    )
  )
)

```

(SK.BOX.TRANSLATEFN

[LAMBDA (SKELT DELTAPOS)

(* rrb "28-Apr-85 18:46")

(* returns a curve element which has the box translated by DELTAPOS)

```

(PROG ((GBOXELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of SKELT)))
  (RETURN (create GLOBALPART
    COMMONGLOBALPART _ (APPEND (fetch (GLOBALPART COMMONGLOBALPART) of SKELT))
    INDIVIDUALGLOBALPART _ (create BOX using GBOXELT GLOBALREGION _
      (REL.MOVE.REGION (fetch (BOX GLOBALREGION)
        of GBOXELT)
        (fetch (POSITION XCOORD) of DELTAPOS)
        (fetch (POSITION YCOORD) of DELTAPOS])
      )
    )
  )
)

```

(SK.BOX.TRANSFORMFN

[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR)

(* rrb "12-Jul-85 17:16")

(* returns a copy of the global BOX element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to transformfn.)

```

(PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (RETURN (SK.BOX.CREATE (SK.TRANSFORM.REGION (fetch (BOX GLOBALREGION) of INDVPART)
    TRANSFORMFN TRANSFORMDATA)
    (SK.TRANSFORM.BRUSH (fetch (BOX BRUSH) of INDVPART)
      SCALEFACTOR)
    (fetch (BOX BOXDASHING) of INDVPART)
    (fetch (BOX BOXINITSCALE) of INDVPART)
    (fetch (BOX BOXFILLING) of INDVPART])
  )
)

```

(SK.BOX.TRANSLATEPTSFN

[LAMBDA (BOXELT SELPTS GDELTA WINDOW)

(* rrb "12-Jul-85 17:55")

(* returns a closed wire element which has the knots that are members of SELPTS translated by the global amount GDELTA.)

```

(PROG ((GBOXELT (fetch (SCREENELT INDIVIDUALGLOBALPART) of BOXELT))
  OLDGLOBALREGION LLX LLY URX URY)
  (SETQ OLDGLOBALREGION (fetch (BOX GLOBALREGION) of GBOXELT))
  [COND
    [(MEMBER (fetch (LOCALBOX BOXLL) of (fetch (SCREENELT LOCALPART) of BOXELT))
      SELPTS)
      (* lower left point is moving.)
      (SETQ LLX (PLUS (fetch (REGION LEFT) of OLDGLOBALREGION)

```

```

      (fetch (POSITION XCOORD) of GDELTA)))
    (SETQ LLY (PLUS (fetch (REGION BOTTOM) of OLDGLOBALREGION)
      (fetch (POSITION YCOORD) of GDELTA]
    (T (SETQ LLX (fetch (REGION LEFT) of OLDGLOBALREGION))
      (SETQ LLY (fetch (REGION BOTTOM) of OLDGLOBALREGION]
[COND
  [(MEMBER (fetch (LOCALBOX BOXUR) of (fetch (SCREENELT LOCALPART) of BOXELT))
    SELPTS)
    (* upper right point)
  (SETQ URX (PLUS (fetch (REGION PRIGHT) of OLDGLOBALREGION)
    (fetch (POSITION XCOORD) of GDELTA)))
  (SETQ URY (PLUS (fetch (REGION PTOP) of OLDGLOBALREGION)
    (fetch (POSITION YCOORD) of GDELTA]
  (T (SETQ URX (fetch (REGION PRIGHT) of OLDGLOBALREGION))
    (SETQ URY (fetch (REGION PTOP) of OLDGLOBALREGION]
  (RETURN (SK.BOX.CREATE (CREATEREGION (MIN LLX URX)
    (MIN LLY URY)
    (ABS (DIFFERENCE LLX URX))
    (ABS (DIFFERENCE LLY URY))))
    (fetch (BOX BRUSH) of GBOXELT)
    (fetch (BOX BOXDASHING) of GBOXELT)
    (fetch (BOX BOXINITSCALE) of GBOXELT)
    (fetch (BOX BOXFILLING) of GBOXELT]))

```

(UNSCALE.REGION.TO.GRID

[LAMBDA (REGION SCALE GRIDSIZE)

(* rrb "25-Oct-84 12:53")

(* scales a region from a window region to the larger coordinate

space.)

```

(PROG [(LFT (TIMES SCALE (fetch (REGION LEFT) of REGION)))
  (BTM (TIMES SCALE (fetch (REGION BOTTOM) of REGION)))
  (WDTH (TIMES SCALE (fetch (REGION WIDTH) of REGION)))
  (HGHT (TIMES SCALE (fetch (REGION HEIGHT) of REGION]
[COND
  (GRIDSIZE
    (SETQ LFT (NEAREST.ON.GRID LFT GRIDSIZE))
    (SETQ BTM (NEAREST.ON.GRID BTM GRIDSIZE))
    (SETQ WDTH (NEAREST.ON.GRID WDTH GRIDSIZE))
    (SETQ HGHT (NEAREST.ON.GRID HGHT GRIDSIZE]
  (RETURN (CREATEREGION LFT BTM WDTH HGHT]))

```

(* move X and Y to nearest point on the grid)

(INCREASEREGION

[LAMBDA (REGION BYAMOUNT)

(* rrb " 9-Sep-84 19:58")

(* * increases a region by a fixed amount in all directions.)

```

(CREATEREGION (DIFFERENCE (fetch (REGION LEFT) of REGION)
  BYAMOUNT)
  (DIFFERENCE (fetch (REGION BOTTOM) of REGION)
  BYAMOUNT)
  (PLUS (fetch (REGION WIDTH) of REGION)
  (TIMES BYAMOUNT 2))
  (PLUS (fetch (REGION HEIGHT) of REGION)
  (TIMES BYAMOUNT 2]))

```

(INSUREREGIONSIZE

[LAMBDA (REGION MINSIZE)

(* rrb " 5-Dec-84 11:27")

(* * makes sure the height and width of REGION are at least MINSIZE.)

```

(PROG (X)
  (COND
    ((GREATERP MINSIZE (SETQ X (fetch (REGION WIDTH) of REGION)))
      (replace (REGION LEFT) of REGION with (DIFFERENCE (fetch (REGION LEFT) of REGION)
        (QUOTIENT (DIFFERENCE MINSIZE X)
          2)))
      (replace (REGION WIDTH) of REGION with MINSIZE)))
    ((GREATERP MINSIZE (SETQ X (fetch (REGION HEIGHT) of REGION)))
      (replace (REGION BOTTOM) of REGION with (DIFFERENCE (fetch (REGION BOTTOM) of REGION)
        (QUOTIENT (DIFFERENCE MINSIZE X)
          2)))
      (replace (REGION HEIGHT) of REGION with MINSIZE)))
  (RETURN REGION]))

```

(EXPANDREGION

[LAMBDA (REGION BYFACTOR)

(* rrb "30-Nov-84 10:43")

(* * expands a region by a factor.)

```

(PROG ((WIDTH (fetch (REGION WIDTH) of REGION))
  (HEIGHT (fetch (REGION HEIGHT) of REGION))
  NEWWIDTH NEWHEIGHT)
  (SETQ NEWWIDTH (TIMES WIDTH BYFACTOR))
  (SETQ NEWHEIGHT (TIMES HEIGHT BYFACTOR))

```

```
(RETURN (CREATEREGION (DIFFERENCE (fetch (REGION LEFT) of REGION)
(QUOTIENT (IDIFFERENCE NEWWIDTH WIDTH)
2))
(DIFFERENCE (fetch (REGION BOTTOM) of REGION)
(QUOTIENT (IDIFFERENCE NEWHEIGHT HEIGHT)
2))
NEWWIDTH NEWHEIGHT])
```

(REGION.FROM.COORDINATES

[LAMBDA (X1 Y1 X2 Y2)

(* rrb "11-Sep-84 16:27")

(* * returns the region for which { X1 Y1 } and { X2 Y2 } are the corners.)

```
(CREATEREGION (MIN X1 X2)
(MIN Y1 Y2)
(ADD1 (ABS (IDIFFERENCE X2 X1)))
(ADD1 (ABS (IDIFFERENCE Y2 Y1)))
)
(DECLARE%: DONTCOPY
(DECLARE%: EVAL@COMPILE
(TYPERECORD BOX (GLOBALREGION BRUSH BOXDASHING BOXINITSCALE BOXFILLING))
(RECORD LOCALBOX ((BOXLL BOXUR)
LOCALHOTREGION LOCALREGION LOCALBOXBRUSH LOCALBOXFILLING LOCALBOXDASHING))
)
)
(READVARS-FROM-STRINGS '(BOXICON)
"({ (READBITMAP) (20 12
% " @ @ @ @ @ @ @ @ % "
% " G O O O N @ @ @ @ % "
% " G O O O N @ @ @ @ % "
% " F @ @ @ F @ @ @ @ % "
% " F @ @ @ F @ @ @ @ % "
% " F @ @ @ F @ @ @ @ % "
% " F @ @ @ F @ @ @ @ % "
% " F @ @ @ F @ @ @ @ % "
% " F @ @ @ F @ @ @ @ % "
% " G O O O N @ @ @ @ % "
% " G O O O N @ @ @ @ % "
% " @ @ @ @ @ @ @ @ @ @ % " ) } )
")
```

:: fns for the arc sketch element type

(DEFINEQ

(SKETCH.CREATE.ARC

[LAMBDA (CENTERPT RADIUSPT ANGLEPT BRUSH DASHING ARROWHEADS DIRECTION SCALE)

(* rrb "7-Jul-86 14:49")
(* creates a sketch arc element.)

```
(ARC.CREATE (SK.INSURE.POSITION CENTERPT)
(SK.INSURE.POSITION RADIUSPT)
(COND
((NUMBERP ANGLEPT)
(SK.COMPUTE.ARC.ANGLE.PT.FROM.ANGLE CENTERPT RADIUSPT ANGLEPT))
(T (SK.INSURE.POSITION ANGLEPT)))
(SK.INSURE.BRUSH BRUSH)
(SK.INSURE.DASHING DASHING)
(OR (NUMBERP SCALE)
1.0)
(SK.INSURE.ARROWHEADS ARROWHEADS)
(SK.INSURE.DIRECTION DIRECTION])
```

(ARC.DRAWFN

[LAMBDA (ARCELT WINDOW REGION)

(* rrb "20-Jun-86 17:12")
(* draws a arc from a arc element.)

```
(PROG ((GARC (fetch (SCREENELT INDIVIDUALGLOBALPART) of ARCELT))
(LARC (fetch (SCREENELT LOCALPART) of ARCELT))
BRUSH DASHING LOCALPTS LOCALARROWPTS GARROWSPECS)
(AND REGION (NOT (REGIONSINTERSECTP REGION (SK.ITEM.REGION ARCELT))))
(RETURN))
(SETQ GARROWSPECS (fetch (ARC ARCARROWHEADS) of GARC))
(SETQ LOCALARROWPTS (fetch (LOCALARC LOCALARCARROWHEADPTS) of LARC))
(SETQ BRUSH (fetch (LOCALARC LOCALARCBRUSH) of LARC))
(SETQ DASHING (fetch (LOCALARC LOCALARCDASHING) of LARC))
(COND
[(EQ T (fetch (ARC ARCANGLEPT) of GARC)) (* T means greater than 360)
(PROG ((CPT (fetch (LOCALARC LOCALARCCENTERPT) of LARC))
(RPT (fetch (LOCALARC LOCALARCRADIUSPT) of LARC)))
(RETURN (\CIRCLE.DRAWFN1 CPT RPT (DISTANCEBETWEEN CPT RPT)
```

```

      BRUSH DASHING WINDOW]
    (T (SETQ LOCALPTS (\SK.ADJUST.FOR.ARROWHEADS (fetch (LOCALARC LOCALARCKNOTS) of LARC)
      LOCALARROWPTS GARROWSPECS WINDOW))
      (* draw the curve from the knots)
      (DRAWCURVE LOCALPTS NIL BRUSH DASHING WINDOW)))
    (DRAWARROWHEADS GARROWSPECS LOCALARROWPTS WINDOW BRUSH])

```

(ARC.EXPANDFN

[LAMBDA (GARC SCALE)

(* rrb "20-Jun-86 13:58")

(* returns a screen elt that has a arc screen element calculated from the global part.)

```

(PROG ((INDGARC (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GARC))
  CENTER RADIUSPT ANGLEPT LOCALKNOTS LOCALARROWHEADS)
  (SETQ CENTER (SK.SCALE.POSITION.INTO.VIEWER (fetch (ARC ARCCENTERPT) of INDGARC)
    SCALE))
  (SETQ RADIUSPT (SK.SCALE.POSITION.INTO.VIEWER (fetch (ARC ARCRADIUSPT) of INDGARC)
    SCALE))
  (SETQ ANGLEPT (SK.SCALE.POSITION.INTO.VIEWER (\SK.GET.ARC.ANGLEPT INDGARC)
    SCALE))
  (SETQ LOCALKNOTS (\SK.COMPUTE.ARC.PTS CENTER RADIUSPT ANGLEPT (fetch (ARC ARCDIRECTION) of INDGARC)))
  (COND
    ((AND (fetch (ARC ARCARROWHEADS) of INDGARC)
      (NOT (fetch (ARC ARCARROWHEADPOINTS) of INDGARC))))

```

(* check to make sure the global arrowhead points have been calculated. Old form didn't have them.)

```

    (SET.ARC.ARROWHEAD.POINTS INDGARC)))
  (SETQ LOCALARROWHEADS (\SK.EXPAND.ARROWHEADS (fetch (ARC ARCARROWHEADPOINTS) of INDGARC)
    SCALE))
  (RETURN (create SCREENELT
    LOCALPART _
    (create LOCALARC
      LOCALARCCENTERPT _ CENTER
      LOCALARCRADIUSPT _ RADIUSPT
      LOCALARCANGLEPT _ ANGLEPT
      LOCALARCARROWHEADPTS _ LOCALARROWHEADS
      LOCALARCBRUSH _ (SCALE.BRUSH (fetch (ARC ARCBRUSH) of INDGARC)
        (fetch (ARC ARCINITSCALE) of INDGARC)
        SCALE)
      LOCALARCKNOTS _ LOCALKNOTS
      LOCALARCDASHING _ (fetch (ARC ARCDASHING) of INDGARC))
    GLOBALPART _ GARC])

```

(ARC.INPUTFN

[LAMBDA (WINDOW)

(* rrb "20-May-86 10:53")

(* reads three points from the user and returns the arc figure element that it represents.)

```

(PROG [CENTER RADPT ANGLEPT DIRECTION (SKCONTEXT (WINDOWPROP WINDOW 'SKETCHCONTEXT)
  (SETQ DIRECTION (fetch (SKETCHCONTEXT SKETCHARCDIRECTION) of SKCONTEXT))
  (STATUSPRINT WINDOW "
    " "Indicate center of the arc")
  (COND
    ((SETQ CENTER (SK.READ.POINT.WITH.FEEDBACK WINDOW ELLIPSE.CENTER NIL NIL NIL NIL
      SKETCH.USE.POSITION.PAD))
      (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTER)
        NIL WINDOW))
      (T (CLOSEPROMPTWINDOW WINDOW)
        (RETURN NIL)))
    (STATUSPRINT WINDOW "
      " "Indicate end of the arc")
      (COND
        [(SETQ RADPT (\SK.READ.CIRCLE.POINT WINDOW (fetch (INPUTPT INPUT.POSITION) of CENTER)
          (COND
            (DIRECTION (* use a cursor that shows the arc going in the correct direction.)
              CW.ARC.RADIUS.CURSORS)
            (T ARC.RADIUS.CURSORS)
          (* erase center pt on way out)
          (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTER)
            NIL WINDOW)
          (CLOSEPROMPTWINDOW WINDOW)
          (RETURN NIL)))
          (COND
            ((NEQ SKETCH.VERBOSE.FEEDBACK 'ALWAYS) (* if feedback in medium mode, put up circle)
              (SK.INVERT.CIRCLE CENTER RADPT WINDOW))
            (T (* if feedback is in very verbose mode, just put up the radius pt.)
              (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of RADPT)
                NIL WINDOW)))
          (STATUSPRINT WINDOW "
            " "Indicate the angle of the arc")
            (SETQ ANGLEPT (\SK.READ.ARC.ANGLE.POINT WINDOW (COND
              (DIRECTION CW.ARC.ANGLE.CURSORS)
              (T ARC.ANGLE.CURSORS)

```

```

      (fetch (INPUTPT INPUT.POSITION) of CENTER)
      (fetch (INPUTPT INPUT.POSITION) of RADPT)
      DIRECTION))
(CLOSEPROMPTWINDOW WINDOW) (* erase the point marks.)
(COND
  (NEQ SKETCH.VERBOSE.FEEDBACK 'ALWAYS) (* if feedback in medium mode, put up circle)
  (SK.INVERT.CIRCLE CENTER RADPT WINDOW))
(T (* if feedback is in very verbose mode, just put up the radius pt.)
  (MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of RADPT)
    NIL WINDOW)))
(MARK.SPOT (fetch (INPUTPT INPUT.POSITION) of CENTER)
  NIL WINDOW)
(OR ANGLEPT (RETURN NIL))

(* the list of knots passed to SK.ARROWHEAD.CREATE is only used to determine right and left so don't bother to create a
good one. Actually this introduces a bug when the angle point is not on the same side of the radius point as the end of the
arc is. should fix.)

(RETURN (ARC.CREATE (SK.MAP.INPUT.PT.TO.GLOBAL CENTER WINDOW)
  (SK.MAP.INPUT.PT.TO.GLOBAL RADPT WINDOW)
  (SK.MAP.INPUT.PT.TO.GLOBAL ANGLEPT WINDOW)
  (fetch (SKETCHCONTEXT SKETCHBRUSH) of SKCONTEXT)
  (fetch (SKETCHCONTEXT SKETCHDASHING) of SKCONTEXT)
  (SK.INPUT.SCALE WINDOW)
  (SK.ARROWHEAD.CREATE WINDOW (LIST RADPT ANGLEPT))
  DIRECTION])

```

(SK.INVERT.CIRCLE

```

[LAMBDA (CENTERPT RADIUSPT SKW) (* rrb "18-Nov-85 14:36")

  (* draws a circle as feedback while the user in inputting the angle point of an arc.)

  (PROG ((PREVOP (DSOPERATION 'INVERT SKW)))
    (RETURN (PROG1 (SK.SHOW.CIRCLE (fetch (POSITION XCOORD) of (fetch (INPUTPT INPUT.POSITION) of RADIUSPT)
      (fetch (POSITION YCOORD) of (fetch (INPUTPT INPUT.POSITION) of RADIUSPT))
      SKW
      (fetch (INPUTPT INPUT.POSITION) of CENTERPT))
      (DSOPERATION PREVOP SKW])

```

(SK.READ.ARC.ANGLE.POINT

```

[LAMBDA (WINDOW CURSOR CENTERPT RADIUSPT DIRECTION) (* rrb "20-May-86 10:48")

  (* reads a point from the user prompting them with an arc that follows the cursor)

  (SK.READ.POINT.WITH.FEEDBACK WINDOW CURSOR (AND (EQ SKETCH.VERBOSE.FEEDBACK 'ALWAYS)
    (FUNCTION SK.SHOW.ARC))
    (LIST CENTERPT RADIUSPT DIRECTION)
    'MIDDLE NIL SKETCH.USE.POSITION.PAD])

```

(SK.SHOW.ARC

```

[LAMBDA (X Y WINDOW ARCARGS) (* rrb "15-Nov-85 14:32")
  (* draws an arc as feedback for reading the angle point of an arc.)
  (* Mark the point too.)

  (SHOWSKETCHXY X Y WINDOW)
  (DRAWCURVE (SK.COMPUTE.ARC.PTS (CAR ARCARGS)
    (CADR ARCARGS)
    (create POSITION
      XCOORD _ X
      YCOORD _ Y)
    (CADDR ARCARGS))
    NIL 1 NIL WINDOW])

```

(ARC.CREATE

```

[LAMBDA (CENTERPT RADPT ANGLEPT BRUSH DASHING INITSSCALE ARROWHEADS DIRECTION)
  (* rrb "19-Mar-86 17:19")
  (* creates a global arc element.)

  (PROG ((ARCANGLEPT (SK.COMPUTE.ARC.ANGLE.PT CENTERPT RADPT ANGLEPT)))
    (RETURN (SET.ARC.SCALES (create GLOBALPART
      INDIVIDUALGLOBALPART _
      (SET.ARC.ARROWHEAD.POINTS (create ARC
        ARCCENTERPT _ CENTERPT
        ARCRADIUSPT _ RADPT
        ARCBRUSH _ BRUSH
        ARCDASHING _ DASHING
        ARCINITSSCALE _ INITSSCALE
        ARCARROWHEADS _ ARROWHEADS
        ARCANGLEPT _ ARCANGLEPT
        ARCDIRECTION _ DIRECTION])

```

(SK.UPDATE.ARC.AFTER.CHANGE

```
[LAMBDA (GARCELT)
(* rrb "7-Dec-85 19:52")
(* updates the dependent fields of a arc element when a field
changes.)
(replace (ARC ARCREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GARCELT) with NIL)]
```

(ARC.MOVEFN

```
[LAMBDA (ARCELT SELPOS NEWPOS WINDOW)
(* rrb "15-Dec-86 15:19")
(* returns a global arc element which has the part SELPOS
moved to NEWPOS.)
(PROG ((LOCALEL (fetch (SCREENELT LOCALPART) of ARCELT))
(GLOBALEL (fetch (SCREENELT INDIVIDUALGLOBALPART) of ARCELT))
CENTERPT ANGLEPT RADPT PTSCALE)
(SETQ CENTERPT (fetch (ARC ARCCENTERPT) of GLOBALEL))
(SETQ ANGLEPT (fetch (ARC ARCANGLEPT) of GLOBALEL))
(SETQ RADPT (fetch (ARC ARCRADIUSPT) of GLOBALEL)) (* find the point that has moved and change it.)
[COND
((EQUAL SELPOS (fetch (LOCALARC LOCALARCCENTERPT) of LOCALEL))
(SETQ CENTERPT (SK.MAP.FROM.WINDOW.TO.GLOBAL.GRID NEWPOS WINDOW)))
((EQUAL SELPOS (fetch (LOCALARC LOCALARCANGLEPT) of LOCALEL))
(SETQ ANGLEPT (SK.MAP.FROM.WINDOW.TO.GLOBAL.GRID NEWPOS WINDOW)))
((EQUAL SELPOS (fetch (LOCALARC LOCALARCRADIUSPT) of LOCALEL))
(SETQ RADPT (SK.MAP.FROM.WINDOW.TO.GLOBAL.GRID NEWPOS WINDOW))
(* return a new global elt because the orientation changes but is needed to erase the one that is already on the screen.)
(RETURN (SK.CREATE.ARC.USING CENTERPT RADPT ANGLEPT (fetch (SCREENELT GLOBALPART) of ARCELT)))]
```

(ARC.TRANSLATEPTS

```
[LAMBDA (ARCELT SELPTS GLOBALDELTA WINDOW)
(* rrb "15-Dec-86 15:19")
(* returns a new global arc element which has the points on SELPTS moved by a global distance.)
(PROG ((LOCALEL (fetch (SCREENELT LOCALPART) of ARCELT))
(GLOBALEL (fetch (SCREENELT INDIVIDUALGLOBALPART) of ARCELT))
CENTERPT ANGLEPT RADPT PTSCALE)
(SETQ CENTERPT (fetch (ARC ARCCENTERPT) of GLOBALEL))
(SETQ ANGLEPT (fetch (ARC ARCANGLEPT) of GLOBALEL))
(SETQ RADPT (fetch (ARC ARCRADIUSPT) of GLOBALEL)) (* find the point that has moved and change it.)
[COND
((MEMBER (fetch (LOCALARC LOCALARCCENTERPT) of LOCALEL)
SELPTS)
(SETQ CENTERPT (PTPLUS CENTERPT GLOBALDELTA))
[COND
((MEMBER (fetch (LOCALARC LOCALARCRADIUSPT) of LOCALEL)
SELPTS)
(SETQ RADPT (PTPLUS RADPT GLOBALDELTA))
[COND
((MEMBER (fetch (LOCALARC LOCALARCANGLEPT) of LOCALEL)
SELPTS)
(COND
[EQ ANGLEPT T]
(* user moved the point that is both the radius pt and the angle pt.
If it was the only point moved, don't move the angle pt, just the radius pt.)
(COND
((NULL (CDR SELPTS))
(SETQ ANGLEPT (fetch (ARC ARCRADIUSPT) of GLOBALEL))
(T (SETQ ANGLEPT (PTPLUS ANGLEPT GLOBALDELTA))
(RETURN (SK.CREATE.ARC.USING CENTERPT RADPT ANGLEPT (fetch (SCREENELT GLOBALPART) of ARCELT)))]
```

(ARC.INSIDFN

```
[LAMBDA (GARC WREG)
(* rrb "20-Jan-87 14:44")
(* determines if the global arc GARC is inside of WREG.)
(REGIONSINTERSECTP WREG (ARC.GLOBALREGIONFN GARC))
```

(ARC.REGIONFN

```
[LAMBDA (ARCSCRELT)
(* rrb "30-May-85 12:23")
(* returns the region occupied by an arc.)
(* uses the heuristic that the region containing the curve is not more than 10% larger than the knots.
This was determined empirically on several curves.)
```

```
(INCREASEREGION (EXPANDREGION (REGION.CONTAINING.PTS (fetch (LOCALARC LOCALARCKNOTS)
of (fetch (SCREENELT LOCALPART) of ARCSCRELT)))
1.1)
(IQUOTIENT [ADD1 (SK.BRUSH.SIZE (fetch (LOCALARC LOCALARCBRUSH) of (fetch (SCREENELT LOCALPART)
of ARCSCRELT))
2])
```

(ARC.GLOBALREGIONFN

```
[LAMBDA (GARCELT)
(* rrb "20-Jun-86 14:04")
```


(* returns the global region occupied by a global arc element.)

```
(OR (fetch (ARC ARCREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GARCELT))
  (PROG ((INDVARC (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GARCELT))
        REGION)
```

(* uses the heuristic that the region containing the curve is not more than 10% larger than the knots. This was determined empirically on several curves.)

```
[SETQ REGION (INCREASEREGION (EXPANDREGION (REGION.CONTAINING.PTS (SK.COMPUTE.ARC.PTS
  (fetch (ARC ARCCENTERPT)
    of INDVARC)
  (fetch (ARC ARCRADIUSPT)
    of INDVARC)
  (SK.GET.ARC.ANGLEPT INDVARC
  )
  (fetch (ARC ARCDIRECTION)
    of INDVARC)))
  1.1)
  (SK.BRUSH.SIZE (fetch (ARC ARCBRUSH) of INDVARC)]
(replace (ARC ARCREGION) of INDVARC with REGION)
(RETURN REGION])
```

(ARC.TRANSLATE

```
[LAMBDA (GARCELT DELTAPOS)
  (* rrb "15-Dec-86 15:20")
  (* returns a global arc element which has the arc translated by DELTAPOS.)
  (PROG ((GLOBALEL (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GARCELT)))
    (RETURN (SK.CREATE.ARC.USING (PTPLUS (fetch (ARC ARCCENTERPT) of GLOBALEL)
      DELTAPOS)
      (PTPLUS (fetch (ARC ARCRADIUSPT) of GLOBALEL)
        DELTAPOS)
      (COND
        ((POSITIONP (fetch (ARC ARCANGLEPT) of GLOBALEL))
          (PTPLUS (fetch (ARC ARCANGLEPT) of GLOBALEL)
            DELTAPOS))
        (T
          T))
      GARCELT])
  (* T marks greater than 360)
```

(ARC.TRANSFORMFN

```
[LAMBDA (GELT TRANSFORMFN TRANSFORMDATA SCALEFACTOR)
  (* rrb "15-Dec-86 15:20")
  (* returns a copy of the global element that has had each of its control points transformed by transformfn. TRANSFORMDATA is arbitrary data that is passed to tranformfn.)
  (PROG ((INDVPART (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
    NEWGELT)
    (SETQ NEWGELT (SK.CREATE.ARC.USING (SK.TRANSFORM.POINT (fetch (ARC ARCCENTERPT) of INDVPART)
      TRANSFORMFN TRANSFORMDATA)
      (SK.TRANSFORM.POINT (fetch (ARC ARCRADIUSPT) of INDVPART)
        TRANSFORMFN TRANSFORMDATA)
      (COND
        ((POSITIONP (fetch (ARC ARCANGLEPT) of INDVPART))
          (SK.TRANSFORM.POINT (fetch (ARC ARCANGLEPT) of INDVPART)
            TRANSFORMFN TRANSFORMDATA))
        (T
          T))
      GELT))
    (* update the brush too.)
    (replace (ARC ARCBRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of NEWGELT)
      with (SK.TRANSFORM.BRUSH (fetch (ARC ARCBRUSH) of INDVPART)
        SCALEFACTOR))
    (replace (ARC ARCARROWHEADS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of NEWGELT)
      with (SK.TRANSFORM.ARROWHEADS (fetch (ARC ARCARROWHEADS) of INDVPART)
        SCALEFACTOR))
    (SET.ARC.ARROWHEAD.POINTS (fetch (GLOBALPART INDIVIDUALGLOBALPART) of NEWGELT))
    [AND (EQ TRANSFORMFN 'SK.APPLY.AFFINE.TRANSFORM)
      (COND
        ([COND
          [(GREATERP 0.0 (fetch (AFFINETRANSFORMATION Ax) of TRANSFORMDATA))
            (* x coord is reflected, switch direction unless Y is reflected also.)
            (NOT (GREATERP 0.0 (fetch (AFFINETRANSFORMATION Ey) of TRANSFORMDATA)]
              (T (GREATERP 0.0 (fetch (AFFINETRANSFORMATION Ey)
                TRANSFORMDATA)
                (* change the direction if the transformation reflects.)
                (replace (ARC ARCDIRECTION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of NEWGELT)
                  with (NOT (fetch (ARC ARCDIRECTION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART)
                    (RETURN NEWGELT]))
```

(ARC.READCHANGEFN

```
[LAMBDA (SKW SCRNETS)
  (* rrb "17-Dec-85 16:22")
  (* changefn for arcs)
  (PROG (ASPECT HOW)
    (SETQ HOW (SELECTQ [SETQ ASPECT (\CURSOR.IN.MIDDLE.MENU (create MENU
      CENTERFLG _ T
      TITLE _ "Which aspect?")
```

```

ITEMS _
(APPEND
[COND
  ((SKETCHINCOLORP)
  ' ((Color 'BRUSHCOLOR "changes the
    color of the outline"]
  ' ((Arrowheads 'ARROW "allows changing
    of arrow head
    characteristics.")
  (Size 'SIZE "changes the size of the
    brush")
  (Angle 'ANGLE "changes the amount of
    angle in the arc.")
  (Dashing 'DASHING "changes the
    dashing of the line.")
  (Direction 'DIRECTION "changes which
    way around the circle the arc
    is drawn."]

```

```

(SIZE (READSIZECHANGE "Change size how?"))
(ANGLE (READANGLE))
(ARROW (READ.ARROW.CHANGE SCRNELTS))
(DASHING (READ.DASHING.CHANGE))
(DIRECTION (READARCDIRECTION))
(BRUSHCOLOR [READ.COLOR.CHANGE "Change color how?" NIL
  (fetch (BRUSH BRUSHCOLOR) of (GETSKETCHELEMENTPROP
    (fetch (SCREENELT GLOBALPART)
      of (CAR SCRNELTS))
    ' BRUSH])

```

```

NIL))
(RETURN (AND HOW (LIST ASPECT HOW]))

```

)

(DEFINEQ

(SK.COMPUTE.ARC.ANGLE.PT

[LAMBDA (CENTERPT RADPT ANGLEPT)

(* rrb "26-Jun-86 17:04")

(* computes the intersection of the line CENTERPT ANGLEPT with the circle with center CENTERPT that goes through RADPT.)

(COND

((EQ ANGLEPT T)

(* used to mark more than 360.0)

T)

(T (PROG ((RADIUS (**DISTANCEBETWEEN** CENTERPT RADPT))
 (ARCANGLE (**SK.COMPUTE.SLOPE.OF.LINE** CENTERPT ANGLEPT))))

(RETURN (**create** POSITION

XCOORD _ (PLUS (**fetch** (POSITION XCOORD) **of** CENTERPT)
 (TIMES RADIUS (COS ARCANGLE)))

YCOORD _ (PLUS (**fetch** (POSITION YCOORD) **of** CENTERPT)
 (TIMES RADIUS (SIN ARCANGLE]))

(SK.COMPUTE.ARC.ANGLE.PT.FROM.ANGLE

[LAMBDA (CENTERPT RADPT ANGLE)

(* rrb " 7-Jul-86 14:49")

(* computes the point on the circle with center CENTERPT that goes through RADPT that is angle ANGLE from RADPT.)

(COND

((OR (GEQ ANGLE 360.0)

(LEQ ANGLE -360.0))

(* T denotes all the way around.)

T)

(T (PROG ((RADIUS (**DISTANCEBETWEEN** CENTERPT RADPT))
 (DELTA (PLUS (**SK.COMPUTE.SLOPE.OF.LINE** CENTERPT RADPT)
 ANGLE))))

(RETURN (**create** POSITION

XCOORD _ (PLUS (**fetch** (POSITION XCOORD) **of** CENTERPT)
 (TIMES RADIUS (COS DELTA)))

YCOORD _ (PLUS (**fetch** (POSITION YCOORD) **of** CENTERPT)
 (TIMES RADIUS (SIN DELTA]))

(SK.COMPUTE.ARC.PTS

[LAMBDA (CENTERPT RADIUSPT ARCPT DIRECTION)

(* DECLARATIONS%: FLOATING)

(* rrb " 5-May-86 14:11")

(* computes a list of knots that a spline goes through to make an

arc)

(PROG ((RADIUS (**DISTANCEBETWEEN** CENTERPT RADIUSPT))
 (ALPHA (**SK.COMPUTE.SLOPE.OF.LINE** CENTERPT RADIUSPT))
 (OMEGA (**SK.COMPUTE.SLOPE.OF.LINE** CENTERPT ARCPT))
 (CENTERX (**fetch** (POSITION XCOORD) **of** CENTERPT))
 (CENTERY (**fetch** (POSITION YCOORD) **of** CENTERPT))
 PTLST ANGLEINCR DEGREESARC)

[COND

[DIRECTION

(* if non-NIL go in a counterclockwise direction.)

(COND

((GREATERP OMEGA ALPHA)

```

      (SETQ OMEGA (DIFFERENCE OMEGA 360.0])
    (T (COND
      ((GREATERP ALPHA OMEGA)
        (SETQ OMEGA (PLUS OMEGA 360.0]
          (* angle crosses angle change point, correct.)
      )
    )
    (* calculate an increment close to 10.0 that is exact but always have at least 5 knots and don't have more than a knot every 5 pts)
    [SETQ ANGLEINCR (FQUOTIENT (SETQ DEGREESARC (DIFFERENCE OMEGA ALPHA))
      (IMIN (IMAX (ABS (FIX (FQUOTIENT DEGREESARC 10.0)))
        5)
      (PROGN
        (IMAX (ABS (FIX (QUOTIENT (TIMES RADIUS 6.3 (QUOTIENT DEGREESARC 360.0))
          4)))
        3]
        (* don't have more than a knot every 5 pts)
    )
  )

```

(* go from initial point to just past the last point. The just past (PLUS OMEGA (QUOTIENT ANGLEINCR 5.0)) picks up the case where the floating pt rounding error accumulates to be greater than the last point when it is very close to it.)

```

[SETQ PTLST (for ANGLE from ALPHA to (PLUS OMEGA (QUOTIENT ANGLEINCR 5.0)) by ANGLEINCR
  collect (create POSITION
    XCOORD _ (PLUS CENTERX (TIMES RADIUS (COS ANGLE)))
    YCOORD _ (PLUS CENTERY (TIMES RADIUS (SIN ANGLE]
      (* add first and last points exactly.
      (CONS RADIUSPT (NCONC1 PTLST
        (create POSITION XCOORD _ (FIXR
          PLUS CENTERX (TIMES RADIUS
            COS OMEGA)))) YCOORD _ (FIXR
          PLUS CENTERY (TIMES RADIUS
            SIN OMEGA)))))))]
(RETURN PTLST])

```

(SK.SET.ARC.DIRECTION

```

[LAMBDA (SKW NEWDIR)
  (* rrb "31-May-85 17:29")

```

(* * reads a value of arc direction and makes it the default)

```

(PROG [(LOCALNEWDIR (OR NEWDIR (READARCDIRECTION "Which way should new arcs go?")
  (RETURN (AND LOCALNEWDIR (replace (SKETCHCONTEXT SKETCHARCDIRECTION) of (WINDOWPROP SKW 'SKETCHCONTEXT)
    with (EQ LOCALNEWDIR 'CLOCKWISE))

```

(SK.SET.ARC.DIRECTION.CW

```

[LAMBDA (SKW)
  (SK.SET.ARC.DIRECTION SKW 'CLOCKWISE])
  (* sets the default to clockwise)

```

(SK.SET.ARC.DIRECTION.CCW

```

[LAMBDA (SKW)
  (SK.SET.ARC.DIRECTION SKW 'COUNTERCLOCKWISE])
  (* sets the default direction of arcs to counterclockwise)

```

(SK.COMPUTE.SLOPE.OF.LINE

```

[LAMBDA (PT1 PT2)
  (SK.COMPUTE.SLOPE (DIFFERENCE (fetch (POSITION XCOORD) of PT2)
    (fetch (POSITION XCOORD) of PT1))
    (DIFFERENCE (fetch (POSITION YCOORD) of PT2)
      (fetch (POSITION YCOORD) of PT1]))
  (* rrb "31-May-85 12:26")
  (* computes the angle of a line)

```

(SK.CREATE.ARC.USING

```

[LAMBDA (CENTERPT RADPT ANGLEPT GARCELT)
  (SET.ARC.SCALES (create GLOBALPART
    COMMONGLOBALPART _ (APPEND (fetch (GLOBALPART COMMONGLOBALPART) of GARCELT))
    INDIVIDUALGLOBALPART _ (SET.ARC.ARROWHEAD.POINTS (create ARC
      using (fetch (GLOBALPART
        INDIVIDUALGLOBALPART
          )
        of GARCELT)
      ARCCENTERPT _ CENTERPT
      ARCRADIUSPT _ RADPT
      ARCANGLEPT
      (SK.COMPUTE.ARC.ANGLE.PT
        CENTERPT RADPT ANGLEPT)
      ARCREGION _ NIL])
    (* rrb "15-Dec-86 15:20")
    (* creates an arc global element that is like another one but has

```

different positions.)

```

    )
  )

```

(SET.ARC.SCALES

```

[LAMBDA (GARCELT)
  (* rrb "30-May-85 11:33")

```

(* updates the scale fields of an arc. Called upon creation and when a point is moved.)

```
(PROG [(RAD (DISTANCEBETWEEN (fetch (ARC ARCCENTERPT) of (fetch (GLOBALPART INDIVIDUALGLOBALPART)
of GARCELT))
(fetch (ARC ARCRADIUSPT) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GARCELT]
(replace (GLOBALPART MAXSCALE) of GARCELT with RAD)
(replace (GLOBALPART MINSCALE) of GARCELT with (QUOTIENT RAD 3000.0))
(RETURN GARCELT])
)
```

(DEFINEQ

(SK.INSURE.DIRECTION

(* rrb "16-Oct-85 16:11")

[LAMBDA (DIR)

(* decodes a DIRECTION spec which indicates whether an arc goes clockwise or counterclockwise.
T is CLOCKWISE. NIL is COUNTERCLOCKWISE.)

```
(SELECTQ DIR
((NIL COUNTERCLOCKWISE)
NIL)
((T CLOCKWISE)
T)
(\ILLEGAL.ARC DIR])
)
```

(RPAQ? **SK.NUMBER.OF.POINTS.IN.ARC** 8)

(DECLARE%: DOEVAL@COMPILE DONTCOPY


(GLOBALVARS SK.NUMBER.OF.POINTS.IN.ARC)


(DECLARE%: DONTCOPY


(DECLARE%: EVAL@COMPILE


(TYPEARECORD ARC (ARCCENTERPT ARCRADIUSPT ARCRBRUSH ARCDASHING ARCINITSSCALE ARCARROWHEADS ARCANGLEPT ARCDIRECTION
ARCREGION ARCARROWHEADPOINTS))

(RECORD LOCALARC ((LOCALARCCENTERPT LOCALARCRADIUSPT LOCALARCANGLEPT)
LOCALHOTREGION LOCALARCARROWHEADPTS LOCALARCRBRUSH LOCALARCKNOTS LOCALARCDASHING))

(RPAQ **ARC.RADIUS.CURSOR** (CURSORCREATE ' 
'NIL 15 7))

(RPAQ **ARC.ANGLE.CURSOR** (CURSORCREATE ' 
'NIL 7 15))

(RPAQ **CW.ARC.ANGLE.CURSOR** (CURSORCREATE ' 
'NIL 7 15))

(RPAQ **CW.ARC.RADIUS.CURSOR** (CURSORCREATE ' 
'NIL 15 7))

```
(READVARS-FROM-STRINGS '(ARCICON)
"({ (READBITMAP) (20 13
% " @ @ @ @ @ @ @ @ % "
% " @ A O H @ @ @ @ % "
% " @ C O L @ @ @ @ % "
% " @ G @ N @ @ @ @ % "
% " @ F @ F @ @ @ @ % "
% " @ N @ G @ @ @ @ % "
% " @ L @ C @ @ @ @ % "
% " @ @ @ C @ @ @ @ % "
% " @ @ @ G @ @ @ @ % "
% " @ @ @ F @ @ @ @ % "
% " @ @ @ N @ @ @ @ % "
% " @ @ @ L @ @ @ @ % "
% " @ @ @ @ @ @ @ @ % " ) } )
")
```

:: property getting and setting stuff

(DEFINEQ

(GETSKETCHELEMENTPROP

[LAMBDA (ELEMENT PROPERTY)

(* rrb "26-Jun-86 14:16")

(* gets the property from a sketch element.)

(* knows about and sets the system ones specially. All others go to the elements property list.)

```
(SELECTQ PROPERTY
  (TYPE (fetch (GLOBALPART GTYPE) of ELEMENT))
  (SCALE (\SKELT.GET.SCALE ELEMENT))
  (REGION (SK.ELEMENT.GLOBAL.REGION ELEMENT))
  ((POSITION 1STCONTROLPT
    (\SK.GET.1STCONTROLPT ELEMENT))
  (2NDCONTROLPT (\SK.GET.2NDCONTROLPT ELEMENT))
  (3RDCONTROLPT (\SK.GET.3RDCONTROLPT ELEMENT))
  (DATA (\SKELT.GET.DATA ELEMENT))
  (BRUSH (\SK.GET.BRUSH ELEMENT))
  (FILLING (\SK.GET.FILLING ELEMENT))
  (DASHING (\SK.GET.DASHING ELEMENT))
  (ARROWHEADS (\SK.GET.ARROWHEADS ELEMENT))
  (FONT (\SK.GET.FONT ELEMENT))
  (JUSTIFICATION
    (\SK.GET.JUSTIFICATION ELEMENT))
  (DIRECTION (\SK.GET.DIRECTION ELEMENT))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of ELEMENT)
    PROPERTY])
```

\SK.GET.ARC.ANGLEPT

[LAMBDA (INDVARCELT)

(* rrb "20-Jun-86 13:54")

(* returns the arc point of an individual arc element. Special because T is used to denote arcs of greater than 360 degrees.)

```
(COND
  ((POSITIONP (fetch (ARC ARCCANGLEPT) of INDVARCELT)))
  (T
    (* for arcs of greater than 360 degrees, the radiuspt is T and is marked as being the same as the radius pt.)
    (fetch (ARC ARCRADIUSPT) of INDVARCELT]))
```

\GETSKETCHELEMENTPROP1

[LAMBDA (ELEMENT PROPERTY)

(* * version of GETSKETCHELEMENTPROP that doesn't look for system properties.)

```
(LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of ELEMENT)
  PROPERTY])
```

\SK.GET.BRUSH

[LAMBDA (GELT)

(* rrb " 7-Dec-85 19:52")

(* gets the brush field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  ((WIRE CLOSEDWIRE OPENCURVE CLOSEDCURVE BOX)
    (fetch (WIRE BRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  ((CIRCLE ARC)
    (fetch (CIRCLE BRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (ELLIPSE (fetch (ELLIPSE BRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (TEXTBOX (fetch (TEXTBOX TEXTBOXBRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'BRUSH])
```

\SK.GET.FILLING

[LAMBDA (GELT)

(* rrb " 7-Dec-85 18:58")

(* gets the filling field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  ((CLOSEDWIRE CLOSEDCURVE BOX)
    (fetch (CLOSEDWIRE CLOSEDWIREFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (CIRCLE (fetch (CIRCLE CIRCLEFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (ELLIPSE (fetch (ELLIPSE ELLIPSEFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (TEXTBOX (fetch (TEXTBOX TEXTBOXFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'FILLING])
```

\SK.GET.ARROWHEADS

[LAMBDA (GELT)

(* rrb " 7-Dec-85 19:17")

(* gets the arrowhead field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  (WIRE (fetch (WIRE WIREARROWHEADS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (OPENCURVE (fetch (OPENCURVE CURVEARROWHEADS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (ARC (fetch (ARC ARCARROWHEADS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'ARROWHEADS])
```

\SK.GET.FONT

[LAMBDA (GELT)

(* rrb " 7-Dec-85 19:22")

(* gets the font field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  ((TEXT TEXTBOX)
   (fetch (TEXT FONT) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'FONT])
```

(\SK.GET.JUSTIFICATION

[LAMBDA (GELT)

; Edited 8-Jan-87 19:46 by rrb
(* gets the justification field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  ((TEXT TEXTBOX)
   (fetch (TEXT TEXTSTYLE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'JUSTIFICATION])
```

(\SK.GET.DIRECTION

[LAMBDA (GELT)

(* rrb " 7-Dec-85 19:21")
(* gets the direction field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  (ARC (fetch (ARC ARCDIRECTION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'DIRECTION])
```

(\SK.GET.DASHING

[LAMBDA (GELT)

(* rrb " 7-Dec-85 20:05")
(* gets the dashing field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  ((WIRE CIRCLE ARC)
   (fetch (WIRE OPENWIREDASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  ((CLOSEDWIRE OPENCURVE CLOSEDCURVE BOX)
   (fetch (CLOSEDWIRE CLOSEDWIREDASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (ELLIPSE (fetch (ELLIPSE DASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (TEXTBOX (fetch (TEXTBOX TEXTBOXDASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'DASHING])
```

(PUTSKECHELEMENTPROP

[LAMBDA (ELEMENT PROPERTY VALUE SKETCHTOUPDATE)

(* rrb "26-Jun-86 16:46")
(* puts the property from a sketch element.)

(* knows about and sets the system ones specially. All others go to the elements property list.)
(* mostly not implemented yet.)

```
(PROG1 (GETSKECHELEMENTPROP ELEMENT PROPERTY)
  (AND (SELECTQ PROPERTY
    (TYPE (ERROR "Can't change types"))
    (SCALE (\SKELT.PUT.SCALE ELEMENT VALUE)
      T)
    (REGION (ERROR "Not implemented yet.))
    ((POSITION 1STCONTROLPT)
     (\SK.PUT.1STCONTROLPT ELEMENT VALUE))
    (2NDCONTROLPT (\SK.PUT.2NDCONTROLPT ELEMENT VALUE))
    (3RDCONTROLPT (\SK.PUT.3RDCONTROLPT ELEMENT VALUE))
    (DATA (\SKELT.PUT.DATA ELEMENT VALUE SKETCHTOUPDATE))
    (BRUSH (\SK.PUT.BRUSH ELEMENT VALUE SKETCHTOUPDATE))
    (FILLING (\SK.PUT.FILLING ELEMENT VALUE))
    (DASHING (\SK.PUT.DASHING ELEMENT VALUE))
    (ARROWHEADS (\SK.PUT.ARROWHEADS ELEMENT VALUE))
    (FONT (\SK.PUT.FONT ELEMENT VALUE))
    (JUSTIFICATION
     (\SK.PUT.JUSTIFICATION ELEMENT VALUE))
    (DIRECTION (\SK.PUT.DIRECTION ELEMENT VALUE))
    (PROG ((PLIST (fetch (GLOBALPART SKELEMENTPROPLIST) of ELEMENT)))
     [COND
      (PLIST (LISTPUT PLIST PROPERTY VALUE))
      (T (replace (GLOBALPART SKELEMENTPROPLIST) of ELEMENT with (LIST PROPERTY VALUE)
        be redisplayed.)
        (RETURN NIL)))
    SKETCHTOUPDATE
    (SKETCH.UPDATE SKETCHTOUPDATE ELEMENT))))])
```

(\SK.PUT.FILLING

[LAMBDA (GELT NEWVALUE)

(* rrb "26-Jun-86 16:44")
(* sets the filling field from a global sketch element instance.)

```
(OR (SKFILLINGP NEWVALUE)
  (\ILLEGAL.ARG NEWVALUE))
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  ((CLOSEDWIRE CLOSEDCURVE BOX)
   (replace (CLOSEDWIRE CLOSEDWIREFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
    with NEWVALUE))
```

```

(CIRCLE (replace (CIRCLE CIRCLEFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE)
)
(ELLIPSE (replace (ELLIPSE ELLIPSEFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
with NEWVALUE))
(TEXTBOX (replace (TEXTBOX TEXTBOXFILLING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
with NEWVALUE))
(LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
'FILLING NEWVALUE))
T])

```

(ADDSKETCHELEMENTPROP

```

[LAMBDA (ELEMENT PROPERTY VALUE SKETCHTOUPDATE) (* rrb "11-Dec-85 15:17")

```

(* adds a value to the list of values for a property of a sketch element.)

```

(PROG ((NOWVALUE (GETSKETCHELEMENTPROP ELEMENT PROPERTY)))
(RETURN (PUTSKETCHELEMENTPROP ELEMENT PROPERTY [COND
(NULL NOWVALUE)
(LIST VALUE))
(NLISTP NOWVALUE)
(LIST NOWVALUE VALUE))
(T (APPEND NOWVALUE (CONS VALUE)
SKETCHTOUPDATE]))

```

(REMOVESKETCHELEMENTPROP

```

[LAMBDA (ELEMENT PROPERTY VALUE SKETCHTOUPDATE) (* rrb "11-Dec-85 15:17")

```

(* removes a value to the list of values for a property of a sketch element.)

```

(PROG ((NOWVALUE (GETSKETCHELEMENTPROP ELEMENT PROPERTY)))
(RETURN (PUTSKETCHELEMENTPROP ELEMENT PROPERTY (COND
(EQ NOWVALUE VALUE)
NIL)
(NLISTP NOWVALUE)
NOWVALUE)
(T (REMOVE VALUE NOWVALUE))))
SKETCHTOUPDATE])

```

(\SK.PUT.FONT

```

[LAMBDA (GELT NEWVALUE) (* rrb "26-Jun-86 17:04")

```

(* sets the font field from a global sketch element instance.)

```

(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
(TEXT (replace (TEXT FONT) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with (SK.INSURE.TEXT
NEWVALUE))
(SK.UPDATE.TEXT.AFTER.CHANGE GELT))
(TEXTBOX (replace (TEXTBOX FONT) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with (SK.INSURE.TEXT
NEWVALUE))
(SK.UPDATE.TEXTBOX.AFTER.CHANGE GELT))
(LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
'FONT NEWVALUE))
T])

```

(\SK.PUT.JUSTIFICATION

```

[LAMBDA (GELT NEWVALUE) (* rrb "26-Jun-86 16:45")

```

(* sets the justification field from a global sketch element instance.)

```

(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
(TEXT (replace (TEXT TEXTSTYLE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
with (SK.INSURE.STYLE NEWVALUE SK.DEFAULT.TEXT.ALIGNMENT))
(SK.UPDATE.TEXT.AFTER.CHANGE GELT))
(TEXTBOX (replace (TEXTBOX TEXTSTYLE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
with (SK.INSURE.STYLE NEWVALUE SK.DEFAULT.TEXT.ALIGNMENT))
(SK.UPDATE.TEXTBOX.AFTER.CHANGE GELT))
(LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
'JUSTIFICATION NEWVALUE))
T])

```

(\SK.PUT.DIRECTION

```

[LAMBDA (GELT NEWVALUE) (* rrb "26-Jun-86 16:45")

```

(* puts the direction field from a global sketch element instance.)

```

(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
(ARC (replace (ARC ARCDIRECTION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with (
SK.INSURE.DIRECTION
NEWVALUE))
(SK.UPDATE.ARC.AFTER.CHANGE GELT))
(LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
'DIRECTION NEWVALUE))
T])

```

(\SK.PUT.DASHING

```

[LAMBDA (GELT NEWVALUE) (* rrb "26-Jun-86 16:44")

```

(* sets the dashing field of a global sketch element.)

```
(OR (NULL NEWVALUE)
  (DASHINGP NEWVALUE)
  (\ILLEGAL.ARG NEWVALUE))
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  ((WIRE CIRCLE ARC)
    (replace (WIRE OPENWIREDASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE))
  ((CLOSEDWIRE OPENCURVE CLOSEDCURVE BOX)
    (replace (CLOSEDWIRE CLOSEDWIREDASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
      with NEWVALUE))
  (ELLIPSE (replace (ELLIPSE DASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE))
  (TEXTBOX (replace (TEXTBOX TEXTBOXDASHING) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
    with NEWVALUE))
  (LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'DASHING NEWVALUE))
T])
```

(\SK.PUT.BRUSH

[LAMBDA (GELT NEWVALUE SKETCHTOUPDATE)

(* rrb "26-Jun-86 16:44")

(* sets the brush field from a global sketch element instance.)

```
(COND
  [(NUMBERP NEWVALUE)
    (SETQ NEWVALUE (create BRUSH
      BRUSHSIZE _ NEWVALUE
      BRUSHSHAPE _ 'ROUND)
      ((BRUSHP NEWVALUE))
      (T (\ILLEGAL.ARG NEWVALUE)))
    (SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
      ((WIRE CLOSEDWIRE OPENCURVE CLOSEDCURVE)
        (replace (WIRE BRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE)
        (SK.UPDATE.WIRE.AFTER.CHANGE GELT))
      (BOX (replace (BOX BRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE))
      (CIRCLE (replace (CIRCLE BRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE)
        (SK.UPDATE.CIRCLE.AFTER.CHANGE GELT))
      (ARC (replace (ARC ARCBRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE)
        (SK.UPDATE.ARC.AFTER.CHANGE GELT))
      (ELLIPSE (replace (ELLIPSE BRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE)
        (SK.UPDATE.ELLIPSE.AFTER.CHANGE GELT))
      (TEXTBOX (AND SKETCHTOUPDATE (SKETCH.CLEANUP SKETCHTOUPDATE))
        (replace (TEXTBOX TEXTBOXBRUSH) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE)
        (SK.UPDATE.TEXTBOX.AFTER.CHANGE GELT))
      (LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
        'BRUSH NEWVALUE))
    T])
```

(\SK.PUT.ARROWHEADS

[LAMBDA (GELT NEWVALUE)

; Edited 21-Aug-2021 20:01 by larry

(* sets the arrowhead field from a global sketch element instance.)

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
  (WIRE (replace (WIRE WIREARROWHEADS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
    with (SK.INSURE.ARROWHEADS NEWVALUE))
    (SET.WIRE.ARROWHEAD.POINTS (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (OPENCURVE (replace (OPENCURVE CURVEARROWHEADS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
    with (SK.INSURE.ARROWHEADS NEWVALUE))
    (SET.OPENCURVE.ARROWHEAD.POINTS (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (ARC (replace (ARC ARCARROWHEADS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with (
    SK.INSURE.ARROWHEADS
    NEWVALUE))
    (SET.ARC.ARROWHEAD.POINTS (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
  (LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    'ARROWHEADS NEWVALUE))
T])
```

(\SK.COPY.ELEMENT.PROPERTY.LIST

[LAMBDA (ELEMENT OLDELEMENT)

(* rrb " 6-May-86 11:01")

(* copies the property list of an element from OLDELEMENT if it is given, from itself otherwise.)

```
(replace (GLOBALPART SKELEMENTPROPLIST) of ELEMENT with (APPEND (fetch (GLOBALPART SKELEMENTPROPLIST)
  of (OR OLDELEMENT ELEMENT))
```

(\SKETCH.UPDATE

[LAMBDA (SKETCH ELEMENTS)

(* rrb " 6-Dec-85 14:40")

(* updates all or part of a sketch.)

```
(PROG ((SKSTRUC (INSURE.SKETCH SKETCH))
  ALLVIEWERS)
  (SETQ ALLVIEWERS (ALL.SKETCH.VIEWERS SKSTRUC))
  (COND
    ((NULL ELEMENTS)
      (for SKW in ALLVIEWERS do (SK.UPDATE.AFTER.SCALE.CHANGE SKW)))
    ((GLOBALELEMENTP ELEMENTS)
```



```
(SKETCH.UPDATE1 ELEMENTS ALLVIEWERS))
(LISTP ELEMENTS)
(for ELT in ELEMENTS do (SKETCH.UPDATE1 ELT ALLVIEWERS))
(T (\ILLEGAL.ARG ELEMENTS])
```

(SKETCH.UPDATE1

```
[LAMBDA (GELT VIEWERS) (* rrb "26-Sep-86 14:49")
(* updates the element GELT in the sketch viewers VIEWERS.)
(bind SELECTION for SKW in VIEWERS do (COND
((AND [SCREENELEMENTP (SETQ SELECTION (fetch (TEXTELTSELECTION
SKTEXTELT)
of (WINDOWPROP SKW
'SELECTION])
(EQ GELT (fetch (SCREENELT GLOBALPART) of SELECTION)))
(* if the element being updated is the current text selection, clear
the selection.)
(SKED.CLEAR.SELECTION SKW)))
(SK.UPDATE.ELEMENT1 GELT GELT SKW T])
```

(\SKELT.GET.SCALE

```
[LAMBDA (GELT) (* rrb "29-Oct-85 13:44")
(* gets the scale field from a global sketch element instance.)
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
((TEXT TEXTBOX SKIMAGEOBJ BITMAPELT)
(fetch (TEXT INITIALSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
((WIRE OPENCURVE CIRCLE ARC)
(fetch (WIRE OPENWIREINITSSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
((CLOSEDWIRE CLOSEDCURVE BOX)
(fetch (CLOSEDWIRE CLOSEDWIREINITSSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
(ELLIPSE (fetch (ELLIPSE ELLIPSEINITSSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
NIL])
```

(\SKELT.PUT.SCALE

```
[LAMBDA (GELT NEWVALUE) (* rrb "16-Oct-85 21:24")
(* sets the scale field of a global sketch element instance.)
(COND
((NUMBERP NEWVALUE)
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
((TEXT TEXTBOX SKIMAGEOBJ BITMAPELT)
(replace (TEXT INITIALSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT) with NEWVALUE))
((WIRE OPENCURVE CIRCLE ARC)
(replace (WIRE OPENWIREINITSSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
with NEWVALUE))
((CLOSEDWIRE CLOSEDCURVE BOX)
(replace (CLOSEDWIRE CLOSEDWIREINITSSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
with NEWVALUE))
(ELLIPSE (replace (ELLIPSE ELLIPSEINITSSCALE) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)
with NEWVALUE))
NIL))
(T (\ILLEGAL.ARG NEWVALUE])
```

(\SKELT.PUT.DATA

```
[LAMBDA (GELT NEWVALUE SKETCHTOUPDATE) (* rrb "26-Jun-86 16:40")
(* changes the data of a sketch element.)
(* this is harder than it seems because all of the dependent fields must be updated also -
lots of grubby details duplicated.)
(PROG ((INDVELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
(GROUP (COND
([OR (NLISTP NEWVALUE)
(NOT (EVERY NEWVALUE (FUNCTION GLOBALELEMENTP]
(\ILLEGAL.ARG NEWVALUE)))
(replace (GROUP LISTOFGLOBALELTS) of INDVELT with NEWVALUE)
(SK.UPDATE.GROUP.AFTER.CHANGE GELT))
((TEXT TEXTBOX) (* before changing the text element, make sure any interactive
editing is closed off.)
(AND SKETCHTOUPDATE (SKETCH.CLEANUP SKETCHTOUPDATE))
(SK.REPLACE.TEXT.IN.ELEMENT GELT (SK.INSURE.TEXT NEWVALUE)))
(BITMAPELT (replace (BITMAPELT SKBITMAP) of INDVELT with NEWVALUE))
(SKIMAGEOBJ (replace (SKIMAGEOBJ SKIMAGEOBJ) of INDVELT with NEWVALUE)
(SK.UPDATE.IMAGEOBJECT.AFTER.CHANGE GELT))
((WIRE OPENCURVE CLOSEDWIRE CLOSEDCURVE)
(replace (WIRE LATLONKNOTS) of INDVELT with NEWVALUE)
(SK.UPDATE.WIRE.ELT.AFTER.CHANGE GELT))
(RETURN NIL))
(RETURN T])
```

(SK.REPLACE.TEXT.IN.ELEMENT

```
[LAMBDA (GTEXTELT NEWSTRS) (* rrb "15-Dec-85 18:00")
(* changes the characters in a text or textbox element.)
```

```
(SELECTQ (fetch (GLOBALPART GTYPE) of GTEXTFLT)
(TEXTBOX (replace (TEXTBOX LISTOFCHARACTERS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTFLT)
with (OR NEWSTRS (CONS "")))
(SK.UPDATE.TEXTBOX.AFTER.CHANGE GTEXTFLT))
(TEXT (replace (TEXT LISTOFCHARACTERS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GTEXTFLT)
with NEWSTRS)
(SK.UPDATE.TEXT.AFTER.CHANGE GTEXTFLT))
(\ILLEGAL.ARG GTEXTFLT))
GTEXTFLT])
```

(SKELT.GET.DATA

```
[LAMBDA (GELT)
(* rrb " 6-Dec-85 14:52")
(* changes the data of a sketch element.)
(PROG ((INDVELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
(RETURN (SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
(GROUP (fetch (GROUP LISTOFGLOBALELTS) of INDVELT))
((TEXT TEXTBOX)
(fetch (TEXT LISTOFCHARACTERS) of INDVELT))
(BITMAPELT (fetch (BITMAPELT SKBITMAP) of INDVELT))
(SKIMAGEOBJ (fetch (SKIMAGEOBJ SKIMAGEOBJ) of INDVELT))
((WIRE OPENCURVE CLOSEDWIRE CLOSEDCURVE)
(fetch (WIRE LATLONKNOTS) of INDVELT))
(LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
'DATA])
```

(SK.GET.1STCONTROLPT

```
[LAMBDA (GELT PROPERTY)
(* rrb " 9-Dec-85 11:33")
(* gets the first control point field from a global sketch element instance.)
(SELECTQ (fetch (GLOBALPART GTYPE) of GELT)
((TEXT CIRCLE ARC ELLIPSE)
(fetch (TEXT LOCATIONLATLON) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
((TEXTBOX BOX)
(LOWERLEFTCORNER (fetch (BOX GLOBALREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))))
((BITMAPELT SKIMAGEOBJ)
(LOWERLEFTCORNER (fetch (SKIMAGEOBJ SKIMOBJ.GLOBALREGION) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))))
((WIRE CLOSEDWIRE OPENCURVE CLOSEDCURVE)
(CAR (fetch (WIRE LATLONKNOTS) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))))
(GROUP (fetch (GROUP GROUPCONTROLPOINT) of (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT)))
(LISTGET (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
PROPERTY])
```

(SK.PUT.1STCONTROLPT

```
[LAMBDA (GELT NEWPOSITION)
(* rrb "26-Jun-86 16:22")
(* changes the first control point field from a global sketch element instance.)
(OR (POSITIONP NEWPOSITION)
(\ILLEGAL.ARG NEWPOSITION))
(PROG ((INDVELT (fetch (GLOBALPART INDIVIDUALGLOBALPART) of GELT))
X)
(SELECTQ (CAR INDVELT)
(TEXT (replace (TEXT LOCATIONLATLON) of INDVELT with NEWPOSITION)
(SK.UPDATE.TEXT.AFTER.CHANGE GELT))
(CIRCLE (replace (CIRCLE CENTERLATLON) of INDVELT with NEWPOSITION)
(SK.UPDATE.CIRCLE.AFTER.CHANGE GELT))
(ARC (replace (ARC ARCCENTERPT) of INDVELT with NEWPOSITION)
(SK.UPDATE.ARC.AFTER.CHANGE GELT))
(ELLIPSE (replace (ELLIPSE ELLIPSECENTERLATLON) of INDVELT with NEWPOSITION)
(SK.UPDATE.ELLIPSE.AFTER.CHANGE GELT))
(TEXTBOX (replace (TEXTBOX TEXTBOXREGION) of INDVELT with (create REGION using (fetch (BOX GLOBALREGION)
)
of INDVELT)
LEFT _ (fetch (POSITION XCOORD)
of NEWPOSITION)
BOTTOM _ (fetch (POSITION YCOORD)
of NEWPOSITION))))
(SK.UPDATE.TEXTBOX.AFTER.CHANGE GELT))
(BOX (replace (BOX GLOBALREGION) of INDVELT with (create REGION using (fetch (BOX GLOBALREGION)
of INDVELT)
LEFT _ (fetch (POSITION XCOORD)
of NEWPOSITION)
BOTTOM _ (fetch (POSITION YCOORD)
of NEWPOSITION))))
(SK.UPDATE.BOX.AFTER.CHANGE GELT))
(SKIMAGEOBJ (replace (SKIMAGEOBJ SKIMOBJ.GLOBALREGION) of INDVELT with (create REGION
using (fetch (SKIMAGEOBJ
```



```
(T (RPLACA (CDDR X) (* there is at least one knot)
    (NEWPOSITION)))
  (SK.UPDATE.WIRE.ELT.AFTER.CHANGE GELT))
  (LISTPUT (fetch (GLOBALPART SKELEMENTPROPLIST) of GELT)
    '3RDCONTROLPT NEWPOSITION))
T])
```

)

(DEFINEQ

(LOWERLEFTCORNER

```
[LAMBDA (REGION)
  (CREATEPOSITION (FETCH (REGION LEFT) OF REGION)
    (FETCH (REGION BOTTOM) OF REGION])
```

(* returns a position which is the lower left corner of a region.)

(UPPERRIGHTCORNER

```
[LAMBDA (REGION)
  (CREATEPOSITION (fetch (REGION RIGHT) of REGION)
    (fetch (REGION TOP) of REGION])
```

(* rrb "16-Oct-85 21:10")

(* returns a position which is the lower left corner of a region.)

)

FUNCTION INDEX

ADD.EOLS	76	KNOTS.REGIONFN	25
ADD.KNOWN.SKETCH.FONT	59	KNOTS.TRANSLATEFN	25
ADDSKETCHELEMENTPROP	95	LEFT.MOST.IS.BEGINP	43
ALL.EMPTY.REGIONS	71	LOWERLEFTCORNER	101
ARC.ARROWHEAD.POINTS	38	LTEXT.LINE.REGIONS	53
ARC.CREATE	87	MARK.SPOT	17
ARC.DRAWFN	85	MAXEXTENT	19
ARC.EXPANDFN	86	MAYEXTENT	20
ARC.GLOBALREGIONFN	88	OPEN.WIRE.DRAWFN	31
ARC.INPUTFN	86	OPENCURVE.DRAWFN	20
ARC.INSIDEFN	88	OPENCURVE.EXPANDFN	20
ARC.MOVEFN	88	OPENCURVE.GLOBALREGIONFN	25
ARC.READCHANGEFN	89	OPENCURVE.INPUTFN	19
ARC.REGIONFN	88	OPENCURVE.READCHANGEFN	21
ARC.TRANSFORMFN	89	OPENCURVE.TRANSFORMFN	21
ARC.TRANSLATE	89	OPENCURVE.TRANSLATEFN	21
ARC.TRANSLATEPTS	88	OPENCURVE.TRANSLATEPTSFN	22
ARROW.HEAD.POSITIONS	41	OPENWIRE.FEEDBACKFN	34
ARROWHEAD.POINTS.LIST	42	OPENWIRE.GLOBALREGIONFN	25
BOX.DRAWFN1	77	OPENWIRE.READCHANGEFN	32
BOX.SET.SCALES	80	OPENWIRE.TRANSFORMFN	32
BREAK.AT.CARRIAGE.RETURNS	59	OPENWIRE.TRANSLATEFN	33
CHANGE.ELTS.ARROWHEADS	36	OPENWIRE.TRANSLATEPTSFN	33
CHANGE.ELTS.BRUSH	26	PUTSKETCHELEMENTPROP	94
CHANGE.ELTS.BRUSH.SHAPE	26	READ.ARROW	35
CHANGE.ELTS.BRUSH.SIZE	26	READ.ARROWHEAD.END	41
CHANGED.ARROW	39	READ.COLOR.CHANGE	5
CIRCLE.DRAWFN	8	READ.FILLING.MODE	7
CIRCLE.EXPANDFN	7	READ.LIST.OF.POINTS	23
CIRCLE.GLOBALREGIONFN	10	READ.TEXT	53
CIRCLE.INPUTFN	9	READSIZECHANGE	29
CIRCLE.INSIDEFN	10	REGION.CONTAINING.PTS	25
CIRCLE.READCHANGEFN	10	REGION.FROM.COORDINATES	85
CIRCLE.REGIONFN	10	REL.MOVE.REGION	53
CIRCLE.TRANSFORMFN	11	REMOVESKETCHELEMENTPROP	95
CIRCLE.TRANSLATE	10	SET.ARC.ARROWHEAD.POINTS	38
CIRCLE.TRANSLATEPTS	11	SET.ARC.SCALES	91
CLOSE.PROMPT.WINDOW	51	SET.CIRCLE.SCALE	12
CLOSED.WIRE.DRAWFN	36	SET.OPENCURVE.ARROWHEAD.POINTS	38
CLOSED.WIRE.INPUTFN	36	SET.WIRE.ARROWHEAD.POINTS	39
CLOSEDCURVE.DRAWFN	22	SHOWSKETCHPOINT	24
CLOSEDCURVE.EXPANDFN	22	SHOWSKETCHXY	24
CLOSEDCURVE.GLOBALREGIONFN	23	SK.ARROWHEAD.CREATE	41
CLOSEDCURVE.INPUTFN	23	SK.ARROWHEAD.END.TEST	41
CLOSEDCURVE.READCHANGEFN	23	SK.ARROWHEADP	47
CLOSEDCURVE.REGIONFN	23	SK.BOX.CREATE	81
CLOSEDCURVE.TRANSFORMFN	24	SK.BOX.DRAWFN	77
CLOSEDCURVE.TRANSLATEPTSFN	24	SK.BOX.EXPANDFN	79
CLOSEDWIRE.EXPANDFN	31	SK.BOX.GETREGIONFN	80
CLOSEDWIRE.FEEDBACKFN	34	SK.BOX.GLOBALREGIONFN	81
CLOSEDWIRE.GLOBALREGIONFN	34	SK.BOX.INPUTFN	80
CLOSEDWIRE.READCHANGEFN	36	SK.BOX.INSIDEFN	81
CLOSEDWIRE.REGIONFN	34	SK.BOX.READCHANGEFN	81
CLOSEDWIRE.TRANSFORMFN	37	SK.BOX.REGIONFN	81
CLOSEDWIRE.TRANSLATEPTSFN	37	SK.BOX.TRANSFORMFN	83
COMPUTE.ELLIPSE.ORIENTATION	18	SK.BOX.TRANSLATEFN	83
CREATE.SKETCH.ELEMENT.TYPE	5	SK.BOX.TRANSLATEPTSFN	83
CREATE.SKETCH.TERMTABLE	65	SK.BREAK.INTO.LINES	67
CREATE.TEXT.ELEMENT	54	SK.BRUSH.READCHANGE	12
CURVE.ARROWHEAD.POINTS	42	SK.BRUSH.SIZE	69
CURVE.REGIONFN	25	SK.CHANGE.ANGLE	28
DISTANCEBETWEEN	18	SK.CHANGE.ARC.DIRECTION	28
DRAWARROWHEADS	43	SK.CHANGE.ARROWHEAD	40
ELLIPSE.CREATE	16	SK.CHANGE.ARROWHEAD1	40
ELLIPSE.DRAWFN	14	SK.CHANGE.BRUSH.COLOR	27
ELLIPSE.EXPANDFN	13	SK.CHANGE.BRUSH.SHAPE	26
ELLIPSE.GLOBALREGIONFN	16	SK.CHANGE.BRUSH.SIZE	27
ELLIPSE.INPUTFN	14	SK.CHANGE.ELEMENT.KNOTS	29
ELLIPSE.INSIDEFN	15	SK.CHANGE.FILLING	82
ELLIPSE.REGIONFN	16	SK.CHANGE.FILLING.COLOR	82
ELLIPSE.TRANSFORMFN	17	SK.CHANGE.FILLING.MODE	7
ELLIPSE.TRANSLATEFN	16	SK.CHANGE.TEXT	57
ELLIPSE.TRANSLATEPTS	17	SK.CHOOSE.TEXT.FONT	60
EXPANDREGION	84	SK.CIRCLE.CREATE	12
GETSKETCHELEMENTPROP	92	SK.COLLECT.FONT.SIZES	64
INCREASEREGION	84	SK.COMPUTE.ARC.ANGLE.PT	90
INIT.SKETCH.ELEMENTS	3	SK.COMPUTE.ARC.ANGLE.PT.FROM.ANGLE	90
INSUREREGIONSIZE	84	SK.COMPUTE.ARC.ARROWHEAD.POINTS	38
INVISIBLEPART	24	SK.COMPUTE.ARC.PTS	90
KNOT.SET.SCALE.FIELD	20	SK.COMPUTE.CURVE.ARROWHEAD.POINTS	38
KNOTS.INSIDEFN	31	SK.COMPUTE.ELLIPSE.MINOR.RADIUS.PT	18
KNOTS.OF.REGION	77	SK.COMPUTE.SLOPE.OF.LINE	91

```
{MEDLEY}<library>sketch>SKETCH-ELEMENTS.;1
```

SK.COMPUTE.TEXTBOX.REGION.FOR.STRING	66	SKETCH.CREATE.CLOSED.WIRE	36
SK.COMPUTE.WIRE.ARROWHEAD.POINTS	39	SKETCH.CREATE.ELLIPSE	13
SK.COPY.ELEMENT.PROPERTY.LIST	96	SKETCH.CREATE.OPEN.CURVE	19
SK.CREATE.ARC.USING	91	SKETCH.CREATE.TEXT	49
SK.CREATE.ARROWHEAD	40	SKETCH.CREATE.TEXTBOX	66
SK.CREATE.DEFAULT.FILLING	6	SKETCH.CREATE.WIRE	30
SK.CURVE.CREATE	19	SKETCH.ELEMENT.NAMEP	5
SK.DECREASING.FONT.LIST	61	SKETCH.ELEMENT.TYPEP	5
SK.DISTANCE.TO	18	SKETCH.UPDATE	96
SK.DRAWAREABOX	78	SKETCH.UPDATE1	97
SK.DRAWBOX	79	SKETCHINCOLORP	5
SK.EXPAND.ARROWHEAD	39	SKFILLINGP	6
SK.EXPAND.ARROWHEADS	37	SQUARE	18
SK.FONT.LIST	65	TEXT.CHANGEFN	49
SK.GUESS.FONTSAVAILABLE	61	TEXT.DRAWFN	51
SK.INSURE.ARROWHEADS	46	TEXT.DRAWFN1	51
SK.INSURE.BRUSH	12	TEXT.EXPANDFN	52
SK.INSURE.COLOR	6	TEXT.GLOBALREGIONFN	55
SK.INSURE.DASHING	12	TEXT.INPUTFN	53
SK.INSURE.DIRECTION	92	TEXT.INSIDEFN	52
SK.INSURE.FILLING	6	TEXT.POSITION.AND.CREATE	54
SK.INSURE.FONT	65	TEXT.READCHANGEFN	49
SK.INSURE.POINT.LIST	30	TEXT.REGIONFN	55
SK.INSURE.POSITION	30	TEXT.SET.GLOBAL.REGIONS	55
SK.INSURE.STYLE	66	TEXT.SET.SCALES	59
SK.INSURE.TEXT	66	TEXT.TRANSFORMFN	56
SK.INVERT.CIRCLE	87	TEXT.TRANSLATEFN	55
SK.NEXTSIZEFONT	61	TEXT.TRANSLATEPTSFN	56
SK.PICK.FONT	59	TEXT.UPDATE.GLOBAL.REGIONS	52
SK.READ.ARC.ANGLE.POINT	87	TEXT.UPDATEFN	56
SK.READ.CIRCLE.POINT	9	TEXTBOX.CHANGEFN	70
SK.READ.ELLIPSE.MAJOR.PT	15	TEXTBOX.DRAWFN	70
SK.READ.ELLIPSE.MINOR.PT	15	TEXTBOX.EXPANDFN	71
SK.READ.POINTS.WITH.FEEDBACK	33	TEXTBOX.GLOBALREGIONFN	73
SK.READ.WIRE.POINTS	33	TEXTBOX.INPUTFN	72
SK.READFONTFAMILY	51	TEXTBOX.INSIDEFN	72
SK.READFONTSIZE	64	TEXTBOX.READCHANGEFN	74
SK.REPLACE.TEXT.IN.ELEMENT	97	TEXTBOX.REGIONFN	73
SK.SET.ARC.DIRECTION	91	TEXTBOX.SET.GLOBAL.REGIONS	73
SK.SET.ARC.DIRECTION.CCW	91	TEXTBOX.TRANSFORMFN	74
SK.SET.ARC.DIRECTION.CW	91	TEXTBOX.TRANSLATEFN	73
SK.SET.ARROWHEAD.ANGLE	45	TEXTBOX.TRANSLATEPTSFN	73
SK.SET.ARROWHEAD.LENGTH	45	TEXTBOX.UPDATEFN	74
SK.SET.ARROWHEAD.TYPE	45	UNSCALE.REGION.TO.GRID	84
SK.SET.DEFAULT.BRUSH.SIZE	29	UPPERRIGHTCORNER	101
SK.SET.DEFAULT.TEXT.FACE	65	WIRE.ADD.POINT.TO.END	35
SK.SET.FONT	63	WIRE.ARROWHEAD.POINTS	43
SK.SET.LINE.ARROWHEAD	45	WIRE.EXPANDFN	31
SK.SET.LINE.LENGTH.MODE	46	WIRE.INPUTFN	33
SK.SET.TEXT.FONT	63	\CIRCLE.DRAWFN1	8
SK.SET.TEXT.HORIZ.ALIGN	63	\CURSOR.IN.MIDDLE.MENU	5
SK.SET.TEXT.LOOKS	65	\GETSKETCHELEMENTPROPI	93
SK.SET.TEXT.SIZE	63	\SK.ADJUST.FOR.ARROWHEADS	44
SK.SET.TEXT.VERT.ALIGN	64	\SK.DRAW.TRIANGLE.ARROWHEAD	44
SK.SET.TEXTBOX.HORIZ.ALIGN	76	\SK.ENDPT.OF.ARROW	44
SK.SET.TEXTBOX.VERT.ALIGN	76	\SK.GET.1STCONTROLPT	98
SK.SHOW.ARC	87	\SK.GET.2NDCONTROLPT	99
SK.SHOW.CIRCLE	9	\SK.GET.3RDCONTROLPT	100
SK.SHOW.ELLIPSE.MAJOR.RADIUS	15	\SK.GET.ARC.ANGLEPT	93
SK.SHOW.ELLIPSE.MINOR.RADIUS	15	\SK.GET.ARROWHEADS	93
SK.TEXT.ELT.WITH.SAME.FIELDS	50	\SK.GET.BRUSH	93
SK.TEXT.FROM.TEXTBOX	54	\SK.GET.DASHING	94
SK.TEXT.LINE.REGIONS	52	\SK.GET.DIRECTION	94
SK.TEXTBOX.CREATE	69	\SK.GET.FILLING	93
SK.TEXTBOX.CREATE1	69	\SK.GET.FONT	93
SK.TEXTBOX.FROM.TEXT	75	\SK.GET.JUSTIFICATION	94
SK.TEXTBOX.POSITION.IN.BOX	69	\SK.PUT.1STCONTROLPT	98
SK.TEXTBOX.TEXT.POSITION	75	\SK.PUT.2NDCONTROLPT	99
SK.TEXTURE.AROUND.REGIONS	70	\SK.PUT.3RDCONTROLPT	100
SK.TRANSLATE.MODE	6	\SK.PUT.ARROWHEADS	96
SK.UPDATE.ARC.AFTER.CHANGE	87	\SK.PUT.BRUSH	96
SK.UPDATE.ARROWHEAD.FORMAT	46	\SK.PUT.DASHING	95
SK.UPDATE.BOX.AFTER.CHANGE	81	\SK.PUT.DIRECTION	95
SK.UPDATE.CIRCLE.AFTER.CHANGE	9	\SK.PUT.FILLING	94
SK.UPDATE.ELLIPSE.AFTER.CHANGE	16	\SK.PUT.FONT	95
SK.UPDATE.TEXT.AFTER.CHANGE	54	\SK.PUT.JUSTIFICATION	95
SK.UPDATE.TEXTBOX.AFTER.CHANGE	69	\SK.READ.FONT.SIZE1	50
SK.UPDATE.WIRE.ELT.AFTER.CHANGE	32	\SKELT.GET.DATA	98
SK.WIRE.CREATE	34	\SKELT.GET.SCALE	97
SKETCH.CREATE.ARC	85	\SKELT.PUT.DATA	97
SKETCH.CREATE.BOX	77	\SKELT.PUT.SCALE	97
SKETCH.CREATE.CIRCLE	7		
SKETCH.CREATE.CLOSED.CURVE	22		

VARIABLE INDEX

ARC.ANGLE.CURSOR	92	SK.ARROW.EDIT.MENU	49	SK.DEFAULT.TEXT.ALIGNMENT	66
ARC.RADIUS.CURSOR	92	SK.ARROW.END.MENU	49	SK.DEFAULT.TEXTBOX.ALIGNMENT	76
CIRCLE.CENTER	13	SK.ARROWHEAD.ANGLE.INCREMENT	48	SK.DEFAULT.TEXTURE	13
CIRCLE.EDGE	13	SK.ARROWHEAD.LENGTH.INCREMENT	48	SK.HORIZONTAL.STYLES	66
CURVE.KNOT	30	SK.ARROWHEAD.TYPES	48	SK.NUMBER.OF.POINTS.IN.ARC	92
CW.ARC.ANGLE.CURSOR	92	SK.DEFAULT.ARROW.ANGLE	48	SK.VERTICAL.STYLES	66
CW.ARC.RADIUS.CURSOR	92	SK.DEFAULT.ARROW.LENGTH	48	SKETCH.TERMTABLE	66
ELLIPSE.CENTER	19	SK.DEFAULT.ARROW.TYPE	48	SKETCHINCOLORFLG	5
ELLIPSE.SEMI.MAJOR	19	SK.DEFAULT.BACKCOLOR	5	TEXTBOXICON	76
ELLIPSE.SEMI.MINOR	19	SK.DEFAULT.BRUSH	13	\FONTSONFILE	66
FILLINGMODEFLG	5	SK.DEFAULT.DASHING	13	\KNOWN.SKETCH.FONT SIZES	62
FILLPOLYGONFLG	5	SK.DEFAULT.FONT	66		
INDICATE.TEXT.SHADE	66	SK.DEFAULT.OPERATION	5		

RECORD INDEX

ARC	92	CLOSEDWIRE	47	LOCALCLOSEDCURVE	30	LOCALWIRE	47
ARROWHEAD	47	ELLIPSE	18	LOCALCLOSEDWIRE	30,47	OPENCURVE	30
BOX	85	KNOTELT	30	LOCALCURVE	30	SKFILLING	6
BRUSH	13	LOCALARC	92	LOCALELLIPSE	18	TEXT	62
CIRCLE	13	LOCALBOX	85	LOCALTEXT	63	TEXTBOX	76
CLOSEDCURVE	30	LOCALCIRCLE	13	LOCALTEXTBOX	76	WIRE	47