

File created: 28-Apr-88 17:29:39 {ERIS}<CUTTING>RPC>RPCSTRUCT.;4

changes to: (IL:VARS IL:RPCSTRUCTCOMS)
(IL:STRUCTURES RPC-STREAM)
(FILE-ENVIRONMENTS IL:RPCSTRUCT)

previous date: 15-Oct-87 18:49:03 {ERINYES}<LISPUSERS>MEDLEY>RPCSTRUCT.LSP;1

Read Table: XCL

Package: RPC2

Format: XCCS

; Copyright (c) 1987, 1988 by Stanford University and Xerox Corporation. All rights reserved.

```
(IL:RPAQQ IL:RPCSTRUCTCOMS ((IL:PROPS (IL:RPCSTRUCT IL:MAKEFILE-ENVIRONMENT IL:FILETYPE))
                               (IL:STRUCTURES RPC-PROGRAM RPC-PROCEDURE RPC-STREAM AUTHENTICATION)))
```

```
(IL:PUTPROPS IL:RPCSTRUCT IL:MAKEFILE-ENVIRONMENT (:READTABLE "XCL" :PACKAGE "RPC2"))
```

```
(IL:PUTPROPS IL:RPCSTRUCT IL:FILETYPE :COMPILE-FILE)
```

(DEFSTRUCT **RPC-PROGRAM**

```
"
Structure describing a Sun RPC Protocol Remote Program.
"
(NUMBER 0 :TYPE INTEGER)           ; RPC Program Number
(VERSION 0 :TYPE INTEGER)          ; RPC Version Number
NAME                               ; String or Symbol. This name is used only by this program and
                                   ; has no significance to the remote program. The name is
                                   ; assumed to uniquely specify an RPC structure.
                                   ; A symbol. Either RPC::UDP or RPC::TCP.
PROTOCOL                           ; List of (<constant> <def>) pairs.
CONSTANTS                          ; List of (<typename> <typedef>) pairs
TYPES                              ; List of names of RPC names whose types and constants are
INHERITS                           ; inherited by this RPC.
PROCEDURES                         ; List of RPC-PROCEDURE structures defining the procedures
                                   ; for this remote program.
)
```

(DEFSTRUCT **RPC-PROCEDURE**

```
"Structure defining a single procedure of a SUN RPC Protocol remote program.
"
NAME                               ; The procedure name. A string or symbol.
(PROCNUM 0 :TYPE INTEGER)          ; The procedure number. An integer.
ARGTYPES                           ; List of argument types. May be typenames or typedefs. NIL for
                                   ; no arguments.
RESULTTYPES                        ; Same as ARGTYPES except for returned values.
)
```

(DEFSTRUCT **RPC-STREAM**

```
"Holds info and functions for encoding, decoding and executing remote procedure calls"
PROTOCOL                           ; UDP, TCP, or STRING
IPSOCKET                           ; Local IP Socket
INSTREAM                           ; Incoming (Reply) Stream or Packet
INBYTEPTR                          ; Byte Pointer to current position in incoming data. For UDP it is
                                   ; the byte pointer in the UDP packet. For TCP it is decremented,
                                   ; saying how many bytes left in this RM record before another
                                   ; RM header must be read.
OUTSTREAM                           ; UDP outgoing packet, or outgoing stream used by TCP and
                                   ; STRING.
OUTBYTEPTR                          ; Byte Pointer to current position in outgoing string used to build
                                   ; RM record for TCP. See page 10 of "Remote Procedure Call
                                   ; Protocol Specification" for details of the RM 'Record Marking
                                   ; Standard'.
OUTSTRING                           ; Used by TCP to encode as string before sending
GETBYTE                             ; Function to read byte of incoming data
GETBYTES                            ; Function to do bulk read of incoming data
GETCELL                             ; Function to get 32 bit two's complement integer of incoming
                                   ; data. Would be better to have 32 bit unsigned as the primitive
GETOFFSET                           ; Get current offset into incoming data.
PUTBYTE                             ; Function to write byte of outgoing data
PUTBYTES                            ; Function to do bulk write of outgoing data.
PUTCELL                             ; Function to write 32 bit two's complement integer of outgoing
                                   ; data.
PUTOFFSET                           ; Set current position in incoming data.
PRIVATE                             ; Can be used by user as desired
OS-DESTADDR                         ; Address of the destination. Only used by os-networking.
)
```

```
{MEDLEY}<lispusers>RPCSTRUCT.;1
```

Page 2

```
(DEFSTRUCT AUTHENTICATION
```

```
  "Sun RPC Version 2 Authentication Record"
```

```
  TYPE
```

```
  STRING
```

```
)
```

```
; 0 = NULL
```

```
; 1 = Unix
```

```
; 2 = Short
```

```
;
```

```
; Encoding of any fields of that type authentication. String is a
```

```
; Common Lisp string rather than an XDR-STRING.
```

```
(IL:PUTPROPS IL:RPCSTRUCT IL:COPYRIGHT ("Stanford University and Xerox Corporation" 1987 1988))
```

STRUCTURE INDEX

AUTHENTICATION2 RPC-PROCEDURE1 RPC-PROGRAM1 RPC-STREAM1

PROPERTY INDEX

IL:RPCSTRUCT1
