

File created: 13-Jul-88 16:12:14 {POGO:AISNORTH:XEROX}<LOOPSCORE>INTERNAL>LOOPS-ABC.;2
 changes to: (VARS LOOPS-ABCCOMS)
 previous date: 30-Sep-87 17:07:14 {POGO:AISNORTH:XEROX}<LOOPSCORE>INTERNAL>LOOPS-ABC.;1
 Read Table: INTERLISP
 Package: INTERLISP
 Format: XCCS

::
 :: Copyright (c) 1986, 1987, 1988 by Xerox Corporation. All rights reserved.

(RPAQQ **LOOPS-ABCCOMS**
 (COMS

::: The Loops tester

;; This stuff is bogus, and should be removed
 [INITVARS (LOOPSTESTDIR "{POGO:}<LOOPS>TESTER>")
 (CoreTesterFiles '(LTBASIC LTSUB LTKER LTFILES LTCASES))
 (TESTFILES '(LTBASIC LTSUB LTKER LTFILES LTCASES LTCORETESTS LTLISPUNTESTS LTMETHODTESTS
 LTPUTMETHODTEST)]
 (FNS TESTLOOPS))

::, Loops debugging stuff

```

(INITVARS (\DebugLoopsOldDir NIL))
(FNS AnalyzeLoops DebugLoops LOOPSDIR i/d PPI)
(ADDVARS (*GIVE-AND-TAKE-DIRECTORIES* "{POGO:}<LOOPSCORE>SYSTEM>"))
(FILES LOOPS-EXPORTS.ALL)
(DECLARE%: DONTCOPY (PROP MAKEFILE-ENVIRONMENT LOOPS-ABC)))

```

::: The Loops tester

; This stuff is bogus, and should be removed

```

(RPAQ? LOOPSTESTDIR "{POGO:}<LOOPS>TESTER>")
(RPAQ? CoreTesterFiles '(LTBASIC LTSUB LTKER LTFILES LTCASES))
(RPAQ? TESTFILES '(LTBASIC LTSUB LTKER LTFILES LTCASES LTCORETESTS LTLISPUNTESTS LTMETHODTESTS  

  LTPUTMETHODTEST))

```

(DEFINEQ

TESTLOOPS
 [LAMBDA (options breakFlg) (* smL "22-Apr-86 19:19")]

(* * loads and runs tests as determined by the options)
 (* * options -
 T%: Load LTFILES and stop. NIL -
 load LTFILES and then load StandardTestFiles and run them. varName -
 load LTFILES and then load files in varName and run them)

```

(SETQ DIRECTORIES (UNION (LIST LOOPSTESTDIR LOOPSDIRECTORY)
  DIRECTORIES))
(DOFILESLOAD CoreTesterFiles)
(COND
  ((EQ options T))
  (T (TestFromFiles (COND
    ((NULL options)
     AllTestFiles)
    ((LITATOM options)
     (EVAL options))
    (T options))
    breakFlg)))
)

```

::, Loops debugging stuff

(RPAQ? \DebugLoopsOldDir NIL)

(DEFINEQ

AnalyzeLoops
 [LAMBDA (updateDB?)

; Edited 22-Jun-87 09:39 by smL

:: Analyze all the Loops files with Masterscope.

```

(DebugLoops)
(if updateDB?
  then [for file in LOOPSFIES do (for fn in (FILECOMSLST file)
                                         do (MASTERSCOPE '(ANALYZE ',fn)
  elseif (AND (MOUSECONFIRM "Delete current MasterScope database and analyze Loops from scratch?" NIL
                           \TopLevelTtyWindow T)
              (MOUSECONFIRM "Are you sure?" NIL \TopLevelTtyWindow T))
  then (MASTERSCOPE '(ERASE))
  (for file in LOOPSFIES do (printout T "Loading fns from " file "..."))
    (LOADFNS (for fn in (FILECOMSLST file)
      when [NOT (OR (EXPRP fn)
                     (EXPRP (GETPROP fn 'EXPR)
                     collect fn)
                   file
                   'PROP)
      (printout T "Analyzing")
      [for fn in (FILECOMSLST file)
        do (MASTERSCOPE '(ANALYZE ',fn)
      (printout T T])
    )
  )

(DebugLoops
[LAMBDA (turnOffFlg) ; Edited 25-Jun-87 12:51 by smL
;; Add LOOPSFIES to FILELST and LOOPSDIRECTORY to directories, or reverse if turnOffFlg =T. Used to put Loops into a mode for debugging
;; Loops system code.
(DECLARE (GLOBALVARS \DebugLoopsOldDir))
(if turnOffFlg
  then (SETQ FILELST (for x in FILELST when [AND (NOT (FMEMB x LOOPSFIES))
                                                (NOT (MEMB x '(LOOPS-EXPORTS.ALL LOOPS-EXPORTS LOOPS-ABC)
                                                collect x)))
  (SETQ DIRECTORIES (for x in DIRECTORIES when (NEQ x LOOPSDIRECTORY) collect x))
  (COND
    (\DebugLoopsOldDir (CNDIR \DebugLoopsOldDir)
      (SETQ \DebugLoopsOldDir NIL)))
  "Return to normal"
else (SETQ DIRECTORIES (UNION (LIST LOOPSDIRECTORY)
                               DIRECTORIES))
  (if (NULL \DebugLoopsOldDir)
    then (SETQ \DebugLoopsOldDir (DIRECTORYNAME T T)))
(LOOPSDIR)
(FILESLOAD LOOPS-EXPORTS.ALL)
(for f in LOOPSFIES unless (BOUNDP (FILECOMS f)) do (LOADFROM f NIL 'ALLPROP))
(SETQ FILELST (UNION (for file in LOOPSFIES collect file when (GETPROP file 'FILE)
                           FILELST)))
"Debugging Loops"])

(LOOPSDIR
[LAMBDA (SUBDIR) (* smL "27-Feb-85 13:24")
(* * Connects to the directory for saving LOOPS sources.)
(/CNDIR (PACK* LOOPSDIRECTORY (OR SUBDIR "")))

(i/d
[LAMBDA (item) (* dbg%:" 3-DEC-82 01:46")
(* short form of call)
(INSPECT/DATATYPE item))

(PPI
[LAMBDA (INSTANCE RECORDNAME FILE) (* smL "17-Jan-86 16:32")
(* Pretty-prints an instance of a record.)
(PROG [(POS (ADD1 (POSITION FILE)))
        (DEC (RECLOOK (OR RECORDNAME (COND
          ((LISTP INSTANCE)
           (CAR INSTANCE))
          (T (TYPERENAME INSTANCE))
        )
        (COND
          (DEC (printout FILE "[" %# (for FIELD in (RECORDFIELDNAMES DEC) unless (EQ FIELD 'PERFORMOPS)
            do (printout NIL .TAB0 POS .P2 FIELD " = " .PPV (RECORDACCESS FIELD
              INSTANCE DEC)
            )
          )
          "]" T))
        (T (printout FILE .PPV INSTANCE T))
      )
    )
  )
  (ADDTOVAR *GIVE-AND-TAKE-DIRECTORIES* "{POGO: }<LOOPSCORE>SYSTEM>")
  (FILESLOAD LOOPS-EXPORTS.ALL)
  (DECLARE%: DONTCOPY

```

```
{MEDLEY}<loops>internal>LOOPS-ABC.;1  
(PUTPROPS LOOPS-ABC MAKEFILE-ENVIRONMENT (:PACKAGE "IL" :READTABLE "INTERLISP" :BASE 10))  
)  
(PUTPROPS LOOPS-ABC COPYRIGHT ("Xerox Corporation" 1986 1987 1988))
```

FUNCTION INDEX

AnalyzeLoops ...1 DebugLoops2 i/d2 LOOPSDIR2 PPI2 TESTLOOPS1

VARIABLE INDEX

GIVE-AND-TAKE-DIRECTORIES2 LOOPSTESTDIR1 \DebugLoopsOldDir1
CoreTesterFiles1 TESTFILES1

PROPERTY INDEX

LOOPS-ABC3
