

File created: 15-Aug-90 16:25:38 {DSK}<usr>local>lde>SOURCES>loops>LIBRARY>GAUGEINSTRUMENTS.;2

changes to: (VARS GAUGEINSTRUMENTSCOMS)

previous date: 11-Mar-88 12:02:18 {DSK}<usr>local>lde>SOURCES>loops>LIBRARY>GAUGEINSTRUMENTS.;1

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

::
:: Copyright (c) 1986, 1987, 1988, 1990 by Venue & Xerox Corporation. All rights reserved.

(RPAQQ **GAUGEINSTRUMENTSCOMS**

```
((DECLARE%: DONTCOPY (PROP MAKEFILE-ENVIRONMENT GAUGEINSTRUMENTS)
  (PROP FILETYPE GAUGEINSTRUMENTS))
 (FILES (FROM VALUEOF LOOPSLIBRARYDIRECTORY)
  GAUGES)
 (CLASSES Meter Instrument RoundScale StraightScale)
 (METHODS Instrument.ComputeDisplayVal Instrument.ComputeScale Instrument.PrintLabelScale
  Instrument.SetParameters Instrument.ShowInstrument Meter.ComputeScale Meter.DrawInstrument
  Meter.Set Meter.SetParameters Meter.Shape Meter.ShowLabels Meter.ShowTicks RoundScale.Reset
  RoundScale.Set RoundScale.ShowReading StraightScale.Attach)
 (FNS ShowRayLabelLength)))
```

(DECLARE%: DONTCOPY

(PUTPROPS **GAUGEINSTRUMENTS MAKEFILE-ENVIRONMENT** (:PACKAGE "IL" :READTABLE "INTERLISP" :BASE 10))

(PUTPROPS **GAUGEINSTRUMENTS FILETYPE** :COMPILE-FILE)

)

(FILESLOAD (**FROM** VALUEOF LOOPSLIBRARYDIRECTORY)
 GAUGES)

(DEFCLASSES Meter Instrument RoundScale StraightScale)

(DEFCLASS Meter (MetaClass Class doc "A circular instrument that will wrap around any number of times" Edited%:
 (* RBGMartin "2-May-86 13:06"))

```
(Supers RoundScale)
(InstanceVariables (ticks 10 doc "ticks on the instrument; value is number or NIL; smallTicks is number
  between each large tick")
  (lower 90 doc "lower bound for internal displayVal")
  (displayVal 90 doc "Internal value relative to instrument")
  (range -360 doc "range for internal displayVal")
  (inputRange 10 doc "range for external reading")
  (labels (0 1 2 3 4 5 6 7 8 9)
   doc "labels for the instrument")
  (height 10)
  (width 10)))
```

(DEFCLASS Instrument (MetaClass AbstractClass doc "A numeric gauge scaled externally by inputLower and
 inputRange, and internally by lower and range" Edited%:
 (* edited%: "22-May-86 13:05"))

```
(Supers Gauge)
(InstanceVariables (displayVal 0 doc "Internal value relative to instrument")
  (ticks 5 tickLength 9 smallTicks 1 doc "ticks on the instrument; value is number or NIL;
  smallTicks is number between each large tick")
  (brushWidth 1 doc "scale factor for width of ticks, rays and circles.")
  (labels NIL doc "labels for the instrument")
  (labelScale (1 . 0)
   doc "CAR of this is 1 or -1 to indicate the sign. CDR is the exponent of the scale
  factor.")
  (spaceForLabelScale 20 doc "extra vertical space to display scale label")
  (lower 0 doc "lower bound for internal displayVal")
  (inputLower 0 doc "lower bound for external reading")
  (range 1 doc "range for internal displayVal")
  (inputRange 1 doc "range for external reading")))
```

(DEFCLASS RoundScale (MetaClass AbstractClass Edited%: (* mjs%: "28-JAN-83 10:19")
 doc "AbstractClass for instruments with circular (arc) scales")

```
(Supers Instrument)
(InstanceVariables (needleLength 15 doc "radius of needle")
  (radius 10 doc "radius of arc in instrument")
  (xc 0 doc "x center of arc")
  (yc 0 doc "y center of arc")))
```

(DEFCLASS StraightScale (MetaClass AbstractClass Edited%: (* edited%: "31-Oct-86 21:09")
 doc "Abstract classes are placeholders in the inheritance network, which cannot
 themselves be instantiated.")

```
(Supers BoundedMixin Instrument)
(InstanceVariables (labels (0 0.1 0.2 0.3 0.4 0.5 0.6 0.7 0.8 0.9 1.0))
  (shade 65535 doc "shade of bar")
  (ticks 11 tickLength 7)))
```

```
(\BatchMethodDefs)

(METH Instrument ComputeDisplayVal (reading)
  "Computes displayVal of instrument in bounded range"
  (category (Instrument)))

(METH Instrument ComputeScale (min max labelScale)
  "Compute a scale covering min and max, with ticks and labels at multiples of one of the appropriate
  multiples of either 0.2 0.25 0.5 or 1.0"
  (category (Instrument)))

(METH Instrument PrintLabelScale NIL "Print the scale of labelling on instrument" (category (Instrument)))

(METH Instrument SetParameters NIL "Dummy function where default values are appropriate" (category (Internal)))

(METH Instrument ShowInstrument NIL "show the instrument including the current displayVal" (category (Internal))
)

(METH Meter ComputeScale (newReading)
  "Meters always have 0 to 9 scale. This computes the proper label scale."
  (category (Instrument)))

(METH Meter DrawInstrument NIL "I" (category (Meter)))

(METH Meter Set (newReading)
  "Move the setting on a RoundScale instrument from current setting to that specified by input."
  (category (Meter)))

(METH Meter SetParameters NIL "Compute width, height, center and radius etc. for meters" (category (Internal)))

(METH Meter Shape (newRegion noUpdateFlg ExtraSpaceFlg)
  "Shapes outside of region to specified shape. if ExtraSpaceFlg is T and newRegion is NIL, then the meter
  is interactively shaped to have extra white space. Shaping from the window menu will keep the meter square
  except for the space at the bottom for the label."
  (category (Public)))

(METH Meter ShowLabels NIL "If there are any labels, show them on the dial" (category (Meter)))

(METH Meter ShowTicks NIL "Draw ticks at even intervals around the circle starting from 90" (category (Meter)))

(METH RoundScale Reset (newReading)
  "set reading to value, and then update gauge so that it shows that reading without going through
  intermediate states"
  (category (Gauge)))

(METH RoundScale Set (newReading)
  "Move the setting on a RoundScale instrument from current setting to that specified by input."
  (category (RoundScale)))

(METH RoundScale ShowReading NIL "dgb: 26-JAN-83 23:43" (category (RoundScale)))

(METH StraightScale Attach (obj varName shade propName type xOrPos y)
  "same as Gauge.Attach, but with additional argument of shade for setting the shade of the scale."
  (category (Public)))

[Method ((Instrument ComputeDisplayVal)
  self reading) ; edited: 22-May-86 00:48
  "Computes displayVal of instrument in bounded range"
  (PLUS (@ lower)
    (FQUOTIENT (TIMES (FDIFFERENCE reading (@ inputLower))
      (@ range))
      (@ inputRange]))

[Method ((Instrument ComputeScale)
  self min max labelScale) ; edited: 29-Jan-87 11:23
  "Compute a scale covering min and max, with ticks and labels at multiples of one of the appropriate
  multiples of either 0.2 0.25 0.5 or 1.0"
  (PROG ((maxTicks (@ ticks))
    scaleFactor scaleFactorExpt estIncr estIncrScale estIncrFloor goodIncr goodMinVal goodMaxVal
    precision)
    (* Don't bother for no ticks)
    (COND
      ((OR (NULL maxTicks)
        (EQ maxTicks 0))
        (_@
          inputLower min)
        (_@
          inputRange
          (IDIFFERENCE max min))
        (RETURN)))
      (AND labelScale (_@
        labelScale labelScale))
      [SETQ scaleFactor (FloorOfLog (MAX (ABS max)
        (ABS min))
      (OR labelScale (_@
        labelScale
        (CONS 1 scaleFactor)))
```



```
inputRange
(DIFFERENCE goodMaxVal goodMinVal]
```

```
[Method ((Instrument PrintLabelScale)
self) ; edited: 29-Jan-87 11:13
"Print the scale of labelling on instrument"
(PROG [(window (@ window))
[superscriptDistance (FIX (TIMES 0.4 (FONTPROP (@ font)
'SIZE]
(sign (CAR (@ labelScale)))
(exponent (CDR (@ labelScale]
(COND
((@ ticks) (* bitblt BLACKSHADE and DISMISS to warn user scale has
changed.)
(BITBLT NIL NIL NIL window 0 0 (STRINGWIDTH "X-10-00" (@ font))
(@ spaceForLabelScale)
'TEXTURE
'REPLACE BLACKSHADE)
(DISMISS 100 NIL 'NOBLOCK)
(BITBLT NIL NIL NIL window 0 0 (STRINGWIDTH "X-10-00" (@ font))
(@ spaceForLabelScale)
'TEXTURE
'REPLACE WHITESHAE)
(* erase the current scale assuming "0" is at least as wide as any of the integers, and assuming
(ABS (CDR labelScale) < 100)
```

```
(COND
[ (NOT (MINUSP sign)) (* positive scale)
(MOVETO 1 1 window)
(PRIN1 "x" window)
(DSPXPOSITION (PLUS (DSPXPOSITION NIL window)
(Charwidth (CHARCODE -)
(@ font)))
window) (* space over the width of the -
character.)
(COND
((NEQ 0 exponent) (* with exponent)
(PRIN1 "10" window) (* print rest of -10)
(DSPYPOSITION superscriptDistance window)
(* move up to print exponent as superscript.)
(PRIN1 exponent window))
(T (* no exponent)
(PRIN1 "1" window]
((MINUSP sign) (* negative scale)
(MOVETO 1 1 window)
(PRIN1 "x-1" window)
(COND
((NEQ 0 exponent) (* with exponent)
(PRIN1 "0" window) (* print rest of -10)
(DSPYPOSITION superscriptDistance window)
(* move up to print exponent as superscript.)
(PRIN1 exponent window]
```

```
(Method ((Instrument SetParameters)
self) ; edited: 29-Jan-87 10:30
"Dummy function where default values are appropriate"
(_Super)
[_@
spaceForLabelScale
(ADD1 (FIX (TIMES 1.5 (FONTPROP (@ font)
'SIZE]
[_@
brushWidth
(ADD1 (IQUOTIENT (FONTPROP (@ font)
'SIZE)
8))) ; make sure we have an integer value
[_@
ticks%,tickLength
(IMAX (QUOTIENT (FONTPROP (@ font)
'SIZE)
2)
6)))
```

```
(Method ((Instrument ShowInstrument)
self) ; edited: 22-May-86 13:20
"show the instrument including the current displayVal"
(AND (@ ticks)
(PROGN (_ self ShowLabels)
(_ self ShowTicks)))
(_ self PrintLabelScale)
(_ self DrawInstrument))
```

```
(Method ((Meter ComputeScale)
self newReading) ; RBGMartin 29-Apr-86 18:57
"Meters always have 0 to 9 scale. This computes the proper label scale."
(PROG (tempScale)
```

```

[SETQ tempScale (COND
                  ((ZEROP newReading)
                   0)
                  (T (FloorOfLog (ABS newReading]
                    )
    (_@
     inputRange
     (TIMES 10 (EXPT 10 tempScale)))
    (_@
     labelScale
     (CONS (COND
            ((MINUSP newReading)
             -1)
            (T 1))
            tempScale))
    )
  (_ self PrintLabelScale))

(Method ((Meter DrawInstrument)
        self)
  "I"
  (DRAWCIRCLE (@ xc)
              (@ yc)
              (@ radius)
              (@ brushWidth)
              NIL
              (@ window)))

[Method ((Meter Set)
        self newReading)
  "Move the setting on a RoundScale instrument from current setting to that specified by input."
  (PROG [(ABSnewReading (ABS newReading))
        (EXPO (CDR (@ labelScale)
                  (COND
                    ((MINUSP (TIMES newReading (@ reading)))
                     (* readings are different signs. Set Meter to 0, change scale,
                     and move needle.)
                    (_ self ShowReading)
                     (* erase the needle)
                    (_@
                     reading 0)
                    (_ self ShowReading)
                     (* display needle at 0)
                    (_ self ComputeScale newReading)
                    (_@
                     reading newReading)
                    (RotateLine (@ xc)
                                (@ yc)
                                (@ needleLength)
                                (@ displayVal)
                                (_@
                                 displayVal
                                 (_ self ComputeDisplayVal ABSnewReading))
                                (@ window)
                                (@ brushWidth)))
                    (T
                     (PROG NIL
                      (COND
                       ((LESSP ABSnewReading (EXPT 10 EXPO))
                        (* new reading is between 0 and 1 on the current scale. Rotate the needle, then rescale.)

                        (RotateLine (@ xc)
                                    (@ yc)
                                    (@ needleLength)
                                    (@ displayVal)
                                    (_@
                                     displayVal
                                     (_ self ComputeDisplayVal ABSnewReading))
                                    (@ window)
                                    (@ brushWidth))

                        (_@
                         reading newReading)
                        (_ self ShowReading)
                         (* erase the needle)
                        (_ self ComputeScale newReading)
                         (* rescale)
                        (_ self ShowReading)
                         (* draw the needle)
                        )
                        ((GREATERP ABSnewReading (TIMES 10 (EXPT 10 EXPO)))
                         (* new reading is higher than current gauge scale)
                        (_ self ShowReading)
                         (* erase the needle)
                        (_ self ComputeScale newReading)
                         (* rescale)
                        (_ self ShowReading)
                         (* draw the needle)
                        (_@
                         reading newReading)
                        (RotateLine (@ xc)
                                    (@ yc)
                                    (@ needleLength)
                                    (@ displayVal)
                                    (_@
                                     displayVal

```

```

        (_ self ComputeDisplayVal ABSnewReading))
        (@ window)
        (@ brushWidth))
(T
  (_@
    reading newReading)
  (RotateLine (@ xc)
    (@ yc)
    (@ needleLength)
    (@ displayVal)
    (_@
      displayVal
      (_ self ComputeDisplayVal ABSnewReading))
    (@ window)
    (@ brushWidth]
(* the new reading is on the current scale.)

```

```

[Method ((Meter SetParameters)
  self) ; edited: 27-Jan-87 09:59

```

```

"Compute width, height, center and radius etc. for meters"
(LET ((MaxStrWidth (MAXSTRINGWIDTH (@ labels)
  (@ font)))
  (FontHeight (FONTHEIGHT (@ font)))
  meterSize maxFontDimension)
  (_Super)
  (SETQ maxFontDimension (MAX FontHeight MaxStrWidth))
  [SETQ meterSize (MAX (TIMES 6 maxFontDimension)
    (TIMES 2 (PLUS 3 (ShowRayLabelLength self (TIMES 2 (@ ticks%:,tickLength)))
      (IQUOTIENT maxFontDimension 2]

```

(* there are 6 numbers on a side of the meter. This gaurantees the numbers will not overlap. Also, check to make sure that this is not smaller than two numbers on either side of a circle with a diameter 4 times the tickLength. Refer to ShowRayLabel.)

```

(_@
  height%:,min
  (HEIGHTIFWINDOW (PLUS (@ spaceForLabelScale)
    meterSize)
    (@ title)))
(_@
  width%:,min
  (WIDTHIFWINDOW meterSize))
(_@
  height
  (MAX (@ height)
    (@ height%:,min))) (* need this in case the font is bigger)
(_@
  width
  (MAX (@ width)
    (@ width%:,min)))
[_@
  yc
  (PLUS (@ spaceForLabelScale)
    (_@
      xc
      (IQUOTIENT (IMIN (InteriorWidth self)
        (DIFFERENCE (InteriorHeight self)
          (@ spaceForLabelScale)))
        2]
  (_@
    radius
    (IDIFFERENCE (@ xc)
      (PLUS 3 maxFontDimension))) (* radius leaves room for labels around sides)
  (_@
    needleLength
    (IDIFFERENCE (@ radius)
      (@ ticks%:,tickLength]

```

```

[Method ((Meter Shape)
  self newRegion noUpdateFlg ExtraSpaceFlg) ; RBGMartin 28-Jan-87 17:11

```

```

"Shapes outside of region to specified shape. if ExtraSpaceFlg is T and newRegion is NIL, then the meter
is interactively shaped to have extra white space. Shaping from the window menu will keep the meter
square except for the space at the bottom for the label."
(COND
  ((NOT ExtraSpaceFlg)
    (_Super
      self Shape (if newRegion
        then (GetMinRegion newRegion self)
        else (GETREGION (@ width%:,min)
          (@ height%:,min)
          (WINDOWPROP (@ window)
            'REGION)
          (FUNCTION MeterNEWREGIONfn)
            self))
      noUpdateFlg))
  (T (_Super
    self Shape newRegion noUpdateFlg]

```

```
[Method ((Meter ShowLabels)
  self
  "If there are any labels, show them on the dial"
  (COND
    ((@ labels)
     (DSPRIGHTMARGIN (IPLUS (WINDOWPROP (@ window)
                                     'WIDTH)
                             50)
                     (@ window)
                     (* so that labels on the right won't go to the next line)
                     (for lab in (@ labels) as a in (EvenIntervals 90 -360 (@ ticks)) do (ShowRayLabel self a lab]
    )
  )
```

```
(Method ((Meter ShowTicks)
  self
  "Draw ticks at even intervals around the circle starting from 90"
  (for a in (EvenIntervals 90 -360 (@ ticks)) bind (incr _ (IQUOTIENT -360 (@ ticks)))
    do (DrawTick self a (@ ticks%:,smallTicks)
        incr 0.5)))
  ; RBGMartin 29-Apr-86 15:44
```

```
(Method ((RoundScale Reset)
  self newReading)
  ; RBGMartin 29-Apr-86 15:46
  "set reading to value, and then update gauge so that it shows that reading without going through
  intermediate states"
  (_ self ShowReading)
  (_@
   reading newReading)
  (_ self ShowReading))
```

```
[Method ((RoundScale Set)
  self newReading)
  ; edited: 22-May-86 13:19
  "Move the setting on a RoundScale instrument from current setting to that specified by input."
  (PROG ((newVal (_ self ComputeDisplayVal newReading)))
    (_@
     reading newReading)
    (AND (_ self HasLispWindow)
          (RotateLine (@ xc)
                      (@ yc)
                      (@ needleLength)
                      (@ displayVal)
                      (_@
                       displayVal newVal)
                      (@ window)
                      (@ brushWidth]
```

```
(Method ((RoundScale ShowReading)
  self)
  ; edited: 22-May-86 13:16
  "dgb: 26-JAN-83 23:43"
  ;|
  (DrawRay (@ xc)
            (@ yc)
            (@ needleLength)
            [_@
             displayVal
             (_ self ComputeDisplayVal (ABS (@ reading)
                                             (@ brushWidth)
                                             'INVERT
                                             (@ window)))
```

```
(Method ((StraightScale Attach)
  self obj varName shade propName type xOrPos y)
  ; RBGMartin 5-Nov-86 16:21
  "same as Gauge.Attach, but with additional argument of shade for setting the shade of the scale."
  (_@
   shade shade)
  (_Super
   self Attach obj varName propName type xOrPos y))
```

(\UnbatchMethodDefs)

(DEFINEQ

```
(ShowRayLabelLength
  [LAMBDA (self radius)
    (IPLUS 3 radius (IQUOTIENT (MAX (MAXSTRINGWIDTH (@ labels))
                                    (FONTHEIGHT (@ font)))
                                2))
  (* RBGMartin "30-Apr-86 10:58")
)
```

FUNCTION INDEX

ShowRayLabelLength7

PROPERTY INDEX

GAUGEINSTRUMENTS1
