

File created: 6-Jul-2022 22:31:30 {DSK}<home>larry>loops>users>rules>RULESC.;3

changes to: (VARS RULESCCOMS)

previous date: 11-May-93 13:06:22 {DSK}<home>larry>loops>users>rules>RULESC.;1

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

::
:: Copyright (c) 1993 by Venue.

```
(RPAQQ RULESCCOMS ((DECLARE%: DONTCOPY (PROP MAKEFILE-ENVIRONMENT RULESC))  
; Copyright (c) 1982 by Xerox Corporation  
; Written in August 1982 by Mark Stefik, Alan Bell, and Danny  
; Bobrow  
; Fns for compiling LOOPS RuleSets.
```

```
(FNS * RULECOMPILEFNS)  
(VARS (ASSUMELISFPLG)))
```

```
(DECLARE%: DONTCOPY
```

```
(PUTPROPS RULESC MAKEFILE-ENVIRONMENT (:PACKAGE "INTERLISP" :READTABLE "INTERLISP" :BASE 10))  
)
```

:: Copyright (c) 1982 by Xerox Corporation
:: Written in August 1982 by Mark Stefik, Alan Bell, and Danny Bobrow
:: Fns for compiling LOOPS RuleSets.

```
(RPAQQ RULECOMPILEFNS  
(AuditRecordCodeGen BreakLHSCodeGen BreakRHSCodeGen CheckVariableNameConflict CompileAssnStmnt  
CompileComment CompileCompositeGetTerm CompileCompositePutTerm CompileExpr CompileGetTerm  
CompileLHS CompileOpPrecedenceExpr CompileParenExpr CompilePopStmnt CompilePopTerms  
CompilePropGetTerm CompilePropPutTerm CompilePushStmnt CompilePushTerm CompilePutTerm  
CompileQuotedConstant CompileRHS CompileRule CompileRuleList CompileRuleOrLabel  
ContainsItem ExprCodeGen FPrecedence ForTemplate GPrecedence GetRuleStrings OSSetCode OSTestCode  
TraceLHSCodeGen TraceRHSCodeGen))
```

```
(DEFINEQ
```

(AuditRecordCodeGen

```
[LAMBDA NIL
```

```
(* RBGMartin "18-Feb-87 15:06")
```

```
(* Subroutine of CompileRHS. Generates LISP code for creating an audit record for the current rule.)
```

```
(PROG [auditVars setStatements allSpecifications code metaVal  
      (auditTemplate (CONSTANT '(PROGN  
                                (SETQ ^auditRecord (_ ($ ^auditClassName)  
                                                    New))  
                                ^setStatements]  
      (SETQ allSpecifications (APPEND ruleAuditSpecification auditSpecification))  
      (for assnVar in allSpecifications unless (FMEMB (CAR assnVar)  
                                                auditVars)  
        do (SETQ auditVars (CONS (CAR assnVar)  
                                auditVars)))  
      [SETQ setStatements (for assnVar in auditVars collect [SETQ metaVal (CompileGetTerm (CDR (ASSOC assnVar  
                                                                                               allSpecifications  
                                                                                               ]  
                                                                                               (LIST 'PutValue '^auditRecord (KWOTE assnVar)  
                                                                                               (COND  
                                                                                               [(Object? metaVal)  
                                                                                               (LIST 'GetObjFromUID (KWOTE (UID  
                                                                                               ruleObject  
                                                                                               ]  
                                                                                               (T metaVal)]  
      (SETQ code (SUBST (ClassName rsAuditClass)  
                       '^auditClassName auditTemplate))  
      (SETQ code (LSUBST setStatements '^setStatements code))  
      (RETURN code)])
```

(BreakLHSCodeGen

```
[LAMBDA NIL
```

```
(* RBGMartin "18-Feb-87 14:10")
```

```
(* Generates varCode for tracing variables and breaking when the LHS of a rule is tested.)
```

```
(PROG (varCode traceCode ruleCode code)
```

```
(* Compute the parts of the break code.)
```

```
[COND  
  (debugVars (SETQ varCode (CONS 'WRITETTY (for var in debugVars
```

```

                                join (LIST " " (CONCAT (UnParseTerm var)
                                                         "=")
                                       (CompileGetTerm var])
(SETQ ruleCode (LIST '_ (LIST 'GetObjFromUID (KWOTE (UID ruleObject)))
                       'Print))
(SETQ traceCode (LIST 'TraceLHS (KWOTE rsName)
                      (KWOTE ruleLabel)
                      ruleNumber))

(* * Splice the code together.)

[SETQ code (LIST (LIST 'RE]
[COND
  (varCode (SETQ code (CONS varCode code)
                           (ruleCode (SETQ code (CONS ruleCode code)
                                                         (SETQ code (CONS 'PROGN (CONS '
                                                         (CONS traceCode code)
                                                         (* Rule Breaking and Tracing Code)
                                                         (RETURN code]))

```

(BreakRHSCodeGen

(* RBGMartin "18-Feb-87 14:11")

```

[LAMBDA NIL
(* * Generates varCode for tracing variables and breaking when the RHS of a rule is executed.)
(PROG (varCode traceCode ruleCode code)
(* * Compute the parts of the break code.)
[COND
  (debugVars (SETQ varCode (CONS 'WRITETTY (for var in debugVars
                                         join (LIST " " (CONCAT (UnParseTerm var)
                                                         "=")
                                                         (CompileGetTerm var]
                                                         (EQ rsBreakFlg 'B)
(* If B options, generate code to print rule. Skip if BT since LHS trace already prints the rule.)
  (SETQ ruleCode (LIST '_ (LIST 'GetObjFromUID (KWOTE (UID ruleObject)))
                           'Print]
(SETQ traceCode (LIST 'TraceRHS (KWOTE rsName)
                        (KWOTE ruleLabel)
                        ruleNumber))

(* * Splice the code together.)

[SETQ code (LIST (LIST 'RE]
[COND
  (varCode (SETQ code (CONS varCode code)
                           (ruleCode (SETQ code (CONS ruleCode code)
                                                         (SETQ code (CONS 'PROGN (CONS '
                                                         (CONS traceCode code)
                                                         (* Rule Breaking and Tracing Code)
                                                         (RETURN code]))

```

(CheckVariableNameConflict

(* sml "19-Dec-85 16:40")

(* Checks that the names of variables in different categories are

```

unique.)
(PROG [badVars (varLists (CONSTANT ' (wsClassVars wsVars taskVars tempVars lispVars)
                               (for v11 in varLists when (BOUNDP v11) do (for v12 in varLists unless (OR (NOT (BOUNDP v12))
                                                                 badVars
                                                                 (EQ v11 v12))
                                                                 do (COND
                                                                 ((SETQ badVars (INTERSECTION (EVALV v11)
                                                                 (EVALV v12)))
                                                                 (SETQ parseErrorFlg T)
                                                                 (FlushRule "Variable name conflict for " badVars])

```

(CompileAssnStmnt

(* mjs%: "22-JAN-83 09:26")

(* Parse an assignment statement in a rule. Subroutine of Expr. Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)

```

(PROG (assnVar assnVal)
(* * Get the assignment variable.)
(SETQ assnVar (pop ruleSetTokens))
(* * Pop the _)
```

```
(pop ruleSetTokens)
(* Parse the assignment value.)
(SETQ assnVal (CompileExpr))
(* Parse the assignment variable.)
(RETURN (CompilePutTerm assnVar assnVal))
```

CompileComment

```
[LAMBDA NIL (* mjs%: "22-JAN-83 09:26")
(* Parse a comment. Subroutine of ParseRuleList. Input is in the global variable ruleSetTokens.
The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)
(* Collect all ruleSetTokens until reaching the closing right parenthesis.)
(PROG (token doneFlg commentCode)
(pop ruleSetTokens)
[repeatuntil doneFlg do (SETQ token (pop ruleSetTokens))
(COND
((EQ token lpar) (* Recur for embedded parens.)
(push commentCode (CompileComment)))
((EQ token rpar) (* quit after right paren.)
(SETQ doneFlg T)
(SETQ token asterisk))
(T (* otherwise collect the token.)
(push commentCode token)
(SETQ commentCode (DREVERSE commentCode))
(SELECTQ controlType
((DO1 CYCLE1) (* For cycle1 and do1, embed the comments in NO-OP clauses
for the COND statement.)
(SETQ commentCode (LIST NIL commentCode NIL)))
NIL)
(RETURN commentCode])
```

CompileCompositeGetTerm

```
[LAMBDA (term) (* mjs%: " 8-JUN-83 10:51")
(* Compile Composite Get forms of an expression in a rule. Sub of CompileGetTerm.)
(SELECTQ (CAR term)
(% (* A.B = (_ A B))
(LIST leftArrow (CompileGetTerm (CADR term))
(CADDR term)))
(\ (* Lisp variables.)
(CADDR term))
(.(LIST 'DoMethod (CompileGetTerm (CADR term))
(CompileGetTerm (CADDR term))))
(%: %:!) (* a%:b and a%:!b)
[LIST 'GetValue (CompileGetTerm (CADR term))
(COND
((EQ (CAR term)
colon)
(KWOTE (CADDR term)))
((EQ (CAR term)
colonBang)
(CompileGetTerm (CADDR term)))]
(|::| |::!|) (* |a::b| and |a::!b|)
[LIST 'GetClassValue (CompileGetTerm (CADR term))
(COND
((EQ (CAR term)
coloncolon)
(KWOTE (CADDR term)))
((EQ (CAR term)
colonColonBang)
(CompileGetTerm (CADDR term)))]
(|..| (* A..B = (RunRS A B))
(LIST 'RunRS [KWOTE (CADR (CompileGetTerm (CADR term))
(CompileGetTerm (CADDR term)))]))
(., (* A.,B = (_ ($ Task) New A B ^rs))
(LIST leftArrow '($ Task)
'New
(CompileGetTerm (CADR term))
(CompileGetTerm (CADDR term))
'^rs))
(..* (* A..*B is transfer call for A..B)
(LIST 'RuleSetTransfer (LIST 'LIST (CompileGetTerm (CADR term))
(CompileGetTerm (CADDR term))
'^rs)))
(%:, %:,!) (* property values.)
(CompilePropGetTerm term))
($ (* Loops term.)
term)
```

(FlushRule "Bad Term " term))

(CompileCompositePutTerm

[LAMBDA (term assnVal)

(* mjs%: " 8-JUN-83 11:33")

(* * Subroutine of CompilePutTerm. Handles cases of composite term.)

(COND

((EQ (CAR term) backSlash) (LIST 'SETQ (CADDR term) assnVal)) (* lisp vars.)

[(FMEMB (CAR term) (CONSTANT (LIST colon colonBang))) (* a%.b and a%:lb)

(COND

((AND ruleAuditFlg ruleRHSFlg) (SETQ ruleNeedsAuditFlg T) (LIST 'PutAuditRec (CompileGetTerm (CADR term))

[COND ((EQ (CAR term) colon) (KWOTE (CADDR term))) ((EQ (CAR term) colonBang) (CompileGetTerm (CADDR term]

assnVal '^auditRecord))

(T (LIST 'PutValue (CompileGetTerm (CADR term))

[COND ((EQ (CAR term) colon) (KWOTE (CADDR term))) ((EQ (CAR term) colonBang) (CompileGetTerm (CADDR term]

assnVal]

[(FMEMB (CAR term) (CONSTANT (LIST coloncolon colonColonBang))) (* [a::b] and [a:::lb]

(COND

((AND ruleAuditFlg ruleRHSFlg) (SETQ ruleNeedsAuditFlg T) (LIST 'PutClassAuditRec (CompileGetTerm (CADR term))

[COND ((EQ (CAR term) colon) (KWOTE (CADDR term))) ((EQ (CAR term) colonBang) (CompileGetTerm (CADDR term]

assnVal '^auditRecord))

(T (LIST 'PutClassValue (CompileGetTerm (CADR term))

[COND ((EQ (CAR term) coloncolon) (KWOTE (CADDR term))) ((EQ (CAR term) colonColonBang) (CompileGetTerm (CADDR term]

assnVal]

[(FMEMB (CAR term) (CONSTANT (LIST colonComma colonCommaBang))) (* property values.)

(CompilePropPutTerm term assnVal))

(T (FlushRule "Bad Term on left in Assignment Statement:" term) NIL))

(CompileExpr

[LAMBDA NIL

(* mjs%: "27-JAN-83 00:50")

(* * Parse an expression in a rule. Subroutine of ParseLHS and ParseRHS. Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)

(COND

(parseErrorFlg (SkipRule)) ((AND (EQ (CADR ruleSetTokens) leftArrow) (NEQ (CAR ruleSetTokens) lpar)) (* Here for Assignment Statements.)

(CompileAssnStmnt))

((EQ (CADR ruleSetTokens) push) (* Here for Push Statements.)

(CompilePushStmnt))

((EQ (CADR ruleSetTokens) pop) (* Here for Pop Statements.)


```

((EQ ruleTraceFlg 'TT)
 (SETQ exprCode (CONS (TraceLHSCodeGen)
                      exprCode]
(COND
 ((EQ ruleBreakFlg 'BT)
  (SETQ exprCode (CONS (BreakLHSCodeGen)
                      exprCode]
(* ** Return the LHS code.)
[SETQ exprCode (COND
 (parseErrorFlg
  NIL)
 (EQP (FLENGTH exprCode)
  1)
 (CAR exprCode))
 (T
  (CONS 'AND exprCode]
(RETURN exprCode])
(* Add extra LHS clause if Rule Tracing is requested on test.)
(* Add extra LHS clause if Rule Test Breaking is requested.)
(* NIL on parsing error.)
(* One expr = <expr>)
(* Several expressions = (AND <expr> <expr> [...])

```

(CompileOpPrecedenceExpr

[LAMBDA NIL

(* mjs%: "17-MAR-83 14:15")

(* ** Parse the operator precedence part expression in a rule. Subroutine of ParseExpr.
Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes,
and to return LISP code as its value.)

```

(PROG [nextToken prevType term oprStack argStack (endTokens (CONSTANT (LIST semicolon rightArrow)))
      (specOprs (CONSTANT (LIST unaryMinus notSign lbracket)))
      (operators (CONSTANT (LIST lbracket rbracket plus minus plusplus minusminus unaryMinus asterisk
                                slash lessSign greaterSign lessEqSign greaterEqSign eqSign eqeqSign
                                notSign neqSign membSign leftArrow endExpr]
      (* Initialize stacks for operators and operands.)
      (SETQ oprStack (LIST endExpr))
      NextToken
      (SETQ nextToken (CAR ruleSetTokens))
      (COND
        (parseErrorFlg (GO QUIT)))
      [COND
        ((OR (FMEMB nextToken endTokens)
              (FMEMB nextToken thenSpellings))
         (GO LastReduceLoop))
        ((NOT (FMEMB nextToken operators))
         (* Here for operand.)
         (COND
          ((EQ prevType 'operand)
           (* Two sequential operands -> end of expr.)
           (GO LastReduceLoop))
          ((EQ (CAR ruleSetTokens)
               quoteSign)
           (* Here for quoted constant.)
           (SETQ term (CompileQuotedConstant))
           (push argStack term)
           (SETQQ prevType operand)
           (GO NextToken))
          ((EQ (CAR ruleSetTokens)
               lpar)
           (* Here for Fn Call etc.)
           (SETQ term (CompileParenExpr))
           (push argStack term)
           (SETQQ prevType operand)
           (GO NextToken))
          (T
           (* Here for term.)
           (SETQ term (CompileGetTerm (pop ruleSetTokens)))
           (push argStack term)
           (SETQQ prevType operand)
           (GO NextToken]
           (* Here for operator)
         (COND
          ((AND (FMEMB nextToken specOprs)
                (EQ prevType 'operand))
           (* operand followed by unary opr or bracket expression -> end
           of expr.)
           (GO LastReduceLoop))
          (SETQ prevType 'operator)
          (COND
            ((ILESSP (FPrecedence (CAR oprStack))
                     (GPrecedence nextToken))
             (* Shift!)
             (push oprStack (pop ruleSetTokens)))
            (T
             (* Reduce!)
             (ExprCodeGen)))
          (GO NextToken)
        (* ** Here if no more ruleSetTokens in the expression.)
      LastReduceLoop
      (COND
        (parseErrorFlg (GO QUIT)))
      (COND
        ((AND (NULL (CADR oprStack))
              (NULL (CADR argStack)))
         (* Normal Finish)
         (GO QUIT)))

```

```

  (ExprCodeGen)
  (GO LastReduceLoop)
QUIT
  (RETURN (CAR argStack])

```

(CompileParenExpr

[LAMBDA NIL (* dgb%: "21-Feb-84 15:21")

(* Parse a parenthesized clause -- either a LISP function call or a LOOPS SEND message statement or a STOP statement -- in a rule. Subroutine of Expr. Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)

```

(PROG (fnName object selector args)

  (* Pop the left parenthesis and get the function name.)

  (pop ruleSetTokens)
  (SETQ fnName (pop ruleSetTokens))

  (* Collect the function name or SEND preface.)

  [COND
    ((FMEMB fnName sendSpellings) (* msg.)
      (SETQ object (CompileExpr))
      (SETQ selector (COND
        ((EQ fnName leftArrowBang) (* For _! msg evaluate the selector.)
          (CompileExpr))
        (T (* For _ msg do not eval selector.)
          (pop ruleSetTokens]

    (* Collect the Arguments.)

    (SETQ args (while (AND ruleSetTokens (NEQ (CAR ruleSetTokens)
      rpar)
      (NEQ (CAR ruleSetTokens)
      semicolon))
      collect (CompileExpr)))

    (* pop the right parenthesis.)

    (COND
      ((NEQ (CAR ruleSetTokens)
      rpar)
      (FlushRule "Missing right parenthesis"))
      (T (pop ruleSetTokens)))

    (* Return the Function, STOP statement, or Msg expression.)

    (RETURN (COND
      [(EQ fnName leftArrowBang) (* !_ msg.)
        (CONS 'DoMethod (CONS object (CONS selector (CONS NIL args]
      [(FMEMB fnName sendSpellings) (* _ msg)
        (CONS leftArrow (CONS object (CONS selector args]
      [(FMEMB fnName stopSpellings) (* STOP statement)
        (LIST 'PROGN ' (* ^value set by RuleSetStop)
          (CONS 'RuleSetStop args)
          (LIST 'GO 'QUIT]
      (T (* LISP fn)
        (COND
          ([AND (NOT (FNTYP fnName))
            (NOT (GETPROP fnName 'CLISPPWORD)
            (printout PDefault T T "Warning Unrecognized LISP fn " .FONT BOLDFONT fnName
            .FONT DEFAULTFONT T)))
          (CONS fnName args])

```

(CompilePopStmnt

[LAMBDA NIL (* mjs%: "22-JAN-83 09:26")

(* Parse a pop statement in a rule. Subroutine of Expr. Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)

```

(PROG (assnVar stackVar) (* Get the assignment variable.)
  (SETQ assnVar (pop ruleSetTokens)) (* Pop the _ token.)
  (pop ruleSetTokens) (* Get the pop value.)
  (SETQ stackVar (pop ruleSetTokens)) (* Compile it.)
  (RETURN (CompilePopTerms assnVar stackVar])

```

(CompilePopTerms

[LAMBDA (assnVar stackVar) (* mjs%: "26-OCT-82 11:17")

(* Parse the terms in a pop statement. The subroutine is expected to return LISP code as its value. Generates code to Pop the first item of the list stored as the value of stackVar, update the stack, and return the item.)

```

(PROG [getStackCode putStackCode putItemCode (popTemplate (CONSTANT ' (PROG (^item ^stack)

```

```
(* Pop Statement. ^assnVar _ ^stackVar)
  (SETQ ^stack ^getStackCode)
  (SETQ ^item (CAR ^stack))
  (SETQ ^stack (CDR ^stack))
  ^putStackCode
  ^putItemCode
  (RETURN ^item]
```

(* * Generate code for getting the stack, storing the revised stack, and storing the item.)

```
(SETQ getStackCode (CompileGetTerm stackVar))
(SETQ putStackCode (CompilePutTerm stackVar '^stack))
(SETQ putItemCode (CompilePutTerm assnVar '^item))
```

(* * Substitute the code into the pop template.)

```
(SETQ popTemplate (SUBST getStackCode '^getStackCode popTemplate))
(DSUBST putStackCode '^putStackCode popTemplate)
(DSUBST putItemCode '^putItemCode popTemplate)
(DSUBST assnVar '^assnVar popTemplate)
(DSUBST stackVar '^stackVar popTemplate)
```

(* * Return the instantiated template for the pop statement.)

```
(RETURN popTemplate)]
```

(CompilePropGetTerm

[LAMBDA (term)

(* mjs%: " 8-JUN-83 10:49")

(* * Subroutine of CompileCompositeGetTerm. Handles the property values cases for a%:,b |a.b:,c| etc.)

```
(COND
  [(LISTP (CADR term))
   (PROG (term1)
    (SETQ term1 (CADR term))
    (RETURN (COND
      ((FMEMB (CAR term1)
        (CONSTANT (LIST colon colonBang coloncolon colonColonBang))))
      (* colon/coloncolon combinations)
      (LIST (COND
        ((FMEMB (CAR term1)
          (CONSTANT (LIST coloncolon colonColonBang)))
         'GetClassValue)
         (T 'GetValue))
        (CompileGetTerm (CADR term1)))
      [COND
        ((FMEMB (CAR term1)
          (CONSTANT (LIST colon coloncolon)))
         (KWOTE (CADDR term1)))
        (T (CompileGetTerm (CADDR term1))
          (COND
            ((EQ colonComma (CAR term))
             (KWOTE (CADDR term)))
            ((EQ colonCommaBang (CAR term))
             (CompileGetTerm (CADDR term))
             (* Bad property request.)
             (* A%:,B = (GetValue self (QUOTE A)
              (QUOTE B)))
            ((OR (FMEMB (CADR term)
              ruleVars)
              (FMEMB (CADR term)
              compileTimeVars))
             (FlushRule "Illegal to fetch property of this var: " term))
            (T
              (LIST 'GetValue 'self (KWOTE (CADR term))
                (COND
                  ((EQ (CAR term)
                    colonComma)
                   (* a%:,b)
                   (KWOTE (CADDR term)))
                  ((EQ (CAR term)
                    colonCommaBang)
                   (* a%:,lb)
                   (CompileGetTerm (CADDR term))
```

(CompilePropPutTerm

[LAMBDA (term assnVal)

(* mjs%: " 8-JUN-83 10:49")

(* * Subroutine of CompilePutTerm. Handles the cases for assignment to property values as in a%:,b etc.)

```
(COND
  [(LISTP (CADR term))
   (PROG (term1)
    (SETQ term1 (CADR term))
    (RETURN (COND
      ((FMEMB (CAR term1)
        (CONSTANT (LIST colon colonBang coloncolon colonColonBang))))
      (* [a.b:,c| and |a:lb:,c| and |a.b:,lc| and |a:lb:,lc|)
      (LIST (COND
```



```

      ((FMEMB (CAR term1)
        (CONSTANT (LIST coloncolon colonColonBang)))
       'PutClassValue)
      (T 'PutValue))
    (CompileGetTerm (CADR term1))
  [COND
    ((FMEMB (CAR term1)
      (CONSTANT (LIST colon coloncolon)))
     (KWOTE (CADDR term1)))
    ((EQ (CAR term1)
      colonBang)
     (CompileGetTerm (CADDR term1])
    assnVal
  (COND
    ((EQ (CAR term)
      colonComma)
     (KWOTE (CADDR term)))
    ((EQ (CAR term)
      colonCommaBang)
     (CompileGetTerm (CADDR term])
    (T (FlushRule "Invalid property access term" term])
  ((OR (FMEMB (CADR term)
    ruleVars))
    (FlushRule "Illegal to store property of RuleVar:" term))
  (T
    (LIST 'PutValue 'self (KWOTE (CADR term))
      assnVal
    (COND
      ((EQ (CAR term)
        colonComma)
       (KWOTE (CADDR term)))
      ((EQ (CAR term)
        colonCommaBang)
       (CompileGetTerm (CADDR term])

```

(CompilePushStmnt

[LAMBDA NIL

(* mjs%: "22-JAN-83 09:26")

(* Parse a push statement in a rule. Subroutine of Expr. Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)

```

(PROG (assnVal stackVar)
  (SETQ stackVar (pop ruleSetTokens))
  (pop ruleSetTokens)
  (SETQ assnVal (CompileExpr))
  (RETURN (CompilePushTerm stackVar assnVal]))
(* Get the assignment variable.)
(* Pop the _+)
(* Parse the push value.)
(* Parse the push variable.)

```

(CompilePushTerm

[LAMBDA (stackVar assnVal)

(* mjs%: "26-OCT-82 11:44")

(* Parse the terms in a push statement. The subroutine is expected to return LISP code as its value. Generates code to Push the assnVal onto the list stored as the value of stackVar and return the item.)

```

(PROG [getStackCode putStackCode putItemCode (pushTemplate (CONSTANT '(PROG (^stack ^item)
  (* Push Statement.)
  (SETQ ^item ^assnVal)
  (SETQ ^stack (CONS ^item
    ^getStackCode
  ))
  ^putStackCode
  (RETURN ^item]

```

(* Generate code for getting the stack, storing the revised stack, and storing the item.)

```

(SETQ getStackCode (CompileGetTerm stackVar))
(SETQ putStackCode (CompilePutTerm stackVar '^stack))

```

(* Substitute the code into the push template.)

```

(SETQ pushTemplate (SUBST getStackCode '^getStackCode pushTemplate))
(DSUBST putStackCode '^putStackCode pushTemplate)
(DSUBST assnVal '^assnVal pushTemplate)

```

(* Return the instantiated template for the pop statement.)

```

(RETURN pushTemplate])

```

(CompilePutTerm

[LAMBDA (term assnVal)

(* mjs%: " 9-JUN-83 13:30")

(* Compile the Put form of a term in an expression in a rule. Input is in the argument term. The subroutine is expected to return LISP code as its value. Generates code to Put the value of assnVal into term.)

(COND

```

(NUMBERP term) (* number = error)
(FlushRule "Unexpected Number on left in Assignment Statement:" term)
[ (LITATOM term)
(COND
  ((OR (FMEMB term tempVars) (* tempVars)
        (FMEMB term rsArgs))
    (LIST 'SETQ term assnVal))
  ((FMEMB term taskVars) (* taskVars)
    (LIST 'PutValue '^task (KWOTE term)
          assnVal))
  ((OR (FMEMB term compileTimeVars)
        (FMEMB term reservedRuleWords))
    (FlushRule "Unexpected constant on left in Assignment Statement:" term))
  ((NOT (LetterP term))
    (FlushRule "Unexpected " term))
  ((NOT (FMEMB term wsVars))
    (FlushRule "Unrecognized IV:" term))
  ((AND ruleAuditFlg ruleRHSFlg) (* work space variable audited)
    (SETQ ruleNeedsAuditFlg T)
    (LIST 'PutAuditRec 'self (KWOTE term)
          assnVal
          '^auditRecord))
  (T (* work space variable.)
    (LIST 'PutValue 'self (KWOTE term)
          assnVal))
  ((NLISTP term) (* Error if not list.)
    (FlushRule "Bad Term on left in Assignment Statement" term))
  (T (* Composite put term.)
    (CompileCompositePutTerm term assnVal))
]

```

(CompileQuotedConstant

```

[LAMBDA NIL (* mjs%: "22-JAN-83 10:46")

(** Parse a quoted constant in a rule. Subroutine of Expr. Input is in the global variable ruleSetTokens.
The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)

(PROG [token qTokens doneFlg (qEndTokens (CONSTANT (LIST rpar semicolon]
(* Discard the quoteSign)
(* Get the first token of the quoted constant.)
(pop ruleSetTokens)
(SETQ token (pop ruleSetTokens))
(COND
  ((NEQ token lpar) (* [...] %' NL [...] -> (QUOTE NL))
    (RETURN (KWOTE token)))
  (T (* [...] %' (A1 A2 A3 [...] |...| -> (QUOTE
      (A1 A2 A3 [...])))
    (SETQ qTokens (eachtime (SETQ token (pop ruleSetTokens)) until (FMEMB token qEndTokens)
      collect token))
    (COND
      ((EQ token semicolon)
        (FlushRule "Unexpected" "semicolon" "in quoted constant")))
    (RETURN (KWOTE qTokens))

```

(CompileRHS

```

[LAMBDA NIL (* mjs%: " 7-JUN-83 11:16")

(** Parse the RHS of a rule. Subroutine of ParseRule. Input is in the global variable ruleSetTokens.
The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value.)

(PROG (token exprCode)
(SETQ ruleRHSFlg T)

(** Here to compile RHS)

(COND
  ((FMEMB (CAR ruleSetTokens)
    thenSpellings) (* Pop the THEN.)
    (pop ruleSetTokens)))

(** Collect the code from each of the exprs of the RHS.)

[SETQ exprCode (collect (CompileExpr) until (OR parseErrorFlg (EQ (CAR ruleSetTokens)
  semicolon]
(COND
  ((AND oneShotFlg (NULL oneShotBangFlg))

(** Add extra RHS clause if this is a one-shot rule but not a one-shot-bang rule.)

  (SETQ exprCode (CONS (OSSetCode)
    exprCode])

(COND
  (ruleTraceFlg (* Here to trace a rule.)
    (SETQ exprCode (CONS (TraceRHSCodeGen)
      exprCode)))
  (ruleTraceFlg (* Here to trace if rule is tested.)
    (SETQ exprCode (CONS (LIST 'TraceRHS (KWOTE ruleLabel)

```

```

                                ruleNumber)
                                exprCode]
[COND
  (ruleBreakFlg
    (SETQ exprCode (CONS (BreakRHSCodeGen)
                          exprCode)
    (* Add extra RHS clause if rule tracing is requested.)
[COND
  (ruleNeedsAuditFlg
    (SETQ exprCode (CONS (AuditRecordCodeGen)
                          exprCode)
    (* Add extra RHS clause if rule needs audit record.)
(** Return the RHS code.)
[SETQ exprCode (COND
  ((EQP (FLENGTH exprCode)
        1)
    (CONS 'SETQ (CONS '^value exprCode)))
  (T
    (CONS 'SETQ (CONS '^value (CONS (CONS 'PROGN exprCode]
    (* One expr = (SETQ ^value <expr>))
    (* Several expressions = (SETQ ^value
    (PROGN <expr> <expr> [...]))
    (* Save the compiled code in the rule object.)
  (RETURN exprCode])

```

CompileRule

```
[LAMBDA (self ruleSetSource) (* RBGMartin "16-Feb-87 16:55")
```

(* Parse a rule. Subroutine of CompileRuleList. Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes, and to return LISP code as its value. Most of the work is done in CompileRule1. Variable self is the current RuleSet.)

```

(PROG (ruleCode ruleOldSource)
  (** Increment rule number.)
  (SETQ ruleNumber (ADD1 ruleNumber))
  (SPACES 1 PPDefault)
  (PRIN1 ruleNumber PPDefault)
  (** Fetch old rule object, if any.)
  (SETQ ruleObject (CAR (NTH rsRuleObjects ruleNumber)))
  (RETURN (CompileRule1))

```

CompileRule1

```
[LAMBDA (specialFlg) (* dbg%: "17-Feb-84 18:08")
```

(* Subroutine of CompileRule and of the RuleExec. Argument specialFlg is T if not compiling a rule in a RuleSet -- that is, if called by RuleExec.)

```

(PROG (firstLastFlg (ruleBndry (CONSTANT (LIST semicolon)))
      ruleForm ruleCode)
  (DECLARE (SPECVARS firstLastFlg) (* Interpret any meta information.)
  (GetRuleMetaDecls)
  [SETQ ruleForm (COND
    ((FMEMB (CAR ruleSetTokens)
             ifSpellings)
     (* IF [...] = IfThen)
     (pop ruleSetTokens)
     'IfThen)
    ((FMEMB (CAR ruleSetTokens)
             thenSpellings)
     (* -> [...] = OnlyThen)
     (pop ruleSetTokens)
     'OnlyThen)
    ((ScanFor thenSpellings ruleBndry)
     (* [...] -> [...] ; = IfThen)
     'IfThen)
    (T
     (* [...] ; = OnlyThen)
     'OnlyThen]
  [COND
    ((AND (EQ ruleForm 'OnlyThen)
          (OR ruleBreakFlg ruleTraceFlg oneShotFlg))
     (* Augment an OnlyThen rule if OneShot, or Tracing or
     Breaking.)
     (SETQ ruleForm 'AugmentedOnlyThen]
  (** Frame the rule code depending on the controlType. If this is a first or last rule, then we always want the simple
  conditional form)
  (SETQ ruleCode (SELECTQ (COND
    (firstLastFlg 'DOALL)
    (T controlType))
    ((DO1 WHILE1 FOR1)
     (SELECTQ ruleForm
       (IfThen (LIST (CompileLHS NIL NIL specialFlg)
                     (CompileRHS)))
       (OnlyThen (LIST T (CompileRHS)))
       (AugmentedOnlyThen
        (LIST (CompileLHS 'Augmented NIL specialFlg)

```

```

                (CompileRHS)))
            (FlushRule "Unrecognized Rule Syntax"))
        ((DOALL WHILEALL FORALL)
         (SELECTQ ruleForm
          (IfThen (LIST 'COND (LIST (CompileLHS NIL NIL specialFlg)
                                   (CompileRHS))))
          (OnlyThen (CompileRHS))
          (AugmentedOnlyThen
           (LIST 'COND (LIST (CompileLHS 'Augmented NIL specialFlg)
                             (CompileRHS))))
          (FlushRule "Unrecognized Rule Syntax"))
        ((DONEXT WHILENEXT)
         (SELECTQ ruleForm
          (IfThen [LIST ruleNumber (LIST 'COND (LIST (CompileLHS NIL NIL specialFlg)
                                                       (CompileRHS))]
          (OnlyThen (LIST ruleNumber (CompileRHS)))
          (AugmentedOnlyThen
           (LIST 'COND (LIST (CompileLHS 'Augmented NIL specialFlg)
                             (CompileRHS))))
          (FlushRule "Unrecognized Rule Syntax"))
          (FlushRule "Unrecognized controlType: " controlType)))
(COND
  ((EQ (CAR ruleSetTokens)
        semicolon)
   (* Pop the semicolon.)
   (pop ruleSetTokens)))
(* * First and last rules are not collected in the ruleSet, and are always done when applicable)
(SELECTQ firstLastFlg
  (F (SETQ firstRules (NCONC1 firstRules ruleCode)))
  (L (SETQ lastRules (NCONC1 lastRules ruleCode)))
  (RETURN (LIST ruleCode)))
(RETURN NIL))

```

(CompileRuleList

[LAMBDA (self ruleSetSource)

; Edited 11-Jul-88 20:59 by jrb:

(* * Subroutine of RuleSet.CompileRules. Argument self is the RuleSet.
 Input ruleSetTokens are in the global variable ruleSetTokens. An instantiated codeTemplate for executing the RuleList is returned as value of this subroutine.)

```

(PROG (codeTemplate whileTemplate rules progVars firstRules lastRules)
  (DECLARE (SPECVARS firstRules lastRules) (* Kludge!)
   (SETQ rsInternalTempVars NIL)
  (COND
   ((NULL wsClass)
    (FlushRule "No " " workspace " "set yet. ")
    (RETURN NIL)))
  (SETQ ruleNumber 0)
  (* * Parse the Rules and substitute them into the code template.)
  [while (AND (ILEQ ruleNumber rsNumRules)
              ruleSetTokens
              (NOT parseErrorFlg))
   do (COND
        ((OR (EQ (CAR ruleSetTokens)
                 semicolon)
             (NULL (CAR ruleSetTokens)))
         (pop ruleSetTokens))
        (T (SETQ parseErrorFlg NIL)
           (SETQ rules (NCONC rules (CompileRuleOrLabel self ruleSetSource)]
  [COND
   ((AND rsRuleAppliedFlg (EQ controlType 'WHILE1)) (* Add extra rule for WHILE1.)
    (SETQ rules (NCONC1 rules '(T (* Here if no rules were executed.)
                                  (SETQ ruleApplied NIL]
  (* * Determine the codeTemplate for the RuleSet.)
  (SETQ codeTemplate (GetRuleSetTemplate))
  (* * Compute the vars for the PROG of the RuleSet.)
  (SETQ progVars (GetProgVars))
  (SETQ codeTemplate (SUBST progVars '^progVars codeTemplate))
  [COND
   ((FMEMB controlType cyclicControlStructures)
    (COND
     ((NULL rsWhileCondition)
      (FlushRule "No While Condition specified for " controlType ". Assuming T.")
      (SETQ rsWhileCondition T))
     (SETQ ruleSetTokens (NCONC1 rsWhileCondition rightArrow))
     [PROG ((ASSUMELISPFLG T)) (* Inside iteration conditions assume Lisp variables when not
                               told otherwise)
           (SETQ whileTemplate (CompileLHS NIL 'New 'Special]
   (SETQ codeTemplate (SELECTQ controlType

```

```

                ((FOR1 FORALL)                (* Special case for Fors)
                 (ForTemplate codeTemplate whileTemplate))
                (DSUBST whileTemplate '^whileCondition codeTemplate]
(SETQ codeTemplate (LSUBST rules '^rules codeTemplate))
(AND firstRules (SETQ codeTemplate (LSUBST firstRules '^firstRules codeTemplate)))
(AND lastRules (SETQ codeTemplate (LSUBST lastRules '^lastRules codeTemplate)))
(_@
 taskVars taskVars)

(* * Compile and Substitute the While Condition.)

(CompileRuleList codeTemplate)
(RETURN codeTemplate])

```

(CompileRuleOrLabel

```

[LAMBDA (self ruleSetSource)                (* mjs%: "7-JUN-83 11:20")

(* * Parse a rule, a label, or a comment. Subroutine of CompileRuleList.
Input is in the global variable ruleSetTokens. The subroutine is expected to remove the ruleSetTokens that it recognizes,
and to return LISP code as its value.)

(SETQ ruleLabel NIL)
(COND
 ((EQ (CADR ruleSetTokens)
      colon)                (* <label>%: |...| Return ^ruleLabel and discard colon.)
  (SETQ ruleLabel (pop ruleSetTokens))
  (pop ruleSetTokens)
  ruleLabel)                (* Discard any comments.)
 (FlushComment?)           (* Compile the Rule.)
 (CompileRule self ruleSetSource])

```

(ContainsItem

```

[LAMBDA (item expr)                (* dbg%: "21-Feb-84 09:30")
 (COND
 ((NLISTP expr)
  (EQ item expr))
 (T (OR (ContainsItem item (CAR expr))
        (ContainsItem item (CDR expr))

```

(ExprCodeGen

```

[LAMBDA NIL                (* mjs%: "17-MAR-83 14:08")

(* * Code generation function for expression parsing called from ParseOpPrecedenceExpr.
Operates by side effect on implicitly passed variables oprStack, argStack, and nextToken.)

(PROG [operator arg1 arg2 (noPops (CONSTANT (LIST lbracket rbracket)))
      (unaryOprs (CONSTANT (LIST unaryMinus notSign]
(SETQ operator (pop oprStack))
[COND
 ((FMEMB operator unaryOprs)                (* pop 1 arg for unary oprs.)
  (SETQ arg1 (pop argStack)))
 ((FMEMB operator noPops)                (* Skip popping for noPops)
  NIL)
 (T                (* pop 2 args for binary oprs.)
  (SETQ arg2 (pop argStack))
  (SETQ arg1 (pop argStack]

(* * Reduce the operator.)

(SETQ reducedArg (SELECTQ operator
 (%[ (COND
 ((EQ nextToken rbracket)
  (pop ruleSetTokens)
  (SETQ nextToken (CAR ruleSetTokens))
  (SETQ prevType 'operand)
  (RETURN))
 (T (FlushRule "Bracket error in expression"))))
 (%] (FlushRule "Bracket error in expression"))
 (+ (LIST 'PLUS arg1 arg2))
 (- (LIST 'DIFFERENCE arg1 arg2))
 (-1- (LIST 'MINUS arg1))
 (++) (LIST 'PLUSPLUS arg1 arg2))
 (--) (LIST 'MINUSMINUS arg1 arg2))
 (* (LIST 'TIMES arg1 arg2))
 (/ (LIST 'QUOTIENT arg1 arg2))
 (< (LIST 'LESSP arg1 arg2))
 (<= (LIST 'LEQ arg1 arg2))
 (> (LIST 'GREATERP arg1 arg2))
 (>= (LIST 'GEQ arg1 arg2))
 (= (LIST 'EQ arg1 arg2))
 (== (LIST 'EQUALS arg1 arg2))
 (~= (LIST 'NEQ arg1 arg2))
 (<< (LIST 'FMEMB arg1 arg2))
 (~ (LIST 'NOT arg1))

```

```

      (_ (CompilePutTerm arg1 arg2))
      (FlushRule "Unrecognized operator " operator))

```

(* * Push reduced arg on Opr Stack.)

```
(push argStack reducedArg])
```

(FPrecedence

```
[LAMBDA (operator) (* mjs%: "17-MAR-83 14:04")
```

(* * F-Precedence function for expression parsing. Called by ParseExpr.)

```
(SELECTQ operator
 (%[ -1)
 (%] 6)
 (+ 3)
 (- 3)
 (-1- 3)
 (++) 3)
 (--) 3)
 (* 5)
 (/ 5)
 (< 1)
 (<= 1)
 (> 1)
 (>= 1)
 (= 1)
 (== 1)
 (~= 1)
 (<< 1)
 (_ 2)
 (~ 5)
 (endExpr -2)
 (FlushRule "Unrecognized operator" operator])
```

(ForTemplate

```
[LAMBDA (codeTemplate whileTemplate) (* dbg%: "21-Feb-84 17:47")
```

```
(PROG [(wt (LIST 'SETQ '^value (COND
 [(NOT (ContainsItem 'ruleSet whileTemplate))
 (APPEND whileTemplate (LIST 'DO 'ruleSet)
 (T whileTemplate)
 (RETURN (DSUBST (SUBST (SELECTQ controlType
 (FOR1 (LIST 'COND '^rules)
 '^rules)
 'ruleSet wt)
 '^forLoop codeTemplate])
```

(GPrecedence

```
[LAMBDA (operator) (* mjs%: "17-MAR-83 14:05")
```

(* * G-Precedence function for expression parsing. Called by ParseExpr.)

```
(SELECTQ operator
 (%[ 6)
 (%] -1)
 (+ 2)
 (- 2)
 (-1- 2)
 (++) 2)
 (--) 2)
 (* 4)
 (/ 4)
 (< 1)
 (<= 1)
 (> 1)
 (>= 1)
 (= 1)
 (== 1)
 (<< 1)
 (~= 1)
 (_ 2)
 (~ 4)
 (endExpr -2)
 (FlushRule "Unrecognized operator" operator])
```

(GetRuleStrings

```
[LAMBDA (sourceRules) (* mjs%: "11-NOV-82 09:59")
```

(* * Partitions the sourceRules into a list of strings into individual statements (rules and declarations) - ending in semicolons. Called by RuleSetSource.EditRules to create rsOldRuleStrings and rsRuleStrings. These lists are compared during RuleSet compilation. Rule objects are created to describe only those rules that have been changed.)

```
(PROG (startPos stopPos ruleStrings)
      (SETQ stopPos 0)
      (SETQ ruleStrings (while (PROGN (SETQ startPos (ADD1 stopPos))
                                     (SETQ stopPos (STRPOS semicolon sourceRules startPos)))
                              collect (SUBSTRING sourceRules startPos stopPos)))
      (RETURN ruleStrings])
```

(OSSetCode

```
[LAMBDA NIL (* mjs%: "11-OCT-82 15:42")
```

(* Generate the Set Code for a one-shot rule. E.G. _@ (^task triedRule7)_T)

```
(COND (rsTaskFlg (* If tasking, set Task var.)
      (LIST '_@ (^task oneShotFlg T))
      (T (* If not tasking, set Rule var.)
         (LIST 'SETQ oneShotFlg T]))
```

(OSTestCode

```
[LAMBDA NIL (* mjs%: "11-OCT-82 13:26")
```

(* Generate the Test Code for a one-shot rule. E.G., (NOT @ (^task triedRule7)))

```
(COND (rsTaskFlg (* Use Task Var if RuleSet to be used in a Task.)
      (LIST 'NOT (LIST '@ (^task oneShotFlg)))
      (T (* Use Rule Var RuleSet not to be used in a task.)
         (LIST 'NOT oneShotFlg]))
```

(TraceLHSCodeGen

```
[LAMBDA NIL (* RBGMartin "18-Feb-87 14:12")
```

(* Generates varCode for tracing variables when the LHS of a rule is tested.)

```
(PROG (varCode traceCode ruleCode code)
      (* Compute the parts of the trace code.)
      [COND (debugVars (SETQ varCode (CONS 'WRITETTY (for var in debugVars
                                             join (LIST " " (CONCAT (UnParseTerm var)
                                                                    "=")
                                                                    (CompileGetTerm var)
                                                                    " "))
                                             (SETQ ruleCode (LIST '_ (LIST 'GetObjFromUID (KWOTE (UID ruleObject)))
                                                                    'Print)))
                                             (SETQ traceCode (LIST 'TraceLHS (KWOTE rsName)
                                                                    (KWOTE ruleLabel)
                                                                    ruleNumber)))
            (* Splice the code together.)
            (SETQ code (LIST))
            [COND (varCode (SETQ code (CONS varCode code))
                  [COND (ruleCode (SETQ code (CONS ruleCode code))
                        [SETQ code (CONS 'PROGN (CONS '
                                                         (CONS traceCode code)
                                                         (* Rule Tracing Code)
                                                         )
                                                         (CONS traceCode code)
                                                         )
                        (RETURN code])])])])
```

(TraceRHSCodeGen

```
[LAMBDA NIL (* RBGMartin "18-Feb-87 14:12")
```

(* Generates varCode for tracing variables when the RHS of a rule is satisfied.)

```
(PROG (varCode traceCode ruleCode code)
      (* Compute the parts of the trace code.)
      [COND (debugVars (SETQ varCode (CONS 'WRITETTY (for var in debugVars
                                             join (LIST " " (CONCAT (UnParseTerm var)
                                                                    "=")
                                                                    (CompileGetTerm var)
                                                                    " "))
                                             (SETQ ruleCode (LIST '_ (LIST 'GetObjFromUID (KWOTE (UID ruleObject)))
                                                                    'Print)))
                                             (SETQ traceCode (LIST 'TraceRHS (KWOTE rsName)
                                                                    (KWOTE ruleLabel)
                                                                    ruleNumber)))
            (* Splice the code together.)
            (SETQ code (LIST))
            [COND (varCode (SETQ code (CONS varCode code))
                  [COND (ruleCode (SETQ code (CONS ruleCode code))
                        [SETQ code (CONS 'PROGN (CONS '
                                                         (CONS traceCode code)
                                                         (* Rule Tracing Code)
                                                         )
                                                         (CONS traceCode code)
                                                         )
                        (RETURN code])])])])
```

(* * Splice the code together.)

(SETQ code (LIST))

[COND

(varCode (SETQ code (CONS varCode code]

[COND

(ruleCode (SETQ code (CONS ruleCode code]

[SETQ code (CONS 'PROGN (CONS ' (CONS traceCode code]

(* Rule Tracing Code)

(RETURN code])

)

(RPAQQ ASSUMELISPFLG NIL)

(PUTPROPS RULESC COPYRIGHT ("Venue" 1993))

FUNCTION INDEX

AuditRecordCodeGen	1	CompileParenExpr	7	CompileRuleList	12
BreakLHSCodeGen	1	CompilePopStmnt	7	CompileRuleOrLabel	13
BreakRHSCodeGen	2	CompilePopTerms	7	ContainsItem	13
CheckVariableNameConflict	2	CompilePropGetTerm	8	ExprCodeGen	13
CompileAssnStmnt	2	CompilePropPutTerm	8	ForTemplate	14
CompileComment	3	CompilePushStmnt	9	FPrecedence	14
CompileCompositeGetTerm	3	CompilePushTerm	9	GetRuleStrings	14
CompileCompositePutTerm	4	CompilePutTerm	9	GPrecedence	14
CompileExpr	4	CompileQuotedConstant	10	OSSetCode	15
CompileGetTerm	5	CompileRHS	10	OSTestCode	15
CompileLHS	5	CompileRule	11	TraceLHSCodeGen	15
CompileOpPrecedenceExpr	6	CompileRule1	11	TraceRHSCodeGen	15

VARIABLE INDEX

ASSUMELISPFLG	16	RULECOMPILEFNS	1
---------------------	----	----------------------	---

PROPERTY INDEX

RULESC	1
--------------	---
