

File created: 26-Dec-2021 14:32:50 {DSK}<Users>kaplan>Local>medley3.5>my-medley>sources>ATBL.;32

changes to: (FNS MAKE-READER-ENVIRONMENT)

previous date: 19-Dec-2021 14:09:43 {DSK}<Users>kaplan>Local>medley3.5>my-medley>sources>ATBL.;31

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

::
:: Copyright (c) 1982-1987, 1990, 1993, 2018, 2021 by Venue & Xerox Corporation.

(RPAQQ **ATBLCOMS**

```
[ (COMS
      (DECLARE%: DONTCOPY (EXPORT (MACROS \SYNCODE \SETSYNCODE)
      (RECORDS CHARTABLE))
      (CONSTANTS \NSCHARHASHKEYS \NSCHARHASHOVERFLOW)
      (MACROS \CREATENSCHARHASH))
      (FNS GETSYNTAX SETSYNTAX SYNTAXP \COPYSYNTAX \GETCHARCODE \SETFATSYNCODE \MAPCHARTABLE))
      (COMS
      (FNS CONTROL COPYTERMTABLE DELETECONTROL GETDELETECONTROL ECHOCHAR ECHOCONTROL ECHOMODE
      GETECHOMODE GETCONTROL GETTERMTABLE RAISE GETRAISE RESETTERMTABLE SETTERMTABLE TERMTABLEP
      \GETTERMSYNTAX \GTERMTABLE \ORIGTERMTABLE \SETTERMSYNTAX \TERMCLASSTOCODE \TERMCODETOCLASS
      \LITCHECK)
      (DECLARE%: DONTCOPY (EXPORT (CONSTANTS * CCECHOMODES)
      (CONSTANTS * TERMCLASSES)
      (RECORDS TERMCODE TERMTABLEP)))
      (INITRECORDS TERMTABLEP))
      (COMS
      (FNS COPYREADTABLE FIND-READTABLE IN-READTABLE ESCAPE GETBRK GETREADTABLE GETSEPR READMACROS
      READTABLEP READTABLEPROP RESETREADTABLE SETBRK SETREADTABLE SETSEPR \GETREADSYNTAX
      \GTREADTABLE \GTREADTABLE1 \ORIGREADTABLE \READCLASSTOCODE \SETMACROSYNTAX \SETREADSYNTAX
      \READTABLEP.DEFPRINT)
      (PROP ARGUMENTS READTABLEPROP)
      (DECLARE%: EVAL@COMPILE DONTCOPY
      ; READCLASSTOKENS Generates READCLASSES and some
      ; interesting SELECTQ's
      ; OTHER must be zero because of initialization.
      [VARS READCLASSTOKENS (READCLASSES (MAPCAR READCLASSTOKENS (FUNCTION
      (LAMBDA
      (PAIR)
      (LIST (PACK* (CAR PAIR)
      ".RC")
      (CADR PAIR])
      (MACROS \COMPUTED.FORM)
      ; This macro ought to be official somehow
      (RECORDS CONTEXTS ESCAPES WAKEUPS)
      (EXPORT (MACROS \GETREADMACRODEF \GTREADTABLE \GTREADTABLE1)
      (CONSTANTS MACROBIT BREAKBIT STOPATOMBIT ESCAPEBIT INNERESCAPEBIT)
      (CONSTANTS * READCODEMASKS)
      (CONSTANTS * READMACROCONTEXTS)
      (CONSTANTS * READCLASSES)
      (CONSTANTS * READMACROWAKEUPS)
      (CONSTANTS * READMACROESCAPES)
      (RECORDS READCODE READMACRODEF READTABLEP))
      (GLOBALVARS \ORIGREADTABLE \READTABLEHASH \ORIGTERMTABLE))
      (INITRECORDS READTABLEP))
      (COMS (INITVARS (\READTABLEHASH))
      (FNS \ATBLSET)
      (INITRECORDS READER-ENVIRONMENT)
      ; Definition is on CMLREAD, need it here to initialize
      ; *OLD-INTERLISP-READ-ENVIRONMENT*
      (FNS MAKE-READER-ENVIRONMENT EQUAL-READER-ENVIRONMENT SET-READER-ENVIRONMENT)
      (INITVARS (*LISP-PACKAGE*)
      (*INTERLISP-PACKAGE*)
      (*KEYWORD-PACKAGE*))
      (DECLARE%: DONTEVAL@LOAD DOCOPY (P (\ATBLSET]
      (LOCALVARS . T)
      (DECLARE%: DONTEVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILERVARS (ADDVARS (NLAMA)
      (NLAML)
      (LAMA READTABLEPROP]))
```

:: Common features of read and terminal tables

```
(DECLARE%: DONTCOPY
```

:: FOLLOWING DEFINITIONS EXPORTED

```
(DECLARE%: EVAL@COMPILE
```

```
(PUTPROPS \SYNCODE DMACRO [OPENLAMBDA (TABLE CHAR)
      (CHECK (type? CHARTABLE TABLE)) ; 0 is either NONE.TC, REAL.CCE, or OTHER.RC
      (COND
```



```

      CHARTBL))
    ((SETQ TEM (\TERMCLASSTOCODE CH))
     (SETQ CHARTBL (fetch TERMSA of (\GTTERMTABLE TABLE T)))
     (\MAPCHARTABLE [FUNCTION (LAMBDA (VAL KEY)
                          (DECLARE (USEDFREE TEM RESULT))
                          (COND
                            ((EQ TEM (fetch TERMCLASS of VAL))
                             (push RESULT (PROG1 KEY
                                             (* SELECTC TEM ((LIST NONE.TC WORDSEPR.TC)
                                                             (* ; "Only these classes have multiple members") KEY)
                                             (RETURN (CONS KEY))))
                             ) ]
                          )
     CHARTBL))
    [(FMEMB CH ' (MACRO SPLICE INFIX))
     (PROG [LST (A (fetch READMACRODEFS of (\GTREADTABLE TABLE T]
              (COND
                (A [MAPHASH A (FUNCTION (LAMBDA (DEF C)
                                           (AND (EQ CH (fetch MACROTYPE of DEF))
                                                (push LST C]
                (RETURN LST]
     ((SETQ TEM (fetch (CONTEXTS VAL) of CH))
      (SETQ CHARTBL (fetch READSA of (\GTREADTABLE TABLE T)))
      (\MAPCHARTABLE [FUNCTION (LAMBDA (VAL KEY)
                          (DECLARE (USEDFREE TEM RESULT))
                          (COND
                            ((EQ TEM (fetch MACROCONTEXT of VAL))
                             (push RESULT KEY]
                          )
      CHARTBL))
    ((SETQ TEM (fetch (WAKEUPS VAL) of CH))
     (SETQ CHARTBL (fetch READSA of (\GTREADTABLE TABLE T)))
     (\MAPCHARTABLE [FUNCTION (LAMBDA (VAL KEY)
                          (DECLARE (USEDFREE TEM RESULT))
                          (COND
                            ((EQ TEM (fetch WAKEUP of VAL))
                             (push RESULT KEY]
                          )
     CHARTBL))
    ((SETQ TEM (fetch (ESCAPES VAL) of CH))
     (SETQ CHARTBL (fetch READSA of (\GTREADTABLE TABLE T)))
     (\MAPCHARTABLE [FUNCTION (LAMBDA (VAL KEY)
                          (DECLARE (USEDFREE TEM RESULT))
                          (COND
                            ((EQ TEM (fetch ESCAPE of VAL))
                             (push RESULT KEY]
                          )
     CHARTBL))
    (T (\ILLEGAL.ARG CH))
    (RETURN RESULT))

```

(SETSNTAX

(* rmk%: "20-Nov-84 15:47")

```

[LAMBDA (CHAR CLASS TBL)
  (OR (FIXP (SETQ CHAR (\GETCHARCODE CHAR)))
      (\ILLEGAL.ARG CHAR))
  [OR (type? READTABLEP TBL)
      (type? TERMTABLEP TBL)
      (SETQ TBL (COND
                  ((OR (type? TERMTABLEP CLASS)
                      (\TERMCLASSTOCODE CLASS))
                   (\GTTERMTABLE TBL))
                  (T (\GTREADTABLE TBL]
      [COND
        ((OR (type? READTABLEP CLASS)
            (type? TERMTABLEP CLASS)
            (SELECTQ CLASS
              ((NIL T ORIG)
               T)
              NIL))
         (SETQ CLASS (GETSYNTAX CHAR CLASS)))
        ((FIXP (SETQ CLASS (\GETCHARCODE CLASS)))
         (SETQ CLASS (GETSYNTAX CLASS TBL]
      (COND
        ((type? READTABLEP TBL)
         (PROG1 (\GETREADSYNTAX CHAR TBL)
                (\SETREADSYNTAX CHAR CLASS TBL)))
        (T (PROG1 (\GETTERMSYNTAX CHAR TBL)
                  (\SETTERMSYNTAX CHAR CLASS TBL]))

```

(SYNTAXP

(* rmk%: " 5-JUN-80 22:40")

```

[LAMBDA (CODE CLASS TABLE)
  (PROG (D)
    (RETURN (COND
              ((EQ CLASS 'BREAK)
               (fetch BREAK of (\SYNCODE (fetch READSA of (\GTREADTABLE TABLE))
                                         CODE)))
              ((SETQ D (\READCLASSTOCODE CLASS))
               (EQ D (\SYNCODE (fetch READSA of (\GTREADTABLE TABLE))
                               CODE)))

```

```

([SETQ D (\TERMCLASSTOCODE CLASS))
(EQ D (fetch TERMCLASS of (\SYNCODE (fetch TERMSA of (\GTTERMTABLE TABLE))
CODE])
[FMEMB CLASS '(MACRO SPLICE INFIX))
(AND (SETQ D (fetch READMACRODEFS of (\GTREADTABLE TABLE)))
(EQ CLASS (fetch MACROTYPE of (GETHASH CODE D]
([SETQ D (fetch (CONTEXTS VAL) of CLASS))
(EQ D (fetch MACROCONTEXT of (\SYNCODE (fetch READSA of (\GTREADTABLE TABLE))
CODE])
([SETQ D (fetch (WAKEUPS VAL) of CLASS))
(EQ D (fetch WAKEUP of (\SYNCODE (fetch READSA of (\GTREADTABLE TABLE))
CODE])
([SETQ D (fetch (ESCAPES VAL) of CLASS))
(EQ D (fetch ESCAPE of (\SYNCODE (fetch READSA of (\GTREADTABLE TABLE))
CODE])
(T (\ILLEGAL.ARG CLASS])

```

(\COPYSYNTAX

[LAMBDA (A B) (* gbn "15-Sep-85 22:36")

```

;; Copies chartable A into chartable B
(CHECK (AND (type? CHARTABLE A)
(type? CHARTABLE B)))
(\MOVEBYTES A 0 B 0 (ADD1 \MAXTHINCHAR))
(COND
((fetch (CHARTABLE NSCHARHASH) of A)
(replace (CHARTABLE NSCHARHASH) of B with (REHASH (fetch (CHARTABLE NSCHARHASH) of A)
(\CREATENSCHARHASH])

```

(\GETCHARCODE

[LAMBDA (C) (* rmk%: "20-Nov-84 15:46")

```

(COND
((AND (NUMBERP C)
(\CHARCODEP (FIX C)))
(FIX C))
((AND (LITATOM C)
(EQ 1 (NCHARS C)))
(CHCON1 C))
(T C])

```

(\SETFATSYNCODE

[LAMBDA (TABLE CHAR CODE) (* bvm%: " 8-Mar-86 17:03")

;; Called by \SETSYNCODE macro for fat characters

```

(SETQ TABLE (\DTEST TABLE 'CHARTABLE)) ; CODE = 0 is REAL.CCE, NONE.TC, OTHER.RC
(COND
((ILEQ CHAR \MAXTHINCHAR)
(\PUTBASEBYTE TABLE CHAR CODE))
((EQ 0 CODE)
(COND
((fetch (CHARTABLE NSCHARHASH) of TABLE) ; there was already a table here so record the change
(PTHASH CHAR CODE (fetch (CHARTABLE NSCHARHASH) of TABLE)))
(T ; No hashtable yet, and only the default is being stored, so don't
; build the hashtable
0)))
(T (PTHASH CHAR CODE (OR (fetch (CHARTABLE NSCHARHASH) of TABLE)
(replace (CHARTABLE NSCHARHASH) of TABLE with (\CREATENSCHARHASH])

```

(\MAPCHARTABLE

[LAMBDA (FN CHARTBL) ; Edited 20-Apr-2018 16:53 by rmk:

```

(for I from 0 to \MAXTHINCHAR do (APPLY* FN (\GETBASEBYTE CHARTBL I)
I))
(COND
((fetch (CHARTABLE NSCHARHASH) of CHARTBL)
(MAPHASH (fetch (CHARTABLE NSCHARHASH) of CHARTBL)
FN])
)

```

;; terminal tables

(DEFINEQ

(CONTROL

[LAMBDA (MODE TTBL) (* rmk%: " 8-FEB-80 11:59")

```

(PROG1 (fetch CONTROLFLG of (SETQ TTBL (\GTTERMTABLE TTBL)))
(replace CONTROLFLG of TTBL with (AND MODE T))))

```

(COPYTERMTABLE

[LAMBDA (TTBL) (* lmm "14-APR-81 14:27")

```

(create TERMTABLEP using (SETQ TTBL (\GTTERMTABLE TTBL T))

```

TERMSA _ (create CHARTABLE using (fetch TERMSA of TTBL))

(DELETECONTROL

```
[LAMBDA (TYPE MESSAGE TTBL) (* lmm " 1-Jan-85 21:34")
  (PROG [VAL (TBL (\GTTERMTABLE TTBL (NULL MESSAGE)
    (SETQ VAL (SELECTQ TYPE
      ((ECHO NOECHO)
        (PROG1 (fetch DELCHARECHO of TBL)
          (replace DELCHARECHO of TBL with TYPE)))
      (DELCHARECHO (PROG1 (fetch DELCHARECHO of TBL)
        (SELECTQ MESSAGE
          (NIL ; Called only to get current value
            )
          ((ECHO NOECHO)
            (replace DELCHARECHO of TBL with MESSAGE))
          (LISPERROR "ILLEGAL ARG" MESSAGE))))
      ((LINEDELETE DELETEDLINE)
        (PROG1 (fetch LINEDELETE of TBL)
          (AND MESSAGE (replace LINEDELETE of TBL with (\LITCHECK MESSAGE))))
      (1STCHDEL (PROG1 (fetch 1STCHDEL of TBL)
        (AND MESSAGE (replace 1STCHDEL of TBL with (\LITCHECK MESSAGE))))
      (NTHCHDEL (PROG1 (fetch NTHCHDEL of TBL)
        (AND MESSAGE (replace NTHCHDEL of TBL with (\LITCHECK MESSAGE))))
      (POSTCHDEL (PROG1 (fetch POSTCHDEL of TBL)
        (AND MESSAGE (replace POSTCHDEL of TBL with (\LITCHECK MESSAGE))))
      (EMPTYCHDEL (PROG1 (fetch EMPTYCHDEL of TBL)
        (AND MESSAGE (replace EMPTYCHDEL of TBL with (\LITCHECK MESSAGE))))
      (LISPERROR "ILLEGAL ARG" TYPE)))
    (RETURN (COND
      ((STRINGP VAL)
        (CONCAT VAL))
      (T VAL])])])])])
```

(GETDELETECONTROL

```
[LAMBDA (TYPE TTBL) (* lmm " 1-Jan-85 21:20")
  (PROG (TBL VAL)
    (SETQ TBL (\GTTERMTABLE TTBL T))
    (SETQ VAL (SELECTQ TYPE
      ((ECHO NOECHO)
        (fetch DELCHARECHO of TBL))
      (DELCHARECHO (fetch DELCHARECHO of TBL))
      ((LINEDELETE DELETEDLINE)
        (fetch LINEDELETE of TBL))
      (1STCHDEL (fetch 1STCHDEL of TBL))
      (NTHCHDEL (fetch NTHCHDEL of TBL))
      (POSTCHDEL (fetch POSTCHDEL of TBL))
      (EMPTYCHDEL (fetch EMPTYCHDEL of TBL))
      (LISPERROR "ILLEGAL ARG" TYPE)))
    (RETURN (COND
      ((STRINGP VAL)
        (CONCAT VAL))
      (T VAL])])])
```

(ECHOCHAR

```
[LAMBDA (CHARCODE MODE TTBL) (* lmm " 1-Jan-85 21:29")
  (COND
    ((LISTP CHARCODE)
      (for X in CHARCODE do (ECHOCHAR X MODE TTBL)))
    (T (PROG [B (SA (fetch TERMSA of (\GTTERMTABLE TTBL (NULL MODE)
      (RETURN (PROG1 (SELECTC (fetch CCECHO of (SETQ B (\SYNCODE SA CHARCODE)))
        (REAL.CCE 'REAL)
        (IGNORE.CCE 'IGNORE)
        (SIMULATE.CCE 'SIMULATE)
        'INDICATE)
      [AND MODE (\SETSYNCODE SA CHARCODE (create TERMCODE using B CCECHO _
        (SELECTQ MODE
          (REAL REAL.CCE)
          (IGNORE IGNORE.CCE)
          (SIMULATE SIMULATE.CCE)
          ((INDICATE UPARROW)
            INDICATE.CCE)
          (\ILLEGAL.ARG MODE)]])])])])])
```

(ECHOCONTROL

```
[LAMBDA (CHAR MODE TTBL) (* rmk%: "20-Nov-84 15:14")
  (PROG ((C (\GETCHARCODE CHAR)))
    (OR [AND (\THINCHARCODEP C)
      (OR (ILESSP C 32)
        (AND (IGE Q C (CHARCODE A))
          (ILEQ C (CHARCODE Z))
          (SETQ C (IDIFFERENCE C 64]
        (\ILLEGAL.ARG C))
    (RETURN (ECHOCHAR C MODE TTBL])])])
```

(ECHOMODE
 [LAMBDA (FLG TTBL) (* rmk%: " 8-FEB-80 11:57")
 (PROG1 (fetch ECHOFLG of (SETQ TTBL (\GTTERMTABLE TTBL)))
 (replace ECHOFLG of TTBL with (AND FLG T))))]

(GETECHOMODE
 [LAMBDA (TTBL) (* Imm " 1-Jan-85 21:21")
 (fetch ECHOFLG of (\GTTERMTABLE TTBL T])]

(GETCONTROL
 [LAMBDA (TTBL) (* Imm " 1-Jan-85 21:21")
 (fetch CONTROLFLG of (\GTTERMTABLE TTBL T])]

(GETTERMTABLE
 [LAMBDA (TTBL)
 (\GTTERMTABLE TTBL NIL)]

(RAISE
 [LAMBDA (FLG TTBL) (* bvm%: "14-Feb-85 00:17")
 (PROG1 (fetch RAISEFLG of (SETQ TTBL (\GTTERMTABLE TTBL)))
 (replace RAISEFLG of TTBL with (COND
 ((EQ FLG 0)
 0)
 (FLG T))))])]

(GETRAISE
 [LAMBDA (TTBL) (* Imm " 1-Jan-85 21:21")
 (fetch RAISEFLG of (\GTTERMTABLE TTBL T])]

(RESETTERMTABLE
 [LAMBDA (TTBL FROM) (* Imm "14-APR-81 14:34")
 (PROG ((FR (\GTTERMTABLE FROM T))
 (TT (\GTTERMTABLE TTBL)))
 (\COPYSYNTAX (fetch TERMSA of FR)
 (fetch TERMSA of TT))
 (replace RAISEFLG of TT with (fetch RAISEFLG of FR))
 (replace DELCHARECHO of TT with (fetch DELCHARECHO of FR))
 (replace LINEDELETE of TT with (fetch LINEDELETE of FR))
 (replace 1STCHDEL of TT with (fetch 1STCHDEL of FR))
 (replace NTHCHDEL of TT with (fetch NTHCHDEL of FR))
 (replace POSTCHDEL of TT with (fetch POSTCHDEL of FR))
 (replace EMPTYCHDEL of TT with (fetch EMPTYCHDEL of FR))
 (replace CONTROLFLG of TT with (fetch CONTROLFLG of FR))
 (replace ECHOFLG of TT with (fetch ECHOFLG of FR))
 (RETURN TT))]

(SETTERMTABLE
 [LAMBDA (TBL) (* rmk%: " 8-FEB-80 12:16")
 (PROG1 \PRIMTERMTABLE
 [SETQ \PRIMTERMSA (fetch TERMSA of (SETQ \PRIMTERMTABLE (\GTTERMTABLE TBL)])])]

(TERMTABLEP
 [LAMBDA (TTBL) (* rmk%: "20-FEB-80 12:29")
 (AND (type? TERMTABLEP TTBL)
 TTBL)]

(\GETTERMSYNTAX
 [LAMBDA (C TBL) (* rmk%: "24-APR-80 09:44")
 (\TERMCODETOCLASS (fetch TERMCLASS of (\SYNCODE (fetch TERMSA of TBL)
 C)])]

(\GTTERMTABLE
 [LAMBDA (TTBL FLG) (* Imm " 6-MAY-80 20:35")
 (COND
 ((type? TERMTABLEP TTBL)
 TTBL)
 ((NULL TTBL)
 \PRIMTERMTABLE)
 ((AND (EQ TTBL 'ORIG)
 FLG)
 \ORIGTERMTABLE)
 (T (LISPERROR "ILLEGAL TERMINAL TABLE" TTBL))])]

(\ORIGTERMTABLE

[LAMBDA NIL

; Edited 21-Aug-2021 08:06 by rmk:

:: Creates the original terminal table

:: must be created with a hash table big enough to hold all of the indicates in character set 1 because this gets evaluated in the loadup before
:: HASHOVERFLOW is defined. rrb 5-oct-85

```
(PROG ((TBL (create TERMTABLEP
  TERMSA _ (create CHARTABLE
    NSCHARHASH _ (\CREATENSCHARHASH 300))
  DELCHARECHO _ 'ECHO
  ECHOFLG _ T
  LINEDELETE _ "##
  "
  1STCHDEL _ "\"
  NTHCHDEL _ ""
  POSTCHDEL _ "\"
  EMPTYCHDEL _ "##
  ")))
```

```
(PROGN (\SETTERMSYNTAX (SELECTQ (SYSTEMTYPE)
  ((TENEX D)
    (CHARCODE ^A))
  ((JERICHO VAX TOPS-20)
    (CHARCODE DEL))
  (SHOULDNT))
  'CHARDELETE TBL)
```

```
(\SETTERMSYNTAX (CHARCODE ^H)
```

; Added ^H as a CHARDELETE character 9/30/85

```
'CHARDELETE TBL)
```

```
(\SETTERMSYNTAX (CHARCODE ^W)
```

```
'WORDDELETE TBL)
```

```
(\SETTERMSYNTAX (SELECTQ (SYSTEMTYPE)
```

```
((TENEX D)
  (CHARCODE ^Q))
  ((JERICHO VAX)
  (CHARCODE ^U))
  (SHOULDNT))
```

```
'LINEDELETE TBL)
```

```
(\SETTERMSYNTAX (CHARCODE ^R)
```

```
'RETYPE TBL)
```

```
(\SETTERMSYNTAX (CHARCODE ^V)
```

```
'CTRLV TBL)
```

```
(\SETTERMSYNTAX (CHARCODE EOL)
```

```
'WAKEUPCHAR TBL)
```

```
(for C
```

```
in (CHARCODE (SPACE TAB ! @ %# $ ~ & * - = + % | { } ^ _ %: ; < > %, %. ? /))
```

```
do (\SETTERMSYNTAX C 'WORDSEPR TBL))
```

```
(PROGN (ECHOCHAR (CHARCODE (NULL ^A ^B ^C ^D ^E ^F ^H ^K ^L ^N ^O ^P ^Q ^R ^S ^T ^U ^V ^W ^X ^Y ^Z
```

```
^ \ ^%] ^^))
```

```
'INDICATE TBL)
```

```
(ECHOCHAR (CHARCODE (BELL TAB LF CR))
```

```
'REAL TBL)
```

```
(SELECTQ (SYSTEMTYPE)
```

```
(D (ECHOCHAR (CHARCODE (NULL ^A ^W ^Q ^R))
```

```
'IGNORE TBL)
```

```
(ECHOCHAR (CHARCODE (BELL TAB ESCAPE LF TENEXEOL))
```

```
'SIMULATE TBL))
```

```
(JERICHO (ECHOCHAR [CONSTANT (CONS ERASECHARCODE (CHARCODE (BELL TAB ESCAPE EOL]
```

```
'SIMULATE TBL))
```

```
(VAX (ECHOCHAR (CHARCODE (TAB ESCAPE EOL DEL))
```

```
'SIMULATE TBL))
```

```
NIL))
```

```
(for C from 128 to \MAXTHINCHAR do (ECHOCHAR C 'REAL TBL))
```

```
(for C from (CHARCODE Meta,0) to (CHARCODE Meta,377) do (ECHOCHAR C 'INDICATE TBL))
```

```
(RETURN TBL])
```

(\SETTERMSYNTAX

[LAMBDA (C CLASS TBL)

(* rmk%: "26-Mar-85 23:45")

:: Changes the terminal syntax class for charcode C. Unlike Interlisp-10, does not turn off previous characters for CHARDELETE, etc. classes

```
(\SETSYNCODE (fetch TERMSA of TBL)
```

```
C
```

```
(create TERMCODE using (\SYNCODE (fetch TERMSA of TBL)
```

```
C)
```

```
TERMCLASS _ (OR (\TERMCLASSTOCODE CLASS)
```

```
(LISPERROR "ILLEGAL ARG" CLASS])
```

(\TERMCLASSTOCODE

[LAMBDA (CLASS)

(* rmk%: "11-FEB-82 21:24")

```
(SELECTQ CLASS
```

```
((EOL WAKEUPCHAR)
```

```
EOL.TC)
```

```
(NONE NONE.TC)
```

```
(CHARDELETE CHARDELETE.TC)
```

```
(WORDDELETE WORDDELETE.TC)
```

```
(WORDSEPR WORDSEPR.TC)
```

```
(LINEDELETE LINEDELETE.TC)
```

```
(RETYPE RETYPE.TC)
```

((CTRLV CNTRLV)
CTRLV.TC)
NIL])

(\TERMCODETOCLASS

(* rmk%: "11-FEB-82 21:24")

[LAMBDA (CODE)
(SELECTC CODE
(EOL.TC 'EOL)
(NONE.TC 'NONE)
(CHARDELETE.TC
'CHARDELETE)
(WORDDELETE.TC
'WORDDELETE)
(WORDSEPR.TC 'WORDSEPR)
(LINEDELETE.TC
'LINEDELETE)
(RETYPE.TC 'RETYPE)
(CTRLV.TC 'CNTRLV)
NIL])

(\LITCHECK

(* rmk%: "11-FEB-82 21:26")

[LAMBDA (X)
(COND
((EQ X 'BACKUP)
X)
(LITATOM X)
(MKSTRING X))
(STRINGP X)
(CONCAT X))
(T (\ILLEGAL.ARG X])

; Means take terminal/implementation dependent backup action

(DECLARE%: DONTCOPY

:: FOLLOWING DEFINITIONS EXPORTED

(RPAQQ **CCECHOMODES** (REAL.CCE IGNORE.CCE SIMULATE.CCE INDICATE.CCE))

(DECLARE%: EVAL@COMPILE

(RPAQQ **REAL.CCE** 0)

(RPAQQ **IGNORE.CCE** 8)

(RPAQQ **SIMULATE.CCE** 16)

(RPAQQ **INDICATE.CCE** 24)

(CONSTANTS REAL.CCE IGNORE.CCE SIMULATE.CCE INDICATE.CCE)

(RPAQQ **TERMCLASSES** (NONE.TC EOL.TC CHARDELETE.TC WORDDELETE.TC WORDSEPR.TC LINEDELETE.TC RETYPE.TC CTRLV.TC))

(DECLARE%: EVAL@COMPILE

(RPAQQ **NONE.TC** 0)

(RPAQQ **EOL.TC** 1)

(RPAQQ **CHARDELETE.TC** 2)

(RPAQQ **WORDDELETE.TC** 6)

(RPAQQ **WORDSEPR.TC** 7)

(RPAQQ **LINEDELETE.TC** 3)

(RPAQQ **RETYPE.TC** 4)

(RPAQQ **CTRLV.TC** 5)

(CONSTANTS NONE.TC EOL.TC CHARDELETE.TC WORDDELETE.TC WORDSEPR.TC LINEDELETE.TC RETYPE.TC CTRLV.TC)

(DECLARE%: EVAL@COMPILE

(ACCESSFNS TERMCODE ((CCECHO (LOGAND DATUM 24))
(TERMCLASS (LOGAND DATUM 7))))
(**CREATE** (LOGOR CCECHO TERMCLASS)))

; We assume that values are appropriately shifted

(DATATYPE TERMTABLEP (TERMSA RAISEFLG DELCHARECHO LINEDELETE 1STCHDEL NTHCHDEL POSTCHDEL EMPTYCHDEL (CONTROLFLG
FLAG)

(ECHOFLG FLAG))
TERMSA _ (**create** CHARTABLE))


```

)
(/DECLAREDATATYPE 'TERMTABLEP' (POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER FLAG FLAG)
;; ---field descriptor list elided by lister---
'16)
)

```

:: END EXPORTED DEFINITIONS

```

(/DECLAREDATATYPE 'TERMTABLEP' (POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER POINTER FLAG FLAG)
;; ---field descriptor list elided by lister---
'16)

```

:: read tables

(DEFINEQ

```

(COPYREADTABLE
[LAMBDA (RDTBL)
  (RESETREADTABLE (create READTABLEP)
    (\GTREADTABLE RDTBL T])
  (* rmk%: "2-FEB-80 12:26")

```

```

(FIND-READTABLE
[LAMBDA (NAME)
  (GETHASH NAME \READTABLEHASH])
  (* bvm%: "27-Jul-86 15:53")

```

```

(IN-READTABLE
[LAMBDA (RDTBL)
  (SETQ *READTABLE* (\GTREADTABLE RDTBL T])
  (* bvm%: "27-Jul-86 15:55")

```

```

(ESCAPE
[LAMBDA (FLG RDTBL)
  (PROG1 (fetch ESCAPEFLG of (SETQ RDTBL (\GTREADTABLE RDTBL)))
    (replace ESCAPEFLG of RDTBL with (NEQ FLG NIL))))
  (* rmk%: "1-FEB-80 13:12")

```

```

(GETBRK
[LAMBDA (RDTBL)
  (GETSYNTAX 'BREAK RDTBL])
  (* rmk%: "2-MAY-80 17:04")

```

```

(GETREADTABLE
[LAMBDA (RDTBL)
  (\GTREADTABLE RDTBL])
  (* Imm%: 4-FEB-76 3 50)

```

```

(GETSEPR
[LAMBDA (RDTBL)
  (GETSYNTAX 'SEPR RDTBL])
  (* rmk%: "2-MAY-80 17:05")

```

```

(READMACROS
[LAMBDA (FLG RDTBL)
  (PROG1 (fetch READMACROFLG of (SETQ RDTBL (\GTREADTABLE RDTBL)))
    (replace READMACROFLG of RDTBL with (NEQ FLG NIL))))
  (* rmk%: "1-FEB-80 13:11")

```

```

(READTABLEP
[LAMBDA (RDTBL)
  (AND (type? READTABLEP RDTBL)
    RDTBL])
  (* rmk%: "20-FEB-80 12:32")

```

```

(READTABLEPROP
[LAMBDA ARGS
  (COND
    ((LESSP ARGS 2)
      (\ILLEGAL.ARG NIL))
    ((GREATERP ARGS 3)
      (\ILLEGAL.ARG (ARG ARGS 4)))
    (T (LET [(RDTBL (\GTREADTABLE (ARG ARGS 1)))
              (NEWVALUEP (EQ ARGS 3))
              (NEWVALUE (AND (EQ ARGS 3)
                              (ARG ARGS 3))
              (SELECTQ (ARG ARGS 2)
                (NUMBERBASE (PROG1 (fetch (READTABLEP NUMBERBASE) of RDTBL)
                  (COND
                    (NEWVALUEP (replace (READTABLEP NUMBERBASE) of RDTBL with NEWVALUE))))))
                (NAME [LET ((OLDNAME (fetch (READTABLEP READTBLNAME) of RDTBL)))
                  (PROG1 OLDNAME
                    (COND

```

```

(COND
  (NEWVALUEP (COND
    (OLDNAME (REHASH OLDNAME \READTABLEHASH)))
    (replace (READTABLE READTBLNAME) of RDTBL with NEWVALUE)
    (PUTHASH NEWVALUE RDTBL \READTABLEHASH))))]
(COMMONLISP (PROG1 (fetch (READTABLE COMMONLISP) of RDTBL)
  [COND
    (NEWVALUEP (replace (READTABLE COMMONLISP) of RDTBL with NEWVALUE)
      (if NEWVALUE
        then ; COMMONLISP implies COMMONNUMSYNTAX and not
              ; USESILPACKAGE
              (replace (READTABLE COMMONNUMSYNTAX) of RDTBL
                with T)
              (replace (READTABLE USESILPACKAGE) of RDTBL with NIL)))
    (COMMONNUMSYNTAX
      (PROG1 (fetch (READTABLE COMMONNUMSYNTAX) of RDTBL)
        (COND
          (NEWVALUEP (replace (READTABLE COMMONNUMSYNTAX) of RDTBL with NEWVALUE))))))
    (USESILPACKAGE
      (PROG1 (fetch (READTABLE USESILPACKAGE) of RDTBL)
        (COND
          (NEWVALUEP (replace (READTABLE USESILPACKAGE) of RDTBL with NEWVALUE))))))
    (CASEINSENSITIVE
      (PROG1 (fetch (READTABLE CASEINSENSITIVE) of RDTBL)
        (COND
          (NEWVALUEP (replace (READTABLE CASEINSENSITIVE) of RDTBL with NEWVALUE))))))
    (ESCAPECHAR (PROG1 (fetch (READTABLE ESCAPECHAR) of RDTBL)
      (COND
        (NEWVALUEP (\SETREADSYNTAX NEWVALUE 'ESCAPE RDTBL)
          (replace (READTABLE ESCAPECHAR) of RDTBL with NEWVALUE))))))
    (MULTIPLE-ESCAPECHAR
      (PROG1 (fetch (READTABLE MULTESCAPECHAR) of RDTBL)
        (COND
          (NEWVALUEP (\SETREADSYNTAX NEWVALUE 'MULTIPLE-ESCAPE RDTBL)
            (replace (READTABLE MULTESCAPECHAR) of RDTBL with NEWVALUE))))))
    (PACKAGECHAR (PROG1 (fetch (READTABLE PACKAGECHAR) of RDTBL)
      (COND
        (NEWVALUEP (\SETREADSYNTAX NEWVALUE 'PACKAGEDELIM RDTBL)
          (replace (READTABLE PACKAGECHAR) of RDTBL with NEWVALUE))))))
    (HASHMACROCHAR
      (PROG1 (fetch (READTABLE HASHMACROCHAR) of RDTBL)
        (COND
          (NEWVALUEP (\SETREADSYNTAX NEWVALUE '(INFIX ALWAYS NONIMMEDIATE ESCQUOTE
            READVBAR)
              RDTBL)
            (replace (READTABLE HASHMACROCHAR) of RDTBL with NEWVALUE))))))
    (\ILLEGAL.ARG (ARG ARGS 2])

```

(RESETREADTABLE

[LAMBDA (RDTBL FROM)

; Edited 12-Feb-2021 22:54 by larry
; Edited 20-Apr-2018 16:22 by rmk:
(* bvm%: "27-Aug-86 22:28")

:: RMK: Copy the macrodefs

```

[replace READMACROFLG of (SETQ RDTBL (\GTREADTABLE RDTBL)) with (fetch READMACROFLG of (SETQ FROM
  (\GTREADTABLE FROM T])
(replace ESCAPEFLG of RDTBL with (fetch ESCAPEFLG of FROM))
(replace (READTABLE COMMONLISP) of RDTBL with (fetch (READTABLE COMMONLISP) of FROM))
(replace (READTABLE NUMBERBASE) of RDTBL with (fetch (READTABLE NUMBERBASE) of FROM))
(replace (READTABLE CASEINSENSITIVE) of RDTBL with (fetch (READTABLE CASEINSENSITIVE) of FROM))
(replace (READTABLE COMMONNUMSYNTAX) of RDTBL with (fetch (READTABLE COMMONNUMSYNTAX) of FROM))
(replace (READTABLE USESILPACKAGE) of RDTBL with (fetch (READTABLE USESILPACKAGE) of FROM))
(replace (READTABLE HASHMACROCHAR) of RDTBL with (fetch (READTABLE HASHMACROCHAR) of FROM))
(replace (READTABLE ESCAPECHAR) of RDTBL with (fetch (READTABLE ESCAPECHAR) of FROM))
(replace (READTABLE MULTESCAPECHAR) of RDTBL with (fetch (READTABLE MULTESCAPECHAR) of FROM))
(replace (READTABLE PACKAGECHAR) of RDTBL with (fetch (READTABLE PACKAGECHAR) of FROM))
(replace (READTABLE DISPATCHMACRODEFS) of RDTBL with (COPY (fetch (READTABLE DISPATCHMACRODEFS)
  of FROM)))

```

:: Placeholder. If DISPATCHMACRODEFS ends up containing a CHARTABLE or a hash table, will have to do a REHASH or \COPYSYNTAX as
;; well

```

[LET ((RDEFS (fetch (READTABLE READMACRODEFS) of RDTBL))
  (FDEFS (fetch (READTABLE READMACRODEFS) of FROM))
  (COND
    (RDEFS (CLRHASH RDEFS)))
  (AND FDEFS (REHASH FDEFS (OR RDEFS (replace (READTABLE READMACRODEFS) of RDTBL
    with (HASHARRAY (HARRAYSIZE FDEFS)
      7]

```

```

(\COPYSYNTAX (fetch READSA of FROM)
  (fetch READSA of RDTBL))
RDTBL])

```

(SETBRK

[LAMBDA (LST FLG RDTBL)

(* rmk%: "13-AUG-81 00:01")
; This is a very ugly def which needs to be cleaned up cause a
; lot of people call SETBRK

```
(COND
  [(EQ LST T)
   [MAPC (GETSYNTAX 'BREAK RDTBL)
         (FUNCTION (LAMBDA (X)
                   (SETSYNTAX X 'OTHER RDTBL])
         (MAPC (GETSYNTAX 'BREAK (COND
                  ((EQ RDTBL T)
                   'ORIG)
                  (T T)))
              (FUNCTION (LAMBDA (X)
                        (SETSYNTAX X 'BREAK RDTBL])
      (T (SELECTQ FLG
          (NIL
           [MAPC (GETSYNTAX 'BREAK RDTBL)
                 (FUNCTION (LAMBDA (X)
                           (OR (MEMB X LST)
                               (SETSYNTAX X 'OTHER RDTBL])
                           (MAPC LST (FUNCTION (LAMBDA (X)
                                                (SETSYNTAX X 'BREAK RDTBL])
                              (0
                               [MAPC LST (FUNCTION (LAMBDA (X)
                                                       (SETSYNTAX X 'OTHER RDTBL])
                              (1
                               [MAPC LST (FUNCTION (LAMBDA (X)
                                                       (SETSYNTAX X 'BREAK RDTBL])
                              NIL])
          ; reset
          ; clear out lst
          ; add chars
```

```
(SETREADTABLE
  [LAMBDA (RDTBL FLG)
    (PROG1 *READTABLE*
      (SETQ *READTABLE* (\GTREADTABLE RDTBL)))]])
(* bvm%: " 4-May-86 16:32")
```

```
(SETSEPR
  [LAMBDA (LST FLG RDTBL)
    (COND
      [(EQ LST T)
       [MAPC (GETSYNTAX 'SEPR RDTBL)
             (FUNCTION (LAMBDA (X)
                       (SETSYNTAX X 'OTHER RDTBL])
       (MAPC (GETSYNTAX 'SEPR (COND
              ((EQ RDTBL T)
               'ORIG)
              (T T)))
          (FUNCTION (LAMBDA (X)
                    (SETSYNTAX X 'SEPR RDTBL])
      (T (SELECTQ FLG
          (NIL
           [MAPC (GETSYNTAX 'SEPR RDTBL)
                 (FUNCTION (LAMBDA (X)
                           (SETSYNTAX X 'OTHER RDTBL])
                 [MAPC LST (FUNCTION (LAMBDA (X)
                                      (SETSYNTAX X 'SEPR RDTBL])
                              (0
                               [MAPC LST (FUNCTION (LAMBDA (X)
                                                       (SETSYNTAX X 'OTHER RDTBL])
                              (1
                               [MAPC LST (FUNCTION (LAMBDA (X)
                                                       (SETSYNTAX X 'SEPR RDTBL])
                              NIL])
          ; reset
          ; This one also needs to be cleaned up
          ; clear out lst
          ; add chars
```

```
(\GETREADSYNTAX
  [LAMBDA (C TBL)
    (LET ((B (\SYNCODE (fetch READSA of TBL)
                      C)))
```

;; This will turn into a SELECTQ that keys off syntax code numbers and produces class tokens. The default clause at the end: if it's not a
 ;; built-in class, must be a macro
 ;; Sample code:

```
(* (SELECTQ B (0 (QUOTE OTHER))
  (96 (QUOTE SEPRCHAR)) (112
  (QUOTE BREAKCHAR)) (113 (QUOTE STRINGDELIM))
  (114 (QUOTE LEFTPAREN)) (115
  (QUOTE RIGHTPAREN)) (116 (QUOTE LEFTBRACKET))
  (117 (QUOTE RIGHTBRACKET))
  (70 (QUOTE ESCAPE)) (71 (QUOTE MULTIPLE-ESCAPE))
  (69 (QUOTE PACKAGEDELIM)) <default>))
```

```
(\COMPUTED.FORM `(SELECTQ B
  (\,@ [for PAIR in READCLASSTOKENS collect (LIST (EVAL (CADR PAIR))
                                                    (KWOTE (CAR PAIR]))
  (LET ((E (\GETREADMACRODEF C TBL))
        KEY)
    `(\, (fetch MACROTYPE of E)
      , (fetch (CONTEXTS KEY) of (fetch MACROCONTEXT of B))
      , @ (AND (NEQ (SETQ KEY (fetch (WAKEUPS KEY) of (fetch WAKEUP of B)))
```

```

      'NONIMMEDIATE)
      (LIST KEY))
    ,@ (AND (NEQ (SETQ KEY (fetch (ESCAPES KEY) of (fetch ESCAPE of B)))
      'ESCQUOTE)
      (LIST KEY))
    , (fetch MACROFN of E])

```

```

(\GTREADTABLE
 [LAMBDA (X FLG)
 (SELECTQ X
 (NIL T)
 (\DTEST *READTABLE* 'READTABLEP))
 (\GTREADTABLE1 X FLG])
 (* bvm%: " 5-May-86 11:05")

```

```

(\GTREADTABLE1
 [LAMBDA (X FLG)
 (COND
 ((type? READTABLEP X)
 X)
 ((AND FLG (GETHASH X \READTABLEHASH)))
 (T (LISPEROR "ILLEGAL READTABLE" X]))
 (* bvm%: "27-Jul-86 15:37")

```

```

(\ORIGREADTABLE
 [LAMBDA NIL
 ;; Creates a copy of the 'original' read-table.
 ; Edited 16-Apr-87 17:45 by bvm:

```

```

 (PROG [(TBL (create READTABLEP
 READMACROFLG _ T
 ESCAPEFLG _ T
 NUMBERBASE _ 10
 USESILPACKAGE _ T
 ESCAPECHAR _ (CHARCODE %%))
 PACKAGECHAR _ (PROGN
 ;; Need to have a character for package delimiter in all read tables, but for old read tables want one
 ;; that is unlikely to have appeared in a symbol in an old source file. Also would like it to be a 7-bit
 ;; char, so we don't needlessly force MAKEFILE to produce binary files.
 (CHARCODE "^^"))
 HASHMACROCHAR _ (CHARCODE "|")]

```

;; Actually, '|' is not defined in ORIG table, but rather later. But the radix printer and others want it, and this is better than nothing

```

 (SETSEPR (CHARCODE (SPACE TENEXEOL CR ^L LF TAB))
 1 TBL)
 (\SETREADSYNTAX (CHARCODE %])
 'RIGHTBRACKET TBL)
 (\SETREADSYNTAX (CHARCODE %[)
 'LEFTBRACKET TBL)
 (\SETREADSYNTAX (CHARCODE %)
 'RIGHTPAREN TBL)
 (\SETREADSYNTAX (CHARCODE %)
 'LEFTPAREN TBL)
 (\SETREADSYNTAX (CHARCODE %%))
 'ESCAPE TBL)
 (\SETREADSYNTAX (CHARCODE %")
 'STRINGDELIM TBL)
 (\SETREADSYNTAX 167 'PACKAGEDELIM TBL)
 ; Old choice for package delim char: the NS section symbol.
 ; Keep for compatibility with Lyric Beta files
 (\SETREADSYNTAX (CHARCODE "^^")
 'PACKAGEDELIM TBL)
 (RETURN TBL])

```

```

(\READCLASSTOCODE
 [LAMBDA (CLASS)
 (* bvm%: " 9-Jul-85 00:43")

```

;;; This turns into a SELECTQ that goes from CLASS token to numeric code

```

 (\COMPUTED.FORM `(SELECTQ CLASS
 (\,@ READCLASSTOKENS)
 (SEPR SEPRCHAR.RC)
 NIL])
 ; Synonym for SEPRCHAR

```

```

(\SETMACROSYNTAX
 [LAMBDA (C CLASS TBL)
 (OR (AND (FMEMB (CAR CLASS)
 ' (MACRO SPLICE INFIX))
 (CDR CLASS))
 (\ILLEGAL.ARG CLASS))
 (PROG (CONTEXT WAKEUP ESCAPE (LST CLASS)
 (A (fetch READMACRODEFS of TBL)))
 LP (COND
 ([CDR (SETQ LST (LISTP (CDR LST]
 (* rmk%: " 3-Jan-84 13:20")

```

```
(OR [AND (NULL CONTEXT)
      (SETQ CONTEXT (fetch (CONTEXTS VAL) of (CAR LST)
      [AND (NULL WAKEUP)
      (SETQ WAKEUP (fetch (WAKEUPS VAL) of (CAR LST)
      [AND (NULL ESCAPE)
      (SETQ ESCAPE (fetch (ESCAPES VAL) of (CAR LST)
      (\ILLEGAL.ARG CLASS))
      (GO LP)))
(OR (LISTP LST)
    (\ILLEGAL.ARG CLASS))
[COND
  (A
   ;; This hack guarantees that the hasharray will not overflow and cause an error in the uninterruptable PUTHASH below. If it didn't
   ;; already have a value for C, then the macro bits are not set in C's syntax code, so the T value is harmless.
   (OR (GETHASH C A)
        (PUTHASH C T A)))
  (T (replace READMACRODEFS of TBL with (SETQ A (HASHARRAY 7 7]
      (UNINTERRUPTABLY
       (PUTHASH C (create READMACRODEF
                          MACROTYPE _ (CAR CLASS)
                          MACROFN _ (CAR LST))
                A)
       (\SETSYNCODE (fetch READSA of TBL)
                    C
                    (LOGOR (OR CONTEXT ALWAYS.RMC)
                           (OR ESCAPE ESC.RME)
                           (OR WAKEUP NONIMMEDIATE.RMW))))))])
```

(\SETREADSYNTAX

```
[LAMBDA (C CLASS TBL)
  (PROG ((OLDSYNTAX (\SYNCODE (fetch (READTABLEP READSA) of TBL)
                                   C))
        TEM)
    [COND
      ((EQ CLASS 'BREAK)
       (COND
        ((fetch BREAK of OLDSYNTAX)
         (RETURN))
        (T (SETQ CLASS 'BREAKCHAR]
           ; If already a BREAK character but also something else, like
           ; LPAR, leave it alone
      (COND
       ((LISTP CLASS)
        (\SETMACROSYNTAX C CLASS TBL))
       ((SETQ TEM (\READCLASSTOCODE CLASS))
        (UNINTERRUPTABLY
         [COND
           ((fetch MACROP of OLDSYNTAX)
            (REMHASH C (fetch READMACRODEFS of TBL]
            (\SETSYNCODE (fetch READSA of TBL)
                         C TEM))
           (T (\ILLEGAL.ARG CLASS])
           ; No longer a macro
```

(\READTABLEP.DEFPRINT

```
[LAMBDA (RDTBL STREAM)
  ;; Print read table as, for example, #<ReadTable name/76,5432>
  (LET ((NAME (fetch (READTABLEP READTBLNAME) of RDTBL))
        [.SPACECHECK. STREAM (IPLUS (CONSTANT (NCHARS "<ReadTable />"))
                                       (PROGN
                                        10)
                                       ; Longest address is '177,177777'
                                       (COND
                                        (NAME (NCHARS NAME))
                                        (T 0]
        (\OUTCHAR STREAM (fetch (READTABLEP HASHMACROCHAR) of *READTABLE*))
        (\SOUT "<ReadTable" STREAM)
        (COND
         (NAME (\OUTCHAR STREAM (CHARCODE SPACE))
              (\SOUT (MKSTRING NAME)
                     STREAM)))
        (\OUTCHAR STREAM (CHARCODE /))
        (\PRINTADDR RDTBL STREAM)
        (\OUTCHAR STREAM (CHARCODE >))
        T])
```

)

```
(PUTPROPS READTABLEPROP ARGNAMES (RDTBL PROP NEWVALUE))
```

```
(DECLARE%: EVAL@COMPILE DONTCOPY
```

(RPAQQ READCLASSTOKENS

```
((OTHER 0)
 (SEPRCHAR (LOGOR ESCAPEBIT STOPATOMBIT 0))
 (BREAKCHAR (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 0))
 (STRINGDELIM (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 1))
```

```
(LEFTPAREN (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 2))
(RIGHTPAREN (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 3))
(LEFTBRACKET (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 4))
(RIGHTBRACKET (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 5))
(ESCAPE (LOGOR ESCAPEBIT INNERESCAPEBIT 6))
(MULTIPLE-ESCAPE (LOGOR ESCAPEBIT INNERESCAPEBIT 7))
(PACKAGEDELIM (LOGOR ESCAPEBIT INNERESCAPEBIT 1))))
```

```
(RPAQ READCLASSES [MAPCAR READCLASSTOKENS (FUNCTION (LAMBDA (PAIR)
                                                    (LIST (PACK* (CAR PAIR)
                                                            ".RC")
                                                            (CADR PAIR))
```

```
(DECLARE%: EVAL@COMPILE
```

```
(PUTPROPS \COMPUTED.FORM MACRO [X (CONS 'PROGN (MAPCAR X (FUNCTION EVAL])
)
```

```
(DECLARE%: EVAL@COMPILE
```

```
[ACCESSFNS CONTEXTS ((KEY (SELECTC DATUM
                          (ALWAYS.RMC 'ALWAYS)
                          (FIRST.RMC 'FIRST)
                          (ALONE.RMC 'ALONE)
                          NIL))
 (VAL (SELECTQ DATUM
       (ALWAYS ALWAYS.RMC)
       (FIRST FIRST.RMC)
       (ALONE ALONE.RMC)
       NIL])
```

```
[ACCESSFNS ESCAPES ((KEY (SELECTC DATUM
                          (ESC.RME 'ESCQUOTE)
                          (NOESC.RME 'NOESCQUOTE)
                          NIL))
 (VAL (SELECTQ DATUM
       ((ESCQUOTE ESC)
        ESC.RME)
       ((NOESCQUOTE NOESC)
        NOESC.RME)
       NIL])
```

```
[ACCESSFNS WAKEUPS ((KEY (SELECTC DATUM
                          (IMMEDIATE.RMW
                           'IMMEDIATE)
                          (NONIMMEDIATE.RMW
                           'NONIMMEDIATE)
                          NIL))
 (VAL (SELECTQ DATUM
       ((IMMEDIATE IMMED WAKEUP)
        IMMEDIATE.RMW)
       ((NONIMMEDIATE NONIMMED NOWAKEUP)
        NONIMMEDIATE.RMW)
       NIL])
```

:: FOLLOWING DEFINITIONS EXPORTED

```
(DECLARE%: EVAL@COMPILE
```

```
(PUTPROPS \GETREADMACRODEF MACRO ((C TBL)
                                   (GETHASH C (fetch READMACRODEFS of TBL))))
```

```
(PUTPROPS \GTREADTABLE MACRO [ARGS (COND
                                   [(LITATOM (CAR ARGS))
                                    (SUBPAIR 'X . FLG)
                                    ARGS
                                    '(SELECTQ X
                                       ((NIL T)
                                        (\DTEST *READTABLE* 'READTABLEP))
                                       (\GTREADTABLE1 X . FLG]
                                   (T 'IGNOREMACRO])
```

```
(PUTPROPS \GTREADTABLE1 DMACRO [ARGS (COND
                                   [(NULL (CDR ARGS))
                                    (LIST '\DTEST (CAR ARGS)
                                       ''READTABLEP]
                                   (T 'IGNOREMACRO])
```

```
(DECLARE%: EVAL@COMPILE
```

```
(RPAQQ MACROBIT 8)
```

```
(RPAQQ BREAKBIT 16)
```

```
(RPAQQ STOPATOMBIT 32)
```

```

(RPAQQ ESCAPEBIT 64)
(RPAQQ INNERESCAPEBIT 4)
(CONSTANTS MACROBIT BREAKBIT STOPATOMBIT ESCAPEBIT INNERESCAPEBIT)
)
(RPAQQ READCODEMASKS ((CONTEXTMASK (LOGOR MACROBIT STOPATOMBIT BREAKBIT 1))
                        (WAKEUPMASK (LOGOR MACROBIT 2))))
(DECLARE%: EVAL@COMPILE
(RPAQ CONTEXTMASK (LOGOR MACROBIT STOPATOMBIT BREAKBIT 1))
(RPAQ WAKEUPMASK (LOGOR MACROBIT 2))
(CONSTANTS (CONTEXTMASK (LOGOR MACROBIT STOPATOMBIT BREAKBIT 1))
           (WAKEUPMASK (LOGOR MACROBIT 2)))
)
(RPAQQ READMACROCONTEXTS ((ALWAYS.RMC (LOGOR MACROBIT STOPATOMBIT BREAKBIT 0))
                            (FIRST.RMC (LOGOR MACROBIT 0))
                            (ALONE.RMC (LOGOR MACROBIT 1))))
(DECLARE%: EVAL@COMPILE
(RPAQ ALWAYS.RMC (LOGOR MACROBIT STOPATOMBIT BREAKBIT 0))
(RPAQ FIRST.RMC (LOGOR MACROBIT 0))
(RPAQ ALONE.RMC (LOGOR MACROBIT 1))
(CONSTANTS (ALWAYS.RMC (LOGOR MACROBIT STOPATOMBIT BREAKBIT 0))
           (FIRST.RMC (LOGOR MACROBIT 0))
           (ALONE.RMC (LOGOR MACROBIT 1)))
)
(RPAQQ READCLASSES
((OTHER.RC 0)
 (SEPRCHAR.RC (LOGOR ESCAPEBIT STOPATOMBIT 0))
 (BREAKCHAR.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 0))
 (STRINGDELIM.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 1))
 (LEFTPAREN.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 2))
 (RIGHTPAREN.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 3))
 (LEFTBRACKET.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 4))
 (RIGHTBRACKET.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 5))
 (ESCAPE.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 6))
 (MULTIPLE-ESCAPE.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 7))
 (PACKAGEDELIM.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 1)))
(DECLARE%: EVAL@COMPILE
(RPAQQ OTHER.RC 0)
(RPAQ SEPRCHAR.RC (LOGOR ESCAPEBIT STOPATOMBIT 0))
(RPAQ BREAKCHAR.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 0))
(RPAQ STRINGDELIM.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 1))
(RPAQ LEFTPAREN.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 2))
(RPAQ RIGHTPAREN.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 3))
(RPAQ LEFTBRACKET.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 4))
(RPAQ RIGHTBRACKET.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 5))
(RPAQ ESCAPE.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 6))
(RPAQ MULTIPLE-ESCAPE.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 7))
(RPAQ PACKAGEDELIM.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 1))
(CONSTANTS (OTHER.RC 0)
           (SEPRCHAR.RC (LOGOR ESCAPEBIT STOPATOMBIT 0))
           (BREAKCHAR.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 0))
           (STRINGDELIM.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 1))
           (LEFTPAREN.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 2))
           (RIGHTPAREN.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 3))
           (LEFTBRACKET.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 4))
           (RIGHTBRACKET.RC (LOGOR ESCAPEBIT STOPATOMBIT BREAKBIT 5))
           (ESCAPE.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 6))
           (MULTIPLE-ESCAPE.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 7))
           (PACKAGEDELIM.RC (LOGOR ESCAPEBIT INNERESCAPEBIT 1)))
)

```


;; ---field descriptor list elided by lister---
'12)

(RPAQ? \READTABLEHASH)

(DEFINEQ

(\ATBLSET

[LAMBDA NIL

; Edited 28-Jun-2021 09:29 by rmk:
; Edited 3-Dec-86 18:07 by Pavel

(DECLARE (GLOBALVARS \ORIGREADTABLE \ORIGTERMTABLE))

(COND

((NULL (BOUNDP '\PRIMREADTABLE))
(initrecord CHARTABLE)

;; Read tables

;; RMK: If reloading, don't smash an existing hash table

[OR (HARRAYP \READTABLEHASH)

(SETQ \READTABLEHASH (HASHARRAY 20 NIL (FUNCTION STRING-EQUAL-HASHBITS)
(FUNCTION STRING-EQUAL]

(LET (TRDTBL NEW-IL-RDTBL)

(PROGN (SETQ \ORIGREADTABLE (\ORIGREADTABLE)) ; The ORIG read table

(READTABLEPROP \ORIGREADTABLE 'NAME 'ORIG))

(PROGN ; The old Interlisp T read table. May not have a use for this any
; more

(SETQ TRDTBL (COPYREADTABLE \ORIGREADTABLE))

(SETSYNTAX (CHARCODE "|")

' (MACRO READVBAR)

TRDTBL)

(SETSYNTAX (CHARCODE "\"")

' (MACRO FIRST READBQUOTE)

TRDTBL)

(SETSYNTAX (CHARCODE ",")

' (MACRO FIRST READBQUOTECOMMA)

TRDTBL)

(SETSYNTAX (CHARCODE "'")

' (MACRO FIRST READQUOTE)

TRDTBL)

(READTABLEPROP TRDTBL 'NAME "OLD-INTERLISP-T")

(PROGN ; Temporary

(SETTOPVAL '%#CURRENTRDTBL# TRDTBL)))

(PROGN ; The old FILERDTBL

(SETQ FILERDTBL (COPYREADTABLE \ORIGREADTABLE))

(SETSYNTAX (CHARCODE "|")

TRDTBL FILERDTBL)

(READTABLEPROP FILERDTBL 'NAME "OLD-INTERLISP-FILE")

(SETQ *OLD-INTERLISP-READ-ENVIRONMENT*

(create READER-ENVIRONMENT

REREADTABLE _ FILERDTBL

REBASE _ 10

REFORMAT _ :XCCS))

; need this to read files in the loadup

)

(PROGN (SETQ NEW-IL-RDTBL (COPYREADTABLE TRDTBL)) ; The new Interlisp read table is more common lisp

(READTABLEPROP NEW-IL-RDTBL 'MULTIPLE-ESCAPECHAR (CHARCODE "|"))

(READTABLEPROP NEW-IL-RDTBL 'HASHMACROCHAR (CHARCODE "#"))

(SET-DEFAULT-HASHMACRO-SETTINGS NEW-IL-RDTBL)

(READTABLEPROP NEW-IL-RDTBL 'COMMONNUMSYNTAX T)

(READTABLEPROP NEW-IL-RDTBL 'USESILPACKAGE NIL)

(READTABLEPROP NEW-IL-RDTBL 'NAME "INTERLISP")

(for I from 1 to 26 do (SETSYNTAX I 'SEPRCHAR FILERDTBL)

; Make font switch chars seprs

(SETSYNTAX I 'SEPRCHAR NEW-IL-RDTBL))

(SETQ *READTABLE* NEW-IL-RDTBL))

;; Make ^Y like #. in the old T readtable and the new INTERLISP one.

(SETSYNTAX (CHARCODE ^Y)

' [MACRO ALWAYS (LAMBDA (FILE RDTBL)

(EVAL (READ FILE RDTBL)

TRDTBL)

(SETSYNTAX (CHARCODE ^Y)

TRDTBL NEW-IL-RDTBL)

(DEFPRINT 'READTABLEP '\READTABLEP.DEFPRINT))

;; Terminal tables

(SETQ \ORIGTERMTABLE (\ORIGTERMTABLE))

(SETQ \PRIMTERMTABLE (COPYTERMTABLE \ORIGTERMTABLE))

(SETQ \PRIMTERMSA (fetch TERMSA of \PRIMTERMTABLE))

(PUTD '\ATBLSET

(PUTD '\ORIGTERMTABLE)

NIL])

)

(/DECLAREDATATYPE 'READER-ENVIRONMENT '(POINTER POINTER POINTER POINTER POINTER POINTER))

;; ---field descriptor list elided by lister---
' 12)

;; Definition is on CMLREAD, need it here to initialize *OLD-INTERLISP-READ-ENVIRONMENT*

(DEFINEQ

(MAKE-READER-ENVIRONMENT

[LAMBDA (PACKAGE READTABLE BASE FORMAT PACKAGEFORM READTABLEFORM)

; Edited 26-Dec-2021 14:32 by rmk
; Edited 24-Oct-2021 21:53 by rmk:
; Edited 16-Aug-2021 23:44 by rmk:

;; PACKAGE can be a prop list of keyword-values

```
(CL:WHEN (LISTP PACKAGE)
  (CL:UNLESS READTABLE
    (SETQ READTABLE (LISTGET PACKAGE :READTABLE)))
  (CL:UNLESS BASE
    (SETQ BASE (LISTGET PACKAGE :BASE)))
  (CL:UNLESS FORMAT
    (SETQ FORMAT (LISTGET PACKAGE :FORMAT)))
  (SETQ PACKAGE (LISTGET PACKAGE :PACKAGE)))
(creat READER-ENVIRONMENT
  REPACKAGE _ (COND
    ((CL:PACKAGEP PACKAGE)
     PACKAGE)
    [PACKAGE (OR (CL:FIND-PACKAGE PACKAGE)
                 (\DTEST PACKAGE 'PACKAGE)
                 (T *PACKAGE*))])
  REREADTABLE _ (COND
    ((READTABLEP READTABLE)
     [READTABLE (OR (FIND-READTABLE READTABLE)
                    (\DTEST READTABLE 'READTABLEP)
                    (T *READTABLE*))])
    (T *READTABLE*))
  REBASE _ (COND
    (BASE (\CHECKRADIX BASE))
    (T *PRINT-BASE*))
  REFORMAT _ (OR FORMAT *DEFAULT-EXTERNALFORMAT*)
  REPACKAGEFORM _ PACKAGEFORM
  REREADTABLEFORM _ READTABLEFORM])
```

(EQUAL-READER-ENVIRONMENT

[LAMBDA (ENV1 ENV2)

;; Edited 19-Dec-2021 14:09 by rmk: Replace constant :XCCS with *DEFAULT-EXTERNALFORMAT*
;; Edited 19-Dec-2021 14:01 by rmk

```
(AND (EQ (fetc (READER-ENVIRONMENT REREADTABLE) of ENV1)
         (fetc (READER-ENVIRONMENT REREADTABLE) of ENV2))
  (EQ (fetc (READER-ENVIRONMENT REPACKAGE) of ENV1)
      (fetc (READER-ENVIRONMENT REPACKAGE) of ENV2))
  (EQ (fetc (READER-ENVIRONMENT REBASE) of ENV1)
      (fetc (READER-ENVIRONMENT REBASE) of ENV2))
  (EQ (OR (fetc (READER-ENVIRONMENT REFORMAT) of ENV1)
         *DEFAULT-EXTERNALFORMAT*)
      (OR (fetc (READER-ENVIRONMENT REFORMAT) of ENV2)
         *DEFAULT-EXTERNALFORMAT*))
  (EQUAL (fetc (READER-ENVIRONMENT REPACKAGEFORM) of ENV1)
          (fetc (READER-ENVIRONMENT REPACKAGEFORM) of ENV2))
  (EQUAL (fetc (READER-ENVIRONMENT REREADTABLEFORM) of ENV1)
          (fetc (READER-ENVIRONMENT REREADTABLEFORM) of ENV2]))
```

(SET-READER-ENVIRONMENT

[LAMBDA (ENV STREAM)

; Edited 9-Jul-2021 14:42 by rmk:

;;; Sets the reader environment variables from ENV. Should usually only be called inside a WITH-READER-ENVIRONMENT.

```
[SETQ *PACKAGE* (fetc REPACKAGE of (\DTEST ENV 'READER-ENVIRONMENT)
  (SETQ *READTABLE* (fetc REREADTABLE of ENV)
  (SETQ *READ-BASE* (SETQ *PRINT-BASE* (fetc REBASE of ENV)))
  (CL:WHEN STREAM
    (\EXTERNALFORMAT STREAM (fetc (READER-ENVIRONMENT REFORMAT) OF ENV)))
  ENV])
```

```
)
(RPAQ? *LISP-PACKAGE* )
(RPAQ? *INTERLISP-PACKAGE* )
(RPAQ? *KEYWORD-PACKAGE* )
(DECLARE%: DONTEVAL@LOAD DOCOPY
```

(\ATBLSET)

)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(LOCALVARS . T)

)

(DECLARE%: DONTEVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILERVERS

(ADDTOVAR **NLAMA**)

(ADDTOVAR **NLAML**)

(ADDTOVAR **LAMA** READTABLEPROP)

)

(PUTPROPS **ATBL COPYRIGHT** ("Venue & Xerox Corporation" 1982 1983 1984 1985 1986 1987 1990 1993 2018 2021))

FUNCTION INDEX

CONTROL	4	IN-READTABLE	9	\GETREADSYNTAX	11
COPYREADTABLE	9	MAKE-READER-ENVIRONMENT	18	\GETTERMSYNTAX	6
COPYTERMTABLE	4	RAISE	6	\GTREADTABLE	12
DELETECONTROL	5	READMACROS	9	\GTREADTABLE1	12
ECHOCHAR	5	READTABLEP	9	\GTTERMTABLE	6
ECHOCONTROL	5	READTABLEPROP	9	\LITCHECK	8
ECHOMODE	6	RESETREADTABLE	10	\MAPCHARTABLE	4
EQUAL-READER-ENVIRONMENT	18	RESETTERMTABLE	6	\ORIGREADTABLE	12
ESCAPE	9	SET-READER-ENVIRONMENT	18	\ORIGTERMTABLE	6
FIND-READTABLE	9	SETBRK	10	\READCLASSTOCODE	12
GETBRK	9	SETREADTABLE	11	\READTABLEP.DEFPPRINT	13
GETCONTROL	6	SETSEPR	11	\SETFATSYNCODE	4
GETDELETECONTROL	5	SETSYNTAX	3	\SETMACROSYNTAX	12
GETECHOMODE	6	SETTERMTABLE	6	\SETREADSYNTAX	13
GETRAISE	6	SYNTAXP	3	\SETTERMSYNTAX	7
GTREADTABLE	9	TERMTABLEP	6	\TERMCLASSTOCODE	7
GETSEPR	9	\ATBLSET	17	\TERMCODETOCLASS	8
GETSYNTAX	2	\COPYSYNTAX	4		
GETTERMTABLE	6	\GETCHARCODE	4		

CONSTANT INDEX

ALONE.RMC	15	ESCAPEBIT	15	MULTIPLE-ESCAPE.RC	15	SEPRCHAR.RC	15
ALWAYS.RMC	15	FIRST.RMC	15	NOESC.RME	16	SIMULATE.CCE	8
BREAKBIT	15	IGNORE.CCE	8	NONE.TC	8	STOPATOMBIT	15
BREAKCHAR.RC	15	IMMEDIATE.RMW	16	NONIMMEDIATE.RMW	16	STRINGDELIM.RC	15
CHARDELETE.TC	8	INDICATE.CCE	8	OTHER.RC	15	WAKEUPMASK	15
CONTEXTMASK	15	INNERESCAPEBIT	15	PACKAGEDELIM.RC	15	WORDDELETE.TC	8
CTRLV.TC	8	LEFTBRACKET.RC	15	REAL.CCE	8	WORDSEPR.TC	8
EOL.TC	8	LEFTPAREN.RC	15	RETYPE.TC	8	\NSCHARHASHKEYS	2
ESC.RME	16	LINEDELETE.TC	8	RIGHTBRACKET.RC	15	\NSCHARHASHOVERFLOW	2
ESCAPE.RC	15	MACROBIT	15	RIGHTPAREN.RC	15		

VARIABLE INDEX

INTERLISP-PACKAGE	18	CCECHOMODES	8	READCODEMASKS	15	READMACROWAKEUPS	16
KEYWORD-PACKAGE	18	READCLASSES	14,15	READMACROCONTEXTS	15	TERMCLASSES	8
LISP-PACKAGE	18	READCLASSTOKENS	13	READMACROESCAPES	16	\READTABLEHASH	17

RECORD INDEX

CHARTABLE	2	ESCAPES	14	READMACRODEF	16	TERMCODE	8	WAKEUPS	14
CONTEXTS	14	READCODE	16	READTABLEP	16	TERMTABLEP	8		

MACRO INDEX

\COMPUTED.FORM	14	\GETREADMACRODEF	14	\GTREADTABLE1	14	\SYNCODE	1
\CREATENSCHARHASH	2	\GTREADTABLE	14	\SETSYNCODE	2		

PROPERTY INDEX

READTABLEPROP	13
---------------------	----