

File created: 16-May-90 14:26:56 {DSK}<usr>local>lde>lispcore>sources>CMLSEQBASICS.;2

changes to: (VARS CMLSEQBASICSOMS)

previous date: 9-Oct-87 16:34:51 {DSK}<usr>local>lde>lispcore>sources>CMLSEQBASICS.;1

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

::
:: Copyright (c) 1986, 1987, 1990 by Venue & Xerox Corporation. All rights reserved.

(RPAQQ **CMLSEQBASICSOMS**

```
((DECLARE%: EVAL@COMPILE DONTCOPY (FILES CMLSEQCOMMON))
 (FUNCTIONS CL:CONCATENATE CL:COPY-SEQ CL:ELT CL:LENGTH CL:MAKE-SEQUENCE CL:NREVERSE CL:REVERSE CL:SUBSEQ
  %%SETELT)
 (FUNCTIONS MAKE-SEQUENCE-OF-TYPE)
 (SETFS CL:ELT CL:SUBSEQ)
 (PROPS (CMLSEQBASICS FILETYPE))
 (DECLARE%: EVAL@COMPILE DONTCOPY DONTEVAL@LOAD (LOCALVARS . T))))
```

(DECLARE%: EVAL@COMPILE DONTCOPY

(FILESLOAD CMLSEQCOMMON)

)

(CL:DEFUN **CL:CONCATENATE** (RESULT-TYPE &REST SEQUENCES)

```
[LET [(RESULT (MAKE-SEQUENCE-OF-TYPE RESULT-TYPE (LET ((CNT 0)
  (CL:DOLIST (SEQ SEQUENCES CNT)
    (SETQ CNT (+ CNT (CL:LENGTH SEQ))))))
 (SEQ-DISPATCH RESULT [LET ((TAIL RESULT))
  (CL:DOLIST (SEQUENCE SEQUENCES RESULT)
    [SEQ-DISPATCH SEQUENCE (CL:DOLIST (ELEMENT SEQUENCE)
      (RPLACA TAIL ELEMENT)
      (SETQ TAIL (CDR TAIL)))]
    (CL:DOTIMES (I (VECTOR-LENGTH SEQUENCE))
      (RPLACA TAIL (CL:AREF SEQUENCE I))
      (SETQ TAIL (CDR TAIL)))]])]
 (LET ((INDEX 0)
  (CL:DOLIST (SEQUENCE SEQUENCES RESULT)
    [SEQ-DISPATCH SEQUENCE (CL:DOLIST (ELEMENT SEQUENCE)
      (CL:SETF (CL:AREF RESULT INDEX)
        ELEMENT)
      (SETQ INDEX (CL:1+ INDEX)))]
    (CL:DOTIMES (I (VECTOR-LENGTH SEQUENCE))
      (CL:SETF (CL:AREF RESULT INDEX)
        (CL:AREF SEQUENCE I))
      (SETQ INDEX (CL:1+ INDEX)))]])] ]]
```

(CL:DEFUN **CL:COPY-SEQ** (SEQUENCE)

"Returns a copy of SEQUENCE which is EQUALP to SEQUENCE but not EQ."

```
[LET ((LENGTH (CL:LENGTH SEQUENCE))
 (SEQ-DISPATCH SEQUENCE (FORWARD-LIST-LOOP SEQUENCE 0 LENGTH (INDEX CURRENT COPY TAIL)
  COPY
  (COLLECT-ITEM CURRENT COPY TAIL))
 (LET [(COPY (MAKE-VECTOR LENGTH :ELEMENT-TYPE (CL:ARRAY-ELEMENT-TYPE SEQUENCE)
  (COPY-VECTOR-SUBSEQ SEQUENCE 0 LENGTH COPY 0 LENGTH])
```

(CL:DEFUN **CL:ELT** (SEQUENCE INDEX)

(* amd " 5-Jun-86 17:48")

```
(CL:IF (NOT (< -1 INDEX (CL:LENGTH SEQUENCE)))
 (CL:ERROR 'INDEX-BOUNDS-ERROR :NAME SEQUENCE :INDEX INDEX))
 (SEQ-DISPATCH SEQUENCE (CL:NTH INDEX SEQUENCE)
 (CL:AREF SEQUENCE INDEX)))
```

(CL:DEFUN **CL:LENGTH** (SEQUENCE)

```
(SEQ-DISPATCH SEQUENCE [LET ((SIZE 0)
 (REST SEQUENCE))
 (CL:LOOP (CL:IF (NOT (CL:CONSP REST))
 (RETURN SIZE))
 (SETQ REST (CDR REST))
 (SETQ SIZE (CL:1+ SIZE]
 (VECTOR-LENGTH SEQUENCE)))
```

(CL:DEFUN **CL:MAKE-SEQUENCE** (TYPE LENGTH &KEY (INITIAL-ELEMENT NIL INITIAL-ELEMENT-P))

"Make a sequence of the specified type"

```
(CL:IF (EQ TYPE 'LIST)
 (CL:MAKE-LIST LENGTH :INITIAL-ELEMENT INITIAL-ELEMENT)
```

```
(LET ((VECTOR (MAKE-SEQUENCE-OF-TYPE TYPE LENGTH)))
  (CL:IF INITIAL-ELEMENT-P (FILL-VECTOR-SUBSEQ VECTOR 0 LENGTH INITIAL-ELEMENT)
    VECTOR)))
```

```
(CL:DEFUN CL:NREVERSE (SEQUENCE)
  "Returns a sequence of the same elements in reverse order (the argument is destroyed)."  

  [SEQ-DISPATCH SEQUENCE [LET ((REST SEQUENCE)
    LIST-HEAD RESULT)
    (CL:LOOP (CL:IF (NOT (CL:CONSP (SETQ LIST-HEAD REST)))
      (RETURN RESULT))
      (SETQ REST (CDR REST))
      (SETQ RESULT (RPLACD LIST-HEAD RESULT]
    (LET ((LENGTH (VECTOR-LENGTH SEQUENCE)))
      (CL:DO ((LEFT-INDEX 0 (CL:1+ LEFT-INDEX))
        (RIGHT-INDEX (CL:1- LENGTH)
          (CL:1- RIGHT-INDEX))
        (HALF-LENGTH (LRSH LENGTH 1)))
        ((EQL LEFT-INDEX HALF-LENGTH)
          SEQUENCE)
        (CL:ROTATEF (CL:AREF SEQUENCE LEFT-INDEX)
          (CL:AREF SEQUENCE RIGHT-INDEX))))])
```

```
(CL:DEFUN CL:REVERSE (SEQUENCE)
  "Returns a new sequence containing the same elements but in reverse order."  

  [SEQ-DISPATCH SEQUENCE [LET ((REST SEQUENCE)
    RESULT)
    (CL:LOOP (CL:IF (NOT (CL:CONSP REST))
      (RETURN RESULT))
      (CL:PUSH (CAR REST)
        RESULT)
      (SETQ REST (CDR REST]
    (LET ((LENGTH (VECTOR-LENGTH SEQUENCE)))
      (CL:DO ((RESULT (MAKE-VECTOR LENGTH :ELEMENT-TYPE (CL:ARRAY-ELEMENT-TYPE SEQUENCE)))
        (FORWARD-INDEX 0 (CL:1+ FORWARD-INDEX))
        (BACKWARD-INDEX (CL:1- LENGTH)
          (CL:1- BACKWARD-INDEX)))
        ((EQL FORWARD-INDEX LENGTH)
          RESULT)
        (CL:SETF (CL:AREF RESULT FORWARD-INDEX)
          (CL:AREF SEQUENCE BACKWARD-INDEX))))])
```

```
(CL:DEFUN CL:SUBSEQ (SEQUENCE START &OPTIONAL END)
  [LET ((LENGTH (CL:LENGTH SEQUENCE))
    (CL:IF (NULL END)
      (SETQ END LENGTH))
    (CHECK-SUBSEQ SEQUENCE START END LENGTH)
    (SEQ-DISPATCH SEQUENCE (FORWARD-LIST-LOOP SEQUENCE START END (INDEX CURRENT COPY TAIL)
      COPY
      (COLLECT-ITEM CURRENT COPY TAIL))
    (LET [(COPY (MAKE-VECTOR (- END START)
      :ELEMENT-TYPE
      (CL:ARRAY-ELEMENT-TYPE SEQUENCE)
      (COPY-VECTOR-SUBSEQ SEQUENCE START END COPY 0))
```

```
(CL:DEFUN %%SETELT (SEQUENCE INDEX NEWVAL)
  (CL:IF (NOT (< -1 INDEX (CL:LENGTH SEQUENCE)))
    (CL:ERROR 'INDEX-BOUNDS-ERROR :NAME SEQUENCE :INDEX INDEX))
  (SEQ-DISPATCH SEQUENCE (CL:SETF (CL:NTH INDEX SEQUENCE)
    NEWVAL)
    (CL:SETF (CL:AREF SEQUENCE INDEX)
      NEWVAL)))
```

```
(CL:DEFUN MAKE-SEQUENCE-OF-TYPE (TYPE LENGTH)
  [LET ((BROAD-TYPE (TYPE-SPECIFIER TYPE))
    (CL:IF (EQ BROAD-TYPE 'LIST)
      (CL:MAKE-LIST LENGTH)
      [LET [(ELEMENT-TYPE (CASE BROAD-TYPE
        ((CL:SIMPLE-STRING STRING) 'CL:STRING-CHAR)
        ((CL:SIMPLE-BIT-VECTOR CL:BIT-VECTOR) 'BIT)
        (CL:SIMPLE-VECTOR T)
        ((CL:ARRAY CL:VECTOR CL:SIMPLE-ARRAY)
          (CL:IF (CL:CONSP TYPE)
            (LET ((ELT-TYPE (CADR TYPE)))
              (CL:IF [AND ELT-TYPE (NOT (EQ ELT-TYPE 'CL:*)
                ELT-TYPE
                T))
              T)))]
        T)))]
    (CL:IF ELEMENT-TYPE
      (MAKE-VECTOR LENGTH :ELEMENT-TYPE ELEMENT-TYPE)
      (LET ((EXPANDER (CL::TYPE-EXPANDER BROAD-TYPE)))
        (CL:IF EXPANDER
          (MAKE-SEQUENCE-OF-TYPE (CL::TYPE-EXPAND TYPE EXPANDER)
```

```
          LENGTH)
        (CL:ERROR "~S is a bad type specifier for sequences." TYPE))))]]))
```

```
(CL:DEFSETF CL:ELT %%SETELT)
```

```
(CL:DEFSETF CL:SUBSEQ (SEQUENCE START &OPTIONAL END) (NEW-SEQUENCE)
  `(PROGN (CL:REPLACE ,SEQUENCE ,NEW-SEQUENCE :START1 ,START :END1 ,END)
    ,NEW-SEQUENCE))
```

```
(PUTPROPS CMLSEQBASICS FILETYPE CL:COMPILE-FILE)
```

```
(DECLARE%: EVAL@COMPILE DONTCOPY DONTEVAL@LOAD
```

```
(DECLARE%: DOEVAL@COMPILE DONTCOPY
```

```
(LOCALVARS . T)
)
)
```

```
(PUTPROPS CMLSEQBASICS COPYRIGHT ("Venue & Xerox Corporation" 1986 1987 1990))
```

FUNCTION INDEX

%%SETELT	2	CL:ELT	1	MAKE-SEQUENCE-OF-TYPE ...	2	CL:SUBSEQ	2
CL:CONCATENATE	1	CL:LENGTH	1	CL:NREVERSE	2		
CL:COPY-SEQ	1	CL:MAKE-SEQUENCE	1	CL:REVERSE	2		

SETF INDEX

CL:ELT	3	CL:SUBSEQ	3
--------------	---	-----------------	---

PROPERTY INDEX

CMLSEQBASICS	3
--------------------	---
