

File created: 15-Sep-94 11:08:59 {DSK}<lispcore>sources>LLARRAYELT.;7

changes to: (RECORDS ARRAYP)

previous date: 28-Jul-94 13:41:50 {DSK}<lispcore>sources>LLARRAYELT.;6

Read Table: INTERLISP

Package: INTERLISP

Format: XCCS

;;
;; Copyright (c) 1982, 1983, 1984, 1985, 1986, 1987, 1988, 1989, 1990, 1991, 1992, 1993, 1994 by Venue & Xerox Corporation. All rights reserved.

(RPAQQ LLARRAYELTCOMS

```
[ (COMS                                     ; Because we use the UNLESSINEM macro in this file, we need
                                         ; it when compiling.
      (DECLARE%: EVAL@COMPILE DONTCOPY (FILES (SOURCE)
                                             RENAMEMACROS)))
      (PROPS (LLARRAYELT FILETYPE))
      (COMS                                     ; ARRAY entries
      (FNS AIN AOUT ARRAY ARRAYSIZE ARRAYTYP ARRAYORIG COPYARRAY)
      (DECLARE%: DONTCOPY (MACROS ARRAYSIZE))
      (FNS ELT ELTD SETA SETD SUBARRAY))
      [ (COMS                                     ; HASHARRAY entries
      (FNS HARRAY HASHARRAY HARRAYP HARRAYPROP HARRAYSIZE CLRHASH MAPHASH GETHASH PUTHASH CL::PUTHASH
          REMHASH \HASHRECLAIM \HASHACCESS REHASH \COPYHARRAYP \HASHTABLE.DEFPRINT)
      (FNS STRINGHASHBITS STRING-EQUAL-HASHBITS)
      (FNS \STRINGHASHBITS-UFN \STRING-EQUAL-HASHBITS-UFN)
      (DECLARE%: DONTCOPY (EXPORT (RECORDS HARRAYP)
          (MACROS \EQHASHINGBITS))
          (RECORDS HASHSLLOT)
          (MACROS \FIRSTINDEX \HASHSLLOT \REPROBE)
          (CONSTANTS (CELLSPERSLOT 2))
          (GLOBALVARS \HASH.NULL.VALUE SYSHASHARRAY))
      [DECLARE%: DONTVAL@LOAD DOCOPY (P (DEFPRINT 'HARRAYP '\HASHTABLE.DEFPRINT)
      (INITRECORDS HARRAYP)
      (SYSRECORDS HARRAYP)
      (VARS (\HASH.NULL.VALUE '\Hash\Null\Value\])
      (COMS                                     ; System entries for CODE
      (FNS \CODEARRAY \FIXCODENUM \FIXCODEPTR \FIXCODESYM))
      (COMS                                     ; Internal
      (DECLARE%: DONTCOPY (MACROS EQPTR BUCKETINDEX FREEBLOCKCHAIN.N)
          (CONSTANTS \MAXBUCKETINDEX)
          ; \ADDBASE2 and \ADDBASE4 do \ADDBASE of 2*N and 4*N
          ; without boxing
          (EXPORT (MACROS \ADDBASE2 \ADDBASE4 HUNKSIZEFROMNUMBER \BYTELT \BYTESETA \WORDELT)
              (CONSTANTS * BLOCKGCTYPECONSTANTS)
              (CONSTANTS * ARRAYCONSTANTS)
              (CONSTANTS * ARRAYTYPES)
              (CONSTANTS \MAX.CELLSPERHUNK)
              (CONSTANTS (\IN.MAKEINIT))
              (RECORDS SEQUENCEDESCRIPTOR ARRAYP ARRAYBLOCK)
              (GLOBALVARS \NxtArrayPage \FREEBLOCKBUCKETS \HUNKING?))
          (GLOBALVARS \ArrayFrLst \ArrayFrLst2 \RECLAIM.COUNTDOWN))
      (FNS \ALLOCBLOCK \MAIKO.ALLOCBLOCK \ALLOCBLOCK.OLD \ALLOCBLOCK.NEW \PREFIXALIGNMENT?
          \MAKEFREEARRAYBLOCK \DELETEBLOCK? \LINKBLOCK \MERGEBACKWARD \MERGEFORWARD \ARRAYBLOCKMERGER
          \#BLOCKDATACELLS \COPYARRAYBLOCK \RECLAIMARRAYBLOCK \ADVANCE.ARRAY.SEGMENTS)
      (ADDVARS (\MAIKO.MOVDS (\MAIKO.ALLOCBLOCK \ALLOCBLOCK)))
      (FNS \BYTELT \BYTESETA \WORDELT)
      (FNS \ARRAYTYPENAME)
      (VARS (\ARRAYMERGING T))
      (GLOBALVARS \ARRAYMERGING)
      (COMS                                     ; for STORAGE
      (FNS \SHOW.ARRAY.FREELISTS)
      (INITVARS (\ABSTORAGETABLE NIL))
      (GLOBALVARS \ABSTORAGETABLE)
      (DECLARE%: DONTCOPY (RECORDS SAFTABLE)))
      (COMS                                     ; Debugging and RDSYS
      (FNS \CHECKARRAYBLOCK \PARSEARRAYSPACE \PARSEARRAYSPACE1)
      (INITVARS (ARRAYBLOCKCHECKING))
      (GLOBALVARS ARRAYBLOCKCHECKING)))
      (COMS                                     ; Basic hunking
      (FNS \ALLOCHUNK)
      (VARS \HUNK.PTRSIZES)
          ; Compiler needs \HUNK.PTRSIZES for creating closure
          ; environments
      (DECLARE%: EVAL@COMPILE DONTCOPY (EXPORT (MACROS HUNKSIZEFROMNUMBER)
          (CONSTANTS \HUNK.UNBOXEDSIZES \HUNK.CODESIZES \HUNK.PTRSIZES)
          (GLOBALVARS \HUNKING? \UNBOXEDHUNK.TYPENUM.TABLE \CODEHUNK.TYPENUM.TABLE
              \PTRHUNK.TYPENUM.TABLE))
      (COMS ;; Keep a list of all the hunks rejected due to poor page-straddling alignment, or to code falling off the end of a doublepage
      (VARS (\HUNKREJECTS))
      (GLOBALVARS \HUNKREJECTS)))
```

```

[COMS
(FNS PREINITARRAYS POSTINITARRAYS FILEARRAYBASE FILEBLOCKTRAILER FILECODEBLOCK FILEPATCHBLOCK)
(COMS
(FNS \SETUP.HUNK.TYPENUMBERS \COMPUTE.HUNK.TYPEDECLS \TURN.ON.HUNKING \SETUP.TYPENUM.TABLE))
(DECLARE%: DONTCOPY (ADDVARS (INITVALUES (\NxtArrayPage)
(\HUNKING?))
(INITPTRS (\FREEBLOCKBUCKETS)
(ArrayFrLst)
(ArrayFrLst2)
(\UNBOXEDHUNK.TYPENUM.TABLE)
(\CODEHUNK.TYPENUM.TABLE)
(\PTRHUNK.TYPENUM.TABLE))
(INEWCOMS (FNS \#BLOCKDATACELLS \PREFIXALIGNMENT? \ALLOCBLOCK
\MAIKO.ALLOCBLOCK \ALLOCBLOCK.NEW \MAKEFREEARRAYBLOCK
\MERGEBACKWARD \LINKBLOCK \ALLOCHUNK)
(FNS PREINITARRAYS POSTINITARRAYS FILEARRAYBASE FILEBLOCKTRAILER
FILECODEBLOCK FILEPATCHBLOCK)
(FNS \SETUP.HUNK.TYPENUMBERS \COMPUTE.HUNK.TYPEDECLS
\TURN.ON.HUNKING \SETUP.TYPENUM.TABLE))
(MKI.SUBFNS (\IN.MAKEINIT . T)
(\ALLOCBLOCK.OLD . NIL)
(\MERGEFORWARD . NIL)
(\FIXCODENUM . I.FIXUPNUM)
(\FIXCODESYM . I.FIXUPSYM)
(\FIXCODEPTR . I.FIXUPPTR)
(\CHECKARRAYBLOCK . NIL)
(\ARRAYMERGING PROG NIL))
(EXPANDMACROFNS \ADDBASE2 \ADDBASE4 HUNKSIZEFROMNUMBER BUCKETINDEX
FREEBLOCKCHAIN.N)
(RDCOMS (FNS \CHECKARRAYBLOCK \PARSEARRAYSPACE \PARSEARRAYSPACE1))
(RD.SUBFNS (EQPTR . EQUAL)
(ARRAYBLOCKCHECKING . T))
(RDPTRS (\FREEBLOCKBUCKETS))
(RDVALS (\ArrayFrLst)
(ArrayFrLst2)))
EVAL@COMPILE
(ADDVARS (DONTCOMPILEFNS PREINITARRAYS POSTINITARRAYS FILEARRAYBASE FILEBLOCKTRAILER
FILECODEBLOCK FILEPATCHBLOCK)
(DONTCOMPILEFNS \SETUP.HUNK.TYPENUMBERS \COMPUTE.HUNK.TYPEDECLS \TURN.ON.HUNKING
\SETUP.TYPENUM.TABLE])
[COMS
(DECLARE%: EVAL@COMPILE DONTCOPY (GLOBALVARS \ArrayFrLst)
(CONSTANTS \ArrayBlockPassword)
(ADDVARS (DONTCOMPILEFNS \HUNKFIT? \AB.NEXT \AB.BACK)))
(FNS \HUNKFIT? \AB.NEXT \AB.BACK))
(LOCALVARS . T)
(DECLARE%: DONTVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILEVARS (ADDVARS (NLAMA)
(NLAML)
(LAMA CL::PUTHASH HARRAYPROP]))

```

:: Because we use the UNLESSNEW macro in this file, we need it when compiling.

```

(DECLARE%: EVAL@COMPILE DONTCOPY
(FILESLoad (SOURCE)
RENAMEMACROS)
)
(PUTPROPS LLARRAYELT FILETYPE :BCOMPL)

```

:: ARRAY entries

```
(DEFINEQ
```

(AIN

[LAMBDA (APTR INDEX N FILE) ; Edited 23-Nov-86 16:44 by jop:

:: Reads N elements into APTR starting at INDEX. INDEX and N are in terms of the array's indexing units

```

(COND
((NOT (OR (STRINGP APTR)
(ARRAYP APTR)))
(LISPERROR "ILLEGAL ARG" APTR))
((IGREATERP 0 INDEX)
(LISPERROR "ILLEGAL ARG" INDEX)))
(LET (BASE LENGTH OFFST TYP ORIG STBYTE)
(if (STRINGP APTR)
then (SETQ BASE (ffetch (STRINGP BASE) of APTR))
(SETQ LENGTH (ffetch (STRINGP LENGTH) of APTR))
(SETQ OFFST (ffetch (STRINGP OFFST) of APTR))
(SETQ TYP (ffetch (STRINGP TYP) of APTR))
(SETQ ORIG 1)
else (SETQ BASE (ffetch (ARRAYP BASE) of APTR))
(SETQ LENGTH (ffetch (ARRAYP LENGTH) of APTR))
(SETQ OFFST (ffetch (ARRAYP OFFST) of APTR))
(SETQ TYP (ffetch (ARRAYP TYP) of APTR))
(SETQ ORIG (ffetch (ARRAYP ORIG) of APTR)))

```

```
(SETQ STBYTE (IDIFFERENCE INDEX ORIG))
(COND
  ((ILESSP (SELECTC TYP
            ((LIST \ST.BYTE \ST.CODE)
              LENGTH)
            (\ST.POS16 (SETQ OFFST (UNFOLD OFFST BYTESPERWORD))
                      (SETQ N (UNFOLD N BYTESPERWORD))
                      (SETQ STBYTE (UNFOLD STBYTE BYTESPERWORD))
                      (UNFOLD LENGTH BYTESPERWORD))
            ((LIST \ST.INT32 \ST.FLOAT)
              (SETQ OFFST (UNFOLD OFFST BYTESPERCELL))
              (SETQ N (UNFOLD N BYTESPERCELL))
              (SETQ STBYTE (UNFOLD STBYTE BYTESPERCELL))
              (UNFOLD LENGTH BYTESPERCELL))
            (\ST.BIT)
            (LISPERROR "ILLEGAL ARG" APTR))
    (IPLUS STBYTE N))
  (LISPERROR "ILLEGAL ARG" APTR)))
(\BINS (\GETOFD FILE 'INPUT)
  BASE
  (IPLUS STBYTE OFFST)
  N)
APTR])
```

(AOUT

```
[LAMBDA (APTR INDEX N FILE)
```

; Edited 23-Nov-86 16:49 by jop;
; INDEX and N are in terms of the array's indexing unit

```
(COND
  ((NOT (OR (STRINGP APTR)
            (ARRAYP APTR)))
   (LISPERROR "ILLEGAL ARG" APTR))
  ((IGREATERP 0 INDEX)
   (LISPERROR "ILLEGAL ARG" INDEX)))
```

;; Used to be in terms of the block record SEQUENCEDESCRIPTOR, but changed to refer explicitly to arrayp's and stringp's since stringp's no longer look like arrayp's

```
(LET (BASE LENGTH OFFST TYP ORIG STBYTE)
  (if (STRINGP APTR)
    then (SETQ BASE (ffetch (STRINGP BASE) of APTR))
          (SETQ LENGTH (ffetch (STRINGP LENGTH) of APTR))
          (SETQ OFFST (ffetch (STRINGP OFFST) of APTR))
          (SETQ TYP (ffetch (STRINGP TYP) of APTR))
          (SETQ ORIG 1)
    else (SETQ BASE (ffetch (ARRAYP BASE) of APTR))
          (SETQ LENGTH (ffetch (ARRAYP LENGTH) of APTR))
          (SETQ OFFST (ffetch (ARRAYP OFFST) of APTR))
          (SETQ TYP (ffetch (ARRAYP TYP) of APTR))
          (SETQ ORIG (ffetch (ARRAYP ORIG) of APTR)))
  (SETQ STBYTE (IDIFFERENCE INDEX ORIG))
```

; Standardize units before comparing

```
(COND
  ((ILESSP (SELECTC TYP
            ((LIST \ST.BYTE \ST.CODE)
              LENGTH)
            (\ST.POS16 (SETQ N (UNFOLD N BYTESPERWORD))
                      (SETQ STBYTE (UNFOLD STBYTE BYTESPERWORD))
                      (SETQ OFFST (UNFOLD OFFST BYTESPERWORD))
                      (UNFOLD LENGTH BYTESPERWORD))
            ((LIST \ST.INT32 \ST.FLOAT)
              (SETQ N (UNFOLD N BYTESPERCELL))
              (SETQ STBYTE (UNFOLD STBYTE BYTESPERCELL))
              (SETQ OFFST (UNFOLD OFFST BYTESPERCELL))
              (UNFOLD LENGTH BYTESPERCELL))
            (LISPERROR "ILLEGAL ARG" APTR))
    (IPLUS STBYTE N))
  (LISPERROR "ILLEGAL ARG" APTR)))
(\BOUTS (\GETOFD FILE 'OUTPUT)
  BASE
  (IPLUS STBYTE OFFST)
  N)
APTR])
```

(ARRAY

```
[LAMBDA (SIZE TYPE INITVAL ORIG ALIGN)
```

(* JonL "20-Sep-84 19:46")

;; extension of the normal VM definition of an array to allow many different TYPEs, and also allows ORIG of 0

```
(SETQ SIZE (FIX SIZE))
(COND
  ((OR (IGREATERP 0 SIZE)
        (IGREATERP SIZE \MaxArrayLen))
   (LISPERROR "ILLEGAL ARG" SIZE)))
  (PROG (AP TYP GCTYPE (NCELLS SIZE))
    [SETQ TYP (SELECTQ TYPE
                      (BYTE (SETQ NCELLS (FOLDHI SIZE BYTESPERCELL))
                            \ST.BYTE)
                      ((SMALLP SMALLPOSP WORD)
```

; Coerce floats at outset; \ALLOCARRAY wants fixp

```

        (SETQ NCELLS (FOLDHI SIZE WORDSPERCELL))
        \ST.POS16)
((NIL POINTER FLAG)
 (SETQ GCTYPE PTRBLOCK.GCT)
 \ST.PTR)
((0 DOUBLEPOINTER)
 (SETQ NCELLS (UNFOLD SIZE 2))
 (SETQ GCTYPE PTRBLOCK.GCT)
 \ST.PTR2)
(FIXP \ST.INT32)
(FLOATP [COND
 (INITVAL (SETQ INITVAL (FLOAT INITVAL]
 \ST.FLOAT)
(BIT (SETQ NCELLS (FOLDHI SIZE BITSPERCELL))
 \ST.BIT)
(SIGNEDWORD \ST.INT32)
(COND
 (EQ SIZE TYPE)
 \ST.INT32)
 (AND (LISTP TYPE)
 (EQ (CAR TYPE)
 'BITS))
(COND
 ((IGREATERP (CADR TYPE)
 16)
 \ST.INT32)
 ((IGREATERP (CADR TYPE)
 8)
 (SETQ NCELLS (FOLDHI SIZE WORDSPERCELL))
 \ST.POS16)
 ((IGREATERP (CADR TYPE)
 1)
 (SETQ NCELLS (FOLDHI SIZE BYTESPERCELL))
 \ST.BYTE)
 (T (SETQ NCELLS (FOLDHI SIZE BITSPERCELL))
 \ST.BIT)))
(T (\ILLEGAL.ARG TYPE]
(SETQ AP (create ARRAYP
 TYP _ TYP
 LENGTH _ SIZE
 ORIG _ (SELECTQ ORIG
 ((0 1)
 ORIG)
 (NIL 1)
 (LISPERROR "ILLEGAL ARG" ORIG))
 OFFST _ 0
 BASE _ (ALLOCBLOCK NCELLS GCTYPE NIL ALIGN)))
[AND INITVAL (PROG ((BASE (fetch (ARRAYP BASE) of AP))
 (NWORDS (SUB1 (UNFOLD NCELLS WORDSPERCELL)))
 LASTWORD2BASE)
 (SETQ LASTWORD2BASE (\ADDBASE BASE (SUB1 NWORDS)))
 (SELECTC TYP
 (\ST.BYTE (OR (EQ 0 INITVAL)
 (PROGN (\PUTBASE LASTWORD2BASE 1
 (create WORD
 HIBYTE _ INITVAL
 LOBYTE _ INITVAL)
 (\BLT BASE (\ADDBASE BASE 1)
 NWORDS))))))
 (\ST.POS16 (OR (EQ 0 INITVAL)
 (PROGN (\PUTBASE LASTWORD2BASE 1 INITVAL)
 (\BLT BASE (\ADDBASE BASE 1)
 NWORDS))))))
 (\ST.INT32 [OR (EQ 0 INITVAL)
 (PROGN (\PUTBASEFIXP LASTWORD2BASE 0 INITVAL)
 (\BLT BASE (\ADDBASE BASE WORDSPERCELL)
 (SUB1 NWORDS]))
 ((LIST \ST.PTR \ST.PTR2)
 ; Remove \ST.FLOAT when FLOATP is no longer stored in PTR
 ; mode.
 (PROG ((P BASE))
 (FRPTQ NCELLS (\RPLPTR P 0 INITVAL)
 (SETQ P (\ADDBASE P WORDSPERCELL]))
 (\ST.FLOAT [OR (FEQP 0.0 INITVAL)
 (PROGN (\PUTBASEFLOATP LASTWORD2BASE 0 INITVAL)
 (\BLT BASE (\ADDBASE BASE WORDSPERCELL)
 (SUB1 NWORDS]))
 (\ST.BIT (OR (EQ 0 INITVAL)
 (PROGN (\PUTBASE LASTWORD2BASE 1 MASKWORD1'S)
 (\BLT BASE (\ADDBASE BASE 1)
 NWORDS))))))
(SHOULDNT]
(RETURN AP])

```

(ARRAYSIZE

```

[LAMBDA (X)
 (\MACRO.MX (ARRAYSIZE X))

```

(* JonL " 4-NOV-83 12:44")

(ARRAYTYP

```
[LAMBDA (ARRAY)
  ;; This is a VM function which returns valid 2nd argument to ARRAY
  (SELECTC (fetch (ARRAYP TYP) of (\DTEST ARRAY 'ARRAYP))
    (\ST.BYTE 'BYTE)
    (\ST.PTR2 'DOUBLEPOINTER)
    (\ST.PTR 'POINTER)
    (\ST.POS16 'SMALLPOSP)
    (\ST.CODE
      'CODE)
    (\ST.INT32 'FIXP)
    (\ST.FLOAT 'FLOATP)
    (\ST.BIT 'BIT)
    (SHOULDNT])
  ; not valid 2nd arg to ARRAY
(* rmk%: "30-Dec-83 13:12")
```

(ARRAYORIG

```
[LAMBDA (ARRAY)
  (fetch (ARRAYP ORIG) of (\DTEST ARRAY 'ARRAYP))
(* rmk%: "30-Dec-83 13:12")
```

(COPYARRAY

```
[LAMBDA (ARRAY)
  (COND
    [(HARRAYP ARRAY)
     (PROG [(NHARRAY (HASHARRAY (HARRAYSIZE ARRAY)
      (\COPYHARRAYP ARRAY NHARRAY)
      (RETURN (REHASH ARRAY NHARRAY)]
    (T (PROG (NEWARRAY INDEX (ORIG (ARRAYORIG ARRAY))
      (TYPE (ARRAYTYP ARRAY))
      (SIZE (ARRAYSIZE ARRAY)))
      (SETQ NEWARRAY (ARRAY SIZE TYPE NIL ORIG))
      (SETQ INDEX ORIG)
      (FRPTQ SIZE (SETA NEWARRAY INDEX (ELT ARRAY INDEX))
        (add INDEX 1))
      (SELECTQ TYPE
        ((DOUBLEPOINTER)
         (SETQ INDEX ORIG)
         (FRPTQ SIZE (SETD NEWARRAY INDEX (ELTD ARRAY INDEX))
           (add INDEX 1)))
        NIL)
      (RETURN NEWARRAY)])
  )
(DECLARE%: DONTCOPY
(DECLARE%: EVAL@COMPILE
(PUTPROPS ARRAYSIZE DMACRO [(A)
  (fetch (ARRAYP LENGTH) of (\DTEST A 'ARRAYP))
)
(DEFINEQ
(ELT
[LAMBDA (A N)
  (\DTEST A 'ARRAYP)
  (PROG [(BASE (fetch (ARRAYP BASE) of A)]
    (NO (IDIFFERENCE N (fetch (ARRAYP ORIG) of A)]
    (COND
      ((OR (IGREATERP 0 NO)
        (IGEQ NO (fetch (ARRAYP LENGTH) of A)))
       (LISPERROR "ILLEGAL ARG" N)))
      (SETQ NO (IPLUS NO (fetch (ARRAYP OFFST) of A)))
      (RETURN (SELECTC (fetch (ARRAYP TYP) of A)
        ((LIST \ST.PTR \ST.PTR2)
         (\GETBASEPTR (\ADDBASE2 BASE NO)
           0))
         (\ST.INT32 (SETQ BASE (\ADDBASE2 BASE NO))
           (\MAKENUMBER (\GETBASE BASE 0)
             (\GETBASE BASE 1)))
         ((LIST \ST.BYTE \ST.CODE)
          (\GETBASEBYTE BASE NO))
         (\ST.POS16 (\GETBASE BASE NO))
         (\ST.BIT (LOGAND (LRSH (\GETBASE BASE (FOLDLO NO BITSPERWORD))
           (IDIFFERENCE (SUB1 BITSPERWORD)
             (IMOD NO BITSPERWORD)))
           1))
         (\ST.FLOAT (\GETBASEFLOATP BASE (UNFOLD NO WORDSPERCELL)))
         (LISPERROR "ILLEGAL ARG" A)]
  )
(* Imm " 7-Jun-84 17:53")
```

(ELTD

```
[LAMBDA (A N)
  (\DTEST A 'ARRAYP)
  (SELECTC (fetch (ARRAYP TYP) of A)
    (\ST.PTR2 (PROG [(BASE (fetch (ARRAYP BASE) of A))
      (NO (IDIFFERENCE N (fetch (ARRAYP ORIG) of A]
        (COND
          ((OR (IGREATERP 0 NO)
            (IGEQ NO (fetch (ARRAYP LENGTH) of A)))
            (LISPERROR "ILLEGAL ARG" N)))
          (SETQ NO (IPLUS NO (fetch (ARRAYP OFFST) of A)))
          (RETURN (\GETBASEPTR (\ADDBASE2 (\ADDBASE2 BASE (fetch (ARRAYP LENGTH) of A))
            NO)
              0))))))
    (ELT A N])
  (* rmk%: "30-Dec-83 13:13")
```

(SETA

```
[LAMBDA (A N V)
  (COND
    ([fetch (ARRAYP READONLY) of (SETQ A (\DTEST A 'ARRAYP]
      (LISPERROR "ILLEGAL ARG" A)))
    (PROG [(BASE (fetch (ARRAYP BASE) of A))
      (NO (IDIFFERENCE N (fetch (ARRAYP ORIG) of A]
        (COND
          ((OR (ILESSP NO 0)
            (IGEQ NO (fetch (ARRAYP LENGTH) of A)))
            (LISPERROR "ILLEGAL ARG" N)))
          (SETQ NO (IPLUS NO (fetch (ARRAYP OFFST) of A)))
          (RETURN (SELECTC (fetch (ARRAYP TYP) of A)
            ((LIST \ST.PTR \ST.PTR2)
              (\RPLPTR (\ADDBASE2 BASE NO)
                0 V))
            (\ST.INT32 ; 32-bit 2's complement integers
              (\PUTBASEFIXP (\ADDBASE2 BASE NO)
                0 V))
            ((LIST \ST.BYTE \ST.CODE)
              (\PUTBASEBYTE BASE NO V))
            (\ST.POS16 ; Unsigned 16-bit numbers
              (\PUTBASE BASE NO V))
            (\ST.BIT [\PUTBASE BASE (FOLDLO NO BITSPPERWORD)
              (COND
                [(EQ 0 V)
                  (LOGAND (\GETBASE BASE (FOLDLO NO BITSPPERWORD))
                    (LOGXOR (LLSH 1 (IDIFFERENCE (SUB1 BITSPPERWORD)
                      (IMOD NO BITSPPERWORD)))
                      (SUB1 (LLSH 1 BITSPPERWORD))
                    (T (LOGOR (\GETBASE BASE (FOLDLO NO BITSPPERWORD))
                      (LLSH 1 (IDIFFERENCE (SUB1 BITSPPERWORD)
                        (IMOD NO BITSPPERWORD))
                    V)
            (\ST.FLOAT (\PUTBASEFLOATP BASE (UNFOLD NO WORDSPERCELL)
              (FLOAT V)))
            (LISPERROR "ILLEGAL ARG" A])
  (* bvm%: " 6-Feb-85 15:54")
```

(SETD

```
[LAMBDA (A N V)
  (\DTEST A 'ARRAYP)
  (SELECTC (fetch (ARRAYP TYP) of A)
    (\ST.PTR2 (COND
      ((fetch (ARRAYP READONLY) of A)
        (LISPERROR "ILLEGAL ARG" A)))
      (PROG [(BASE (fetch (ARRAYP BASE) of A))
        (NO (IDIFFERENCE N (fetch (ARRAYP ORIG) of A]
          (COND
            ((OR (IGREATERP 0 NO)
              (IGEQ NO (fetch (ARRAYP LENGTH) of A)))
              (LISPERROR "ILLEGAL ARG" N)))
            (SETQ NO (IPLUS NO (fetch (ARRAYP OFFST) of A)))
            (\RPLPTR (\ADDBASE2 (\ADDBASE2 BASE (fetch (ARRAYP LENGTH) of A))
              NO)
                0 V)
            (RETURN V)))
    (SETA A N V])
  (* rmk%: "30-Dec-83 13:14")
```

(SUBARRAY

```
[LAMBDA (X N M OLD NEWORIG)
  (\DTEST X 'ARRAYP)
  (PROG ((LEN (fetch (ARRAYP LENGTH) of X))
    (ORIG (fetch (ARRAYP ORIG) of X))
    (N1 N)
    (M1 M))
    ; N1 and M1 so don't reset user arg
  (COND
    ((IGREATERP 0 N1)
      ; Coerce the first index
      (SETQ N1 (IPLUS N1 LEN 1])
  (* rmk%: "30-Dec-83 13:15")
```


EQUIVFN _ EQUIVFN])

(HARRAYP

[LAMBDA (X)
(AND (type? HARRAYP X)
X)]

(* rmk%: "21-Dec-83 22:20")

(HARRAYPROP

[LAMBDA NARGS

(* bvm%: "21-Jan-86 11:02")

; Nospread so we can tell whether a new value was specified

(PROG ((HARRAY (AND (IGREATERP NARGS 0)
(ARG NARGS 1)))
(PROP (AND (IGREATERP NARGS 1)
(ARG NARGS 2)))
(NEWVALP (IGREATERP NARGS 2))
HA NEWVALUE)
(SETQ HA (\DTEST HARRAY 'HARRAYP)) ; Keep HARRAY explicitly so can tell LISTP case
(AND NEWVALP (SETQ NEWVALUE (ARG NARGS 3)))
[RETURN (SELECTQ PROP
(SIZE (AND NEWVALP (GO CANTUPDATE))
(HARRAYSIZE HA))
(OVERFLOW [COND
[(LISTP HARRAY) ; For compatibility with old code that would enlist the hasharray
(PROG1 (CDR HARRAY)
(AND NEWVALP (REPLACD HARRAY NEWVALUE)))]
(T (PROG1 (fetch (HARRAYP OVERFLOWACTION) of HA)
(AND NEWVALP (replace (HARRAYP OVERFLOWACTION) of HA with NEWVALUE)))]))
(NUMKEYS (AND NEWVALP (GO CANTUPDATE))
(fetch (HARRAYP NUMKEYS) of HA))
(EQUIVFN (PROG1 (fetch (HARRAYP EQUIVFN) of HA)
[AND NEWVALP (COND
((NEQ (fetch (HARRAYP NUMKEYS) of HA)
0) ; Absurd to change equivalence relation in midstream
(GO CANTUPDATE))
(T (replace (HARRAYP EQUIVFN) of HA with NEWVALUE]))
(RECLAIMABLE (PROG1 (fetch (HARRAYP RECLAIMABLE) of HA)
(AND NEWVALP (replace (HARRAYP RECLAIMABLE) of HA with NEWVALUE))))
(HASHBITSFN (PROG1 (fetch (HARRAYP HASHBITSFN) of HA)
[AND NEWVALP (COND
((NEQ (fetch (HARRAYP NUMKEYS) of HA)
0)
(GO CANTUPDATE))
(T (replace (HARRAYP HASHBITSFN) of HA with NEWVALUE))]
(PROG1 (LISTGET (SETQ HARRAY (fetch (HARRAYP HASHUSERDATA) of HA))
PROP)
[AND NEWVALP (COND
((NULL HARRAY)
(replace (HARRAYP HASHUSERDATA) of HA with (LIST PROP NEWVALUE)))
(T (LISTPUT HARRAY PROP NEWVALUE))]
CANTUPDATE
(ERROR "Can't update this hash array property" PROP)])

(HARRAYSIZE

[LAMBDA (HARRAY)
(fetch NUMSLOTS of (\DTEST HARRAY 'HARRAYP))

(* rmk%: "21-Dec-83 23:33")

(CLRHASH

[LAMBDA (HARRAY)
(PROG ((HA (\DTEST HARRAY 'HARRAYP))
SLOT)
(SETQ SLOT (fetch HARRAYPBASE of HA))
(UNINTERRUPTABLY
(bind [LASTSLOT _ (fetch (HASHSLOT NEXTSLOT) of (\HASHSLOT SLOT (fetch (HARRAYP LASTINDEX) of HA]
do (replace (HASHSLOT KEY) of SLOT with NIL)
(replace (HASHSLOT VALUE) of SLOT with NIL)
repeatuntil (EQ (SETQ SLOT (fetch (HASHSLOT NEXTSLOT) of SLOT))
LASTSLOT))
(replace (HARRAYP NULLSLOTS) of HA with (fetch (HARRAYP NUMSLOTS) of HA))
(replace (HARRAYP NUMKEYS) of HA with 0))
(RETURN HARRAY)])

(* bvm%: "21-Jan-86 11:32")

(MAPHASH

[LAMBDA (HARRAY MAPHFN)
(DECLARE (LOCALVARS . T))
(LET ((HA (\DTEST HARRAY 'HARRAYP))
SLOT)
(SETQ SLOT (fetch HARRAYPBASE of HA))
(bind V [LASTSLOT _ (fetch (HASHSLOT NEXTSLOT) of (\HASHSLOT SLOT (fetch (HARRAYP LASTINDEX) of HA]
(NULLVALUE _ \HASH.NULL.VALUE) when (SETQ V (fetch (HASHSLOT VALUE) of SLOT))
do (APPLY* MAPHFN (AND (NEQ V NULLVALUE)
V)

(* bvm%: "21-Jan-86 11:28")


```

      (fetch (HASHSLOT KEY) of SLOT))
  repeatuntil (EQ (SETQ SLOT (fetch (HASHSLOT NEXTSLOT) of SLOT))
              LASTSLOT)
  finally (RETURN HARRAY)]

```

(GETHASH

[LAMBDA (ITEM HARRAY DEFAULT RETURNMVS) ; Edited 26-Feb-91 13:07 by jds

;;; RETURNMVS, if true return multiple values, else don't.

```

(PROG ((HA (\DTEST HARRAY 'HARRAYP))
      INDEX SLOT SKEY FIRSTINDEX REPROBE LIMIT BITS EQFN ABASE VALUE)
 [SETQ BITS (COND
              ((SETQ BITS (fetch (HARRAYP HASHBITSFN) of HA))
               (APPLY* BITS ITEM))
              (T (\EQHASHINGBITS ITEM)
               (SETQ INDEX (\FIRSTINDEX BITS HA)) ; Do first index outside of loop, so don't have to do setup on fast
               ; case
              (SETQ ABASE (fetch HARRAYPBASE of HA))
              (SETQ SLOT (\HASHSLOT ABASE INDEX))
              [COND
               ((SETQ VALUE (fetch (HASHSLOT VALUE) of SLOT)) ; Slot is occupied
                (COND
                 ((OR (EQ ITEM (SETQ SKEY (fetch (HASHSLOT KEY) of SLOT)))
                     (AND (SETQ EQFN (fetch (HARRAYP EQUIVFN) of HA))
                          (APPLY* EQFN ITEM SKEY)))
                  (GO FOUND))) ; else try again
                )
               [(NULL (fetch (HASHSLOT KEY) of SLOT)) ; Null slot
                (RETURN (COND
                        (RETURNMVS (CL:VALUES DEFAULT NIL))
                        (T DEFAULT)
                (T ; Deleted slot: null value, non-nil key
                 (SETQ EQFN (fetch (HARRAYP EQUIVFN) of HA)) ; Perhaps we hit right on
                 (SETQ FIRSTINDEX INDEX)
                 (SETQ REPROBE (\REPROBE BITS HA)) ; Compute reprobe interval
                 (SETQ LIMIT (ADD1 (fetch (HARRAYP LASTINDEX) of HA)))
                 LP (SETQ INDEX (IREMAINDER (IPLUS INDEX REPROBE)
                                           LIMIT))

```

;; Since table size is a power of two, any wraparound in the IPLUS16 will be consistent with the LOGAND

```

(COND
 ((EQ INDEX FIRSTINDEX) ; Should never happen, since we don't allow full occupancy
 (SHOULDNT "Hashing in full hash table")))
 (SETQ SLOT (\HASHSLOT ABASE INDEX))
 (SETQ SKEY (fetch (HASHSLOT KEY) of SLOT))
 [COND
 [(SETQ VALUE (fetch (HASHSLOT VALUE) of SLOT)) ; Slot is occupied
  (COND
   ((OR (EQ (SETQ SKEY (fetch (HASHSLOT KEY) of SLOT))
            ITEM)
        (AND EQFN (APPLY* EQFN ITEM SKEY))) ; Found it
   (GO FOUND)
   ((NULL (fetch (HASHSLOT KEY) of SLOT)) ; Empty slot
    (RETURN (COND
            (RETURNMVS (CL:VALUES DEFAULT NIL))
            (T DEFAULT)
    (GO LP)
  FOUND
  (RETURN (COND
          (RETURNMVS (CL:VALUES (AND (NEQ VALUE \HASH.NULL.VALUE)
                                   VALUE)
                               T))
          (T (AND (NEQ VALUE \HASH.NULL.VALUE)
                 VALUE)])

```

(PUTHASH

[LAMBDA (KEY VAL HARRAY) (* raf "22-Aug-86 16:55")

;;; Store new value VAL, or remove old value if VAL = NIL

```

(\HASHACCESS KEY VAL HARRAY (NULL VAL))
VAL])

```

(CL::PUTHASH

(CL:LAMBDA (KEY CL:HASH-TABLE VALUE &OPTIONAL (EXTRA NIL EXTRA-P)) ; Edited 23-Mar-87 12:00 by bvm:

;; SETF inverse for CL:GETHASH. Subtlety is that CL:GETHASH has an optional arg DEFAULT, so if you passed one of those 3-argument
;; forms to SETF, you'd get 4 arguments in this call. In this case, the fourth argument is the new value and you should ignore the third.

```

(CL:CHECK-TYPE CL:HASH-TABLE CL:HASH-TABLE)
(\HASHACCESS KEY (CL:IF EXTRA-P
                       EXTRA

```



```

      (GO ADDNEWENTRY))
      ( (NULL DELSLOT) ; Key non-NIL but value NIL means deleted.
        (SETQ DELSLOT SLOT])
(GO LP)
FOUND
  (UNINTERRUPTABLY
    [COND
      (REMOVE ; Deleted slots are noted by value = NIL and key non-NIL
        (replace (HASHSLOT KEY) of SLOT with T)
        (replace (HASHSLOT VALUE) of SLOT with NIL)
        (add (fetch (HARRAYP NUMKEYS) of HA)
          -1))
      (T ; If writing value NIL must write distinguished non-NIL value. Ultimately, this should be a non-interned symbol, so that
        ; nobody could mistakenly type it (!) but it still wouldn't be ref counted (in present world)
        (replace (HASHSLOT VALUE) of SLOT with (OR VAL \HASH.NULL.VALUE]))
    (RETURN T)
  ADDNEWENTRY ; Didn't find this item in table. If REMOVE is T, nothing to do.

(COND
  (REMOVE (RETURN NIL)))
(COND
  ((EQ 0 (fetch (HARRAYP NULLSLOTS) of HA))
    (COND
      ((fetch (HARRAYP RECLAIMABLE) of HA) ; Before rehashing, remove anything with ref cnt 1
        (\HASHRECLAIM HA)))
      (SETQ HARRAY (HASHOVERFLOW (OR HARRAY SYSHASHARRAY)))
      (SETQ HA (\DTEST HARRAY 'HARRAYP))
      ;; ERRORX2 doesn't handle SYSHASHARRAY specially; on 10, SYSHASHARRAY is rehashed directly in PUTHASH, without going
      ;; through ERRORX2 and independent of the normal LISTP conventions.
      (SETQ DELSLOT NIL) ; Non-NIL DELSLOT is a pointer into the old array
      (GO PHTOP)))
  (UNINTERRUPTABLY
    (OR (EQ SLOT DELSLOT)
      (add (fetch (HARRAYP NULLSLOTS) of HA)
        -1))
      (add (fetch (HARRAYP NUMKEYS) of HA)
        1)
      (replace (HASHSLOT KEY) of SLOT with ITEM)
      (replace (HASHSLOT VALUE) of SLOT with (OR VAL \HASH.NULL.VALUE)))
  (RETURN VAL])

```

(REHASH

```

[LAMBDA (OLDAR NEWAR) ; (* rmk%: "26-Dec-83 11:50")
  (CLRHASH NEWAR)
  (PROG [SLOT LASTSLOT V (APTR1 (\DTEST OLDAR 'HARRAYP) ; This is maphash expanded out
    (SETQ SLOT (fetch HARRAYPBASE of APTR1))
    (SETQ LASTSLOT (\ADDBASE4 SLOT (fetch (HARRAYP LASTINDEX) of APTR1)))
  LP (COND
    ((SETQ V (fetch (HASHSLOT VALUE) of SLOT))
      (PUTHASH (fetch (HASHSLOT KEY) of SLOT)
        V NEWAR)))
    (COND
      ((EQ SLOT LASTSLOT)
        (RETURN NEWAR)))
    (SETQ SLOT (fetch (HASHSLOT NEXTSLOT) of SLOT))
  (GO LP])

```

(COPYHARRAYP

```

[LAMBDA (SOURCE TARGET) ; (* rmk%: "31-Dec-83 13:58")
  ;; Copies all properties of SOURCE into TARGET; called from HASHOVERFLOW
  (replace NULLSLOTS of TARGET with (fetch NULLSLOTS of SOURCE))
  (replace LASTINDEX of TARGET with (fetch LASTINDEX of SOURCE))
  (replace HARRAYPBASE of TARGET with (fetch HARRAYPBASE of SOURCE))
  (replace OVERFLOWACTION of TARGET with (fetch OVERFLOWACTION of SOURCE))
  (replace NUMSLOTS of TARGET with (fetch NUMSLOTS of SOURCE))
  (replace NUMKEYS of TARGET with (fetch NUMKEYS of SOURCE])

```

(HASHTABLE.DEFPRINT

```

[LAMBDA (CL:HASH-TABLE STREAM) ; Edited 23-Mar-87 11:38 by bvm:
  ;; For benefit of common lisp, print harray by name "hash table", for example, #<Hash-Table @ 76,5432>
  [.SPACECHECK. STREAM (CONSTANT (+ (NCHARS "<Hash-Table @ >")
    (PROGN ; Longest address is '177,177777'
      10]
    (\OUTCHAR STREAM (fetch (READTABLEP HASHMACROCHAR) of *READTABLE*))
    (\SOUT "<Hash-Table @ " STREAM)
    (\PRINTADDR CL:HASH-TABLE STREAM)
    (\OUTCHAR STREAM (CHARCODE >)) ; Return T to say we printed it ourselves
  T])

```

)

(DEFINEQ

(STRINGHASHBITS

[LAMBDA (STRING)
(MISCN STRINGHASHBITS STRING)]

; Edited 2-Mar-89 14:11 by jds

(STRING-EQUAL-HASHBITS

[LAMBDA (STRING)

; Edited 2-Mar-89 14:14 by jds

;;; A hashbits function for the hash equivalence STRING-EQUAL.

;;; This is similar to the atom hash algorithm, but we OR in 40Q to cause uppercase and lowercase chars to have the same codes.

(MISCN STRING-EQUAL-HASHBITS STRING)]

)

(DEFINEQ

(\STRINGHASHBITS-UFN

[LAMBDA (INDEX ARGCOUNT ARG-PTR)

; Edited 2-Mar-89 14:06 by jds

;; UFN for the STRINGHASHBITS MISCN opcode. Computes a hash index for strings and symbols, so identical string CONTENTS hash to the
;; same place.

(LET ((STRING (\GETBASEPTR ARG-PTR 0)))
(for C inpname STRING bind (HASHBITS _ 0) do

[SETQ HASHBITS
(IPLUS16 C (IPLUS16 (SETQ HASHBITS
(IPLUS16 HASHBITS
(LLSH (LOGAND HASHBITS 4095)
2)))
(LLSH (LOGAND HASHBITS 255)
8])

; This is similar to the atom hash algorithm

finally (RETURN HASHBITS])

(\STRING-EQUAL-HASHBITS-UFN

[LAMBDA (INDEX ARGCOUNT ARG-PTR)

; Edited 2-Mar-89 14:09 by jds

;;; A hashbits function for the hash equivalence STRING-EQUAL.

;;; This is similar to the atom hash algorithm, but we OR in 40Q to cause uppercase and lowercase chars to have the same codes.

(LET ((STRING (\GETBASEPTR ARG-PTR 0)))
(for C inpname STRING bind (HASHBITS _ 0) do

[SETQ HASHBITS
(IPLUS16 (LOGOR C 32)
(IPLUS16 (SETQ HASHBITS
(IPLUS16 HASHBITS (LLSH (LOGAND HASHBITS
4095)
2)))
(LLSH (LOGAND HASHBITS 255)
8])

finally (RETURN HASHBITS])

)

(DECLARE%: DONTCOPY

;; FOLLOWING DEFINITIONS EXPORTED

(DECLARE%: EVAL@COMPILE

(DATATYPE HARRAYP ((NULLSLOTS WORD)
(LASTINDEX WORD)

; Number of NIL-NIL slots, which break chains
; Slot offset of last slot. Used in probe computations
; computations. Microcode support for \ADDBASE4 would help

(HARRAYPBASE POINTER)
(RECLAIMABLE FLAG)
(OVERFLOWACTION POINTER)
(NUMSLOTS WORD)

; True if keys can go away when no other refs

(NUMKEYS WORD)
(HASHBITSFN POINTER)
(EQUIVFN POINTER)
(HASHUSERDATA POINTER))

; The maximum number of logical slots--returned by
; HARRAYSIZE
; The number of distinct keys in the array

)

(/DECLAREDATATYPE 'HARRAYP ' (WORD WORD POINTER FLAG POINTER WORD WORD POINTER POINTER POINTER)

;; ---field descriptor list elided by lister---

' 14)

(DECLARE%: EVAL@COMPILE

(PUTPROPS \EQHASHINGBITS MACRO [OPENLAMBDA (X)

; Spread out objects whose low bits are in small arithmetic
; progression, esp atoms

```

      (LOGXOR (\HILOC X)
        (LOGXOR (LLSH (LOGAND (\LOLOC X)
                          8191)
                    3)
          (LRSH (\LOLOC X)
                9]))
    )

```

:: END EXPORTED DEFINITIONS

(DECLARE%: EVAL@COMPILE

```

[BLOCKRECORD HASHSLOT ((KEY POINTER)
                      (VALUE POINTER))
 (ACCESSFNS ((NEXTSLOT (\ADDBASE DATUM (UNFOLD WORDSPERCELL CELLSPERSLOT]
)

```

(DECLARE%: EVAL@COMPILE

```

(PUTPROPS FIRSTINDEX MACRO [(BITS APTR1)
 (IREMAINDER BITS (ADD1 (fetch (HARRAYP LASTINDEX) of APTR1))]
)

```

```

(PUTPROPS HASHSLOT MACRO (= . \ADDBASE4))

```

```

(PUTPROPS REPROBE MACRO ((BITS HA)
 (LOGOR [IREMAINDER (LOGXOR BITS (LRSH BITS 8))
        (IMIN 64 (ADD1 (fetch (HARRAYP LASTINDEX) of HA)
                        1)))]
)

```

(DECLARE%: EVAL@COMPILE

(RPAQQ **CELLSPERSLOT** 2)

```

(CONSTANTS (CELLSPERSLOT 2))
)

```

(DECLARE%: DOEVAL@COMPILE DONTCOPY

```

(GLOBALVARS \HASH.NULL.VALUE SYSHASHARRAY)
)
)

```

(DECLARE%: DONTEVAL@LOAD DOCOPY

```

(DEFPRINT 'HARRAYP '\HASHTABLE.DEFPRINT)
)

```

```

(/DECLAREDATATYPE 'HARRAYP ' (WORD WORD POINTER FLAG POINTER WORD WORD POINTER POINTER POINTER)
;; ---field descriptor list elided by lister---
' 14)

```

```

(ADDTOVAR SYSTEMRECLST
 (DATATYPE HARRAYP ((NULLSLOTS WORD)
                    (LASTINDEX WORD)
                    (HARRAYPBASE POINTER)
                    (RECLAIMABLE FLAG)
                    (OVERFLOWACTION POINTER)
                    (NUMSLOTS WORD)
                    (NUMKEYS WORD)
                    (HASHBITSFN POINTER)
                    (EQUIVFN POINTER)
                    (HASHUSERDATA POINTER))))
)

```

(RPAQQ **HASH.NULL.VALUE** \Hash\Null\Value\)

:: System entries for CODE

(DEFINEQ

(\CODEARRAY

```

[LAMBDA (NBYTES INITONPAGE)
 (PROG NIL (* lmm "15-Aug-84 11:51")

```

;; NBYTES is the number of bytes required, INITONPAGE is the number of CELLS which must reside on same page

```

(COND
 ((OR (IGREATERP 0 NBYTES)
      (IGREATERP NBYTES 65535))
 (LISPERROR "ILLEGAL ARG" NBYTES))) ; dolphin requires code blocks aligned quadword
(RETURN (create ARRAYP
  TYP _ \ST.CODE
  BASE _ (\ALLOCBLOCK (FOLDHI NBYTES BYTESPERCELL)
                     CODEBLOCK.GCT INITONPAGE CELLSPERQUAD)
  LENGTH _ NBYTES
  ORIG _ 0))

```

(\FIXCODENUM

```
[LAMBDA (CA BN NUM MASK) ; Edited 7-Jan-91 13:29 by jds
  (DECLARE (IGNORE MASK) ; MASK is used by the renamed version of this function.
  ;; Do fixup for a 2-byte number in the code stream. Used for type numbers only, for now.
  (PROG ((BASE (fetch (ARRAYP BASE) of CA)))
    (\PUTBASEBYTE BASE BN (LOGAND 255 NUM))
    (\PUTBASEBYTE BASE (SETQ BN (SUB1 BN))
      (LOGOR (\GETBASEBYTE BASE BN)
        (LRSH NUM 8)))
    (RETURN NUM])
```

(\FIXCODEPTR

```
[LAMBDA (CA BN PTR MASK) ; Edited 12-Nov-92 17:03 by sybalsky:mv:envos
  (DECLARE (IGNORE MASK) ; MASK is used by the renamed version of this function.
  (PROG ((BASE (fetch (ARRAYP BASE) of CA))
    (LO (\LOLOC PTR)))
    (UNINTERRUPTABLY
      (\ADDRESS PTR)
      (\PUTBASEBYTE BASE BN (LOGAND LO 255))
      (\PUTBASEBYTE BASE (SUB1 BN)
        (LRSH LO 8))
      (\PUTBASEBYTE BASE (IDIFFERENCE BN 2)
        (LOGOR (\GETBASEBYTE BASE (IDIFFERENCE BN 2))
          (LOGAND (\HILOC PTR)
            255)))
      (\PUTBASEBYTE BASE (IDIFFERENCE BN 3)
        (LOGOR (\GETBASEBYTE BASE (IDIFFERENCE BN 3))
          (LRSH (\HILOC PTR)
            8))))
    (RETURN PTR])
```

(\FIXCODESYM

```
[LAMBDA (CA BN SYM MASK) ; Edited 13-Nov-92 04:56 by sybalsky:mv:envos
  (DECLARE (IGNORE MASK) ; MASK is used by the renamed version of this function.
  ;; Perform fix-up for a symbol in an IL-Compiled function -- either 2 or 4 bytes, depending on the architecture.
  ;; CA -- the code array
  ;; BN -- byte number of the low-order byte to be fixed up
  ;; SYM -- the symbol, expressed as a FIXP or a NEW-ATOM.
  (NEW-SYMBOL-CODE (PROG (HIBYTE NUM (BASE (fetch (ARRAYP BASE) of CA)))
    ;; For 3-byte-symbol machines, handle 3 bytes worth of atom number.
    [COND
      ((SMALLP SYM)
        (SETQ NUM SYM)
        (SETQ HIBYTE 0))
      ((FIXP SYM)
        (SETQ NUM (LOGAND SYM 65535))
        (SETQ HIBYTE (LRSH SYM 16)))
      (T (SETQ NUM (\LOLOC SYM))
        (SETQ HIBYTE (\HILOC SYM)]
    (UNINTERRUPTABLY
      (\PUTBASEBYTE BASE BN (LOGAND NUM 255))
      (\PUTBASEBYTE BASE (SUB1 BN)
        (LOGAND (LRSH NUM 8)
          255))
      (\PUTBASEBYTE BASE (IDIFFERENCE BN 2)
        (LOGOR (\GETBASEBYTE BASE (IDIFFERENCE BN 2))
          (LOGAND HIBYTE 255)))
      (\PUTBASEBYTE BASE (IDIFFERENCE BN 3)
        (LOGOR (\GETBASEBYTE BASE (IDIFFERENCE BN 3))
          (LRSH HIBYTE 8))))
    (RETURN (+ (LLSH HIBYTE 16)
      NUM)))
  (PROG ((NUM (\LOLOC SYM))
    (BASE (fetch (ARRAYP BASE) of CA)))
    ;; 2-BYTE case: Just fill it in.
    (\PUTBASEBYTE BASE BN (LOGAND 255 NUM))
    (\PUTBASEBYTE BASE (SETQ BN (SUB1 BN))
      (LOGOR (\GETBASEBYTE BASE BN)
        (LRSH NUM 8)))
    (RETURN NUM])
```

)

;; Internal

(DECLARE%: DONTCOPY


```

(\UsedArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT
1))
(\CodeArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT
(LLSH CODEBLOCK.GCT 1)
1))))

```

(DECLARE%: EVAL@COMPILE

(RPAQQ \ArrayBlockHeaderCells 1)

(RPAQQ \ArrayBlockHeaderWords 2)

(RPAQQ \ArrayBlockTrailerCells 1)

(RPAQQ \ArrayBlockTrailerWords 2)

(RPAQ \ArrayBlockOverheadCells (IPLUS \ArrayBlockHeaderCells \ArrayBlockTrailerCells))

(RPAQ \ArrayBlockOverheadWords (IPLUS \ArrayBlockHeaderWords \ArrayBlockTrailerWords))

(RPAQQ \ArrayBlockLinkingCells 2)

(RPAQ \MinArrayBlockSize (IPLUS \ArrayBlockOverheadCells \ArrayBlockLinkingCells))

(RPAQQ \MaxArrayBlockSize 65535)

(RPAQ \MaxArrayNCells (IDIFFERENCE \MaxArrayBlockSize \ArrayBlockOverheadCells))

(RPAQQ \MaxArrayLen 65535)

(RPAQQ \ABPASSWORDSHIFT 3)

(RPAQ \ArrayBlockPassword (LRSH 43690 \ABPASSWORDSHIFT))

(RPAQ \FreeArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT)
(LLSH UNBOXEDBLOCK.GCT 1)))

(RPAQ \UsedArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT)
1))

(RPAQ \CodeArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT)
(LLSH CODEBLOCK.GCT 1)
1))

```

(CONSTANTS \ArrayBlockHeaderCells \ArrayBlockHeaderWords \ArrayBlockTrailerCells \ArrayBlockTrailerWords
(\ArrayBlockOverheadCells (IPLUS \ArrayBlockHeaderCells \ArrayBlockTrailerCells))
(\ArrayBlockOverheadWords (IPLUS \ArrayBlockHeaderWords \ArrayBlockTrailerWords))
\ArrayBlockLinkingCells
(\MinArrayBlockSize (IPLUS \ArrayBlockOverheadCells \ArrayBlockLinkingCells))
(\MaxArrayBlockSize 65535)
(\MaxArrayNCells (IDIFFERENCE \MaxArrayBlockSize \ArrayBlockOverheadCells))
\MaxArrayLen
(\ABPASSWORDSHIFT 3)
(\ArrayBlockPassword (LRSH 43690 \ABPASSWORDSHIFT))
(\FreeArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT)
(LLSH UNBOXEDBLOCK.GCT 1)))
(\UsedArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT)
1))
(\CodeArrayFlagWord (LOGOR (LLSH \ArrayBlockPassword \ABPASSWORDSHIFT)
(LLSH CODEBLOCK.GCT 1)
1)))
)

```

```

(RPAQQ ARRAYTYPES ((\ST.BYTE 0)
(\ST.POS16 1)
(\ST.INT32 2)
(\ST.CODE 4)
(\ST.PTR 6)
(\ST.FLOAT 7)
(\ST.BIT 8)
(\ST.PTR2 11)))

```

(DECLARE%: EVAL@COMPILE

(RPAQQ \ST.BYTE 0)

(RPAQQ \ST.POS16 1)

(RPAQQ \ST.INT32 2)

(RPAQQ \ST.CODE 4)

(RPAQQ \ST.PTR 6)

(RPAQQ \ST.FLOAT 7)

(RPAQQ \ST.BIT 8)

(RPAQQ \ST.PTR2 11)

(CONSTANTS (\ST.BYTE 0)
(\ST.POS16 1)
(\ST.INT32 2)
(\ST.CODE 4)
(\ST.PTR 6)
(\ST.FLOAT 7)
(\ST.BIT 8)
(\ST.PTR2 11))
)

(DECLARE%: EVAL@COMPILE

(RPAQQ \MAX.CELLSPERHUNK 64)

(CONSTANTS \MAX.CELLSPERHUNK)
)

(DECLARE%: EVAL@COMPILE

(RPAQQ \IN.MAKEINIT NIL)

(CONSTANTS (\IN.MAKEINIT))
)

(DECLARE%: EVAL@COMPILE

(BLOCKRECORD SEQUENCEDESCRIPTOR ((ORIG BITS 1)
(NIL BITS 1)
(READONLY FLAG)
(NIL BITS 1)
(BASE POINTER)
(TYP BITS 4)
(NIL BITS 4)
(LENGTH BITS 24)
(OFFST FIXP)))

(DATATYPE ARRAYP (;; Describes an INTERLISP ARRAYP, as opposed to a CL array.

(ORIG BITS 1) ; Origin, 0 or 1
(NIL BITS 1)
(READONLY FLAG) ; probably no READONLY arrays now
(NIL BITS 1)
(BASE POINTER)
(TYP BITS 4) ; Type of the contents
(NIL BITS 4)
(LENGTH BITS 24) ; Array's length
(OFFST FIXP) ; Offset from BASE where the data really starts.

)

;; note that while ARRAYP is a DATATYPE, the allocation of it actually happens at MAKEINIT time under INITDATATYPE{NAMES}

)

[BLOCKRECORD ARRAYBLOCK ((PASSWORD BITS 13)
(GCTYPE BITS 2) ; Unboxed, Pointers, or Code
(INUSE FLAG)
(ARLEN WORD)
(FWD FULLXPOINTER) ; Only when on free list
(BKWD FULLXPOINTER))
(BLOCKRECORD ARRAYBLOCK ((ABFLAGS WORD) ; Used for header and trailer

))

[ACCESSFNS ARRAYBLOCK ((DAT (\ADDBASE DATUM \ArrayBlockHeaderWords)
(TRAILER (\ADDBASE2 DATUM (IDIFFERENCE (fetch (ARRAYBLOCK ARLEN) of DATUM)
\ArrayBlockTrailerCells]

(TYPE? (AND (EQ 0 (NTYPX DATUM))
(IGEQ (\HILOC DATUM)
\FirstArraySegment]

)

(/DECLAREDATATYPE 'ARRAYP ' ((BITS 1)
(BITS 1)
FLAG
(BITS 1)
POINTER
(BITS 4)
(BITS 4)
(BITS 24)
FIXP)

;; ---field descriptor list elided by lister---

' 6)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

```
(GLOBALVARS \NxtArrayPage \FREEBLOCKBUCKETS \HUNKING?)
)
```

:: END EXPORTED DEFINITIONS

```
(DECLARE%: DOEVAL@COMPILE DONTCOPY
```

```
(GLOBALVARS \ArrayFrLst \ArrayFrLst2 \RECLAIM.COUNTDOWN)
)
)
```

```
(DEFINEQ
```

(\ALLOCBLOCK

```
[LAMBDA (NCELLS GCTYPE INITONPAGE ALIGN) (* bvm%: "7-Feb-85 15:30")
```

:: NCELLS is number of cells wanted not counting overhead cell. For code arrays, INITONPAGE is number of cells to be kept on a single page. It
:: might be necessary to flag a block with an aligned indicator, to help a compacting garbage collector preserve the align proptry. --- Does not
:: assume that caller is uninterruptable --- Returns NIL if NCELLS = 0 --- GCTYPE is one of the constants PTRBLOCK.GCT, CODEBLOCK.GCT,
:: UNBOXEDBLOCK.GCT, indicating any special behavior to be performed when the block is reclaimed. NIL defaults to UNBOXEDBLOCK.GCT

```
(DECLARE (GLOBALVARS \ArrayFrLst))
```

```
(COND
```

```
((ILESSP NCELLS \ArrayBlockLinkingCells)
```

```
(COND
```

```
((ILESSP NCELLS 0)
```

```
(\ILLEGAL.ARG NCELLS)))
```

```
(SETQ NCELLS \ArrayBlockLinkingCells))
```

```
((IGREATERP NCELLS \MaxArrayNCells)
```

```
(\LISPERROR NCELLS "ARRAY STORAGE BLOCK TOO LARGE")))
```

; NCELLS is number of data cells; remember for allocation
; counter below

```
(SELECTQ GCTYPE
```

```
(NIL (SETQ GCTYPE UNBOXEDBLOCK.GCT))
```

```
(T (SETQ GCTYPE PTRBLOCK.GCT))
```

```
NIL)
```

; This SELECTQ can be removed when all callers are upgraded
; to constants

```
(COND
```

```
((AND INITONPAGE (OR (ILESSP INITONPAGE 0)
```

```
(IGREATERP INITONPAGE CELLSPERPAGE)))
```

```
(\ILLEGAL.ARG INITONPAGE)))
```

```
(COND
```

```
((NULL ALIGN))
```

```
((OR (ILESSP ALIGN 0)
```

```
(IGREATERP ALIGN CELLSPERPAGE)))
```

```
(\ILLEGAL.ARG ALIGN))
```

```
((ILEQ ALIGN 1)
```

```
(SETQ ALIGN))
```

```
((AND INITONPAGE (PROGN
```

; Some check for consistency between ALIGN and INITONPAGE
; is needed here

```
NIL))
```

```
(ERROR "INITONPAGE and ALIGN too high")))
```

```
(OR (AND \HUNKING? (ILEQ NCELLS \MAX.CELLSPERHUNK)
```

```
(\ALLOCHUNK NCELLS GCTYPE INITONPAGE ALIGN))
```

```
(PROG ((ARLEN (IPLUS NCELLS \ArrayBlockOverheadCells))
```

```
ABLOCK)
```

```
RETRY
```

```
(UNINTERRUPTABLY
```

```
(SETQ ABLOCK (OR (\ALLOCBLOCK.OLD ARLEN GCTYPE INITONPAGE ALIGN)
```

```
(\ALLOCBLOCK.NEW ARLEN GCTYPE INITONPAGE ALIGN)
```

```
(PROGN (FRPTQ 10 (RECLAIM))
```

; We're probably out of array space; our last chance is to collect and hope something shows
; up on the free list.

```
(\ALLOCBLOCK.OLD ARLEN GCTYPE INITONPAGE ALIGN))
```

```
(GO FULL)))
```

; ABLOCK now points to the beginning of the actual block of
; storage to be used

```
(replace (ARRAYBLOCK INUSE) of ABLOCK with T)
```

```
(replace (ARRAYBLOCK INUSE) of (fetch (ARRAYBLOCK TRAILER) of ABLOCK) with T)
```

```
(replace (ARRAYBLOCK GCTYPE) of ABLOCK with GCTYPE)
```

```
(CHECKARRAYBLOCK ABLOCK NIL)
```

```
(.INCREMENT.ALLOCATION.COUNT. NCELLS) ; NCELLS because CREATEREF accounts for overhead cell
```

```
(SETQ ABLOCK (\ADDBASE ABLOCK \ArrayBlockHeaderWords))
```

```
(\CREATEREF ABLOCK)
```

```
(RETURN ABLOCK))
```

```
FULL
```

```
(LISPERROR "ARRAYS FULL" NIL T)
```

; User might release something, so retry.

```
(GO RETRY))
```

(\MAIKO.ALLOCBLOCK

```
[LAMBDA (NCELLS GCTYPE INITONPAGE ALIGN) ; Edited 29-Jun-90 12:17 by ON
```

:: Maiko specific \ALLOCBLOCK. Does not decrement \RECLAIM.COUNTDOWN.

:: NCELLS is number of cells wanted not counting overhead cell. For code arrays, INITONPAGE is number of cells to be kept on a single page. It
:: might be necessary to flag a block with an aligned indicator, to help a compacting garbage collector preserve the align proptry. --- Does not
:: assume that caller is uninterruptable --- Returns NIL if NCELLS = 0 --- GCTYPE is one of the constants PTRBLOCK.GCT, CODEBLOCK.GCT,
:: UNBOXEDBLOCK.GCT, indicating any special behavior to be performed when the block is reclaimed. NIL defaults to UNBOXEDBLOCK.GCT

```
(DECLARE (GLOBALVARS \ArrayFrLst))
(COND
  ((ILESSP NCELLS \ArrayBlockLinkingCells)
    (COND
      ((ILESSP NCELLS 0)
        (\ILLEGAL.ARG NCELLS)))
      (SETQ NCELLS \ArrayBlockLinkingCells))
    ((IGREATERP NCELLS \MaxArrayNCells)
      (\LISPERROR NCELLS "ARRAY STORAGE BLOCK TOO LARGE"))) ; NCELLS is number of data cells; remember for allocation
                                                                ; counter below

(SELECTQ GCTYPE
  (NIL (SETQ GCTYPE UNBOXEDBLOCK.GCT))
  (T (SETQ GCTYPE PTRBLOCK.GCT))
  NIL) ; This SELECTQ can be removed when all callers are upgraded
                                                                ; to constants

;; Maiko doesn't have to worry about INITONPAGE. ----- '90/06/29 on.
;; (COND ((AND INITONPAGE (OR (ILESSP INITONPAGE 0) (IGREATERP INITONPAGE CELLSPERPAGE))) (\ILLEGAL.ARG INITONPAGE)))
(COND
  ((NULL ALIGN))
  ((OR (ILESSP ALIGN 0)
      (IGREATERP ALIGN CELLSPERPAGE))
    (\ILLEGAL.ARG ALIGN))
  ((ILEQ ALIGN 1)
    (SETQ ALIGN))
  ((AND INITONPAGE (PROGN
                                                                ; Some check for consistency between ALIGN and INITONPAGE
                                                                ; is needed here
                                                                NIL))
    (ERROR "INITONPAGE and ALIGN too high")))
  (OR (AND \HUNKING? (ILEQ NCELLS \MAX.CELLSPERHUNK)
                                                                ; Maiko doesn't have to worry about INITONPAGE so call
                                                                ; \ALLOCHUNK with arg INITONPAGE as NIL.
      (\ALLOCHUNK NCELLS GCTYPE NIL ALIGN))
    (PROG ((ARLEN (IPLUS NCELLS \ArrayBlockOverheadCells))
      ABLOCK)
      RETRY
        (UNINTERRUPTABLY
          (SETQ ABLOCK (OR (\ALLOCBLOCK.OLD ARLEN GCTYPE NIL ALIGN)
                          (\ALLOCBLOCK.NEW ARLEN GCTYPE NIL ALIGN)
                          (PROGN (FRPTQ 10 (RECLAIM))
                                ;; We're probably out of array space; our last chance is to collect and hope something shows
                                ;; up on the free list.
                                (\ALLOCBLOCK.OLD ARLEN GCTYPE INITONPAGE ALIGN))
                            (GO FULL))))
                                                                ; ABLOCK now points to the beginning of the actual block of
                                                                ; storage to be used
          (replace (ARRAYBLOCK INUSE) of ABLOCK with T)
          (replace (ARRAYBLOCK INUSE) of (fetch (ARRAYBLOCK TRAILER) of ABLOCK) with T)
          (replace (ARRAYBLOCK GCTYPE) of ABLOCK with GCTYPE)
          (\CHECKARRAYBLOCK ABLOCK NIL)
          (.CHECK.ALLOCATION.COUNT. NCELLS)
          (SETQ ABLOCK (\ADDBASE PTR (\ADDBASE2 \FREEBLOCKBUCKETS BKT))
            (\DELREF ABLOCK)
            (.CHECK.ALLOCATION.COUNT. 1))
          (RETURN ABLOCK))
      FULL
        (LISPERROR "ARRAYS FULL" NIL T) ; User might release something, so retry.
        (GO RETRY]))
```

(\ALLOCBLOCK.OLD

```
[LAMBDA (ARLEN GCTYPE INITONPAGE ALIGN) (* bvm%: "15-Feb-85 11:01")
```

;; Returns a block of the right size and alignment, or NIL if one couldn't be found.

```
(for BKT from (BUCKETINDEX ARLEN) to \MAXBUCKETINDEX bind ABLOCK
  when (AND (SETQ ABLOCK (\GETBASEPTR (\ADDBASE2 \FREEBLOCKBUCKETS BKT)
    0))
    (bind (1STBLOCK.IN.FREECHAIN _ ABLOCK)
      USABLELEN REMAINDERLEN PREFIXLEN repeatuntil (EQ (SETQ ABLOCK (fetch (ARRAYBLOCK FWD)
        of ABLOCK))
        1STBLOCK.IN.FREECHAIN)
        when (PROGN [COND
          ((OR (NEQ (fetch (ARRAYBLOCK PASSWORD) of ABLOCK)
            \ArrayBlockPassword)
            (NEQ (fetch (ARRAYBLOCK PASSWORD) of (fetch (ARRAYBLOCK TRAILER)
              of ABLOCK))
            \ArrayBlockPassword))
          (RETURN (\MP.ERROR \MP.BADARRAYBLOCK "Bad Array Block" ABLOCK])
          (SETQ PREFIXLEN (COND
            ((OR ALIGN INITONPAGE)
              (\PREFIXALIGNMENT? ARLEN INITONPAGE ALIGN GCTYPE ABLOCK))
            (T 0)))
          (IGEQ (SETQ USABLELEN (IDIFFERENCE (fetch (ARRAYBLOCK ARLEN) of ABLOCK)
            PREFIXLEN))
            ARLEN))
        do (\CHECKARRAYBLOCK ABLOCK T T)
          (\DELETEBLOCK? ABLOCK) ; take it off the free list
```

```

[COND
  ((NEQ PREFIXLEN 0)
   ; We must split off a bit initially, in order to preserve the
   ; INITONPAGE request
   (\MERGEBACKWARD (\MAKEFREEARRAYBLOCK ABLOCK PREFIXLEN))
   (SETQ ABLOCK (\ADDBASE2 ABLOCK PREFIXLEN])
  (SETQ REMAINDERLEN (IDIFFERENCE USABLELEN ARLEN))
  (COND
    [(IGREATERP REMAINDERLEN (COND
      (\HUNKING? (IPLUS \MAX.CELLSPERHUNK
        \ArrayBlockOverheadCells))
      (T 0)))
     ; Split off any extra space from the end of the block.
     (\MERGEFORWARD (\LINKBLOCK (\MAKEFREEARRAYBLOCK (\ADDBASE2 ABLOCK ARLEN)
      REMAINDERLEN]
     ; Coerce the length upwards so as not to have a runt block
     (SETQ ARLEN USABLELEN)))
    (COND
      ((OR (NEQ PREFIXLEN 0)
        (NEQ USABLELEN ARLEN))
       ; If we changed the length of the block, store the new length now
       (\MAKEFREEARRAYBLOCK ABLOCK ARLEN)))
      (\CHECKARRAYBLOCK ABLOCK T)
      (\CLEARCELLS (\ADDBASE ABLOCK \ArrayBlockHeaderWords)
        (IDIFFERENCE ARLEN \ArrayBlockOverheadCells))
        ; clear out old garbage
        ; signal that we found one
        (RETURN T)))
  (RETURN ABLOCK)]
do (RETURN ABLOCK)]

```

(\ALLOCBLOCK.NEW

; Edited 25-Apr-94 15:09 by jds

```

[LAMBDA (ARLEN GCTYPE INITONPAGE ALIGN)
  (DECLARE (GLOBALVARS \ArrayFrLst \NxtArrayPage))
  ;; Patch up a new section of memory beginning at the end of current arrayspace, and make it a freeblock for subsequent usage. Also used to
  ;; increment to the next page/segment boundary when allocating code arrays
  (PROG (FINALWORD FINALPAGE NEXTFREEBLOCK PREFIXLEN)
    RETRY
    [COND
      ([AND (OR INITONPAGE ALIGN)
        (NEQ 0 (SETQ PREFIXLEN (\PREFIXALIGNMENT? ARLEN INITONPAGE ALIGN GCTYPE \ArrayFrLst]
        ; Gobble up a modest amount of space in order to insure correct
        ; alignment.
      (COND
        ((SETQ PREFIXLEN (\ALLOCBLOCK.NEW PREFIXLEN))
          (\MERGEBACKWARD PREFIXLEN))
          ; Problem: what happens if array space switch happened inside
          ; this \ALLOCBLOCK.NEW ?
        )
        (T (RETURN)
          (SETQ FINALWORD (\ADDBASE (\ADDBASE \ArrayFrLst ARLEN)
            (SUB1 ARLEN)))
          ;; FINALWORD is pointer to the last word of the new block. The new \ArrayFrLst will be one past that, i.e., at (\ADDBASE2 \ArrayFrLst ARLEN) --
          ;; The double \ADDBASE avoids large integer arithmetic and computing FINALWORD first avoids negative arguments to \ADDBASE
          (SETQ NEXTFREEBLOCK (\ADDBASE FINALWORD 1))
          [COND
            ((IGREATERP (SETQ FINALPAGE (fetch (POINTER PAGE#) of FINALWORD))
              (IDIFFERENCE \NxtMDSPage \GUARDSTORAGEFULL))
             ; Make sure that there are enough pages to satisfy this request
             ; before we make any global changes.
            (SELECTQ (\CHECKFORSTORAGEFULL (ADD1 (IDIFFERENCE FINALPAGE \NxtArrayPage)))
              (T
                )
              (0
                )
              (GO RETRY))
            (RETURN NIL]
            ; Is ok, go ahead
            ; Is ok, but \NxtArrayPage moved.

```

;; \NxtArrayPage is the page after the page of FINALWORD, the next one that needs to be \NEWPAGEd. \ArrayFrLst's page will be (SUB1 \NxtArrayPage) except when it is allowed to be EQ to the first word on \NxtArrayPage

```

[until (IGREATERP \NxtArrayPage FINALPAGE) do (\MAKEMDSENTRY \NxtArrayPage 0)
  (\NEW2PAGE (create POINTER
    PAGE# _ \NxtArrayPage))
  (UNLESSINEW (\PUTBASEFIXP \NxtArrayPage 0
    (IPLUS \NxtArrayPage 2))
    (SETQ \NxtArrayPage (IPLUS \NxtArrayPage 2]
  (RETURN (PROG1 (\MAKEFREEARRAYBLOCK \ArrayFrLst ARLEN)
    (SETQ.NOREF \ArrayFrLst NEXTFREEBLOCK]))

```

(\PREFIXALIGNMENT?

(* Pavel "16-Oct-86 14:15")

```

[LAMBDA (ARLEN INITONPAGE ALIGN GCTYPE BASE)
  ;; how many cells must be added to to the base address of BASE to get a block whose first data word is aligned according to ALIGN and which has
  ;; its first INITONPAGE cells all on one page
  (PROG ((DAT (fetch (POINTER CELLINSEGMENT) of (\ADDBASE BASE \ArrayBlockHeaderWords))
    (ADJUSTMENT 0)
    FUDGE)
  ;; DAT will hold the cell-in-segment offset of the first dataword of the arrayblock; it is this first dataword which must be aligned etc rather than the

```

;; true beginning of the block.

```

LP (COND
  ((AND ALIGN (NEQ (SETQ FUDGE (IREMAINDER DAT ALIGN))
    0)) ; Not aligned, so adjust first for that.
    (add ADJUSTMENT (SETQ FUDGE (IDIFFERENCE ALIGN FUDGE)))
    (add DAT FUDGE)))
  (COND
    ((AND INITONPAGE (NEQ (FLOOR DAT CELLSPERPAGE)
      (FLOOR (IPLUS DAT INITONPAGE -1)
        CELLSPERPAGE))) ; There aren't INITONPAGE cells on the page, so go to next
      ; page boundary
      [add ADJUSTMENT (SETQ FUDGE (IDIFFERENCE CELLSPERPAGE (IMOD DAT CELLSPERPAGE))]
      (add DAT FUDGE)
      ;; No need to realign at this point. ALIGN must be a power of two, so it's either an alignment less than CELLSPERPAGE, in which
      ;; case this page boundary satisfies it, or it's a multiple of CELLSPERPAGE, in which case the first COND satisfied it and we didn't
      ;; have to touch it in this COND
    ))
  ))
(COND
  ([AND (EQ GCTYPE CODEBLOCK.GCT)
    (IGREATERP (IDIFFERENCE ARLEN \ArrayBlockOverheadCells)
      (SETQ FUDGE (IDIFFERENCE CELLSPERSEGMENT (SETQ DAT (IMOD DAT CELLSPERSEGMENT)
        ;; Code arrays cannot cross segment boundaries. Note that ARLEN includes the overhead cells, hence the extra subtraction.
      (add ADJUSTMENT FUDGE)
      (add DAT FUDGE)
      ;; No need to re-check the alignment since ALIGN and INITONPAGE are both guaranteed satisfied by a block starting on a segment
      ;; boundary
    ))
  ))
  ;; The following code claims to prevent splitting off too small a block, but it's not clear this is intrinsically bad, and the code does not appear to do
  ;; anything rational. -- bvm --- (COND ((AND (NEQ ADJUSTMENT 0) \HUNKING? (IGREATERP (SETQ FUDGE (IDIFFERENCE (IPLUS
  ;; \MAX.CELLSPERHUNK \ArrayBlockOverheadCells) ADJUSTMENT)) 0) (PROGN (** Account for potential merging backwards when this initial
  ;; piece is split off.) (AND (EQ (fetch (ARRAYBLOCK PASSWORD) of (SETQ PREVTRAILER (ADDBASE BASE (MINUS
  ;; \ArrayBlockTrailerCells)))) \ArrayBlockPassword) (NOT (fetch (ARRAYBLOCK INUSE) of PREVTRAILER))) (ILESSP (fetch (ARRAYBLOCK
  ;; ARLEN) of PREVTRAILER) FUDGE))) (* Just to ensure that we don't break up a large arrayblocks into two pieces one of which is too small to
  ;; be usable.) (add ADJUSTMENT FUDGE) (SETQ DAT (IPLUS DAT FUDGE)) (* Go around again, since this function wouldn't have been called
  ;; unless one of INITONPAGE or ALIGN were non-null.) (GO LP)))
  (RETURN ADJUSTMENT])

```

(MAKEFREEARRAYBLOCK

```

[LAMBDA (BLOCK LENGTH) ; (* Imm "25-Jul-84 13:07")
  (replace (ARRAYBLOCK ABFLAGS) of BLOCK with \FreeArrayFlagWord)
  (replace (ARRAYBLOCK ARLEN) of BLOCK with LENGTH)
  (replace (ARRAYBLOCK ABFLAGS) of (fetch (ARRAYBLOCK TRAILER) of BLOCK) with \FreeArrayFlagWord)
  (replace (ARRAYBLOCK ARLEN) of (fetch (ARRAYBLOCK TRAILER) of BLOCK) with LENGTH)
  BLOCK])

```

(DELETEBLOCK?

```

[LAMBDA (BASE) ; (* bvm%: "15-Feb-85 11:04")
  (COND
    ((AND (IGEQ (fetch (ARRAYBLOCK ARLEN) of BASE)
      \MinArrayBlockSize)
      (fetch (ARRAYBLOCK FWD) of BASE)) ; Allegedly, BASE has been 'checked' before coming here.
    (PROG [(F (fetch (ARRAYBLOCK FWD) of BASE))
      (B (fetch (ARRAYBLOCK BKWD) of BASE))
      (FBL (FREEBLOCKCHAIN.N (fetch ARLEN of BASE))]
      (COND
        ((EQ BASE F)
          (COND
            ((EQ BASE (\GETBASEPTR FBL 0))
              (\PUTBASEPTR FBL 0 NIL))
            (T (\MP.ERROR \MP.BADDELETEBLOCK "deleting last block # FREEBLOCKLIST")))
          (RETURN))
        ((EQ BASE (\GETBASEPTR FBL 0))
          (\PUTBASEPTR FBL 0 F))
        (replace (ARRAYBLOCK BKWD) of F with B)
        (replace (ARRAYBLOCK FWD) of B with F])

```

(LINKBLOCK

```

[LAMBDA (BASE) ; (* JonL "16-Jan-85 02:46")
  ;; Add BASE to the free list. Assumes that BASE is a well-formed free block.
  (COND
    (\FREEBLOCKBUCKETS (COND
      ((ILESSP (fetch (ARRAYBLOCK ARLEN) of BASE)
        \MinArrayBlockSize)
        (\CHECKARRAYBLOCK BASE T))
      (T (PROG ((FBL (FREEBLOCKCHAIN.N (fetch ARLEN of BASE)))
        FREEBLOCK)
          (SETQ FREEBLOCK (\GETBASEPTR FBL 0))
          (COND

```

```

      ( (NULL FREEBLOCK)
        (replace (ARRAYBLOCK FWD) of BASE with BASE)
        (replace (ARRAYBLOCK BKWD) of BASE with BASE))
      (T (replace (ARRAYBLOCK FWD) of BASE with FREEBLOCK)
        (replace (ARRAYBLOCK BKWD) of BASE with (fetch (ARRAYBLOCK BKWD)
          of FREEBLOCK))
        (replace (ARRAYBLOCK FWD) of (fetch (ARRAYBLOCK BKWD) of FREEBLOCK)
          with BASE)
        (replace (ARRAYBLOCK BKWD) of FREEBLOCK with BASE)))
      (\PUTBASEPTR FBL 0 BASE)
      (\CHECKARRAYBLOCK BASE T T]

```

BASE])

(MERGEBACKWARD

[LAMBDA (BASE) (* bvm%: "6-Feb-85 16:53")

:: Caller is uninterruptable and asserts that a non-NIL BASE is a free but unlinked arrayblock. We return a linked (if possible) block, either BASE
:: itself or an enlarged previous free block that is linked (if possible) and includes the BASE storage.

```

(PROG (ARLEN PARLEN PBASE PTRAILER SPLIT)
  [COND
    ( (NULL BASE)
      (RETURN NIL))
    ( [OR (NOT \ARRAYMERGING)
      (EQ BASE \ARRAYSPACE)
      (EQ BASE \ARRAYSPACE2)
      (fetch (ARRAYBLOCK INUSE) of (SETQ PTRAILER (\ADDBASE BASE (IMINUS \ArrayBlockTrailerWords]
        :: If this is the absolute 'first' block of array space, then there is nothing behind it to merge; similarly, if the block behind it is in use,
        :: then don't merge.
      (RETURN (\LINKBLOCK BASE]
    [SETQ PBASE (\ADDBASE2 BASE (IMINUS (fetch (ARRAYBLOCK ARLEN) of PTRAILER]
    (\CHECKARRAYBLOCK PBASE T)
    (\DELETEBLOCK? PBASE)
    (RETURN (\ARRAYBLOCKMERGER PBASE BASE])

```

(MERGEFORWARD

[LAMBDA (BASE) (* bvm%: "15-Feb-85 11:18")

:: BASE is a free and linked (if possible) block. Merge with the next block if it is free and not too big. Caller must be uninterruptable.

```

(PROG (NBASE NBINUSE)
  (COND
    ((OR (NOT \ARRAYMERGING)
      (NULL BASE)
      (\CHECKARRAYBLOCK BASE T T)
      (EQ (SETQ NBASE (\ADDBASE2 BASE (fetch (ARRAYBLOCK ARLEN) of BASE)))
        \ArrayFrLst)
      (EQ NBASE \ArrayFrLst2)
      (\CHECKARRAYBLOCK NBASE (NOT (SETQ NBINUSE (fetch (ARRAYBLOCK INUSE) of NBASE]
      NBINUSE)
      (RETURN NIL))) ; Note that if we ever get to here, both blocks have been
                      ; 'checked'
    (\DELETEBLOCK? NBASE)
    (\DELETEBLOCK? BASE)
    (\ARRAYBLOCKMERGER BASE NBASE])

```

(ARRAYBLOCKMERGER

[LAMBDA (BASE NBASE) (* bvm%: "13-Feb-85 14:57")

:: BASE and NBASE are two consecutive unlinked freeblocks. (Called only after the two blocks have been 'checked')

```

(PROG ((ARLEN (fetch (ARRAYBLOCK ARLEN) of BASE))
  (NARLEN (fetch (ARRAYBLOCK ARLEN) of NBASE))
  SECONDBITE MINBLOCKSIZE SHAVEBACK)
  (SETQ SECONDBITE (IDIFFERENCE \MaxArrayBlockSize ARLEN))
  (COND
    ((IGREATERP NARLEN SECONDBITE)
      :: check if sum of NARLEN+ARLEN is leq maximum. (Written this way to stay within small number range.) If not, then break up into
      :: two freeblocks since one can't hold all the cells.
      (SETQ ARLEN \MaxArrayBlockSize)
      (SETQ NARLEN (IDIFFERENCE NARLEN SECONDBITE))
      :: Normal overflow case is just to make the first block as big as possible, then leave the rest in the second block. So the code above
      :: adds to ARLEN and subtracts from NARLEN an equal amount to achieve the desired split. However, check that the remaining
      :: NBASE block is not too small
      (COND
        ((ILESSP NARLEN (SETQ MINBLOCKSIZE (COND
          (\HUNKING? (IPLUS \ArrayBlockOverheadCells
            \MAX.CELLSPERHUNK))
          (T \MinArrayBlockSize]
          :: Decrease ARLEN and SECONDBITE by the amount it will take to get NARLEN up to MINBLOCKSIZE -- SHAVEBACK is
          :: negative
          (SETQ SHAVEBACK (IDIFFERENCE NARLEN (SETQ NARLEN MINBLOCKSIZE)))

```

```

      (add ARLEN SHAVEBACK)
      (add SECONDBITE SHAVEBACK))
;; Okay, make a tail of the second block into a free block of its own
      (\LINKBLOCK (\MAKEFREEARRAYBLOCK (\ADDBASE2 NBASE SECONDBITE)
      NARLEN))
      (SETQ NARLEN 0)))
      (RETURN (\LINKBLOCK (\MAKEFREEARRAYBLOCK BASE (IPLUS ARLEN NARLEN]))

```

(#BLOCKDATACELLS

```

[LAMBDA (DATAWORD)
      (* JonL "20-Sep-84 19:07")
      ;; DATAWORD is a pointer as would be returned by \ALLOCBLOCK Returns the number of cells available to the caller. Compiled closed so that
      ;; we can change internal representations without clients needing to be recompiled.
      (PROG ((TYPENO (NTYPX DATAWORD)))
      (RETURN (COND
      [(EQ 0 TYPENO)
      (COND
      ((type? ARRAYBLOCK DATAWORD)
      (IDIFFERENCE (fetch (ARRAYBLOCK ARLEN) of (\ADDBASE DATAWORD (IMINUS
      \ArrayBlockHeaderWords
      \ArrayBlockOverheadCells))
      (T (\ILLEGAL.ARG DATAWORD]
      (T (OR (AND (OR \HUNKING? (fetch DTDHUNKP of (\GETDTD TYPENO)))
      (HUNKSIZEFROMNUMBER TYPENO))
      (\ILLEGAL.ARG DATAWORD]))

```

(COPYARRAYBLOCK

```

[LAMBDA (OLD)
      ; Edited 3-Mar-87 22:28 by bvm:
      (LET [(HEADER (\ADDBASE OLD (IMINUS \ArrayBlockHeaderWords]
      (COND
      [(AND (IEQ \ArrayBlockPassword (fetch PASSWORD of HEADER))
      (fetch (ARRAYBLOCK INUSE) of HEADER))
      (LET* ((LEN (- (fetch (ARRAYBLOCK ARLEN) of HEADER)
      \ArrayBlockOverheadCells))
      (TYP (fetch (ARRAYBLOCK GCTYPE) of HEADER))
      (NEW (\ALLOCBLOCK LEN TYP)))
      (PROG1 NEW
      (SELECTC TYP
      (PTRBLOCK.GCT
      ; Have to reference count the pointers as we copy
      (FRPTQ LEN (\RPLPTR NEW 0 (COPYALL (\GETBASEPTR OLD 0)))
      (SETQ NEW (\ADDBASE NEW WORDSPERCELL))
      (SETQ OLD (\ADDBASE OLD WORDSPERCELL))))
      (CODEBLOCK.GCT
      ; should increment references from code
      (\COPYCODEBLOCK NEW OLD (UNFOLD LEN WORDSPERCELL)))
      (\BLT NEW OLD (UNFOLD LEN WORDSPERCELL))))])
      (T
      OLD))
      ; Not an array block

```

(RECLAIMARRAYBLOCK

```

[LAMBDA (P)
      ; Edited 8-Jan-88 18:31 by jop
      ;; Called to reclaim objects of type 0. This is called with interrupts turned off. Returns T to tell GC that we reclaimed it.
      (PROG ((B (\ADDBASE P (IMINUS \ArrayBlockHeaderWords))
      (RECLAIM-P T))
      ;; B points to arrayblock header, P to first and subsequent data words
      (IF (OR (< (\HILOC P)
      \FirstArraySegment)
      (NOT (IEQ \ArrayBlockPassword (fetch PASSWORD of B)))
      (NOT (fetch (ARRAYBLOCK INUSE) of B)))
      THEN
      ;; RAID instead of \GCERROR because this error is continuable with ^N.
      (\MP.ERROR \MP.BADARRAYRECLAIM "Bad array block reclaimed--continue with ^N but save state
      ASAP")
      (RETURN T))
      (SELECTC (fetch (ARRAYBLOCK GCTYPE) of B)
      (PTRBLOCK.GCT
      ; Release all pointers
      (for old P (TRAILER _ (fetch (ARRAYBLOCK TRAILER) of B)) by (\ADDBASE P WORDSPERCELL)
      until (EQ P TRAILER) do (\RPLPTR P 0 NIL)))
      (CODEBLOCK.GCT
      ; Release literals
      ;; Since \reclaimcodeblock is a finalization function -- returns nil if do reclaim and t if don't reclaim
      (SETQ RECLAIM-P (NOT (\RECLAIMCODEBLOCK P))))
      NIL)
      [IF RECLAIM-P
      THEN (\MERGEFORWARD (\MERGEBACKWARD (\MAKEFREEARRAYBLOCK B (fetch ARLEN of B)
      ;; Always tell GC that we have reclaimed it
      (RETURN T])

```

(ADVANCE.ARRAY.SEGMENTS

[LAMBDA (NXTPAGE)

; Edited 4-Jan-93 02:08 by jds

:: Called when the first 8mb are exhausted, and we want to switch array space into the next area, starting with page NXTPAGE -- have to first clean up
:: what's left in the old area

```

(PROG (NCELLSLEFT)
  (SETQ.NOREF \ArrayFrLst2 (COND
    ((IGEQ [SETQ NCELLSLEFT (IPLUS (UNFOLD (SUB1 (IDIFFERENCE
      \NxtArrayPage
      (fetch (POINTER PAGE#)
        of \ArrayFrLst)))
      CELLSPERPAGE)
      (IDIFFERENCE CELLSPERPAGE
        (fetch (POINTER CELLINPAGE)
          of \ArrayFrLst]
        \MinArrayBlockSize) ; Make the rest of the already allocated array space into a small
        ; block
      (MERGEBACKWARD (MAKEFREEARRAYBLOCK \ArrayFrLst NCELLSLEFT))
      (create POINTER
        PAGE# _ \LeastMDSPage))
      (T \ArrayFrLst)))
    [SETQ.NOREF \ARRAYSPACE2 (SETQ.NOREF \ArrayFrLst (create POINTER
      PAGE# _ (\PUTBASEFIXP \NxtArrayPage 0 NXTPAGE])
      ; Return code to tell \ALLOCBLOCK.NEW to notice the new
      ; arrangement

  (RETURN 0])
)

```

(ADDTOVAR \MAIKO.MOVDS (\MAIKO.ALLOCBLOCK \ALLOCBLOCK))

(DEFINEQ

(\BYTELT

[LAMBDA (A J) (* JonL "20-Sep-84 20:01")

:: A special function for system accesses to 0-origin byte arrays, of which syntax-tables are the primary example. This compiles open into a
:: GETBASEBYTE, with no checking for argument validity!

```

(OR [AND [EQ 0 (fetch (ARRAYP ORIG) of (SETQ A (\DTEST A 'ARRAYP]
  (OR (EQ \ST.BYTE (fetch (ARRAYP TYP) of A))
    (EQ \ST.CODE (fetch (ARRAYP TYP) of A]
  (LISPERROR "ILLEGAL ARG" A))
(OR (IGREATERP (fetch (ARRAYP LENGTH) of A)
  J)
  (LISPERROR "ILLEGAL ARG" J))
(\GETBASEBYTE (fetch (ARRAYP BASE) of A)
  (IPLUS (fetch (ARRAYP OFFST) of A)
  J])
)

```

(\BYTESETA

[LAMBDA (A J V) (* JonL "20-Sep-84 20:01")

:: A special function for system setting of 0-origin byte arrays, of which syntax-tables are the primary example. This compiles open into a
:: GETBASEBYTE, with no checking for argument validity! --- NOTE: The value is undefined, not V!

```

(OR [AND [EQ 0 (fetch (ARRAYP ORIG) of (SETQ A (\DTEST A 'ARRAYP]
  (OR (EQ \ST.BYTE (fetch (ARRAYP TYP) of A))
    (EQ \ST.CODE (fetch (ARRAYP TYP) of A]
  (LISPERROR "ILLEGAL ARG" A))
(OR (IGREATERP (fetch (ARRAYP LENGTH) of A)
  J)
  (LISPERROR "ILLEGAL ARG" J))
(AND (fetch (ARRAYP READONLY) of A)
  (LISPERROR "ILLEGAL ARG" A))
(\PUTBASEBYTE (fetch (ARRAYP BASE) of A)
  (IPLUS (fetch (ARRAYP OFFST) of A)
  J)
  V])
)

```

(\WORDELT

[LAMBDA (A J) (* JonL "20-Sep-84 20:02")

:: A special function for system accesses to 0-origin word arrays, This compiles open into a GETBASE, with no checking for argument validity!

```

(OR (AND [EQ 0 (fetch (ARRAYP ORIG) of (SETQ A (\DTEST A 'ARRAYP]
  (EQ \ST.POS16 (fetch (ARRAYP TYP) of A)))
  (LISPERROR "ILLEGAL ARG" A))
(OR (IGREATERP (fetch (ARRAYP LENGTH) of A)
  J)
  (LISPERROR "ILLEGAL ARG" J))
(\GETBASE (fetch (ARRAYP BASE) of A)
  (IPLUS (fetch (ARRAYP OFFST) of A)
  J])
)

```

(DEFINEQ

(\ARRAYTYPENAME

(* rmk%: "21-Dec-83 14:55")

```
[LAMBDA (X)
  ;; This is called from the VM function TYPENAME to determine the 'logical' type of the array X
  (SELECTC (fetch (ARRAYP TYP) of X)
    (\ST.CODE 'CCODEP)
    'ARRAYP])
)
```

(RPAQO \ARRAYMERGING T)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS \ARRAYMERGING)

;; for STORAGE

(DEFINEQ

(\SHOW.ARRAY.FREELISTS

(* bvm%: "12-Feb-85 15:25")

```
[LAMBDA (SIZESLST)
  (COND
    ((OR SIZESLST (SETQ SIZESLST STORAGE.ARRAYSIZES))
      (RESETFORM (RECLAIMMIN MAX.SMALLP)
        (PROG ((TABLE \ABSTORAGETABLE)
          (N (LENGTH SIZESLST))
          (TOTAL 0)
          FBL ABLOCK ARLEN)
        [COND
          ((OR (NOT (\BLOCKDATAP TABLE))
            (IGEQ N (FOLDLO (\#BLOCKDATACELLS TABLE)
              2)))
            ;; Need bigger table if someone has enlarged SIZESLST since last time. There are 2 cells per table entry
            (SETQ \ABSTORAGETABLE (SETQ TABLE (\ALLOCBLOCK (UNFOLD (IPLUS N 4)
              2)
              UNBOXEDBLOCK.GCT])
            (\CLEARCELLS TABLE (\#BLOCKDATACELLS TABLE))
            [for BKTI from 0 to \MAXBUCKETINDEX
              do (COND
                ((SETQ FBL (\GETBASEPTR (\ADDBASE2 \FREEBLOCKBUCKETS BKTI)
                  0))
                  (SETQ ABLOCK FBL)
                  (repeatuntil (EQ FBL (SETQ ABLOCK (fetch (ARRAYBLOCK FWD) of ABLOCK)))
                    do (add TOTAL (SETQ ARLEN (fetch (ARRAYBLOCK ARLEN) of ABLOCK)))
                      (for (SAFENTRY _ TABLE) by (\ADDBASE SAFENTRY (TIMES 2 WORDSPERCELL))
                        as X in SIZESLST when (OR (NULL X)
                          (ILEQ ARLEN X))
                        do (add (fetch SAFITEMS of SAFENTRY)
                          1)
                          (add (fetch SAFCELLS of SAFENTRY)
                          ARLEN)
                          (RETURN])
                (printout NIL T " variable-datum free list: " T)
                (for (SAFENTRY _ TABLE) by (\ADDBASE SAFENTRY (TIMES 2 WORDSPERCELL)) as X in SIZESLST
                  do (COND
                    (X (printout NIL "le " X))
                    (T (printout NIL "others ")))
                    (printout NIL 10 .I8 (fetch SAFITEMS of SAFENTRY)
                      " items; " .I8 (fetch SAFCELLS of SAFENTRY)
                      " cells." T)
                    (printout NIL T "Total cells free: " .I8 TOTAL " total pages: " .I4 (FOLDHI TOTAL
                      CELLSPERPAGE)
                      T T))
                )
              )
            )
          )
        )
    )
  )
)
```

(RPAQ? \ABSTORAGETABLE NIL)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS \ABSTORAGETABLE)

(DECLARE%: DONTCOPY

(DECLARE%: EVAL@COMPILE

(BLOCKRECORD SAFTABLE ((SAFITEMS WORD)
 (NIL WORD)
 (SAFCELLS FIXP)))
)

:: Debugging and RDSYS

(DEFINEQ

(\CHECKARRAYBLOCK

```
[LAMBDA (BASE FREE ONFREELIST) (* bvm%: "13-Feb-85 14:50")
(COND
  (ARRAYBLOCKCHECKING (PROG (ERROR TRAILER)
    (COND
      ((NEQ (fetch (ARRAYBLOCK PASSWORD) of BASE)
        \ArrayBlockPassword)
        (SETQ ERROR "ARRAYBLOCK Password wrong"))
      ((NEQ (fetch (ARRAYBLOCK INUSE) of BASE)
        (NOT FREE))
        (SETQ ERROR "ARRAYBLOCK INUSE bit set wrong"))
      ((UNLESSRDSYS (AND FREE (NEQ (\REFCNT BASE)
        1))
        NIL)
        (SETQ ERROR "Free ARRAYBLOCK with RefCnt not 1"))
      ((NEQ (fetch (ARRAYBLOCK PASSWORD) of (SETQ TRAILER (fetch (ARRAYBLOCK TRAILER)
        of BASE)))
        \ArrayBlockPassword)
        (SETQ ERROR "ARRAYBLOCK Trailer password wrong"))
      ((NEQ (fetch (ARRAYBLOCK ARLEN) of BASE)
        (fetch (ARRAYBLOCK ARLEN) of TRAILER))
        (SETQ ERROR "ARRAYBLOCK Header and Trailer length don't match"))
      ((NEQ (fetch (ARRAYBLOCK INUSE) of BASE)
        (NOT FREE))
        (SETQ ERROR "ARRAYBLOCK Trailer INUSE bit set wrong"))
      ((OR (NOT ONFREELIST)
        (ILESSP (fetch (ARRAYBLOCK ARLEN) of BASE)
        \MinArrayBlockSize))
        ; Remaining tests only for blocks on free list
      (RETURN))
      ((OR (NOT (EQPTR (fetch (ARRAYBLOCK FWD) of (fetch (ARRAYBLOCK BKWD)
        of BASE))
        BASE))
        (NOT (EQPTR (fetch (ARRAYBLOCK BKWD) of (fetch (ARRAYBLOCK FWD)
        of BASE))
        BASE)))
        (SETQ ERROR "ARRAYBLOCK links fouled"))
      [(bind (FBL _ (FREEBLOCKCHAIN.N (fetch (ARRAYBLOCK ARLEN) of BASE)))
        ROVER first (OR (SETQ ROVER (\GETBASEPTR FBL 0))
        (RETURN (SETQ ERROR "Free block's bucket empty"))))
        do (AND (EQPTR ROVER BASE)
        (RETURN))
        (\CHECKARRAYBLOCK ROVER T)
        repeatuntil (EQ (SETQ ROVER (fetch (ARRAYBLOCK FWD) of ROVER))
        (\GETBASEPTR FBL 0]
        (T ; Everything ok
        (RETURN)))
      (UNLESSRDSYS (\MP.ERROR \MP.BADARRAYBLOCK ERROR BASE T)
        (ERROR BASE ERROR))
      (RETURN ERROR))
    )
  )
)
```

(\PARSEARRAYSPACE

```
[LAMBDA (FN) (* bvm%: "16-Apr-86 17:05")
(COND
  ((NEQ \ArrayFrLst2 \ARRAYSPACE2)
    (\PARSEARRAYSPACE1 FN \ARRAYSPACE \ArrayFrLst2)
    (\PARSEARRAYSPACE1 FN \ARRAYSPACE2 \ArrayFrLst))
  (T (\PARSEARRAYSPACE1 FN \ARRAYSPACE \ArrayFrLst])
  ; Array space is in two chunks
)
```

(\PARSEARRAYSPACE1

```
[LAMBDA (FN START END) (* bvm%: "9-Jan-85 17:10")
(for (ROVER _ START) repeatuntil [EQPTR END (SETQ ROVER (\ADDBASE2 ROVER (fetch (ARRAYBLOCK ARLEN) of ROVER]
do (\CHECKARRAYBLOCK ROVER (NOT (fetch (ARRAYBLOCK INUSE) of ROVER))
(AND (NOT (fetch (ARRAYBLOCK INUSE) of ROVER))
(fetch (ARRAYBLOCK FWD) of ROVER)))
(AND FN (APPLY* FN ROVER (fetch (ARRAYBLOCK ARLEN) of ROVER)
(fetch (ARRAYBLOCK INUSE) of ROVER)
(fetch (ARRAYBLOCK GCTYPE) of ROVER])
)
```

(RPAQ? ARRAYBLOCKCHECKING)

(DECLARE%: DOEVAL@COMPILE DONTCOPY

(GLOBALVARS ARRAYBLOCKCHECKING)

:: Basic hunking

(DEFINEQ

(\ALLOCHUNK

(* bvm%: "13-Jun-86 15:21")

```

[LAMBDA (NCELLS GCTYPE INITONPAGE ALIGN)
(COND
  ([AND ALIGN (OR (IGREATERP ALIGN \MAX.CELLSPERHUNK)
    (NOT (FMEMB ALIGN (SELECTC GCTYPE
      (UNBOXEDBLOCK.GCT
        (CONSTANT (for X in \HUNK.UNBOXEDSIZES
          when (AND (IGREATERP X 1)
            (ILEQ X \MAX.CELLSPERHUNK)
              (POWEROFTWOP X))
          collect X)))
      (PTRBLOCK.GCT (CONSTANT (for X in \HUNK.PTRSIZES
        when (AND (IGREATERP X 1)
          (ILEQ X \MAX.CELLSPERHUNK)
            (POWEROFTWOP X))
          collect X)))
      (CODEBLOCK.GCT
        (CONSTANT (LIST CELLSPERQUAD)))
      NIL]
    ; Certify that the alignment request is legitimate.
  (ERROR "Oddball alignment request" ALIGN)))
  (PROG ((TYPENUM.TABLE (SELECTC GCTYPE
    (UNBOXEDBLOCK.GCT
      \UNBOXEDHUNK.TYPENUM.TABLE)
    (CODEBLOCK.GCT
      \CODEHUNK.TYPENUM.TABLE)
    (PTRBLOCK.GCT \PTRHUNK.TYPENUM.TABLE)
    (SHOULDNT)))
    (FAILCNT 0)
    DTNUMBER HUNK HUNKSIZE ONPAGE STRADDLERS)
  BEG [do (SETQ DTNUMBER (\GETBASEBYTE TYPENUM.TABLE NCELLS))
    (SETQ HUNKSIZE (HUNKSIZEFROMNUMBER DTNUMBER))
    repeatuntil (OR (NOT ALIGN)
      (EQ 0 (IREMAINDER (FOLDLO (fetch DTDSIZE of (\GETDTD DTNUMBER))
        WORDSPERCELL)
        ALIGN)))
      (COND
        ((IGREATERP (SETQ NCELLS (ADD1 HUNKSIZE))
          \MAX.CELLSPERHUNK)
        (GO LOSE))
        (T ;; We're allowed to chunk up the size of the request in order to meet the alignment; ultimately we should top
          ;; off at \MAX.CELLSPERHUNK
          NIL]
    LP (SETQ HUNK (CREATECELL DTNUMBER))
    (COND
      ([OR (NULL INITONPAGE)
        (ILESSP INITONPAGE (SETQ ONPAGE (IDIFFERENCE CELLSPERPAGE (fetch (POINTER CELLINPAGE)
          of HUNK]
          ; Ah, happy case -- all constraints satisfied
        (RETURN HUNK)))
    ;; Sigh, gotta try to get one with more of the initial 'run' of cells on the same page.
    (COND
      (\IN.MAKEINIT
        ; Lose! Only code has an INITONPAGE requirement, and
        ; makeinit does not allocate code via \ALLOCBLOCK
        (HELP "Call to \ALLOCBLOCK with non-NIL INITONPAGE demand" INITONPAGE))
      (T (COND
        ([AND (EQ GCTYPE CODEBLOCK.GCT)
          (ILEQ (IQUOTIENT (ITIMES 10 ONPAGE)
            HUNKSIZE)
          (COND
            ((ILEQ HUNKSIZE 24)
              60)
            ((ILEQ HUNKSIZE 50)
              50)
            (T 30]
          ;; If the percentage of the page-straddling codehunk that is on the first page is too small, then just toss this loser into the
          ;; 'black hole' This heuristic is based on empirical data taken about Sep 1984 which observed the ratio of 'on-page'
          ;; requirements to code length.
          (\ADDRF HUNK))
        (T
          ; So that a GC doesn't sneak in and put it back on the freelist too
          ; soon.
          (push STRADDLERS HUNK)))
      (COND
        ((IGREATERP (add FAILCNT 1)
          16)
          ; Put a limit to this nonsense of trying to find a
          ; non-page-straddling hunk!
        (GO LOSE))
        (EQ FAILCNT 8)
          ; After too many failures with this size of hunk, try the next
          ; container size up.
        (SETQ NCELLS (ADD1 HUNKSIZE))
        (AND STRADDLERS (SETQ \HUNKREJECTS (NCONC STRADDLERS \HUNKREJECTS)))
        (GO BEG)))

```

```

      (GO LP)))
    LOSE
      (AND STRADDLERS (SETQ \HUNKREJECTS (NCONC STRADDLERS \HUNKREJECTS)))
      (RETURN])
)

```

```
(RPAQQ \HUNK.PTRSIZES (2 4 5 6 7 8 10 12 16 24 32 42 64))
```

:: Compiler needs \HUNK.PTRSIZES for creating closure environments

```
(DECLARE%: EVAL@COMPILE DONTCOPY
```

:: FOLLOWING DEFINITIONS EXPORTED

```
(DECLARE%: EVAL@COMPILE
```

```
(PUTPROPS HUNKSIZEFROMNUMBER MACRO ((NTYPX)
                                         (FOLDLO (fetch DTDSIZE of (\GETDTD NTYPX)
                                         WORDSPERCELL)))
)
```

:: END EXPORTED DEFINITIONS

```
(DECLARE%: EVAL@COMPILE
```

```
(RPAQQ \HUNK.UNBOXEDSIZES (1 2 3 4 5 6 7 8 9 10 12 14 16 20 24 28 32 40 48 64))
```

```
(RPAQQ \HUNK.CODESIZES (12 16 20 24 28 32 36 42 50 64))
```

```
(RPAQQ \HUNK.PTRSIZES (2 4 5 6 7 8 10 12 16 24 32 42 64))
```

```
(CONSTANTS \HUNK.UNBOXEDSIZES \HUNK.CODESIZES \HUNK.PTRSIZES)
)
```

```
(DECLARE%: DOEVAL@COMPILE DONTCOPY
```

```
(GLOBALVARS \HUNKING? \UNBOXEDHUNK.TYPENUM.TABLE \CODEHUNK.TYPENUM.TABLE \PTRHUNK.TYPENUM.TABLE)
)
)
```

:: Keep a list of all the hunks rejected due to poor page-straddling alignment, or to code falling off the end of a doublepage

```
(RPAQQ \HUNKREJECTS NIL)
```

```
(DECLARE%: DOEVAL@COMPILE DONTCOPY
```

```
(GLOBALVARS \HUNKREJECTS)
)
```

:: for MAKEINIT

```
(DEFINEQ
```

(PREINITARRAYS

```
[LAMBDA NIL (* bvm%: " 9-Jan-85 16:50")
```

:: This is called only at the very beginning of MAKEINIT. \ARRAYspace and \ARRAYbase are INITCONSTANTS. This sets up the array allocator
:: so that MAKEINIT can do, e.g., string allocations.

```
(DECLARE (GLOBALVARS \ArrayFrLst \ArrayFrLst2 \NxtArrayPage))
(SETQ.NOREF \ArrayFrLst (\VAG2 \FirstArraySegment 0))
(SETQ.NOREF \ArrayFrLst2 \ARRAYSPACE2)
(SETQ.NOREF \NxtArrayPage (PAGELOC \ArrayFrLst))
```

(POSTINITARRAYS

```
[LAMBDA (AFTERCODEPTR CODESTARTPAGE CODENEXTPAGE) (* bvm%: " 7-Feb-85 15:30")
```

:: Called only from MAKEINIT after all code and data has been copied to the new image. AFTERCODEPTR is a pointer to the first word after the
:: last code byte. CODESTARTPAGE is the page at which MAKEINIT code arrays being. This function makes sure that any unused space
:: between the strings and the beginning of the code gets linked in as free arrayblocks.

```
(SETQ \FREEBLOCKBUCKETS (\ALLOCBLOCK (ADD1 \MAXBUCKETINDEX)))
(PROG [(EXTRACELLS (IDIFFERENCE (UNFOLD CODESTARTPAGE CELLSPERPAGE)
                               (IPLUS (UNFOLD (fetch SEGMENT# of \ArrayFrLst)
                               CELLSPERSEGMENT)
                               (fetch CELLINSEGMENT of \ArrayFrLst]

```

:: First, tell the makeiniter how many pages were left over in the string space. He may want to adjust the constants to keep this down to just a
:: couple of pages.

```
(COND
```

```
((IGREATERP EXTRACELLS \MaxArrayBlockSize)
 (printout T T T "POSTINITARRAYS: You pre-allocated too much string space." T 19
  "MKI.CODESTARTOFFSET on MAKEINIT should be reduced by about " (IDIFFERENCE (FOLDLO
```

CELLSPERPAGE
)

10)

```

      ". " T)
      (HELP)
      ((IGEQ EXTRACELLS \MinArrayBlockSize) ; We don't allow more than one array-block extra.
      (printout T T T "POSTINITARRAYS: There were " (FOLDLO EXTRACELLS CELLSPERPAGE)
      " allocated but unused array pages." T T))
      (T (printout T T "POSTINITARRAYS: String space overflowed into code-arrays" T 19 "You should add
      at least " (ADD1 (FOLDLO (IMINUS EXTRACELLS)
      CELLSPERPAGE))
      " to MKI.CODESTARTOFFSET on MAKEINIT." T)
      (HELP))) ; Cause those pages to get allocated
      (\LINKBLOCK (\ALLOCBLOCK.NEW EXTRACELLS))
      (SETQ.NOREF \ArrayFrLst AFTERCODEPTR) ; \NxtArrayPage is the next page that needs to be NEWPAGED
      (SETQ.NOREF \NxtArrayPage CODENEXTPAGE)
      (for VP from (PAGELOC \ARRAYSPACE) to (PAGELOC \NxtArrayPage) by (FOLDLO \MDSIncrement WORDSPERPAGE)
      do (\MAKEMDSENTRY VP 0])

```

(FILEARRAYBASE

```

[LAMBDA NIL ; (* rmk%: "15-MAR-82 21:55")
  (\ADDBASE \ARRAYSPACE (LOCAL (IPLUS (UNFOLD MKI.CODESTARTOFFSET WORDSPERPAGE)
  (FOLDLO (IDIFFERENCE (GETFILEPTR (OUTPUT))
  MKI.FirstDataByte)
  BYTESPERWORD)])

```

(FILEBLOCKTRAILER

```

[LAMBDA (BLOCKINFO) ; (* rmk%: "18-NOV-82 09:49")
  ;; Sets up block trailer, assuming file is currently positioned just past the last dataword
  (BOUT16 OUTX \UsedArrayFlagWord)
  (BOUT16 OUTX BLOCKINFO)]

```

(FILECODEBLOCK

```

[LAMBDA (NCELLS INITONPAGE) ; (* JonL "20-Sep-84 13:29")
  ;; sort of like CODEARRAY at MAKEINIT time for allocating space on the file; this code borrowed from CODEARRAY and \ALLOCBLOCK.
  ;; Returns ARLEN, which is then passed to FILEBLOCKTRAILER to set trailer length.
  (PROG (PREFIXLEN (ARLEN (IPLUS NCELLS \ArrayBlockOverheadCells)))
  ;; ARLEN is the number of cells in the array . INITONPAGE is number of cells which must reside on same page
  (COND
  (([NEQ 0 (SETQ PREFIXLEN (\PREFIXALIGNMENT? ARLEN INITONPAGE CELLSPERQUAD CODEBLOCK.GCT (
  FILEARRAYBASE
  ]
  ;; Check page first, cause if we did segment first and succeeded but then failed on page, we would have to check segment again.
  (FILEPATCHBLOCK PREFIXLEN)))
  (BOUT16 OUTX \CodeArrayFlagWord)
  (BOUT16 OUTX ARLEN)
  (RETURN ARLEN)]

```

(FILEPATCHBLOCK

```

[LAMBDA (ARLEN) ; (* rmk%: "18-NOV-82 09:50")
  ;; like \PATCHBLOCK for array allocation on files at MAKEINIT time
  (LOCAL (BOUT16 OUTX \FreeArrayFlagWord) ; in-use bit off, password set
  (LOCAL (BOUT16 OUTX ARLEN) ; number of cells in this block
  [COND
  ((IGREATERP ARLEN \ArrayBlockHeaderCells) ; Assumes that header and trailer look alike, so that we only
  ; need one instance for a tiny block.
  (LOCAL (BOUTZEROS (UNFOLD (IDIFFERENCE ARLEN \ArrayBlockOverheadCells)
  BYTESPERCELL))) ; zeros for data words
  (LOCAL (BOUT16 OUTX \FreeArrayFlagWord) ; Set up trailer
  (LOCAL (BOUT16 OUTX ARLEN)
  NIL])

```

;; Hunk Initialization

(DEFINEQ

(\SETUP.HUNK.TYPENUMBERS

[LAMBDA NIL ; Edited 4-Mar-87 11:04 by bvm:

;;; Called before datatype table is initialized. We add to the list of initial datatypes (built-in-system-types) entries for all the hunk types we will want.

;;; Note: the compiler knows about the pointer hunk names, so it is important to coordinate any future changes to \HUNK.PTRSIZEs with the compiler.

```

(SETQ INITIALDTCNTENTS (APPEND \BUILT-IN-SYSTEM-TYPES (\COMPUTE.HUNK.TYPEDECLS \HUNK.PTRSIZEs
PTRBLOCK.GCT ' \PTRHUNK)
(\COMPUTE.HUNK.TYPEDECLS \HUNK.UNBOXEDSIZEs UNBOXEDBLOCK.GCT

```

```
' \UNBOXEDHUNK)
(\COMPUTE.HUNK.TYPEDECLS \HUNK.CODESIZES CODEBLOCK.GCT ' \CODEHUNK])
```

(\COMPUTE.HUNK.TYPEDECLS

[LAMBDA (SIZELST GCTYPE PREFIX)

; Edited 4-Mar-87 11:03 by bvm:

:: Add type entries to INITIALDTDCONENTS for the hunks in SIZELST of type GCTYPE. PREFIX is the start of the name, e.g., \PTRHUNK.
:: Entries are of the form (name size ptrs finalization)

```
(ALLOCAL (for HUNKSIZE in SIZELST BIND (FINAL _ (AND (EQ GCTYPE CODEBLOCK.GCT)
' \RECLAIMCODEBLOCK))
until (> HUNKSIZE \MAX.CELLSPERHUNK) collect (LIST (PACK* PREFIX HUNKSIZE)
(UNFOLD HUNKSIZE WORDSPERCELL)
(COND
(EQ GCTYPE PTRBLOCK.GCT)
; Compute DTDPTRS list, i.e., which fields are pointers (all of
; them)
(for I from 0 by 2
to (SUB1 (UNFOLD HUNKSIZE WORDSPERCELL))
collect I)))
FINAL])
```

(\TURN.ON.HUNKING

[LAMBDA NIL

(* bvm%: "13-Jun-86 17:27")

::: create all the datatypes, and the tables used to calculate a hunk datatype number from the allocation size request.

```
(SETQ \UNBOXEDHUNK.TYPENUM.TABLE (\SETUP.TYPENUM.TABLE \HUNK.UNBOXEDSIZES UNBOXEDBLOCK.GCT ' \UNBOXEDHUNK))
(SETQ \CODEHUNK.TYPENUM.TABLE (\SETUP.TYPENUM.TABLE \HUNK.CODESIZES CODEBLOCK.GCT ' \CODEHUNK))
(SETQ \PTRHUNK.TYPENUM.TABLE (\SETUP.TYPENUM.TABLE \HUNK.PTRSIZES PTRBLOCK.GCT ' \PTRHUNK))
(SETQ \HUNKING? T))
```

(\SETUP.TYPENUM.TABLE

[LAMBDA (SIZELST GCTYPE PREFIX)

; Edited 5-Mar-87 10:12 by bvm:

::: Create a table that maps from number of cells desired to the closest hunk size that fits for a given GCTYPE. SIZELST is list of sizes in cells.
::: PREFIX is the datatype name prefix for this kind of hunk.

```
(for I from 0 to \MAX.CELLSPERHUNK bind (HUNKSIZE _ -1)
(SIZEL _ SIZELST)
(TABLE _ (\ALLOCBLOCK (FOLDHI (IPLUS 4 \MAX.CELLSPERHUNK)
BYTESPERCELL)
UNBOXEDBLOCK.GCT))
TNAME DTD DTNUMBER
do [COND
((IGREATERP I HUNKSIZE)
; Advance to next quantum range in the SIZELST
(SETQ HUNKSIZE (OR (FIXP (pop SIZEL))
\MAX.CELLSPERHUNK))
(SETQ TNAME (PACK* PREFIX HUNKSIZE))
(COND
((for old DTNUMBER from 1 as TYPE in (LOCAL INITIALDTDCONENTS)
when (EQ (LOCAL (CAR TYPE))
TNAME)
do ;; Find the type number that has been assigned to this hunk type. Ordinarily would use \TYPENUMBERFROMNAME,
;; but atoms haven't been initialized yet, so we can only talk locally
(RETURN DTNUMBER))
(SETQ DTD (\GETDTD DTNUMBER))
(replace DIDGCTYPE of DTD with GCTYPE)
(replace DTDHUNKP of DTD with T))
(T (HELP "No type declaration for" TNAME])
(\PUTBASEBYTE TABLE I DTNUMBER)
finally (RETURN TABLE])
)
```

(DECLARE%: DONTCOPY

(ADDTOVAR INITVALUES (\NxtArrayPage)
(\HUNKING?))

(ADDTOVAR INITPTRS (\FREEBLOCKBUCKETS)
(ArrayFrLst)
(ArrayFrLst2)
(\UNBOXEDHUNK.TYPENUM.TABLE)
(\CODEHUNK.TYPENUM.TABLE)
(\PTRHUNK.TYPENUM.TABLE))

(ADDTOVAR INEWCOMS (FNS \#BLOCKDATACELLS \PREFIXALIGNMENT? \ALLOCBLOCK \MAIKO.ALLOCBLOCK \ALLOCBLOCK.NEW
\MAKEFREEARRAYBLOCK \MERGEBACKWARD \LINKBLOCK \ALLOCHUNK)
(FNS PREINITARRAYS POSTINITARRAYS FILEARRAYBASE FILEBLOCKTRAILER FILECODEBLOCK
FILEPATCHBLOCK)
(FNS \SETUP.HUNK.TYPENUMBERS \COMPUTE.HUNK.TYPEDECLS \TURN.ON.HUNKING \SETUP.TYPENUM.TABLE))

(ADDTOVAR MKI.SUBFNS (\IN.MAKEINIT . T)

```
(\ALLOCBLOCK.OLD . NIL)
(\MERGEFORWARD . NIL)
(\FIXCODENUM . I.FIXUPNUM)
(\FIXCODESYM . I.FIXUPSYM)
(\FIXCODEPTR . I.FIXUPPTR)
(\CHECKARRAYBLOCK . NIL)
(\ARRAYMERGING PROGN NIL)
```

(ADDTOVAR **EXPANDMACROFNS** \ADDBASE2 \ADDBASE4 HUNKSIZEFROMNUMBER BUCKETINDEX FREEBLOCKCHAIN.N)

(ADDTOVAR **RDCOMS** (FNS \CHECKARRAYBLOCK \PARSEARRAYSPACE \PARSEARRAYSPACE1))

```
(ADDTOVAR RD.SUBFNS (EQPTR . EQUAL)
  (ARRAYBLOCKCHECKING . T))
```

(ADDTOVAR **RDPTRS** (\FREEBLOCKBUCKETS))

```
(ADDTOVAR RDVALS (\ArrayFrLst)
  (\ArrayFrLst2))
```

```
(ADDTOVAR DONTCOMPILEFNS PREINITARRAYS POSTINITARRAYS FILEARRAYBASE FILEBLOCKTRAILER FILECODEBLOCK
  FILEPATCHBLOCK)
```

```
(ADDTOVAR DONTCOMPILEFNS \SETUP.HUNK.TYPENUMBERS \COMPUTE.HUNK.TYPEDECLS \TURN.ON.HUNKING \SETUP.TYPENUM.TABLE
)
)
```

:: Debugging aids

(DECLARE%: EVAL@COMPILE DONTCOPY

(DECLARE%: DOEVAL@COMPILE DONTCOPY

```
(GLOBALVARS \ArrayFrLst)
)
```

(DECLARE%: EVAL@COMPILE

(RPAQQ \ArrayBlockPassword 5461)

```
(CONSTANTS \ArrayBlockPassword)
)
```

```
(ADDTOVAR DONTCOMPILEFNS \HUNKFIT? \AB.NEXT \AB.BACK)
)
```

(DEFINEQ

(\HUNKFIT?

[LAMBDA (N)

(* JonL "15-Jan-85 00:48")

:: Show how an MDS unit of 2 pages would accomodate chunks of size N cells.

```
(printout NIL T "Hunk size = " N " cells, " (IQUOTIENT (FOLDLO \MDSIncrement WORDSPERCELL)
  N)
```

" fit in a MDS unit with "

```
(IREMAINDER (FOLDLO \MDSIncrement WORDSPERCELL)
  N)
```

" cells left over." T .TAB 8 "(unit' is split with " (IREMAINDER CELLSPERPAGE N)

" cells kept on first page)" T)

T])

(\AB.NEXT

[LAMBDA (ABHI ABLO)

(* JonL "10-Sep-84 05:04")

:: ABHI and ABLO form the \HILOC and \LOLOC of some arrayblock which we want to 'go' to the predecessor of; alternatively, ABHI can be a list of these two address parts, or just a random arrayblock address.

:: Returns a 4-list; size of the next block, whether or not it is free, and the \HILOC and the \LOLOC of that block

[COND

```
  [(AND (LISTP ABHI)
    (NULL ABLO))
```

[COND

```
  ((AND (EQ 4 (LENGTH ABHI))
    (FIXP (CAR ABHI))
    (SELECTQ (CADR ABHI)
```

((INUSE FREE)

T)

NIL))

```
  (SETQ ABHI (CDDR ABHI)
    (COND
```

(COND

```
  ((EQ 2 (LENGTH ABHI))
    (SETQ ABLO (CADR ABHI))
    (SETQ ABHI (CAR ABHI))
```

((OR (EQ ABHI \ArrayFrLst)

(type? ARRAYBLOCK ABHI))

; Result is output of \AB.NEXT itself

; A 2-list of \HILOC and \LOLOC

```
(SETQ ABLO (\LOLOC ABHI))
(SETQ ABHI (\HILOC ABHI])
(OR (IGEQ ABHI 0)
  (ERROR "Negative segment number?" ABHI))
(AND (IGREATERP ABHI (\HILOC \ArrayFrLst))
  (ERROR "Segment number too high?" ABHI))
(OR (IGEQ ABLO 0)
  (ERROR "Negative offset number?" ABLO))
(PROG (PW SIZE SIZE.WORDS (ABADDR (\VAG2 ABHI ABLO)))
  [PROGN
    (SETQ PW (\GETBASE ABADDR 0))
    [COND
      ((NEQ \ArrayBlockPassword (LOADBYTE PW 3 13))
        (SETQ ABADDR)
        (ERROR "Array Password not found at this loc" (LIST ABHI ABLO])
      (SETQ SIZE.WORDS (UNFOLD (SETQ SIZE (\GETBASE ABADDR 1))
        WORDSPERCELL))
      (COND
        [(NEQ \ArrayBlockPassword (LOADBYTE (\GETBASE ABADDR (IDIFFERENCE SIZE.WORDS 2))
          3 13))
          (ERROR "Array Password not found just below this" (PROG1 (LIST ABHI ABLO)
            (SETQ ABADDR])
          ((NEQ SIZE (\GETBASE ABADDR (IDIFFERENCE SIZE.WORDS 1)))
            (ERROR "Header and Trailer lengths disagree" (PROG1 (LIST ABHI ABLO)
              (SETQ ABADDR])
        (SETQ ABADDR (\ADDBASE ABADDR SIZE.WORDS))
        (SETQ PW (\GETBASE ABADDR 0))
        [COND
          ((NEQ \ArrayBlockPassword (LOADBYTE PW 3 13))
            (SETQ ABADDR)
            (ERROR "Array Password not found at this loc" (LIST ABHI ABLO])
          (RETURN (LIST (\GETBASE ABADDR 1)
            (COND
              ((ODDP PW)
                'INUSE)
              (T 'FREE))
            (\HILOC ABADDR)
            (\LOLOC ABADDR]))

```

; Checking on current block

; Result is output of \AB.BACK itself

; A 2-list of \HILOC and \LOLOC

(\AB.BACK

[LAMBDA (ABHI ABLO)

(* JonL " 9-Sep-84 16:28")

;; ABHI and ABLO form the \HILOC and \LOLOC of some arrayblock which we want to 'go' to the predecessor of; alternatively, ABHI can be a list
 ;; of these two address parts, or just a random arrayblock address.

;; Returns a 4-list; size of the block we are starting from, whether or not it is free, and the \HILOC and the \LOLOC of the predecessor block

```
[COND
  [(AND (LISTP ABHI)
    (NULL ABLO))
    [COND
      ((AND (EQ 4 (LENGTH ABHI))
        (FIXP (CAR ABHI))
        (SELECTQ (CADR ABHI)
          ((INUSE FREE)
            T)
          NIL))
        (SETQ ABHI (CDDR ABHI])
      (COND
        ((EQ 2 (LENGTH ABHI))
          (SETQ ABLO (CADR ABHI])
          (SETQ ABHI (CAR ABHI])
        ((OR (EQ ABHI \ArrayFrLst)
          (type? ARRAYBLOCK ABHI))
          (SETQ ABLO (\LOLOC ABHI])
          (SETQ ABHI (\HILOC ABHI])
        (OR (IGEQ ABHI 0)
          (ERROR "Negative segment number?" ABHI))
        (AND (IGREATERP ABHI (\HILOC \ArrayFrLst))
          (ERROR "Segment number too high?" ABHI))
        (OR (IGEQ ABLO 0)
          (ERROR "Negative offset number?" ABLO))
        (PROG (PW SIZE (ABADDR (\ADDBASE (\VAG2 ABHI ABLO)
          -2)))
          (SETQ PW (\GETBASE ABADDR 0))
          [COND
            ((NEQ \ArrayBlockPassword (LOADBYTE PW 3 13))
              (SETQ ABADDR)
              (ERROR "Array Password not found just below this" (LIST ABHI ABLO])
            (SETQ SIZE (\GETBASE ABADDR 1))
            [SETQ ABADDR (\ADDBASE ABADDR (IMINUS (UNFOLD (SUB1 SIZE)
              WORDSPERCELL])
            [COND
              [(NEQ \ArrayBlockPassword (LOADBYTE (\GETBASE ABADDR 0)
                3 13))
                (ERROR "Array Password not found just below this" (PROG1 (LIST ABHI ABLO)
                  (SETQ ABADDR])
              ((NEQ SIZE (\GETBASE ABADDR 1))

```



```
(ERROR "Header and Trailer lengths disagree" (PROG1 (LIST ABHI ABLO)
                                                    (SETQ ABADDR]
(RETURN (LIST SIZE (COND
                ((ODDP PW)
                 ' INUSE)
                (T 'FREE))
        (\HILOC ABADDR)
        (\LOLOC ABADDR])
)
(DECLARE%: DOEVAL@COMPILE DONTCOPY
(LOCALVARS . T)
)
(DECLARE%: DONTEVAL@LOAD DOEVAL@COMPILE DONTCOPY COMPILERVERS
(ADDTOVAR NLAMA )
(ADDTOVAR NLAML )
(ADDTOVAR LAMA CL::PUTHASH HARRAYPROP)
)
(PUTPROPS LLARRAYELT COPYRIGHT ("Venue & Xerox Corporation" 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991
                                1992 1993 1994))
```

FUNCTION INDEX

AIN	2	REHASH	11	\FIXCODENUM	14
AOUT	3	REMHASH	10	\FIXCODEPTR	14
ARRAY	3	SETA	6	\FIXCODESYM	14
ARRAYORIG	5	SETD	6	\HASHACCESS	10
ARRAYSIZE	4	STRING-EQUAL-HASHBITS	12	\HASHRECLAIM	10
ARRAYTYP	5	STRINGHASHBITS	12	\HASHTABLE.DEFPRINT	11
CLRHASH	8	SUBARRAY	6	\HUNKFIT?	31
COPYARRAY	5	\#BLOCKDATACELLS	23	\LINKBLOCK	21
ELT	5	\AB.BACK	32	\MAIKO.ALLOCBLOCK	18
ELTD	6	\AB.NEXT	31	\MAKEFREEARRAYBLOCK	21
FILEARRAYBASE	29	\ADVANCE.ARRAY.SEGMENTS	23	\MERGEBACKWARD	22
FILEBLOCKTRAILER	29	\ALLOCBLOCK	18	\MERGEFORWARD	22
FILECODEBLOCK	29	\ALLOCBLOCK.NEW	20	\PARSEARRAYSPACE	26
FILEPATCHBLOCK	29	\ALLOCBLOCK.OLD	19	\PARSEARRAYSPACE1	26
GETHASH	9	\ALLOCHUNK	27	\PREFIXALIGNMENT?	20
HARRAY	7	\ARRAYBLOCKMERGER	22	\RECLAIMARRAYBLOCK	23
HARRAYP	8	\ARRAYTYPENAME	25	\SETUP.HUNK.TYPENUMBERS	29
HARRAYPROP	8	\BYTELT	24	\SETUP.TYPENUM.TABLE	30
HARRAYSIZE	8	\BYTESETA	24	\SHOW.ARRAY.FREELISTS	25
HASHARRAY	7	\CHECKARRAYBLOCK	26	\STRING-EQUAL-HASHBITS-UFN	12
MAPHASH	8	\CODEARRAY	13	\STRINGHASHBITS-UFN	12
POSTINITARRAYS	28	\COMPUTE.HUNK.TYPEDECLS	30	\TURN.ON.HUNKING	30
PREINITARRAYS	28	\COPYARRAYBLOCK	23	\WORDELT	24
PUTHASH	9	\COPYHARRAYP	11		
CL::PUTHASH	9	\DELETEBLOCK?	21		

CONSTANT INDEX

CELLSPERSLOT	13	\ArrayBlockTrailerWords	16	\MinArrayBlockSize	16
CODEBLOCK.GCT	15	\CodeArrayFlagWord	16	\ST.BIT	17
PTRBLOCK.GCT	15	\FreeArrayFlagWord	16	\ST.BYTE	17
UNBOXEDBLOCK.GCT	15	\HUNK.CODESIZES	28	\ST.CODE	17
\ABPASSWORDSHIFT	16	\HUNK.PTRSIZES	28	\ST.FLOAT	17
\ArrayBlockHeaderCells	16	\HUNK.UNBOXEDSIZES	28	\ST.INT32	17
\ArrayBlockHeaderWords	16	\IN.MAKEINIT	17	\ST.POS16	17
\ArrayBlockLinkingCells	16	\MAX.CELLSPERHUNK	17	\ST.PTR	17
\ArrayBlockOverheadCells	16	\MaxArrayBlockSize	16	\ST.PTR2	17
\ArrayBlockOverheadWords	16	\MaxArrayLen	16	\UsedArrayFlagWord	16
\ArrayBlockPassword	16, 31	\MaxArrayNCells	16		
\ArrayBlockTrailerCells	16	\MAXBUCKETINDEX	15		

VARIABLE INDEX

ARRAYBLOCKCHECKING	26	EXPANDMACROFNs	31	RD.SUBFNs	31	\ABSTORAGETABLE	25
ARRAYCONSTANTS	15	INewCOMs	30	RDCOMs	31	\ARRAYMERGING	25
ARRAYTYPES	16	INITPTRs	30	RDPTRs	31	\HASH.NULL.VALUE	13
BLOCKGCTYPECONSTANTS	15	INITVALUEs	30	RDVALs	31	\HUNKREJECTs	28
DONTCOMPFILEFNs	31	MKI.SUBFNs	30	SYSTEMRECLST	13	\MAIKO.MOVDS	24

MACRO INDEX

ARRAYSIZE	5	HUNKSIZEFROMNUMBER	15, 28	\BYTESETA	15	\REPROBE	13
BUCKETINDEX	15	\ADDBASE2	15	\EQHASHINGBITS	12	\WORDELT	15
EQPTR	15	\ADDBASE4	15	\FIRSTINDEX	13		
FREEBLOCKCHAIN.N	15	\BYTELT	15	\HASHSLOT	13		

RECORD INDEX

ARRAYBLOCK	17	HARRAYP	12	SAFTABLE	25
HARRAYP	17	HASHSLOT	13	SEQUENCEDESCRIPTOR	17

PROPERTY INDEX

LLARRAYELT	2
------------	---