

File created: 16-May-90 21:15:43 {DSK}<usr>local>lde>lispcore>sources>PROFILE.;2

changes to: (IL:VARS IL:PROFILECOMS)

previous date: 27-Feb-87 14:34:18 {DSK}<usr>local>lde>lispcore>sources>PROFILE.;1

Read Table: XCL

Package: XEROX-COMMON-LISP

Format: XCCS

; Copyright (c) 1986, 1987, 1990 by Venue & Xerox Corporation. All rights reserved.

(IL:RPAQQ **IL:PROFILECOMS**

;; The profile type

```
(IL:DEFINE-TYPES PROFILES)
(IL:FUNCTIONS DEFPROFILE)
(IL:TYPES PROFILE)
(IL:STRUCTURES PROFILE-CLAUSE VARIABLE-DEFINITION)
(IL:VARIABLES *PROFILE* *PROFILE-NAME* *PROFILE-VARIABLES* *PROFILES*)
(IL:FUNCTIONS FIND-VARIABLE-DEFINITION IN-PROFILE INSTALL-PROFILE MAKE-VARIABLE-DEFINITION PROFILIZE
  PROFILE-ENTRY-VALUE PROFILE-ENTRY-VALUE-NAME PROFILE-NAME PROFILE-P PROFILE-VALUE-TYPE-CHECK
  SETF-PROFILE-ENTRY-VALUE SETF-PROFILE-ENTRY-VALUE-NAME SETF-PROFILE-NAME MAKE-PROFILE
  COPY-PROFILE RESTORE-PROFILE SAVE-PROFILE WITH-PROFILE FIND-PROFILE SETF-FIND-PROFILE
  LIST-ALL-PROFILES PROFILE-VALUES PROFILE-VARIABLES)
(IL:SETFS FIND-PROFILE PROFILE-ENTRY-VALUE PROFILE-ENTRY-VALUE-NAME PROFILE-NAME)
(PROFILES "READ-PRINT" "LISP" "INTERLISP" "OLD-INTERLISP-T" "XEROX-COMMON-LISP")
(IL:DECLARE\ : IL:DONTCOPY IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE (IL:LOCALVARS . T))
(IL:PROP (IL:MAKEFILE-ENVIRONMENT IL:FILETYPE)
  IL:PROFILE))
```

;; The profile type

(DEF-DEFINE-TYPE **PROFILES** "interaction profiles")

```
(DEFDEFINER (DEFPROFILE (:NAME (LAMBDA (WHOLE)
  (LET ((NAME-CLAUSE (SECOND WHOLE)))
    (IF (CONSP NAME-CLAUSE)
      (STRING (CAR NAME-CLAUSE))
      (STRING NAME-CLAUSE))))))
  PROFILES (NAME-CLAUSE &REST VARIABLE-CLAUSES)
  "Creates a new named profile. name . clauses or (name (:nicknames n1 n2...)) clauses"
  (LET ((NAME (IF (CONSP NAME-CLAUSE)
    (STRING (CAR NAME-CLAUSE))
    (STRING NAME-CLAUSE)))
    (NICKNAMES (AND (CONSP NAME-CLAUSE)
      (MAPCAR #'STRING (CDADR NAME-CLAUSE))))
    ` (LET ((PROFILE (MAKE-PROFILE ,NAME ,@(MAPCAR #'(LAMBDA (CLAUSE)
      VARIABLE-CLAUSES))))
      (INSTALL-PROFILE PROFILE ,NAME ',NICKNAMES))))
```

(DEFTYPE **PROFILE** ()
 \ (SATISFIES PROFILE-P))

```
(DEFSTRUCT (PROFILE-CLAUSE (:TYPE LIST)
  (:CONSTRUCTOR NIL))
  VARIABLE
  NAME
  TYPE
  COERCION-FUNCTION
  NAME-FUNCTION)
```

```
(DEFSTRUCT (VARIABLE-DEFINITION (:TYPE LIST)
  (:CONSTRUCTOR NIL))
  VARIABLE
  TYPE
  COERCION-FUNCTION
  NAME-FUNCTION)
```

(DEFPARAMETER ***PROFILE*** "XCL"
 "The default or current profile.")

(DEFPARAMETER ***PROFILE-NAME*** NIL)

(DEFPARAMETER ***PROFILE-VARIABLES***
 ' ((*PROFILE-NAME* T IDENTITY IDENTITY)
 (*EVAL-FUNCTION* (MEMBER IL:EVAL EVAL))

```

IDENTITY IDENTITY)
(*EXEC-PROMPT* STRING STRING IDENTITY)
(*DEBUGGER-PROMPT* STRING STRING IDENTITY)
(*READTABLE* READTABLE IL:FIND-READTABLE IL:READTABLE-NAME)
(*READ-BASE* (INTEGER 2 36)
  IDENTITY IDENTITY)
(*READ-SUPPRESS* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PACKAGE* PACKAGE FIND-PACKAGE PACKAGE-NAME)
(*READ-DEFAULT-FLOAT-FORMAT* (MEMBER SINGLE-FLOAT DOUBLE-FLOAT LONG-FLOAT SHORT-FLOAT)
  IDENTITY IDENTITY)
(*PRINT-ESCAPE* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-PRETTY* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-CIRCLE* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-BASE* (INTEGER 2 36)
  IDENTITY IDENTITY)
(*PRINT-RADIX* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-CASE* (MEMBER :DOWNCASE :UPCASE :CAPITALIZE)
  IDENTITY IDENTITY)
(*PRINT-GENSYM* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-LEVEL* (OR NULL FIXNUM)
  IDENTITY IDENTITY)
(*PRINT-LENGTH* (OR NULL FIXNUM)
  IDENTITY IDENTITY)
(*PRINT-ARRAY* (MEMBER NIL T)
  IDENTITY IDENTITY)
(*PRINT-STRUCTURE* (MEMBER NIL T)
  IDENTITY IDENTITY))

```

```

(DEFGLOBALVAR *PROFILES* (MAKE-HASH-TABLE :TEST 'EQUAL)
  "Where profiles live.")

```

```

(DEFUN FIND-VARIABLE-DEFINITION (VARIABLE)
  (DOLIST (ENTRY *PROFILE-VARIABLES* NIL)
    (IF (EQ VARIABLE (VARIABLE-DEFINITION-VARIABLE ENTRY))
      (RETURN ENTRY))))

```

```

(DEFUN IN-PROFILE (PROFILE)
  "Makes profile the current profile and resets *profile*"
  (SETQ *PROFILE* (PROFILIZE PROFILE))
  (RESTORE-PROFILE *PROFILE*))

```

```

(DEFUN INSTALL-PROFILE (PROFILE PROFILE-NAME PROFILE-NICKNAMES)
  (DOLIST (NAME (CONS PROFILE-NAME PROFILE-NICKNAMES))
    (IF (AND (FIND-PROFILE NAME)
      (FBOUNDP 'WARN))
      (WARN "Resetting profile ~s." NAME)
      (SETF (FIND-PROFILE NAME)
        PROFILE)))
  )
  ; Make the name and all nicknames point at the new profile.

```

```

(DEFUN MAKE-VARIABLE-DEFINITION (CLAUSE &AUX (DEFINITION NIL))
  "Add a new profile variable entry based on clauses. clauses is bounded by a keyword or nil."
  (DOLIST (DEFAULT ' (NIL
    IGNORE ; variable
    T ; value
    IDENTITY ; type
    IDENTITY ; coercion-function
    IDENTITY ; name-function
  )
    ; Defaults for a definition's slots.
  )
  ; Maps on defaults to always fill all the slots.
  (IF (EQ DEFAULT ' IGNORE)
    (POP CLAUSE) ; Ignore the value slot
    (PUSH
      (IF (NULL CLAUSE)
        DEFAULT ; Push onto the new entry
        (POP CLAUSE) ; If we're at the end of the clause:
          ; ...use the default.
          ; ...otherwise use the next element of the clause.
      )
      DEFINITION))
  (SETQ DEFINITION (NREVERSE DEFINITION))
  (PUSH DEFINITION
    *PROFILE-VARIABLES*)
  DEFINITION)
  ; Flip the push built list.
  ; Put the new definition onto the global list of definitions.

```

```

(DEFUN PROFILIZE (NAME-OR-PROFILE)

```

```
(ETYPESCASE NAME-OR-PROFILE
  ((OR STRING SYMBOL) (OR (FIND-PROFILE NAME-OR-PROFILE)
    (ERROR "Not the name of an existing profile ~s" NAME-OR-PROFILE)))
  (PROFILE NAME-OR-PROFILE)))
```

```
(DEFUN PROFILE-ENTRY-VALUE (VARIABLE &OPTIONAL (PROFILE *PROFILE*))
  "Returns the value of the variable in the current profile or its binding."
  (GETF (PROFILIZE PROFILE)
    VARIABLE
    (EVAL VARIABLE)))
```

```
(DEFUN PROFILE-ENTRY-VALUE-NAME (VARIABLE &OPTIONAL (PROFILE *PROFILE*))
  "Get the name of the value in a variable or the name of the current binding."
  (FUNCCALL (VARIABLE-DEFINITION-NAME-FUNCTION (FIND-VARIABLE-DEFINITION VARIABLE))
    (GETF (PROFILIZE PROFILE)
      VARIABLE
      (EVAL VARIABLE))))
```

```
(DEFUN PROFILE-NAME (&OPTIONAL (PROFILE *PROFILE*))
  "Returns the name of the profile as a string."
  (PROFILE-ENTRY-VALUE '*PROFILE-NAME* (PROFILIZE PROFILE)))
```

```
(DEFUN PROFILE-P (OBJECT)
  "Returns true if the object seems to be a profile. Is true only of profiles, never their names."
  (AND (CONSP OBJECT)
    (SYMBOLP (FIRST OBJECT))
    (EVENP (LENGTH OBJECT))
    T))
```

```
(DEFUN PROFILE-VALUE-TYPE-CHECK (DEFINITION VALUE)
  "Returns correct or corrected value."
  (LET ((COERCION-FUNCTION (VARIABLE-DEFINITION-COERCION-FUNCTION DEFINITION))
    (TYPE (VARIABLE-DEFINITION-TYPE DEFINITION)))
    (LOOP (IF (TYPEP VALUE TYPE) ; Is it of the right type?
      (RETURN VALUE) ; ...just return it
    )
    (COND
      (COERCION-FUNCTION (SETQ VALUE (FUNCCALL COERCION-FUNCTION VALUE))
        (IF (TYPEP VALUE TYPE) ; Perhaps it was a name, coerce it.
          (RETURN VALUE) ; Is it NOW of the right type?
          ; ...just return it
        )
      )
    )))
  ;; Otherwise we were given something that can't either use or coerce; complain, fix and retry
  (CERROR "Give new value" "Profile slot ~s's value ~s not a(n) ~s" (VARIABLE-DEFINITION-VARIABLE
    DEFINITION)
    VALUE TYPE)
  (FORMAT *QUERY-IO* "Give new value expression (will be evaluated)~%"
    (SETQ VALUE (EVAL (READ))))))
```

```
(DEFUN SETF-PROFILE-ENTRY-VALUE (VARIABLE PROFILE VALUE)
  (SETQ PROFILE (PROFILIZE PROFILE))
  (LET ((TYPE (VARIABLE-DEFINITION-TYPE (FIND-VARIABLE-DEFINITION VARIABLE))))
    (ASSERT (TYPEP VALUE TYPE)
      (VALUE)
      "Profile slot ~s's value ~s not a(n) ~s" VARIABLE VALUE TYPE)
    (SETF (GETF PROFILE VARIABLE)
      VALUE)))
```

```
(DEFUN SETF-PROFILE-ENTRY-VALUE-NAME (VARIABLE PROFILE NAME)
  (SETQ PROFILE (PROFILIZE PROFILE))
  (SETF (PROFILE-ENTRY-VALUE VARIABLE PROFILE)
    (FUNCCALL (VARIABLE-DEFINITION-COERCION-FUNCTION (FIND-VARIABLE-DEFINITION VARIABLE))
      NAME)))
```

```
(DEFUN SETF-PROFILE-NAME (PROFILE NAME)
  (SETF (PROFILE-ENTRY-VALUE '*PROFILE-NAME* PROFILE)
    (STRING NAME)))
```

```
(DEFUN MAKE-PROFILE (PROFILE-NAME &REST CLAUSES)
  "Creates a profile with slots described by the clauses. Clauses is an alist of variables and values, similar
  to defstruct's."
  (LET ((PROFILE NIL))
    (DOLIST (CLAUSE CLAUSES)
      (LET* ((VARIABLE (PROFILE-CLAUSE-VARIABLE CLAUSE))
        (NAME (PROFILE-CLAUSE-NAME CLAUSE)) ; Name of the value to be used (or the value itself).
```

```

      (DEFINITION (OR (FIND-VARIABLE-DEFINITION VARIABLE)
                     (MAKE-VARIABLE-DEFINITION CLAUSE))))
      ;; These are pushed on in reverse order so the final prop list format of the profile will be correct.
      (PUSH (PROFILE-VALUE-TYPE-CHECK DEFINITION (EVAL NAME))
            PROFILE)
      (PUSH VARIABLE PROFILE)))
    (CONS '*PROFILE-NAME* (CONS PROFILE-NAME PROFILE)))

```

```

(DEFUN COPY-PROFILE (&OPTIONAL (PROFILE *PROFILE*))
  "Copies the given profile."
  (COPY-SEQ (PROFILIZE PROFILE)))

```

```

(DEFUN RESTORE-PROFILE (&OPTIONAL (PROFILE *PROFILE*))
  "Set profile variables from given profile."
  (SETQ PROFILE (PROFILIZE PROFILE))
  (MAPC #'SET (PROFILE-VARIABLES PROFILE)
        (PROFILE-VALUES PROFILE))
  PROFILE)

```

```

(DEFUN SAVE-PROFILE (&OPTIONAL (PROFILE *PROFILE*))
  "Save current values of bindings into profile."
  (IL:FOR X IL:ON (PROFILIZE PROFILE) IL:BY CDDR IL:DO (SETF (CADR X)
                                                             (EVAL (CAR X))))
  PROFILE)

```

```

(DEFMACRO WITH-PROFILE (PROFILE-FORM &BODY FORMS)
  "Bind all the special IO variables to the values in the profile and execute the body forms."
  `(LET ((*PROFILE* ,PROFILE-FORM)
        (SETQ *PROFILE* (PROFILIZE *PROFILE*))
        (PROGV (PROFILE-VARIABLES *PROFILE*)
              (PROFILE-VALUES *PROFILE*)
              ,@FORMS)))

```

```

(DEFUN FIND-PROFILE (NAME)
  (GETHASH (STRING NAME)
           *PROFILES*))

```

```

(DEFUN SETF-FIND-PROFILE (NAME PROFILE)
  (SETQ NAME (STRING NAME))
  (SETQ PROFILE (PROFILIZE PROFILE))
  (SETF (GETHASH NAME *PROFILES*)
        PROFILE)
  (SETF (PROFILE-NAME PROFILE)
        NAME)
  NAME)

```

```

(DEFUN LIST-ALL-PROFILES ()
  (LET ((PROFILES NIL)
        (MAPHASH #'(LAMBDA (NAME VALUE)
                  (PUSHNEW VALUE PROFILES :TEST #'EQ) ; Avoid repeats due to nicknames
                    )
          *PROFILES*))
    (MAPCAR #'(LAMBDA (PROFILE)
              (PROFILE-NAME PROFILE) ; Convert to name strings
            )
            PROFILES)))

```

```

(DEFUN PROFILE-VALUES (PROFILE)
  (IL:FOR X IL:IN (CDR (PROFILIZE PROFILE)) IL:BY CDDR IL:COLLECT X))

```

```

(DEFUN PROFILE-VARIABLES (&OPTIONAL (PROFILE *PROFILE*))
  (IL:FOR X IL:IN (PROFILIZE PROFILE) IL:BY CDDR IL:COLLECT X))

```

```

(DEFSETF FIND-PROFILE SETF-FIND-PROFILE)

```

```

(DEFSETF PROFILE-ENTRY-VALUE SETF-PROFILE-ENTRY-VALUE)

```

```

(DEFSETF PROFILE-ENTRY-VALUE-NAME SETF-PROFILE-ENTRY-VALUE-NAME)

```

```

(DEFSETF PROFILE-NAME SETF-PROFILE-NAME)

```

```

(DEFPROFILE "READ-PRINT" (*READTABLE* "LISP")
  (*READ-BASE* 10)
  (*READ-SUPPRESS* NIL)
  (*PACKAGE* "USER")
  (*READ-DEFAULT-FLOAT-FORMAT* ' SINGLE-FLOAT)
  (*PRINT-ESCAPE* T)
  (*PRINT-PRETTY* NIL)
  (*PRINT-CIRCLE* NIL)
  (*PRINT-BASE* 10)
  (*PRINT-RADIX* NIL)
  (*PRINT-CASE* :UPCASE)
  (*PRINT-GENSYM* T)
  (*PRINT-LEVEL* NIL)
  (*PRINT-LENGTH* NIL)
  (*PRINT-ARRAY* NIL)
  (*PRINT-STRUCTURE* NIL))

(DEFPROFILE ("LISP" (:NICKNAMES "CL")) (*READTABLE* "LISP")
  (*PACKAGE* "USER")
  (*EVAL-FUNCTION* ' EVAL)
  (*EXEC-PROMPT* "> ")
  (*DEBUGGER-PROMPT* " : "))

(DEFPROFILE ("INTERLISP" (:NICKNAMES "IL")) (*READTABLE* "INTERLISP")
  (*PACKAGE* "INTERLISP")
  (*EVAL-FUNCTION* ' IL:EVAL)
  (*EXEC-PROMPT* "_ ")
  (*DEBUGGER-PROMPT* "_: "))

(DEFPROFILE "OLD-INTERLISP-T" (*READTABLE* "OLD-INTERLISP-T")
  (*PACKAGE* "INTERLISP")
  (*EVAL-FUNCTION* ' IL:EVAL)
  (*EXEC-PROMPT* "_ ")
  (*DEBUGGER-PROMPT* "_: "))

(DEFPROFILE ("XEROX-COMMON-LISP" (:NICKNAMES "XCL")) (*READTABLE* "XCL")
  (*PACKAGE* "XCL-USER")
  (*EVAL-FUNCTION* ' EVAL)
  (*EXEC-PROMPT* "> ")
  (*DEBUGGER-PROMPT* " : "))

(IL:DECLARE\ : IL:DONTCOPY IL:DONTEVAL@LOAD IL:DOEVAL@COMPILE
(IL:DECLARE\ : IL:DOEVAL@COMPILE IL:DONTCOPY
(IL:LOCALVARS . T)
)
)
(IL:PUTPROPS IL:PROFILE IL:MAKEFILE-ENVIRONMENT (:READTABLE "XCL" :PACKAGE "XCL"))
(IL:PUTPROPS IL:PROFILE IL:FILETYPE COMPILE-FILE)
(IL:PUTPROPS IL:PROFILE IL:COPYRIGHT ("Venue & Xerox Corporation" 1986 1987 1990))

```

FUNCTION INDEX

COPY-PROFILE	4	PROFILE-ENTRY-VALUE	3	RESTORE-PROFILE	4
FIND-PROFILE	4	PROFILE-ENTRY-VALUE-NAME	3	SAVE-PROFILE	4
FIND-VARIABLE-DEFINITION	2	PROFILE-NAME	3	SETF-FIND-PROFILE	4
IN-PROFILE	2	PROFILE-P	3	SETF-PROFILE-ENTRY-VALUE	3
INSTALL-PROFILE	2	PROFILE-VALUE-TYPE-CHECK	3	SETF-PROFILE-ENTRY-VALUE-NAME	3
LIST-ALL-PROFILES	4	PROFILE-VALUES	4	SETF-PROFILE-NAME	3
MAKE-PROFILE	3	PROFILE-VARIABLES	4		
MAKE-VARIABLE-DEFINITION	2	PROFILIZE	2		

PROFILE INDEX

"INTERLISP"	5	"OLD-INTERLISP-T"	5	"XEROX-COMMON-LISP"	5
"LISP"	5	"READ-PRINT"	5		

SETF INDEX

FIND-PROFILE	4	PROFILE-ENTRY-VALUE	4	PROFILE-ENTRY-VALUE-NAME	4	PROFILE-NAME	4
--------------------	---	---------------------------	---	--------------------------------	---	--------------------	---

VARIABLE INDEX

PROFILE	1	*PROFILE-NAME*	1	*PROFILE-VARIABLES*	1	*PROFILES*	2
-----------------	---	----------------------	---	---------------------------	---	------------------	---

STRUCTURE INDEX

PROFILE-CLAUSE	1	VARIABLE-DEFINITION	1
----------------------	---	---------------------------	---

PROPERTY INDEX

IL:PROFILE	5
------------------	---

TYPE INDEX

PROFILE	1
---------------	---

MACRO INDEX

WITH-PROFILE	4
--------------------	---

DEFINER INDEX

DEFPROFILE	1
------------------	---

DEFINE-TYPE INDEX

PROFILES	1
----------------	---
